

nifty



TrackDrive

TRACK MOUNTED WORK PLATFORM

34ft, 42ft & 50ft
Platform heights

Superb Gradeability
Will climb very steep
inclines as high as 60% (31°)

Excellent Traction
Better grip on uneven terrain

**Fully Proportional
Hydraulic Controls**
Simple, reliable &
easy to maintain

Weight Saving Design
Lower cost transportation &
better fuel economy on site

Non-Marking Tracks
Optional rubber-free tracks
available for indoor usage

Variable Width Tracks
Access to narrow openings
improving versatility



niftylift.com



nifty TrackDrive

With platform heights of 33ft 6in, 42ft and 50ft 2in, Nifty's **TrackDrive** work platforms offer a range of capabilities to suit operator requirements.

The **TD34T** is available in two versions, the standard and narrow width machines (**TD34TN**). With 60% gradeability both offer excellent traction on steep or rough terrain and the narrow version will pass through a 2ft 6in opening for restricted access applications.

The **TD42T** offers exceptional all-round performance from such a compact and low weight base, and with a 500lbs safe-working-load, plenty of capacity for tools as well.

The **TD50** also provides an extremely impressive working envelope and its TrackDrive base allows it to travel over ground where even a 4-wheel-drive self propelled platform would have difficulty.



TD50



TD34T

Weight saving designs mean that site-to-site transportation is more economical. The platforms are also more efficient, allowing them to work for longer while using less fuel.



TD42T



TD34TN

Available on rubber-free urethane tracks.



Non-marking tracks

SPECIFICATIONS	TD34TN	TD34T	TD42T	TD50
Working Height	40ft	40ft	48ft 6in	57ft
Platform Height	33ft 6in	33ft 6in	42ft	50ft 6in
Working Outreach	20ft	20ft	25ft	28ft 7in
Slew	406°	406°	400°	360°
Width - Traveling	2ft 6in - 3ft 9in	3ft 7in	4ft 7in	6ft 1in
- Working	9ft 10in	11ft 8in	12ft 6in	14ft 4in
Height	6ft 3in	6ft 3in	6ft 7in	6ft 11in
Length	13ft	13ft	15ft 5in	18ft 4in
Minimum Weight	4,080lbs*	4,100lbs*	4,500lbs*	6,400lbs*
Platform Capacity	265lbs	500lbs	500lbs	500lbs
Platform Size	2ft 6in x 2ft 2in	3ft 7in x 2ft 2in	4ft 7in x 2ft 4in	3ft 7in x 2ft 2in
Drive Speed	1.0mph	1.0mph	1.3mph	1.3mph
Gradeability	60%	60%	45%	32%
Control System	Fully Proportional Hydraulic			
Power System	Diesel - Kubota 722 - 18hp			

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

* Weights may vary according to specification / power options, please confirm before ordering.

Supplied by:

NIFTYLIFT INC

32 Concourse Way,
Greer, SC 29650 USA
Sales: 1-800-NIFTYLIFT (800-643-8954)
Office: 1-877-MYNIFTY (877-696-4389)
Fax: 1-864-968-8836
e.mail: info@niftylift.com
www.niftylift.com

NIFTYLIFT LTD

Fingle Drive, Stonebridge
Milton Keynes, MK13 0ER
England, United Kingdom
Tel.: +44 (0)1908 223456
Fax.: +44 (0)1908 312733
e.mail: info@niftylift.com
www.niftylift.com