

Keyed selector switch, metal Maintained B Cam 3 position Operator only Non-Illuminated Key type 501CH (standard) Key removable center position UL file E22655 in Vol. 6 (7) Sec. 13 (2)

|                                           |                     |
|-------------------------------------------|---------------------|
| Design of the product                     | Actuator round      |
| <b>Enclosure</b>                          |                     |
| Number of command points                  | 1                   |
| Delivery state                            |                     |
| • as a kit                                | No                  |
| <b>Actuator</b>                           |                     |
| Design of the operating mechanism         | Key-operated switch |
| Material of the actuating element         | metal               |
| Type of unlocking device                  | key unlatching      |
| Number of switching positions             | 3                   |
| Switch position for key distraction       | center              |
| Lock make                                 | ILLINOIS            |
| Key number                                | 501CH               |
| <b>Front ring</b>                         |                     |
| Product component front ring              | Yes                 |
| Design of the front ring                  | standard            |
| Material of the front ring                | metal               |
| Color of the front ring                   | chrome              |
| <b>Holder</b>                             |                     |
| Material of the holder                    | Metal               |
| <b>General technical data</b>             |                     |
| Product component                         |                     |
| • Light source                            | No                  |
| Degree of pollution                       | 1                   |
| Protection class IP                       | IP66                |
| Operating frequency maximum               | 600 1/h             |
| <b>Ambient conditions</b>                 |                     |
| Ambient temperature                       |                     |
| • during operation                        | -35 ... +70 °C      |
| • during storage                          | -40 ... +85 °C      |
| <b>Installation/ mounting/ dimensions</b> |                     |
| Shape of the installation opening         | round               |

## Certificates/ approvals

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6BH>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6BH>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6BH>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SC6BH&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6BH&lang=en)

last modified:

11/13/2019