



Figure similar

MLFB-Ordering data

6SL3210-5HE11-5UF0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input

Number of phases	3 AC
Line voltage	200 ... 480 V \pm 10 %
Line frequency	45 ... 66 Hz
Rated current	6.0 A
Inrush current	8.6 A

Output

Number of phases	3 AC
Rated power (at 400V)	1.50 kW (2.04 hp)
Rated current I_N	5.0 A
Max. output current	19.0 A
Pulse frequency	8 kHz
Output frequency for servo control	0 ... 550 Hz

Electronics power supply

Voltage	24 V -15 % ... +20 %
Current demand, max.	1.0 A

Communication

Communication	PROFINET
---------------	----------

Ambient conditions

Installation altitude	1000 m (3280.84 ft)
Cooling	Air cooling using an integrated fan

Ambient temperature during

Operation	0 ... 50 °C (32 ... 122 °F) Better than class 3K3, in acc. with EN 60721-3-3: 2002, without derating
Transport	-40 ... 70 °C (-40 ... 158 °F) Class 2K4, in acc. with EN 60721-3-2: 1997, in transport packaging
Storage	-25 ... 55 °C (-13 ... 131 °F) Class 1K4, in acc. with EN 60721-3-1: 1997, in product packaging

Relative humidity during

Max. operation	95 % RH, condensation not permitted
Transport, max.	95 % at 40 °C (104 °F)
Bearing, max.	95 %

MLFB-Ordering data

6SL3210-5HE11-5UF0



Figure similar

Inputs / outputs		Connections	
Standard digital inputs		Line side	
Number	5 of which 2 for F-DI	Version	push-in spring-type terminals
		Conductor cross-section	0.8 ... 6.0 mm ² / 18 ... 10 AWG
Fail-safe digital inputs		Motor end	
Number	1 Can only be used for STO/SS1	Version	push-in spring-type terminals
		Conductor cross-section	0.8 ... 6.0 mm ² / 18 ... 10 AWG
Mechanical data		DC link (for braking resistor)	
Dimensions		Version	push-in spring-type terminals
Width	70.0 mm (2.76 in)	Conductor cross-section	0.8 ... 6.0 mm ² / 18 ... 10 AWG
Height without shield plate	322.0 mm (12.68 in)	Cable length	10 m (32.81 ft)
Depth	223.0 mm (8.78 in)	PE connection	
Mounting position	vertical wall mounting	Version	M4 screw studs
Degree of protection	IP20 / UL open type	Max. motor cable length	
Size	FSB	Shielded	50 m (164.04 ft)
Net weight	3.30 kg (7.28 lb)	Standards	
		Compliance with standards	CE, cULus, RCM, EAC
		CE marking	Low-voltage directive 2006/95/EC
		Verification of suitability for fail-safety	SIL 2 in acc. with IEC 61508 parts 1-3 (2010) and IEC 61800-5-2 (2016), PL d in acc. with ISO 13849 part 1 (2015), Category 3 in acc. with IEC 60204 (2007)