

Selector switch, metal Spring return from left Long lever Position, B  
Cam 3 position Operator only white insert Non-Illuminated UL file  
E22655 in Vol. 6 (7) Sec. 13 (2)

Design of the product	Actuator round
<b>Enclosure</b>	
Number of command points	1
Delivery state	
• as a kit	No
<b>Actuator</b>	
Design of the operating mechanism	selector switch
Material of the actuating element	plastic
Shape of the actuating element	Extended handle
Type of unlocking device	rotate-to-unlatch mechanism
Number of switching positions	3
<b>Front ring</b>	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome
<b>Holder</b>	
Material of the holder	Metal
<b>General technical data</b>	
Product component	
• Light source	No
Degree of pollution	1
Protection class IP	IP66
Operating frequency maximum	600 1/h
<b>Ambient conditions</b>	
Ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C
<b>Installation/ mounting/ dimensions</b>	
Shape of the installation opening	round
<b>Certificates/ approvals</b>	
<b>Further information</b>	

**Information- and Downloadcenter (Catalogs, Brochures,...)**

[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SB2BBB>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SB2BBB>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SB2BBB>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SB2BBB&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SB2BBB&lang=en)

last modified:

11/13/2019