

EQ® Load Centers—Circuit Breaker Enclosures

1-Phase and 3-Phase, 240V AC Max.

Features

- Circuit breaker enclosures range from 60A to 250A, indoor and outdoor models
- UL listed
- Suitable for use as service entrance equipment
- UL listed for 60/75°C Conductors (See equipment markings for applications)
- Outdoor type 3R devices use HS type hubs (pg. 1-22) except for the W0204ML1060 which uses HA type hubs



Amp Rating	No. of Poles	Indoor Enclosure - NEMA Type 1					Outdoor Enclosure - NEMA Type 3R				
		Catalog Number	Breaker Used ^①	Max Short Circuit Rating	Std. Pkg.	Dimensions (inches) H W D	Catalog Number	Breaker Used ^①	Max Short Circuit Rating	Std. Pkg.	Dimensions (inches) H W D

1-Phase, 3-Wire SN - 120/240 Volts AC - Breaker Factory Installed

100	2	E0202MB1100 LC100CS	Q2100 MP2100	22,000	1	17.3	7.3	4.3	W0202MB1100CU LW100CR	Q2100 MP2100	22,000	1	17.2	7.3	4.3
150	2	—	—	—	—	—	—	—	W0202MB1150CU	QN2150H	—	—	—	—	—
200	2	E0202MB1200 LC200VS	QN2200 MPD2200	22,000 22,000	1	20	8.7	4	W0202MB1200CU LW200VR	QN2200H MPD2200	65,000	1	19.8	8.7	5
150	2	—	—	—	—	—	—	—	WB2150BQR	QR22B150L	—	—	—	—	—
200	2	—	—	—	—	—	—	—	WB2200BQR	QR22B200L	10,000	1	26.9	7.1	4.4
225	2	—	—	—	—	—	—	—	WB2225BQR	QR22B225L	—	—	—	—	—

1-Phase, 3-Wire SN - 120/240 Volts AC - Enclosure Only

60	2	E0204ML1060S ^{②④} E0204ML1060F ^{②④} LC002GS ^②	QP, QPH, or HQP MP-T, MP-HT, or MP-MT	100,000 ^⑥	5	9.9	5.2	2.7	W0204ML1060 ^{②④} — LW002GR ^②	QP, QPH, or HQP — MP-T, MP-HT, or MP-MT	100,000 ^⑥	5	8.1	5.5	3.5
125	2	E0204ML1125SCU ^③ E0204ML1125FCU ^③ LC002HS	QP or QPH MP-T or MP-HT	22,000	1	17.3	7.3	4.3	W0204ML1125CU ^③ — LW002HR	QP or QPH — MP-T or MP-HT	22,000	1	17.2	7.3	4.3
200	2	— LC004VS	— MD-T, MD-HT, or MD-MT	— 65,000	— 1	— 17.3	— 7.3	— 4.3	W0202ML1200CU LW004VR	QN, QNH, or HQN MD-T, MD-HT, or MD-MT	65,000	1	19.8	8.7	5
225	1-4 2	— —	— —	— —	— —	— —	— —	— —	W0406ML1225CU QR2N3R2	QPP or QP QR2, QRH2, or HQR2	10,000 65,000	1	23.2 26.9	10.4 7.1	4.5 4.4
250	2	QR2N1S QR2N1F	QR2, QRH2, HQR2, or HQR2H	100,000	1	31.4	9.6	5.6	— —	— —	— —	— —	— —	— —	— —

3-Phase, 3-Wire 240 Volts AC or 3-Phase, 4-Wire SN — 120/208 Volts AC, 120/240, 240 Volts AC - Enclosure Only

100	2-3	E0303ML3100S ^⑤ LP003CS ^⑤ EB3100S ^⑤	QP or QPH MP-T or MP-HT BQ or BQH	22,000	1	17.3	7.3	4.3	W0303ML3100 ^⑤ LW903CR ^⑤ WB3100 ^⑤	QP or QPH MP-T or MP-HT BQ or BQH	22,000	1	17.2	7.3	4.3
250	2-3	QR2N1S QR2N1F	QR2, QRH2, HQR2, or HQR2H	100,000	1	31.4	9.6	5.6	QR2N3R3 —	QR2, QRH2, HQR2, or HQR2H —	100,000	1	31.4	9.6	5.6

① Additional breaker types may be listed on the wiring diagram.

② Will not accommodate 2-pole GFCI or Circuit breaker with shunt trip.
③ Can accommodate 2-pole GFCI breaker up to 60A.

④ CSA Listed
⑤ Will not accommodate circuit breaker with shunt trip.
⑥ Series rating