
STANDARD TABLES - WOOD LEGS

C7, D7, & P7 SERIES TABLES (OAK OR MAPLE) **ASSEMBLY INSTRUCTIONS**



NOTE:

1. MODEL VIEWS MAY NOT REPRESENT EXACT MODEL PURCHASED

A REV.	CREATED ASSEMBLY INSTRUCTIONS DESCRIPTION	5/5/20	EMR	-				
REV.	DESCRIPTION	DATE NAME ECN NO.						

DWN BY: EMR

ALL DESIGN RIGHTS RESERVED

THE INFORMATION, DATA, DESIGN, AND DRAWINGS EMBODIED IN THIS DOCUMENT AND ALL REPRODUCTIONS THEREOF ARE THE EXCLUSIVE PROPERTY OF DIVERSIFIED WOODCRAFTS, INC.

THESE DOCUMENTS ARE SUPPLIED WITH THE UNDERSTANDING THAT THEY WILL NOT BE DISCLOSED TO THIRD PARTIES WITHOUT WRITTEN CONSENT OF DIVERSIFIED WOODCRAFTS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN CONSENT IS SUBJECT TO LEGAL ACTION.

300 South Krueger Street Suring, WI 54174 diversifiedwoodcrafts.com

STANDARD TABLES - WOOD LEGS ASSEMBLY INSTRUCTIONS

REVISION: C7, D7, & P7 SERIES TABLES NTS

IN HOUSE ASSEMBLY TEMPLATE

TOOLS REQUIRED

½" WRENCH 1/2" SOCKET AND TORQUE WRENCH - OPTIONAL **4MM ALLEN WRENCH**

ASS	EMBLY C	OMPONENTS	
ITEMS INCLUDED	PART#	QTY	
TOP AND APRON ASSEMBLY	N/A	TOP ASSEMBLY (FACTORY ASSEMBLED)	1
LEGS	VARIES	LEG, (OAK OR MAPLE) 2.25X2.25X28.25	4
LEG HARDWARE	520001-4	LEG HARDWARE KIT,4 LEGS	1
LEG BOOT	100076	LEG BOOT,BLK RUBBER	4
STRETCHER	N/A	STRETCHER - SIZE VARIES	VARIES
LEG BRACE	N/A	LEG BRACE - SIZE VARIES	2
CONFIRMATS - LEGS	227578	SCREW,7MMX90MM,CONN,ALLENHEAD, BLACK	8
CONFIRMATS - STRETCHER	228564	SCREW,7MMX50MM,CONN,ALLENHEAD, BLACK	4
SHELF - OPTIONAL	N/A	SHELF - SIZE VARIES (EITHER HALF DEPTH OR FULL DEPTH)	1
SCREWS - SHELF	100066	SCREW,#8X1.5 FSQ SMS TYPE 17	VARIES

NOTE:

- 1. COMPONENTS VARY WITH STYLE OF TABLE PURCHASED.
- 1.2. TOP SELECTIONS:
- CHEMGUARD, PHENOLIC, 13/4" MAPLE, EPOXY, SHOPTOP, OR 1.2.1. COLORED PLASTIC LAMINATE.
- 1.3. SIZES OF TABLE:
- 1.3.1. WIDTH = 48", 54", 60", & 72"; DEPTH = 21", 24", 30, 36", 42"; HEIGHT = 30", 34", OR 36".
- 2. **XX** INDICATES ITEMS THAT ARE ONLY USED ON MODELS WITH LEG BRACES AND STRETCHERS.

A CREATED ASSEMBLY INSTRUCTIONS 5/5/20 EMR - REV. DESCRIPTION DATE NAME ECN NO.						_
A CREATED ASSEMBLY INSTRUCTIONS 5/5/20 EMR -	EV.	DESCRIPTION	DATE	NAME	ECN NO.	
	Α	CREATED ASSEMBLY INSTRUCTIONS	5/5/20	EMR	-	

ALL DIMENSIONS ARE IN INCHES UNLESS NOTED OTHERWISE DECIMALS: X = ± 2000 APR SY:

AND ANGLES: X = ± 000 APR SY:

CABINET SQUARENESS: = ± .0625

APR APR SY: 5/5/20

CONFIDENTIAL:
ALL DESIGN RIGHTS RESERVED
THE INFORMATION, DATA, DESIGN, AND DRAWINGS EMBODIED
IN THIS DOCUMENT AND ALL REPRODUCTIONS THEREOF ARE THE EXCLUSIVE PROPERTY OF DIVERSIFIED WOODCRAFTS, INC.


THESE DOCUMENTS ARE SUPPLIED WITH THE UNDERSTANDING THAT THEY WILL NOT BE DISCLOSED TO THIRD PARTIES WITHOUT WRITTEN CONSENT OF DIVERSIFIED WOODCRAFTS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN CONSENT IS SUBJECT TO LEGAL ACTION.





300 South Krueger Street Suring, WI 54174 diversifiedwoodcrafts.com


STANDARD TABLES - WOOD LEGS TOOLS AND ASSEMBLY COMPONENTS


REVISION: C7, D7, & P7 SERIES TABLES NTS 2 OF 10 REV A



















PRODUCT

Butcher Block (Varnished Tops) Maintenance & Repair

SPILLS

- Be sure any spills are cleaned up immediately. Excessive moisture and certain chemicals allowed to stand on a finished surface can cause damage.
- . Clean spills or soiled areas with a damp cloth and dry thoroughly.
- Periodically, apply a coat of spray wax, paste wax, or lemon oil to finished surface. This will
 enhance and protect the finish and insure a moisture barrier is intact in the event the finish
 becomes scratched or worn.

SCRATCHES & DENTS

- Minor scratches and dents can be easily repaired by rubbing the affected area with steel wool or fine grit (#220) sandpaper. Remember, when rubbing or sanding always sand with the grain of the wood. Feather edges of repair in to the surrounding area. Remove all dust and residue and apply a coat of clear lacquer type finish or paint. Clear lacquer type finish can be purchased at most paint or hardware stores. Small cans of touch-up paint are available form your dealer or representative. Paint colors can easily be matched at most paint stores. Confine touch-up only to the area that was sanded. Remember, follow manufacturing directions on product label when refinishing.
- Major scratches and gouges where large portions of wood have been removed or damaged should be handled by a professional experienced in furniture repair with the proper tools and equipment.

MINERAL STREAKS

 Mineral Streaks-Natural Coloring of wood due to mineral deposits in the tree. Repair is not required and will add to the individuality of your table. Sizes can range up to a 1/4" wide and up to 3" in length.

HUMIDITY GUIDELINES

Your Butcher Block was kiln-dried to an initial moisture content of 7.6%. In order to maintain the beauty and integrity of your Butcher Block, it is recommended that special care be taken to keep the relative humidity and temperature within your home or warehouse in the highlighted range. This will limit the amount of expansion and contraction in your natural wood product and minimize the risk of environmental damage.

- Environment Acclimation: Environmental damage does not constitute defective product. Allowing your Butcher Block to acclimate to the environment for at least 72 hours prior to Installation, following recommended installation practices that allow your Butcher Block to move with the conditions and controlling the environment itself are all key factors that determine the life of your product.
- Temperature Changes: It is important to note that as winter temperatures drop, so does relative
 humidity in the air. The heaters come on which further dries the air. Keeping the area humidified to an
 acceptable level usually becomes necessary during the winter months. The opposite is true in spring
 and summer as humidity rises, dehumidifiers and air conditioners become the method of control.

								REL	ATIV	E HUI	MIDIT	Υ%							
		5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
_	30	1.4	2.6	3.7	4.6	5.5	6.3	7.1	7.8	8.7	9.5	10.4	11,3	12.4	13.5	14.9	17	18.5	21
£	40	1.4	2.6	3.7	4.6	5.5	6.3	7.1	7.8	8.7	9.5	10.4	11.3	12.4	13.5	14.9	17	18.5	21
黑	50	1.4	2.6	3.6	4.6	5.5	6.3	7.1	7.9	8.7	9.5	10.3	11.2	12.3	13.4	14.8	16	18.4	20.9
Ę	60	1.3	2.5	3.6	4.6	5.4	6.2	7	7.8	8.6	9.4	10.2	11.1	12.1	13.3	14.6	16	18.2	20.7
ER/	70	1.3	2.5	3.5	4.5	5.4	6.2	6.9	7.7	8.5	9.2	10.1	11	12	13.1	14.4	16	17.9	20.5
EMPERATURE	80	1.3	2.4	3.5	4.4	5.3	6.1	6.8	7.6	8.3	9.1	9.9	10.8	11.7	12.9	14.2	16	17.7	20.2
Ξ	90	1.2	2.3	3.4	4.3	5.1	5.9	6.7	7.4	8.1	8.9	9.7	10.5	11.85	12.6	13.9	15	17.3	19.8
	100	1.2	2.3	3.3	4.2	5	5.8	6.5	7.2	7.9	8.7	9.5	10.3	11.2	12.3	13.6	15	17	19.5

Example: If conditions in a warehouse are 60% relative humidity at 50 degrees. Fahrenheit Dry wood will pick up moisture until 11.2% is reached, regardless of wood species and initial moisture content.