	<b>FIELD SERVICE BULLETIN, S3U (WINDOWS ONLY) STEERING NOISE SUPPRESSION CABLE INSTALL</b>	<b>DOCUMENT NUMBER</b> 1140.0006.01	<b>REVISION</b> 01
<b>SECTION/CATEGORY</b> Customer Service		<b>DATE</b> MARCH 29, 2010	<b>PAGE</b> 1 of 4

### 1.0 PURPOSE



This document highlights the procedure to provide the field solution for S3u Window bike having an issue with jumpy steering.

### 2.0 SCOPE

This procedure covers the preparation of the handlebar assembly on the bike which includes the removal of required covers, installation of cable, calibration of steering and the re-installation of covers.

### 3.0 SERVICE PARTS

Parts available on the online store at: [ifholdings.biz](http://ifholdings.biz)

8400.0212.02	ASSY, STEERING, BAR, STRAIGHT, S3U	
6000.0116.01	NOISE SUPPRESSION CABLE KIT	

### 4.0 PROCEDURE

#### 4.1. Handlebar Preparation Prior to cable installation.

- 4.1.1. Remove the water tray. Save the screws as they will be needed for re-assembly:



- 4.1.2. Remove steering assembly covers.



## 4.2. Steering noise suppression cable installation

- 4.2.1. The goal is to flood install jumper cable to help reduce the issue with jumpy steering.
- Install provided cable inline with the existing steering cable.

- 4.2.2. Disconnect the cable labeled ST



- 4.2.3. Install the Noise suppression cable (supplied) into the connection just removed.(As shown)





### 4.3. Re-assembly

4.3.1. Re-install steering assembly covers.

4.3.2. Re-install water bottle tray.

4.3.3. Calibrate the steering using the procedure below:

- Enter as a *Guest* and go to the tour selection screen. Do not enter a tour yet.
- At the tour selection screen, press the *Manual* button on the console.
- Enter *7-9-1-3* on the console keys, *Configuration Mode* screen will appear.
- First selection is, *Configure Bike*, press enter and another screen will appear.
- First selection is *Calibrate Steering*; press enter and follow the steps on the display keeping the handlebar to the side that is calibrating.
- Once the calibration steps are complete press the back button on the console until the screen gives you an option to *Exit Configuration Mode*, press enter.

This completes the Steering Noise suppression cable installation instructions.

**For additional technical support the IFH customer service team can be reached at:**

888-528-8589 Ext:2  
From 6:30am to 5pm (Pacific Standard Time)

Or via email at:

support@ifholdings.com