

ASSEMBLY INSTRUCTIONS

STEP 1. Screw in Seat Screws, but do not tighten completely.

STEP 2. Attach the Back (E) onto the rear legs of the chair frame as shown. Ensure the Back is firmly secured onto the rear legs and the pre-drilled screw holes in the rear tube legs and back line up.

STEP 3. (1) Securely tighten Seat Screws. (2) Position Plastic Seat Cover over Seat Frame, aligning 4 connectors. Push hard until you hear a click to indicate that the Plastic Seat Cover is locked in place.

STEP 4. To facilitate assembly and to ensure proper installation, use a rubber mallet when inserting arms.

PREVENTIVE MAINTENANCE

- From time to time, check to make sure screws are securely tightened. Holes in Plastic Seat Cover allow for convenient checking.

A.

Leg Frame (2)

B.

Seat Cushion (1)

C.

Steel Cross Bar(2)

D.

Seat Screw (Long)+Washer(4)

E.

Plastic Backrest

F.

Plastic Seat Cover

G.

Arm (2)

H.

Backrest Screw (short)(4)

I.

Allen Wrench

Model: ALE-EL4314
 Manufactured for / Hecho para / Fabriqué pour Alera® / Essendant Co.
 One Parkway North, Deerfield, IL 60015 © 2015 Essendant Co.
 Made in / Hecho en / Fabriqué à Taiwan
 Product support and parts : 1-800-733-4000
 Ayuda del producto y partes / Support technique et pieces