

REGAL SHEEVING

Assembly Instructions

- (1) Position two uprights (Ref. No. 1) approximately 36 apart. Use two "L" uprights for single units or one "L" and one "T" upright for multiple units. Temporarily place one shelf support (Ref. No. 2) at approximately eye level to properly space uprights.
- (2) Place a shelf support (Ref. No. 2) at rear of unit in bottom two keyslots with tabs turned downward (see enlarged view). Place a second shelf support at bottom front of unit. Place a shelf (Ref. No. 3) over supports.
- (3) Continue assembly by placing supports and shelves as described in step 2. Recommended space between shelves is fitteen inches (eight open slots between supports).
- (4) Top shelf (Ref. No. 3) should be installed flush with upright top.
- (5) Add extra section by using keyslots on common "T" uprights. Follow same assembly procedure as described above.



											ьн	
		(i)	2						1		Item No.	
		Shelf	Shelf Support						Upright		Description	,
PBLS-3618	PELS-3615	PRIS-3612	HS-3614	187610	1876L0	157670	15761.0	127670	1276LO		Part No.	REGAL SHELVING PACKING LIST
1	ı	6	12	1	1	ı	ı	ı	2	RGJ-1236S 36w x 12d x 76h Qty.	STARTER UNITS 5 Openings	
1	6	•	12	ı	ı	1	2	I	ı	RG1536S 36w x 15d x76h Qty.		
6	1	ı	12	1	2	1	ι	ı	l	RCI-1806S 36w x 18d x 76h Qty.		
1 .	1,	6	12	1	1	1			1	RG1236A 36w x 12d x 76h Qty.	ADD-ONUNITS 5 Openings	
1	6	ı	12	1	(-	1	1	Į.	RZ.~1536A 36w x 15d x 76h Qty•		
6	ı	1	1.2	-	1 1	1	ı	1	1	RG1836A 36w × 18d ×76h Qty.		