

# Product data sheet

Specifications



## Rack PDU, Basic, 1U, 20A, 120V, (10)5-20, 5-20P



AP9563

### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### Main

|                           |                                              |
|---------------------------|----------------------------------------------|
| Color                     | Black                                        |
| Product or Component Type | PDU                                          |
| PDU Type                  | Basic                                        |
| Cord length               | 12 ft (3.7 m)                                |
| Number of cables          | 1                                            |
| Provided Equipment        | Installation guide<br>Rack Mounting brackets |

### Complementary

|                          |                     |
|--------------------------|---------------------|
| Input Voltage            | 100 V<br>120 V      |
| Height                   | 1.7 in (4.4 cm)     |
| Width                    | 17.6 in (44.7 cm)   |
| Output Voltage           | 120 V               |
| Depth                    | 2.2 in (5.7 cm)     |
| Net Weight               | 5.5 lb(US) (2.5 kg) |
| mounting location        | Front<br>Rear       |
| Mounting preference      | No preference       |
| Input Plug Type          | NEMA 5-20P          |
| Mounting Mode            | Rack-mounted        |
| Rack units               | 1U                  |
| mounting position        | Horizontal          |
| Line Rated Current       | 16 A                |
| Input current limits     | 20 A                |
| Load Capacity            | 1920 VA             |
| Input Frequency          | 50/60 Hz            |
| Outlet type and quantity | 10 NEMA 5-20R       |

### Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |                                                  |
|---------------------------------------|--------------------------------------------------|
| Product Certifications                | cUL Listed<br>UL Listed                          |
| Ambient Air Temperature for Operation | 23...113 °F (-5...45 °C)                         |
| Relative Humidity                     | 0...95 %                                         |
| Operating altitude                    | 0...10000 ft                                     |
| Ambient Air Temperature for Storage   | -13...149 °F (-25...65 °C)                       |
| Storage Relative Humidity             | 0...95 %                                         |
| Storage altitude                      | 0...50000 ft (0.0000000000...15240.0000000000 m) |

## Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304203889 |
|------|--------------|

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 2.8 in (7 cm)         |
| Package 1 Width              | 9.02 in (22.9 cm)     |
| Package 1 Length             | 18.3 in (46.4 cm)     |
| Package 1 Weight             | 8.02 lb(US) (3.64 kg) |

## Contractual warranty

|          |                           |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant  
[EU RoHS Declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)