

2 Port VGA Video Splitter with Audio - USB Powered

Product ID: ST122LEA



The ST122LEA 2 Port VGA Video Splitter with Audio and USB power is our most compact VGA splitter, allowing a computer to simultaneously display VGA video on two monitors from a single source.

Support for resolutions up to 2048x1536 resolution and stereo audio makes this device perfect for classrooms, tradeshow, or any environment requiring high quality video on several displays.

This VGA splitter is able to draw power from your source PC or media player using an available USB port, instead of using a conventional power adapter making it easy to install where power outlets are not available. The splitter also features a built-in booster circuit that allows you to locate VGA monitors up to 200ft away from your system.

Backed by a StarTech.com 2-year warranty and FREE lifetime tech support.

Certifications, Reports and Compatibility



Applications

- Ideal for small digital signage installations with minimal space or power outlets - simply plug into a USB port
- Use for in-store product merchandising in retail environments to give your advertisements greater visibility
- Display travel schedules and alerts in airports, bus terminals and train stations
- Create engaging multimedia presentations for demonstration in lecture halls and classrooms
- Get your message across multiple displays for trade-shows or information booths/kiosks
- Quick and easy solution to split a video signal in an auditorium or house of worship

Features

- Compact, space-saving design
- Includes USB power cord
- Provides brilliant resolutions up to 2048 x 1536 60 Hz
- 300 MHz bandwidth for high bandwidth fast moving video
- Supports stereo audio using 3.5mm audio jacks
- Maximum distances up to 65 meters (210 feet)

Hardware	Warranty	2 Years
	Audio	Yes
	AV Input	VGA
	AV Output	VGA
	Cabling	Cat 5 UTP or better
	Industry Standards	DDC, DDC2, DDC2B, on Video Out Port 1
	Ports	2
Performance	Maximum Analog Resolutions	2048x1536
	Maximum Cable Length	213.2 ft [65 m]
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - 3.5 mm Mini-Jack (3 Position) Male 1 - VGA (15 pin, High Density D-Sub) Male
	Connector B	1 - 3.5 mm Mini-Jack (3 Position) Female 2 - VGA (15 pin, High Density D-Sub) Female
Indicators	LED Indicators	1 - Green - Power
Power	Output Current	0.5A
	Output Voltage	5 DC
	Power Source	USB-Powered
Environmental	Humidity	0~95% RH
	Operating Temperature	0°C to 70°C (32°C to 158°C)
	Storage Temperature	-20°C to 85°C (-4°C to 185°C)
Physical Characteristics	Color	Black
	Enclosure Type	Plastic
	Product Height	0.9 in [2.3 cm]
	Product Length	2.7 in [68 mm]
	Product Width	2.1 in [53 mm]
	Weight of Product	3.9 oz [111 g]
Packaging Information	Package Height	1.9 in [47 mm]
	Package Length	5.7 in [14.5 cm]
	Package Width	8.3 in [21 cm]

	Shipping (Package) Weight	8.7 oz [246 g]
What's in the Box	Included in Package	1 - Video Splitter
		1 - USB to DC power cable
		1 - User Manual

Product appearance and specifications are subject to change without notice.