

Mini DisplayPort® to HDMI® Active Video and Audio Adapter Converter - Mini DP to HDMI - 1920x1200

StarTech ID: MDP2HDS



The MDP2HDS Adapter converts Mini DisplayPort to HDMl® with audio pass-through support, enabling you to connect a desktop or laptop computer that is equipped with Mini DisplayPort A/V output to an HDMl® monitor, projector, or display.

Unlike a passive adapter, the MDP2HDS actively converts single mode and dual mode DisplayPort output, which is ideal for graphics cards that do not output dual mode/multi-mode (DP++) signals, such as ATI™ Eyefinity cards.

The Mini DP to HDM® adapter is compatible with Intel® Thunderbolt™, when connected directly to a supporting DisplayPort over Thunderbolt™ I/O port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Ideal for digital entertainment centers, home offices, business conference rooms and trade show displays
- Adapt from graphics cards that are not capable of outputting DP++ signals such as AMD EyeFinity Cards.
- Keep your existing HDMI® monitor to be used with your new Mini DisplayPort® device
- Use your HDM® monitor as a secondary display

Features

- Supports display resolutions up to 1920x1200
- Works with video cards that aren't capable of outputting DP++ (multi-mode) signals
- Compliant with DisplayPort 1.1a specifications
- Supports HDCP 1.3
- Compatible with Intel® Thunderbolt™ with DisplayPort output
- 5.1 Surround Sound Audio Pass-through



Technical Specifications

Warranty 2 Years
Converter Type Active
Audio Yes
Industry Standards HDCP

DisplayPort 1.1

Output Signal HDMI

Connector A 1 - Mini-DisplayPort (20 pin) Male

Connector B 1 - HDMI (19 pin) Female

Audio Specifications 5.1 Surround Sound

Maximum Digital Resolutions 1920x1200

Wide Screen Supported Yes
Color Black

Product Length 6.7 in [170 mm]
Product Width 1.6 in [40 mm]
Product Height 0.6 in [15 mm]
Product Weight 1.1 oz [29.8 g]
Humidity 40%-85%RH

Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature 0°C to 70°C (32°F to 158°F)

Shipping (Package) Weight 1.7 oz [49.5 g]

Included in Package 1 - Mini-DisplayPort® to HDMl® Active Adapter

Certifications, Reports and Compatibility





