


HORIZONTAL FLOW WRAPPERS



Bag Styles



Minimum Package Dimensions

Maximum Package Dimensions

600 x 250 x 80 mm
23.6 x 9.8 x 3.1 in
(LxWxH)

Perfect For Packaging:

- Candy Bars
- Sandwiches
- Hamburgers
- Consumer Goods



FEATURES

Packaging Plus Horizontal Flow Wrappers are made to package a wide range of products in 3-side seal pillow bags. This machine can be equipped with two frequency converter units or with two Servo-motors, depending on the bag size range and the product dimensions. Two versions available: A basic model, with a painted steel frame, with duraluminum parts and Full Stainless Steel version.

BENEFITS

- *User-friendly interface control for convenient operations*
- *Stainless Frame & Surfaces for hygiene & durability*
- *Memory function makes the machine ideal for flexible packaging operations*
- *Adjustable forming box make the production flexible*
- *Self-diagnosis function allows for easy troubleshooting*
- *Optional servo motors for high productivity & low noise*

MODEL	Max Bag Length	Max Bag Width	Max Product Height	Max Film Width	Packaging Speed	Power Supply	Machine Dimensions (LxWxH)	Motor Type	Reel Option
2200 L/U	140-300 mm (Single Jaw) 60-170 mm (Double Jaws)	100 mm	35 mm	220 mm	up to 200	220V, 50/60Hz	4240×920×1340 mm 166.9x193.7x52.7 in	Standard	Lower/Upper
2200 LS/US	50-600 mm (Single Jaw)	100 mm	35 mm	220 mm	up to 230	220V, 50/60Hz	4240×920×1340 mm 166.9x193.7x52.7 in	Servo	Lower/Upper
3000 U	140-320 mm (Single Jaw) 80-230 mm (Double Jaws)	140 mm	55 mm	300 mm	up to 200	220V, 50/60Hz	3910×820×1520 mm 153.9x32.2x59.8 in	Standard	Upper
3000 US	120-600 mm (Single Jaw)	140 mm	55 mm	300 mm	up to 230	220V, 50/60Hz	3910×820×1520 mm 153.9x32.2x59.8 in	Servo	Upper
3200 L/U	140-320 mm (Single Jaw) 80-230 mm (Double Jaws)	140 mm	50 mm	320 mm	up to 200	220V, 50/60Hz	3940×880×1520 mm 155.1x34.6x59.8 in	Standard	Lower/Upper
3200 LS/US	60-600 mm (Single Jaw)	140 mm	50 mm	320 mm	up to 230	220V, 50/60Hz	3940×880×1520 mm 155.1x34.6x59.8 in	Servo	Lower/Upper
3500 U	140-320 mm (Single Jaw) 80-230 mm (Double Jaws)	160 mm	60 mm	350 mm	up to 200	220V, 50/60Hz	3940×1010×1400 mm 155.1x39.7x55.1 in	Standard	Upper
3500 US	80-600 mm (Single Jaw)	160 mm	60 mm	350 mm	up to 230	220V, 50/60Hz	3940×1010×1400 mm 155.1x39.7x55.1 in	Servo	Upper
4000 L	140-340 mm (Single Jaw) 80-240 mm (Double Jaws)	180 mm	60 mm	430 mm	up to 200	220V, 50/60Hz	3940×880×1520 mm 155.1x34.6x59.8 in	Standard	Lower
4000 LS/US	80-600 mm (Single Jaw)	180 mm	60 mm	430 mm	up to 230	220V, 50/60Hz	3940×880×1520 mm 155.1x34.6x59.8 in	Servo	Lower/Upper
4500 U	140-340 mm (Single Jaw) 80-230 mm (Double Jaws)	180 mm	65 mm	430 mm	up to 200	220V, 50/60Hz	4130×940×1520 mm 162.5x37x59.8 in	Standard	Upper
4500 US	80-600 mm (Single Jaw)	180 mm	65 mm	430 mm	up to 230	220V, 50/60Hz	4130×940×1520 mm 162.5x37x59.8 in	Servo	Upper
6000 U	120-450 mm (Single Jaw)	250 mm	80 mm	580 mm	up to 150	220V, 50/60Hz	4040×1020×1545 mm 159x40.1x60.8 in	Standard	Upper
6000 US	120-600 mm (Single Jaw)	250 mm	80 mm	580 mm	up to 150	220V, 50/60Hz	4040×1020×1545 mm 159x40.1x60.8 in	Servo	Upper

DOVERCO

Strategic. Packaging.

68 Brunswick Blvd, Dollard-des-Ormeaux, QC, H9B 2L3
Tel: (514) 420-6060 • Fax: (514) 420-6015

4 Paget Road, Unit 6, Brampton, ON, L6T 5G3
Tel: (289) 256-2141 • Fax: (289) 256-2142

Toll Free: 1-800-363-0697 • www.doverco.ca • web.sales@doverco.ca