

Logix PakStrapper EXS-306

DOVERCO
Strategic. Packaging.

Semi-Automatic Strapping Machine

Constant strapping tension and an overall faster process

Reduce your labour and energy when it comes to your strapping

No need for clips, tensioners or sealers, the EXS-306 replaces all of those functions. All that is required is a person to take the outgoing strap, circle the package and feed the flap back into the machine to finish the entire operation. *It boasts a constant strapping tension and an overall faster process to get all your strapping done with a minimum amount of fuss.* Comfortable working height of 730mm (28.75").



PU Casters

2 free and 2 with brake

ITEM NUMBER	D172320
MIN. PACKAGE SIZE	60 mm (2.4")
MAX. PACKAGE SIZE	Any size
STRAP WIDTH	12mm (0.5") core 8"
TENSION RANGE	5-55 kg
DIMENSIONS (L x W x H)	895 x 565 x 740 mm (35.2" x 22.2" x 29.1")
WEIGHT	100 kg
ELECTRICAL	110V 60HZ 1-PHASE
STRAPPING SPEED	2.5 seconds/strap

Up To
29 CYCLES
PER MINUTE



CSA or equivalent special
inspection certified for
insurance compliance liability

Note: Do not use these machines in
freezers, coolers or high humidity
locations