

2



1

REVISION HISTORY				
REV	ZONE	DESCRIPTION	DATE	APPROVED

B


B

9022-0029
USB CABLE

3065-0096
ADAPTER BOARD

9022-0026
RIBBON CABLE

3DM-CV5-25 PN 6257-4260 (SHOWN)
 3DM-CV5-15 PN 6258-4260
 3DM-CV5-10 PN 6259-4210
 3DM-CX5-45 PN 6271-4260
 3DM-CX5-25 PN 6273-4260
 3DM-CX5-15 PN 6274-4260
 3DM-CX5-10 PN 6275-4260



A

A

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE IN INCHES.
 TOLERANCES:(UOS):
 .X = ± .02
 .XX = ± .01
 .XXX = ± .005
 HOLE DIAMETERS: ± .002
 ANGLES: ± 0.5°
 SURFACE FINISH: 63
 MICROINCHES
 MATERIAL:

DRAWN C.THELEN	4/4/2019
REFERENCE PLM SYSTEM FOR APPROVALS	
THIS DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF LORD-MICROSTRAIN AND SHALL NOT BE PRODUCED WITHOUT PERMISSION FROM LORD-MICROSTRAIN	

L O R D Sensing 459 HURRICANE LN. WILLISTON VT 802-862-6629		
TITLE CX5-XX, CV5-XX USB CABLE ASSEMBLY		
DWG NO 6212-3006	REV -	CAGE CODE OXYZ9
SIZE: A	SHEET 1 OF 1	WWW.MICROSTRAIN.COM

2



1