

High-efficiency photovoltaic module using silicon nitride multicrystalline silicon cells.

Performance

Rated power (P_{\max})	30W
Power tolerance	$\pm 10\%$
Nominal voltage	12V
Limited Warranty ¹	12 years


Configuration

J	Clear universal frame and standard J-Box
----------	--

Electrical Characteristics²

SX330

Maximum power (P_{\max}) ³	30W
Voltage at Pmax (V_{mp})	16.8V
Current at Pmax (I_{mp})	1.78A
Warranted minimum P_{\max}	27W
Short-circuit current (I_{sc})	1.94A
Open-circuit voltage (V_{oc})	21.0V
Temperature coefficient of I_{sc}	$(0.065 \pm 0.015)\% / ^\circ\text{C}$
Temperature coefficient of V_{oc}	$-(80 \pm 10)\text{mV} / ^\circ\text{C}$
Temperature coefficient of power	$-(0.5 \pm 0.05)\% / ^\circ\text{C}$
NOCT (Air 20°C; Sun 0.8kW/m ² ; wind 1m/s)	47 \pm 2°C
Maximum series fuse rating	5A
Maximum system voltage	50V (US NEC rating) 50V (IEC 61215 rating)






Mechanical Characteristics


Dimensions	Length: 595mm (23.4")	Width: 502mm (19.7")	Depth: 50mm (1.97")
Weight	3.9 kg (8.6 pounds)		
Solar Cells	36 cells (57mm x 114mm) in a 4x9 matrix connected in series		
Junction Box	J-Version junction box with 4-terminal connection block; IP 65, accepts PG 13.5, M20, ½ inch conduit, or cable fittings accepting 6-12mm diameter cable. Terminals accept 2.5 to 10mm ² (8 to 14 AWG) wire.		
Construction	Front: High-transmission 3mm (1/8 th inch) tempered glass; Back: Polyester; Encapsulant: EVA		
Frame	Clear anodized aluminum alloy type 6063T6 Universal frame; Color: silver		

1. Module Warranty: 12-year limited warranty of 90% power output; 2-year limited warranty of materials and workmanship. See your local representative for full terms of these warranties.
2. These data represent the performance of typical BP modules, and are based on measurements made in accordance with ASTM E1036 corrected to SRC (STC.)
3. During the stabilization process that occurs during the first few months of deployment, module power may decrease by approx. 1% from typical P_{\max} .

Quality and Safety

	Manufactured in ISO 9001-certified factories; conforms to European Community Directives; certified to IEC 61215
ESTI	Module power measurements calibrated to World Radiometric Reference through ESTI (European Solar Test Installation at Ispra, Italy)
	Listed by Underwriter's Laboratories for electrical and fire safety (Class C fire rating)
	Approved by Factory Mutual Research in NEC Class 1, Division 2, Groups C & D hazardous locations.

SX330 I-V Curves




Qualification Test Parameters

Temperature cycling range	-40°C to +85°C (-40°F to 185°F)
Humidity freeze, damp heat	85% RH
Static load front and back (e.g. wind)	2,400 pa (50psf)
Front loading (e.g. snow)	5,400 pa (113psf)
Hailstone impact	25mm Ø (1 inch) at 23 m/s (52mph)

Module Diagram

Dimensions in brackets are in inches. Un-bracketed dimensions are in millimeters. Overall tolerances $\pm 3\text{mm}$ (1/8")



Included with each module: self-tapping grounding screw, instruction sheet, and warranty document.

Note: This publication summarizes product warranty and specifications, which are subject to change without notice. Additional information may be found on our web site: www.bpsolar.com



For product and purchasing inquiries contact:

ecodirect
CLEAN ENERGY SOLUTIONS
www.ecodirect.com