


Enphase IQ 6 and IQ 6+ Microinverters

Designed for higher powered modules, the smart grid-ready **Enphase IQ 6 Micro™** and **Enphase IQ 6+ Micro™** are built on the sixth-generation platform and achieve the highest efficiency for module-level power electronics and reduced cost per watt.

Part of the Enphase IQ System, the IQ 6 and IQ 6+ Micro integrate seamlessly with the Enphase IQ Envoy™, Enphase IQ Battery™, and the Enphase Enlighten™ monitoring and analysis software.

The IQ 6 and IQ 6+ Micro are very reliable as they have fewer parts and undergo over 1 million hours of testing. Enphase provides an industry-leading warranty of up to 25 years.



Easy to Install

- Lightweight
- Simple cable management
- Built-in rapid shutdown (NEC 2014)

Productive

- Optimized for high powered modules
- Supports 60 and 72-cell modules
- Maximizes energy production

Smart Grid Ready

- Complies with fixed power factor, voltage and frequency ride-through requirements
- Remotely updates to respond to changing grid requirements
- Configurable for varying grid profiles



Enphase IQ 6 and IQ 6+ Microinverters

INPUT DATA (DC)	IQ6-60-2-US AND IQ6-60-5-US		IQ6PLUS-72-2-US AND IQ6PLUS-72-5-US	
Commonly used module pairings ¹	195 W - 330 W +		235 W - 400 W +	
Module compatibility	60-cell PV modules only		60-cell and 72-cell PV modules	
Maximum input DC voltage	48 V		62 V	
Peak power tracking voltage	27 V - 37 V		27 V - 45 V	
Operating range	16 V - 48 V		16 V - 62 V	
Min/Max start voltage	22 V / 48 V		22 V / 62 V	
Max DC short circuit current (module I _{sc})	15 A		15 A	
Overvoltage class DC port	II		II	
DC port backfeed under single fault	0 A		0 A	
PV array configuration	1 x 1 ungrounded array; No additional DC side protection required; AC side protection requires max 20A per branch circuit			
OUTPUT DATA (AC)	IQ6-60-2-US AND IQ6-60-5-US		IQ6PLUS-72-2-US AND IQ6PLUS-72-5-US	
Peak output power	240 VA		290 VA	
Maximum continuous output power	230 VA		280 VA	
Nominal voltage/range ²	240 V / 211-264 V	208 V (1Φ) / 183-229 V	240 V / 211-264 V	208 V (1Φ) / 183-229 V
Nominal output current	0.96 A	1.11 A	1.17 A	1.35 A
Nominal frequency	60 Hz		60 Hz	
Extended frequency range	47 - 68 Hz		47 - 68 Hz	
Power factor at rated power	1.0		1.0	
Maximum units per 20 A branch circuit	16 (240 VAC)		13 (240 VAC)	
	14 (single-phase 208 VAC)		11 (single-phase 208 VAC)	
Overvoltage class AC port	III		III	
AC port backfeed under single fault	0 A		0 A	
Power factor (adjustable)	0.7 leading ... 0.7 lagging		0.7 leading ... 0.7 lagging	
EFFICIENCY	@240 V	@208 V (1Φ)	@240 V	@208 V (1Φ)
CEC weighted efficiency	97.0 %	96.5 %	97.0 %	96.5 %
MECHANICAL DATA				
Ambient temperature range	-40°C to +65°C			
Relative humidity range	4% to 100% (condensing)			
Connector type	MC4 or Amphenol H4 UTX			
Dimensions (WxHxD)	219 mm x 191 mm x 37.9 mm (without bracket)			
Weight	1.5 kg (3.3 lbs)			
Cooling	Natural convection - No fans			
Approved for wet locations	Yes			
Pollution degree	PD3			
Environmental category / UV exposure rating	Outdoor - NEMA 250, type 6 (IP67)			
FEATURES				
Communication	Power line			
Monitoring	Enlighten Manager and MyEnlighten monitoring options Compatible with Enphase IQ Envoy			
Compliance	UL 62109-1, UL1741/IEEE1547, FCC Part 15 Class B, ICES-0003 Class B, CAN/CSA-C22.2 NO. 107.1-01 This product is UL Listed as PV Rapid Shut Down Equipment and conforms with NEC-2014 and NEC-2017 section 690.12 and C22.1-2015 Rule 64-218 Rapid Shutdown of PV Systems, for AC and DC conductors, when installed according manufacturer's instructions.			

1. No enforced DC/AC ratio. See the compatibility calculator at enphase.com/en-us/support/module-compatibility.

2. Nominal voltage range can be extended beyond nominal if required by the utility.

To learn more about Enphase offerings, visit enphase.com