

Illuminate your Elevator With Low Voltage ProLED® 1383 and GBF Lamps

Halco's ProLED 1383 and GBF lamps are the latest in elevator lighting technology, offering low maintenance and high incentives, including energy and cost savings.

Towering Energy Savings with ProLED

Save up-to 87%¹ in energy costs with a ProLED low voltage lamp, compared to its miniature incandescent equivalent. By replacing a 20 watt incandescent lamp with a ProLED 2.6 watt elevator lamp, you'll save \$76.56² over the life of the lamp.



Longest Guaranteed Life Equals Maximum Maintenance Savings

In a constantly operating elevator, the ProLED lamp would last 1,679 days, compared to an incandescent lamp at an average of 36 days. By switching from incandescent to LED, you'll save significant lamp changes over the life of the lamp. This means fewer lamps to purchase, install and dispose of and less hassle for building maintenance. With a useful life³ of 40,000 hours, backed by a 5-year warranty, ProLED lamps are the solution for demanding lighting applications.

Lower Heat Generation

By eliminating 87% of the energy devoted to lighting, there is less heat introduced to the cab of the elevator. With this decrease, the occupants are more comfortable while being safely protected. Plus, there is less impact on the elevator's climate controls, further increasing energy savings.



Existing		Recommended Energy Saving Options	
Lamp	Incandescent	ProLED® R12 1383	ProLED® GBF
Product Code	N/A	1383/3WW/LED	GBF/3WW/LED
Lumens	200	145	145
Watts	20	2.6	2.6
Lumens Per Watt	10	55	55
Average Life	300 - 2,000	40,000	40,000
Energy Cost at 40,000 hours	\$88	\$11.44	\$11.44
Savings	N/A	\$76.56	\$76.56

¹ Based on incandescent lamp life of 300 hours for a 1383 compared to ProLED life of 40,000 hours

² Based on national average of \$0.11 per KWH over 40,000 hours life

³ Useful life is defined as 70% of light output at 40,000 hours



where there's **light**, there's halco.

www.halcolighting.com

Halco
LIGHTING TECHNOLOGIES

Bulb Type	Watts	Base	Product #	Product Code	Description	Volts	Color Temp.	Lumens	Useful Life*	Pkg. Qty.	Beam Spread	MOL
R12	2.6	BA15d	80756	GBF/3WW/LED	Warm White	10-18	2700	145	40000	1/10	-	2.52"
R12	2.6	BA15s	80701	1383/3WW/LED	Warm White	10-18	2700	145	40000	1/10	-	2.52"

NEW ITEM!

* Useful Life is Defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels.

Warranty - Commercial / Industrial: This product is warranted for 5 years from the date of purchase, based on 10 hours of use per day.

Note: May not be compatible with all electronic transformers.

Not for use in enclosed fixtures.

Indoor use only.



For product and purchasing inquiries contact:

ecodirect

CLEAN ENERGY SOLUTIONS
www.ecodirect.com