

PMI-2000MS

- Designed for Marine Applications
- 2000 watts continuous power
- 4000 watts peak power
- Provides 16.6 Amps
- Internal, Replaceable 10 x 15 Amp spade-type Fuses
- Dual 3 Prong UL GFCI 120 volt AC outlet
- Anodized aluminum case provides durability
- Digital LED Display (Input DC Voltage or Output Wattage)
- Built-in Cooling Fan
- Overload Indicator
- Cordless Remote Control included Continued Power

Continued Power

2000W

Peak Load Power Rate

< 4000W

Input DC Voltage Range

10-15.5V

No Load Draw

< 1.2A

Output Frequency Range

60 +/- 3Hz

Output Voltage Range

117 +/- 10%

Max Power Efficiency

> 90%

Max Outer Temperature

< 65 C

Low Voltage Alarm Level

11 +/- 0.5V

High Voltage Cut Off Level

15.5 +/- 1V

Short Protect

Yes

Low Voltage Cut Off Level

10 +/- 0.5V

Dimension (LxWxH) in

14.5 x 10.5 x 3.25

Overload Protect

Yes

Input Voltage

DC 12V

Weight

14.5 lbs

For product and purchase inquiries contact:

ecodirect

CLEAN ENERGY SOLUTIONS

www.ecodirect.com