



samlexamerica

3000W



DC-AC Inverter ⚡ Modified Sine Wave

Model
SAM-3000-12
12 VDC - 115 VAC

Design Features

- Compact design
- Load controlled cooling fan
- Low battery input alarm
- Universal protection circuit: thermal, battery, overload, short circuit, earth fault
- Soft start technology
- Cool surface technology
- Power save mode
- Low interference technology



2 YEAR WARRANTY

MODEL NO.		SAM-3000-12
INPUT	BATTERY SYSTEM VOLTAGE	12 VDC
	NOMINAL INPUT VOLTAGE	12.5 VDC
	INPUT VOLTAGE RANGE	10.5 to 15.0 (+/- 0.5) VDC
	INPUT CURRENT AT CONTINUOUS POWER	269 A to 275 A
	INPUT CURRENT AT NO LOAD	0.85 A to 0.95A
OUTPUT	OUTPUT VOLTAGE WAVE FORM	Modified Sine Wave
	OUTPUT VOLTAGE	115 VAC
	OUTPUT VOLTAGE REGULATION	+13% / - 0%
	OUTPUT FREQUENCY	60 Hz +/- 5%
	OUTPUT POWER, CONTINUOUS (RESISTIVE LOAD)	3000 W
	OUTPUT POWER, SURGE (< 1 SEC, RESISTIVE LOAD)	6000 W
PROTECTIONS	PEAK EFFICIENCY (AT 50% OF CONTINUOUS POWER)	90%
	USB CHARGING PORT	Not available
	LOW INPUT VOLTAGE ALARM	Yes (10.8 +/- 0.3 VDC)
	LOW INPUT VOLTAGE SHUTDOWN	10.5 +/- 0.5 VDC
	HIGH INPUT VOLTAGE SHUTDOWN	Yes. (> 15.5 VDC)
	OVERLOAD SHUT DOWN	Yes (Latches in shutdown condition. Manual reset by switching off and switching on the On / Off Switch)
	OVER TEMPERATURE SHUTDOWN	Yes (Auto reset)
	COOLING FAN, LOAD CONTROLLED, ON AT	90 to 110 W
	LEAKAGE PROTECTION	Yes (Shutdown)
CONNECTIONS	INPUT FUSE, 32 V	480 A (16 X 30 A)
	INPUT CONNECTION	Nut and Bolt
	OUTPUT CONNECTION - No OF NEMA5-15R RECEPTACLES	3
GENERAL	REMOTE CONTROL PORT	Yes
	OPERATING TEMPERATURE RANGE	0 to 25 C at 100% loading; 26 C to 35 C at 80 % loading
	OPERATING HUMIDITY	< 80%
	NEUTRAL TO CHASSIS BONDING	No. Neutral is floating
	DIMENSIONS, MM (L x W x H)	420 x 202 x 84
	DIMENSIONS, INCHES (L x W x H)	16.53 x 7.95 x 3.3
		For product and purchase inquiries contact:
		ecoDIRECT
		CLEAN ENERGY SOLUTIONS
		www.ecodirect.com

NOTE: Specifications are subject to change without notice