



samlexamerica

DC-AC Inverter Pure Sine Wave

Model

SA-2000K-112
12 VDC-110 VAC

SA-2000K-124
24 VDC-110 VAC

Design Features

- Pure sine wave output (THD < 3%)
- Switch selectable output frequency: 50 / 60 Hz
- Switch selectable Power Save Mode wherein the inverter shuts off non essential circuitry and reduces its no load self consumption till it sees a minimum programmed load (40 - 280 Watts)
- Optional wired remote controls for switching and monitoring the operation. Includes Ignition Lockout and Reverse Over-ride Function (ROF)
- Input and output are fully isolated
- Advanced micro-controller
- 2 load controlled cooling fans save power consumption
- 3 tri-color LEDs display operational status and fault indications
- **Protections:** overload; short circuit; leakage; low and high DC input voltages; high temperature; reverse polarity
- **Safety:** Meets UL-458 (Pending listing)
- **EMC:** Complies with FCC Part 15(B), Class A

For product and
purchase inquiries contact:

ecoDIRECT

CLEAN ENERGY SOLUTIONS
www.ecodirect.com



2 YEAR WARRANTY

	MODEL NO.	SA-2000K-112	SA-2000K-124
OUTPUT	OUTPUT VOLTAGE	120 VAC, +/- 5%	
	OUTPUT FREQUENCY	50 / 60 Hz +/- 0.05% (Selected by Switch)	
	TYPE OF OUTPUT WAVEFORM	Pure Sine Wave	
	TOTAL HARMONIC DISTORTION OF OUTPUT WAVEFORM	< 3%	
	CONTINUOUS OUTPUT POWER (At Power Factor = 1)	2000 W	2000 W
	SURGE OUTPUT POWER (At Power Factor = 1)	4000 W	4000 W
	PEAK EFFICIENCY (At full load)	89%	92%
INPUT	AC OUTPUT CONNECTIONS	Dual NEMA5-20R receptacles with GFCI protection; Terminal strip for hardwiring	
	NOMINAL DC INPUT VOLTAGE	12 VDC	24 VDC
	DC INPUT VOLTAGE RANGE	10.5 to 15 VDC, +/- 0.2 VDC	21 to 30 VDC, +/- 0.4 VDC
	DC INPUT CURRENT AT NO LOAD (Power Save on)	0.6 A	0.3 A
	DC INPUT CURRENT AT NO LOAD (Power Save off)	2.8 A	1.5 A
POWER SAVE (SLEEP MODE)	DC INPUT CONNECTIONS	M-8 bolt and nut / Wire with M-8 ring lug terminal	
	ENABLED / DISABLED BY SWITCH	Wake up power: 40 to 280 W (switch selectable)	
DISPLAY	INPUT VOLTAGE, OUTPUT POWER, STATUS	By steady / flashing patterns of three, 3- color LEDs	
REMOTE OPERATION	WIRED REMOTE CONTROL (Simple version) (Optional)	SR-8 with 10 ft cable	
	WIRED REMOTE CONTROL (Upgraded version) (Optional)	SR-6-12 with 10 ft cable	SR-6-24 with 10 ft. cable
PROTECTION	LOW DC INPUT VOLTAGE ALARM	10.5 VDC, +/- 0.2 VDC	21.0 VDC, +/- 0.4 VDC
	LOW DC INPUT VOLTAGE SHUTDOWN	10.0 VDC, +/- 0.2 VDC	20.0 VDC, +/- 0.4 VDC
	HIGH DC INPUT VOLTAGE SHUTDOWN	15.0 VDC, +/- 0.2 VDC	30.0 VDC, +/- 0.4 VDC
	SHORT CIRCUIT SHUTDOWN	Yes	
	OVERLOAD SHUTDOWN	Yes	
	GROUND FAULT SHUTDOWN	Yes. Only for the GFCI protected dual NEMA5-20R receptacles	
	OVER TEMPERATURE SHUTDOWN	Yes	
COOLING	REVERSE POLARITY ON DC INPUT SIDE	Yes. Internal fuses will blow	
	FORCED AIR COOLING	2 fans. Will switch on / off at specified values of load / temperature of internal hot spot	
COMPLIANCE	SAFETY	Meets UL-458	
	EMI / EMC	Meets FCC Part 15(B), Class A	
ENVIRONMENT	OPERATING TEMPERATURE RANGE	0 °C to + 40 °C	
	STORAGE TEMPERATURE RANGE	- 30 °C to 70 °C	
DIMENSIONS	(L X W X H), MM	422 x 208 x 166	
	(L X W X H), INCHES	16.6 x 8.18 x 6.53	
WEIGHT	KG	9	
	LBS	19.8	

NOTE: Specifications are subject to change without notice

To view a full selection of Samlex products visit our website at www.samlexamerica.com or contact us: 1(800) 561-5885 or sales@samlexamerica.com