

MODEL: HAULSTER
TYPE: GASOLINE POWERED AUTOMATIC TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84059



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 26 hp (19.4 kW) rated, 4 cycle, 40.3 ci (660 cc) EFI, three cylinder, liquid-cooled by Suzuki

- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
- **Lubrication:** Pressurized oil system, spin-on filter
- **Air Cleaner:** Dry cartridge with evacuator valve
- **Fuel System:** Electronic fuel injection
- **Ignition:** Solid-state

Electrical: Starter, 60 Amp alternator, 12 Volt maintenance free battery (590 CCA, 85 minute reserve)

Ignition: Electronic with cam trigger, electronic advance & RPM limiter

Drive Train: 3 Speed automatic transmission. (3rd gear electronically disabled in Refresher application)

Brakes: 4 Wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo]. Mechanical hand brake

Rear axle: Differential with hypoid gears

Capacity: Seating for 2 persons

PRODUCT OVERVIEW

Dimensions		Performance	
Overall Length	136.0 in (345 cm)	Seating Capacity	2 Persons
Overall Width	53.0 in (135 cm)	Curb Weight	1440 lb (650 kg)
Overall Height (No Canopy)	51.0 in (130 cm) (Top of steering wheel)	Vehicle load capacity	2400 lb (1090 kg)
Overall Height (With ROPS)	74.0 in (188 cm)	Outside Clearance Circle	20.2 ft (6.2 m)
Wheel Base	88.2 in (224 cm)	Intersecting Aisle Clearance	N/A
Front Wheel Track	42.0 in (107 cm)	Speed (Governed, Level Gnd)	20 mph ± 0.5 mph (32 kph ± 0.8 kph)
Rear Wheel Track	44.0 in (112 cm)	Towing Capacity	2400 lb (1090 kg)
Gnd Clearance @ Differential	5.0 in (13 cm)	Steering & Suspension	
Cargo Deck Size	47.4 in (120 cm) W x 72 in (183 cm) L	Steering	Automotive power
Cargo Deck Material	Diamond pattern steel	Front Suspension	Double A-arm independent w/spring over shocks
Vehicle Power		Rear Suspension	Multiple leaf springs
Power Source	4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder	Rear Axle	Differential with hypoid gears
Valve Train	12 valve, dual OHV/OHC. Chain drive	Service Brake	4 Wheel 7.9 (20 cm) hydraulic drum
Horsepower (kW)	26.0 hp (19.4 kW) @ 3600 rpm (governed)	Parking Brake	Mechanical hand brake
Electrical System	12 Volt starter. 60 amp alternator	Front Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Battery (Qty, Type)	One 12 Volt maintenance free	Rear Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Key or Pedal Start	Key start	Body & Chassis	
Air Cleaner	Dry cartridge	Frame	Unitized welded steel channel. E-coat finish
Lubrication	Pressurized oil system	Front Body & Finish	Polyethylene
Oil Filter	Spin-on	Rear Body & Finish	Steel with rubber fender flairs
Cooling System	Liquid cooled	Storage	Hinged front cowl
Fuel Capacity	7.0 gallon (26.5 L) tank	Standard Color	Yellow
Transmission	3 Speed automatic		
Gear Selection	Neutral - Reverse - Park		
Gear Shift location	Dash		
Rear Axle Ratio	11.16:1		

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld	Item	Std	Opt	Fld
TIRES & WHEELS				WEATHER PROTECTION:			
Front & Rear:				Cab (includes ROPS, windshield wiper, front & rear windows)			
USA Trail 20.5 x 8 - 10 (Load range C)	●			Doors (Cab required) Hunter Green			●
COLORS:				Doors (Cab required) Yellow			
Body Color (Yellow)	●			Doors (Cab required) White			●
Body Color (White)		●		Doors (Cab required) Red			●
Body Color (Hunter Green)		●		CUSTOM REQUIREMENTS:			
Body Color (Red)		●		Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs			
Custom Body Color		●					
OTHER PERFORMANCE:							
Front Bumper		●					
Heater/Defroster		●					
Rear shock absorbers		●					
Rear View Mirrors (outside, qty 2)		●					
ROPS (Roll Over Protection, black with seat belts)		●					
Spark Arrestor			●				
HAULING & TOWING:							
Box sides & tailgate		●					
Pintle hitch (requires rear bumper)		●					
Rear Bumper		●					
Tow hitch (requires rear bumper)		●					
ELECTRICAL:							
12 Volt Outlet	●						
Back-up alarm		●					
Battery level gauge	●						
Brake Lights	●						
Dome Light (Cab Required)		●					
Fuel gauge	●						
Headlights	●						
Horn	●						
Hour meter	●						
Low fluid indicator	●						
Low oil pressure gauge	●						
Park brake Indicator	●						
Speedometer		●					
Tachometer	●						
Taillights	●						
Temperature gauge	●						
Turn Signals with 4-Way Flashers		●					
Volt meter	●						



MODEL: HAULSTER
TYPE: HIGH SPEED GASOLINE POWERED
MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84060

PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 32.2 hp (24.0 kW) rated, 4 cycle, 40.3 cid (660 cc) EFI, three cylinder, liquid-cooled by Suzuki

- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
- **Lubrication:** Pressurized oil system, spin-on filter 3.3 qt (3 L) capacity
- **Air Cleaner:** Dry cartridge with evacuator valve
- **Fuel System:** Electronic fuel injection
- **Ignition:** Solid-state

Electrical: Starter, 60 amp alternator, 12 Volt maintenance free battery (580 cca, 85 minute reserve)

Ignition: Electronic with cam trigger, electronic advance & RPM limiter

Drive Train: 5 Speed manual transmission. Low creeper first gear. All forward gears synchronized

Clutch: 6.7 in (17 cm) dry single disc & pressure plate

Brakes: 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake

Rear Axle: Differential with hypoid gears

Capacity: Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

Overall Length	136.0 in (345 cm)
Overall Width	53.0 in (135 cm)
Overall Height (to top of ROPS)	74.0 in (188 cm)
Wheel Base	88.2 in (224 cm)
Front Wheel Track	42.0 in (107 cm)
Rear Wheel Track	44.0 in (112 cm)
Gnd Clearance @ Differential	5.0 in (13 cm)
Cargo Deck Size	47.4 in (120 cm) W x 72 in (183 cm) L
Cargo Deck Material	Diamond pattern steel

Vehicle Power

Power Source	4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder
Valve Train	12 valve, dual OHV/OHC. Chain drive
Horsepower (kW)	32.2 hp (24.0 kW) @ 4450 rpm (governed)
Electrical System	12 Volt starter. 60 amp alternator
Battery (Qty, Type)	One 12 Volt maintenance free
Key or Pedal Start	Key start
Air Cleaner	Dry cartridge
Lubrication	Pressurized oil system
Oil Filter	Spin-on
Cooling System	Liquid cooled
Fuel Capacity	7.0 gallon (26.5 L) tank
Transmission	Synchronized 5 Speed manual
Gear Selection	5 speeds forward - Neutral - Reverse
Gear Shift location	Dash
Rear Axle Ratio	11.16:1

Performance

Seating Capacity	2 Persons
Curb Weight	1540 lb (699 kg)
Vehicle load capacity	2400 lb (1090 kg)
Outside Clearance Circle	20.2 ft (6.2 m)
Intersecting Aisle Clearance	N/A
Speed (Governed, Level Gnd)	25.5 mph ± 0.5 mph (41 kph ± 0.8 kph)
Towing Capacity	2400 lb (1090 kg)

Steering & Suspension

Steering	Automotive power
Front Suspension	Double A-arm independent w/spring over shocks
Rear Suspension	Multiple leaf springs
Rear Axle	Differential with hypoid gears
Service Brake	4 Wheel 7.9 (20 cm) hydraulic drum
Parking Brake	Mechanical hand brake
Front Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Rear Tires	USA Trail 20.5 x 8 - 10 (Load range C)

Body & Chassis

Frame	Unitized welded steel channel. E-coat finish
Front Body & Finish	Polyethelene
Rear Body & Finish	Steel with rubber fender flairs
Storage	Hinged front cowl
Standard Color	Yellow
Roll Over Protective Structure	2 post ROPS - standard

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld	Item	Std	Opt	Fld
TIRES & WHEELS				CUSTOM REQUIREMENTS:			
Front & Rear:				Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs			
USA Trail 20.5 x 8 - 10 (Load range C)							
COLORS:							
Body Color (Yellow)							
Body Color (Hunter Green)							
Body Color (White)							
Body Color (Red)							
Custom Body Color							
OTHER PERFORMANCE:							
Front Bumper							
Rear shock absorbers							
ROPS (Roll Over Protection, black with seat belts)							
Spark Arrestor							
HAULING & TOWING:							
Box sides & tailgate							
Pintle hitch (requires rear bumper)							
Rear Bumper							
Tow hitch (requires rear bumper)							
ELECTRICAL:							
12 Volt Outlet							
Back-up alarm							
Battery level gauge							
Brake Lights							
Fuel gauge							
Headlights							
Horn							
Hour meter							
Low fluid indicator							
Low oil pressure gauge							
Park brake Indicator							
Speedometer							
Tachometer							
Taillights							
Temperature gauge							
Volt meter							

MODEL: HAULSTER
TYPE: DIESEL POWERED MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84065



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 24.8 hp (18.5 kW) rated, 4 cycle, 69 cid (1123 cc) EFI, three cylinder, liquid-cooled Kubota D1105 Diesel

- **Fuel System:** Indirect
- **Lubrication:** Pressurized oil system, spin-on filter 1.35 gal (5.1 L) capacity
- **Air Cleaner:** Dry cartridge with evacuator valve

Electrical: Starter, 60 amp alternator, 12 Volt maintenance free battery (590 cca, 85 minute reserve)

Acceptable Fuel: N590 Diesel fuel types - Auto / C0 / C1 / C2 / C3 / C4, BS2869 Class A2, ASTM D 975-92 Class 1, 2 and 3 & special grade 3
or
Low Sulphur Diesel (LSD S500) & Ultra Low Sulphur Diesel (USLD S15)
or
Bio-diesel - R.M.E. meeting DIN V 51606, Up to 5% RME. No mixture above 5% is acceptable

Drive Train: 4-speed manual transmission. Low creeper first gear. All forward gears synchronized

Clutch: 7.1 in (18 cm) dry single disc & pressure plate

Brakes: 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake

Rear Axle: Differential with hypoid gears

Capacity: Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

Overall Length	136.0 in (345 cm)
Overall Width	53.0 in (135 cm)
Overall Height (No Canopy)	51.0 in (130 cm) (Top of steering wheel)
Overall Height (With ROPS)	74.0 in (188 cm)
Wheel Base	88.2 in (224 cm)
Front Wheel Track	42.0 in (107 cm)
Rear Wheel Track	44.0 in (112 cm)
Gnd Clearance @ Differential	5.0 in (13 cm)
Cargo Deck Size	47.4 in (120 cm) W x 72 in (183 cm) L
Cargo Deck Material	Diamond pattern steel

Vehicle Power

Power Source	3 Cylinder Liquid-Cooled Kubota Diesel
Horsepower (kW)	24.8 hp (18.5 kW) @ 3000 rpm (governed)
Electrical System	12 Volt starter. 60 amp alternator
Battery (Qty, Type)	One 12 Volt maintenance free
Key or Pedal Start	Key start
Air Cleaner	Dry cartridge
Lubrication	Pressurized oil system
Oil Filter	Spin-on
Cooling System	Liquid cooled
Fuel Capacity	7.0 gallon (26.5 L) tank
Transmission	Synchronized 4 Speed manual
Gear Selection	4 speeds forward - Neutral - Reverse
Gear Shift location	Dash

Rear Axle Ratio	11.16:1
Gear Shift location	Dash

Performance

Seating Capacity	2 Persons
Curb Weight	1570 lb (710 kg)
Vehicle load capacity	2400 lb (1090 kg)
Outside Clearance Circle	20.2 ft (6.2 m)
Intersecting Aisle Clearance	N/A
Speed (Governed, Level Gnd)	17.5 mph ± 0.5 mph (28 kph ± 0.8 kph)
Towing Capacity	2400 lb (1090 kg)

Steering & Suspension

Steering	Automotive power
Front Suspension	Double A-arm independent w/spring over shocks
Rear Suspension	Multiple leaf springs
Rear Axle	Differential with hypoid gears
Service Brake	4 Wheel 7.9 (20 cm) hydraulic drum
Parking Brake	Mechanical hand brake
Front Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Rear Tires	USA Trail 20.5 x 8 - 10 (Load range C)

Body & Chassis

Frame	Unitized welded steel channel. E-coat finish
Front Body & Finish	Polyethelene
Rear Body & Finish	Steel with rubber fender flairs
Storage	Hinged front cowl
Standard Color	Yellow

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld	Item	Std	Opt	Fld
TIRES & WHEELS				WEATHER PROTECTION:			
Front & Rear:				Cab (includes ROPS, windshield wiper, front & rear windows)			
USA Trail 20.5 x 8 - 10 (Load range C)	●			Doors (Cab required) Hunter Green			●
COLORS:				Doors (Cab required) Yellow			
Body Color (Yellow)	●			Doors (Cab required) White			●
Body Color (Hunter Green)		●		Doors (Cab required) Red			●
Body Color (White)		●		CUSTOM REQUIREMENTS:			
Body Color (Red)		●		Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs			
Custom Body Color		●					
OTHER PERFORMANCE:							
Front Bumper		●					
Heater/Defroster		●					
Rear shock absorbers		●					
Rear View Mirrors (outside, qty 2)		●					
ROPS (Roll Over Protection, black with seat belts)		●					
Spark Arrestor			●				
HAULING & TOWING:							
Box sides & tailgate		●					
Pintle hitch (requires rear bumper)		●					
Rear Bumper		●					
Tow hitch (requires rear bumper)		●					
ELECTRICAL:							
12 Volt Outlet	●						
Back-up alarm		●					
Battery level gauge	●						
Brake Lights	●						
Dome Light (Cab Required)		●					
Fuel gauge	●						
Headlights	●						
Horn	●						
Hour meter	●						
Low fluid indicator	●						
Low oil pressure gauge	●						
Park brake Indicator	●						
Speedometer		●					
Tachometer	●						
Taillights	●						
Temperature gauge	●						
Turn Signals with 4-Way Flashers		●					
Volt meter	●						

MODEL: HAULSTER
TYPE: GASOLINE POWERED MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2010
Part No.: 84058



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

- Engine:** 26 hp (19.4 kW) rated, 4 cycle, 40.3 cid (660 cc) EFI, three cylinder, liquid-cooled by Suzuki
- **Valve Train:** 12 overhead valves, dual overhead cam, chain drive
 - **Fuel System:** Electronic fuel injection
 - **Lubrication:** Pressurized oil system, spin-on filter 3.3 qt (3 L) capacity
 - **Ignition:** Solid-state
 - **Air Cleaner:** Dry cartridge with evacuator valve
- Electrical:** Starter, 60 amp alternator, 12 Volt maintenance free battery (580 cca, 85 minute reserve)
- Ignition:** Electronic with cam trigger, electronic advance & RPM limiter
- Drive Train:** 5 Speed manual transmission. Low creeper first gear. All forward gears synchronized
- Clutch:** 6.7 in (17 cm) dry single disc & pressure plate
- Brakes:** 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake
- Rear Axle:** Differential with hypoid gears
- Capacity:** Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

Overall Length	136.0 in (345 cm)
Overall Width	53.0 in (135 cm)
Overall Height (No Canopy)	51.0 in (130 cm) (Top of steering wheel)
Overall Height (With ROPS)	74.0 in (188 cm)
Wheel Base	88.2 in (224 cm)
Front Wheel Track	42.0 in (107 cm)
Rear Wheel Track	44.0 in (112 cm)
Gnd Clearance @ Differential	5.0 in (13 cm)
Cargo Deck Size	47.4 in (120 cm) W x 72 in (183 cm) L
Cargo Deck Material	Diamond pattern steel

Vehicle Power

Power Source	4 cycle, 40.3 ci (660 cc) EFI, 3 cylinder
Valve Train	12 valve, dual OHV/OHC. Chain drive
Horsepower (kW)	26.0 hp (19.4 kW) @ 3600 rpm (governed)
Electrical System	12 Volt starter. 60 amp alternator
Battery (Qty, Type)	One 12 Volt maintenance free
Key or Pedal Start	Key start
Air Cleaner	Dry cartridge
Lubrication	Pressurized oil system
Oil Filter	Spin-on
Cooling System	Liquid cooled
Fuel Capacity	7.0 gallon (26.5 L) tank
Transmission	Synchronized 5 Speed manual
Gear Selection	5 speeds forward - Neutral - Reverse
Gear Shift location	Dash
Rear Axle Ratio	11.16:1

Performance

Seating Capacity	2 Persons
Curb Weight	1440 lb (650 kg)
Vehicle load capacity	2400 lb (1090 kg)
Outside Clearance Circle	20.2 ft (6.2 m)
Intersecting Aisle Clearance	N/A
Speed (Governed, Level Gnd)	20 mph ± 0.5 mph (32 kph ± 0.8 kph)
Towing Capacity	2400 lb (1090 kg)

Steering & Suspension

Steering	Automotive power
Front Suspension	Double A-arm independent w/spring over shocks
Rear Suspension	Multiple leaf springs
Rear Axle	Differential with hypoid gears
Service Brake	4 Wheel 7.9 (20 cm) hydraulic drum
Parking Brake	Mechanical hand brake
Front Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Rear Tires	USA Trail 20.5 x 8 - 10 (Load range C)

Body & Chassis

Frame	Unitized welded steel channel. E-coat finish
Front Body & Finish	Polyethelene
Rear Body & Finish	Steel with rubber fender flairs
Storage	Hinged front cowl
Standard Color	Yellow

Some items shown may be optional equipment

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld	Item	Std	Opt	Fld
TIRES & WHEELS				WEATHER PROTECTION:			
Front & Rear:				Cab (includes ROPS, windshield wiper, front & rear windows)			
USA Trail 20.5 x 8 - 10 (Load range C)	●			Doors (Cab required) Hunter Green			●
COLORS:				Doors (Cab required) Yellow			
Body Color (Yellow)	●			Doors (Cab required) Red			●
Body Color (White)		●		Doors (Cab required) White			●
Body Color (Hunter Green)		●		CUSTOM REQUIREMENTS:			
Body Color (Red)		●		Contact Innovative Designs @ 800 241-5855 X 5972 for quote of individual customer needs			
Custom Body Color		●					
OTHER PERFORMANCE:							
Front Bumper		●					
Heater/Defroster		●					
Rear View Mirrors (outside, qty 2)		●					
ROPS (Roll Over Protection, black with seat belts)		●					
Spark Arrestor			●				
HAULING & TOWING:							
Box sides & tailgate		●					
Pintle hitch (requires rear bumper)		●					
Rear Bumper		●					
Tow hitch (requires rear bumper)		●					
ELECTRICAL:							
12 Volt Outlet	●						
Back-up alarm		●					
Battery level gauge	●						
Brake Lights	●						
Dome Light (Cab Required)		●					
Fuel gauge	●						
Headlights	●						
Horn	●						
Hour meter	●						
Low fluid indicator	●						
Low oil pressure gauge	●						
Park brake Indicator	●						
Speedometer		●					
Tachometer	●						
Taillights	●						
Temperature gauge	●						
Turn Signals with 4-Way Flashers		●					
Volt meter	●						