

CR-10 Chariot | Specifications & Features



CR-10

12 - Volt
1 Passenger
Series Powered

Performance	
Speed, Forward - Maximum	9 MPH
Turning - Curb to Curb	79 Inches
Turning - Intersecting Aisle	41 Inches
Dimensions & Weight	
Overall L x W x H (inches)	52 x 29.5 x 44
Wheelbase (inches)	36
Load Bed Height (inches)	24
Load Bed - L x W (inches)	18 X 16
Vehicle Weight (lbs)	366
Rated Capacity ¹ (lbs)	400
Power Train	
Motor	12-Volt DC, Series wound, Solid copper windings, Class H insulation
Horsepower	0.7 HP at 750 rpm
Batteries	two 6 volt, 225 amp hour, 115 minute, deep cycle
Charger	Built-in, automatic, 120 VAC 60 HZ
Speed Control	3 speed, slide-bar switch
Drive Unit / Differential	Heavy-duty chain to drive wheel, 7:4:1 final drive ratio
Body	
Passenger Capacity	1 passenger - stand up operation
Body	14-gauge Powder coated Diamond plate steel
Instrumentation & Accessories	Dash mounted forward directional controls only, Horn, Battery discharge indicator, Clipboard, Shin guard, Handlebar steering
Chassis	
Frame	Heavy duty welded steel chassis
Steering	Handle bar to front fork
Brakes	4.5" mechanical drum on drive wheel, automatically engaged upon dismount
Tires	4.80" X 8", pneumatic, 6-ply rated, load range C
Popular Options	
	Hour meter, In motion beeper - Non-removable key Electric reverse switch (includes reverse warning alarm) Various tires, Portable charger

* Includes personal, cargo, options and accessories

All specifications are subject to change without notice.

04 -1503