



## XLR w/Rev Cams 2009

**A-A** 37" +/- .1875

**Brace** 8 1/2" +/- .125

**String** 60 11/16"

**Cable** 41 9/16"

<b>Rev Cam</b>	<b>Cam setting @ Brace from .160 hole to <b>inside</b> of limb +/- .050</b>	<b>Speed Rating #70 350 grain arrow</b>
<b>#1 – 32"</b>	<b>.270 gap</b>	<b>330-340 fps</b>
<b>#2 – 31.5"</b>	<b>.170 gap</b>	<b>325-335 fps</b>
<b>#3 – 31"</b>	<b>.130 gap</b>	<b>320-330 fps</b>
<b>#4 – 30.5"</b>	<b>.120 gap</b>	<b>315-325 fps</b>
<b>#5 – 30"</b>	<b>.150 gap</b>	<b>310-320 fps</b>
<b>#6 – 29.5"</b>	<b>.095 gap</b>	<b>305-315 fps</b>
<b>#7 – 29"</b>	<b>.100 gap</b>	<b>298-308 fps</b>

**Deduct 5 fps from rating for #60 peak**

<b>Limb Deflection</b>	<b>Poundage of Bow</b>	<b>Pivots</b>
105	80	Tall
114	70	Tall
135	60	Tall
210	50	Tall
<b>Speed Buttons</b>	<b>Qty</b>	<b>Location</b>
<b>Black(new ones)</b>	2	1 <sup>st</sup> one 4.5" from axle
<b>Spacers</b>	.035 on cable side	.090 on string side
<b>Cable Rod</b>	8 1/2"	
<b>Suppressor Rod with bends</b>	6 1/2"	