



## 2010 GT500

**A-A** 34 7/8" +/- .1875

**Brace** 7 1/8" +/- .125

**String** 58 7/16"

**Cable** 39 1/2"

**Rev Cam**  
(Modular)

Cam setting @ Brace from  
.160 hole to inside of limb

**Speed Rating**  
#70 350 grain arrow

**#0 – 31"**

**.250 gap**

**342-346 fps**

**#0.5 – 30.5"**

**.210 gap**

**337-341 fps**

**#1 – 30"**

**.170 gap**

**332-336 fps**

**#2 – 29.5"**

**Even with the Edge**

**327-331 fps**

**#3 – 29"**

**.010 under limb**

**322-326 fps**

**#4 – 28.5"**

**.035 under limb**

**317-321 fps**

**#5 – 28"**

**.050 under limb**

**312-316 fps**

**#6 – 27.5"**

**.070 under limb**

**307-311 fps**

**#7 – 27"**

**.080 under limb**

**302-306 fps**

**Deduct 5 fps from rating for #60 peak**

**Limb Deflection**

**Poundage of Bow**

**Pivots**

81  
90  
105  
123

90  
80  
70  
60

Tall  
Tall  
Tall  
Tall

**Speed Buttons**

**Qty**

**Location**

Custom Elite

2

1<sup>st</sup> one 4" from axle

**Spacers**

.090 string side +/- .005

.035 on cable side +/- .005

**Cable Rod**

7"

**Suppressor Rod w/ Bends**

5"