



## 2011 HUNTER

**A-A** 31 3/4" +/- .125"

**Brace** 7 1/2" +/- .125

**String** 54 1/2"

**Cable** 36 3/8"

**ESX Cam**  
(Modular)

Cam setting @ Brace from  
.160 hole to inside of limb

**Speed Rating**  
#70 350 grain arrow

**#1 – 30"**

**.860" gap**

**320-323 fps**

**#2 – 29.5"**

**.880" gap**

**315-318 fps**

**#3 – 29"**

**.885" gap**

**310-313 fps**

**#4 – 28.5"**

**.835" gap**

**305-308 fps**

**#5 – 28"**

**.785" gap**

**300-303 fps**

**#6 – 27.5"**

**.740" gap**

**292-295 fps**

**#7 – 27"**

**.700" gap**

**286-289 fps**

**Deduct 2 fps from rating for #60 peak weight**

**Limb Deflection**

**Poundage of Bow**

**Pivots**

90

80

Tall

105

70

Tall

123

60

Tall

220

50

Tall

250

40

Tall

**Speed Buttons**

**Qty**

**Location**

Custom Elite

2

1<sup>st</sup> one 4" from axle

**Spacers**

.060" string side

.070"+/- .005" cable side

**Cable Rod** 7"

**Suppressor Rod with bends** 5 1/2"