

M-SERIES

M-SERIES OUTDOOR UNITS CUT IN/OUT TEMPERATURES



Model Name	Operation Range							
	Cooling Operation Range		Cut in/Cut out in Cooling Mode		Heating Operation Range		Cut in/Cut out in Heating Mode	
	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)
MUY-GE Models								
MUY-GE09NA	14	115	0	-4	N.A	N.A	N.A	N.A
MUY-GE12NA	14	115	0	-4	N.A	N.A	N.A	N.A
MUY-GE15NA	14	115	0	-4	N.A	N.A	N.A	N.A
MUY-GE18NA	14	115	0	-4	N.A	N.A	N.A	N.A
MUY-GE24NA	0	115	0	-4	N.A	N.A	N.A	N.A
MUY-GE09NA2	14	115	0	-4	N.A	N.A	N.A	N.A
MUY-GE12NA2	14	115	0	-4	N.A	N.A	N.A	N.A
MUY-GE15NA2	14	115	0	-4	N.A	N.A	N.A	N.A
MUY-D Models								
MUY-D30NA	14	115	-0.4	-4	N.A	N.A	N.A	N.A
MUY-D36NA	14	115	-0.4	-4	N.A	N.A	N.A	N.A
MUY-GL Models								
MUY-GL09NA	14	115	3	-1	N.A	N.A	N.A	N.A
MUY-GL12NA	14	115	3	-1	N.A	N.A	N.A	N.A
MUY-GL15NA	14	115	3	-1	N.A	N.A	N.A	N.A
MUY-GL18NA	14	115	3	-1	N.A	N.A	N.A	N.A
MUY-GL24NA	14	115	0	-4	N.A	N.A	N.A	N.A
MUZ-GE Models								
MUZ-GE09NA	14	115	0	-4	-4	75	-4	-9
MUZ-GE12NA	14	115	0	-4	-4	75	-4	-9
MUZ-GE15NA	14	115	0	-4	-4	75	-4	-9
MUZ-GE18NA	14	115	0	-4	-4	75	-4	-9
MUZ-GE24NA	0	115	0	-4	-4	75	-4	-9
MUZ-GE09NA2	14	115	0	-4	-4	75	-4	-9
MUZ-GE12NA2	14	115	0	-4	-4	75	-4	-9
MUZ-GE15NA2	14	115	0	-4	-4	75	-4	-9
MUZ-D Models								
MUZ-D30NA	14	115	-0.4	-4	14	75	N.A	N.A
MUZ-D36NA	14	115	-0.4	-4	14	75	N.A	N.A
MUZ-GL Models								
MUZ-GL09NA	14	115	3	-1	-4	75	-4	-9
MUZ-GL12NA	14	115	3	-1	-4	75	-4	-9
MUZ-GL15NA	14	115	3	-1	-4	75	-4	-9
MUZ-GL18NA	14	115	3	-1	-4	75	-4	-9
MUZ-GL24NA	14	115	0	-4	-4	75	-4	-9

M-SERIES OUTDOOR UNIT CUT IN/OUT TEMPERATURES TABLE, CONT.

Model Name	Operation Range							
	Cooling Operation Range		Cut in/Cut out in Cooling Mode		Heating Operation Range		Cut in/Cut out in Heating Mode	
	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)
MUZ-FE Models								
MUZ-FE09NA	14	115	0	-4	-13	75	-14	-18
MUZ-FE12NA	14	115	0	-4	-13	75	-14	-18
MUZ-FE18NA	0	115	0	-4	-13	75	-14	-18
MUZ-FH Models								
MUZ-FH06NA	14	115	3	-1	-13	75	-14	-18
MUZ-FH09NA	14	115	3	-1	-13	75	-14	-18
MUZ-FH12NA	14	115	3	-1	-13	75	-14	-18
MUZ-FH15NA	14	115	0	-4	-13	75	-14	-18
MUZ-FH18NA2	14	115	0	-4	-13	75	-14	-18
MUZ-FH06NAH	14	115	0	-4	-13	75	-14	-18
MUZ-FH09NAH	14	115	0	-4	-13	75	-14	-18
MUZ-FH12NAH	14	115	0	-4	-13	75	-14	-18
MUZ-FH15NAH	14	115	0	-4	-13	75	-14	-18
MUZ-FH18NAH2	14	115	0	-4	-13	75	-14	-18
MUZ-HE Models								
MUZ-HE09NA	14	115	0	-4	-4	75	-4	-9
MUZ-HE12NA	14	115	0	-4	-4	75	-4	-9
MUZ-HE15NA	14	115	0	-4	-4	75	-4	-9
MUZ-HE18NA	14	115	0	-4	-4	75	-4	-9
MUZ-HE24NA	0	115	0	-4	-4	75	-4	-9
MUZ-JP Models								
MUZ-JP09WA	14	115	3	-1	-4	75	-4	-9
MUZ-JP12WA	14	115	3	-1	-4	75	-4	-9
MUZ-WR Models								
MUZ-WR09NA	32	115	3	-1	-4	75	-4	-9
MUZ-WR12NA	32	115	3	-1	-1	75	-4	-9
MUZ-WR18NA	32	115	3	-1	-1	75	-4	-9
MUZ-WR24NA	32	115	3	-1	-1	75	-4	-9

M-SERIES OUTDOOR UNIT CUT IN/OUT TEMPERATURES TABLE, CONT.

Model Name	Operation Range							
	Cooling Operation Range		Cut in/Cut out in Cooling Mode		Heating Operation Range		Cut in/Cut out in Heating Mode	
	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)
MUZ-HM Models								
MUZ-HM09NA	14	115	3	-1	5	75	-4	-9
MUZ-HM12NA	14	115	3	-1	5	75	-4	-9
MUZ-HM15NA	14	115	3	-1	5	75	-4	-9
MUZ-HM18NA	14	115	3	-1	5	75	-4	-9
MUZ-HM24NA	14	115	3	-1	5	75	-4	-9
MUZ-HM09NA2	14	115	3	-1	-4	75	-4	-9
MUZ-HM12NA2	14	115	3	-1	-4	75	-4	-9
MUZ-HM15NA2	14	115	3	-1	-4	75	-4	-9
MUZ-HM18NA2	14	115	3	-1	-4	75	-4	-9
MUZ-HM24NA2	14	115	3	-1	-4	75	-4	-9
MUFZ-KJ Models								
MUFZ-KJ09NA	14	115	14	11	-13	75	-14	-18
MUFZ-KJ12NA	14	115	14	11	-13	75	-14	-18
MUFZ-KJ15NA	14	115	14	11	-13	75	-14	-18
MUFZ-KJ18NA	14	115	14	11	-13	75	-14	-18
SUZ-KA Models								
SUZ-KA09NA	14	115	-4	-9	-4	75	-4	-9
SUZ-KA12NA	14	115	-4	-9	-4	75	-4	-9
SUZ-KA15NA	14	115	-4	-9	-4	75	-4	-9
SUZ-KA18NA	14	115	-4	-9	-4	75	-4	-9
SUZ-KA09NAR1	14	115	-4	-9	-4 ¹	75	-4	-9
SUZ-KA12NAR1	14	115	-4	-9	-4 ¹	75	-4	-9
SUZ-KA15NAR1	14	115	-4	-9	-4 ¹	75	-4	-9
SUZ-KA18NAR1	14	115	-4	-9	-4 ¹	75	-4	-9
SUZ-KA09NA2	14	115	3	-1	-4	75	-4	-9
SUZ-KA12NA2	14	115	3	-1	-4	75	-4	-9
SUZ-KA15NA2	14	115	3	-1	-4	75	-4	-9
SUZ-KA18NA2	14	115	3	-1	-4	75	-4	-9
SUZ-KA24NA2	14	115	5	-1	14	75	14	10
SUZ-KA30NA2	14	115	5	-1	14	75	14	10
SUZ-KA36NA2	14	115	5	-1	14	75	14	10

¹ The minimum heating operation range for combination with SVZ and PEAD is 12° F

M-SERIES OUTDOOR UNIT CUT IN/OUT TEMPERATURES TABLE, CONT.

Model Name	Operation Range							
	Cooling Operation Range		Cut in/Cut out in Cooling Mode		Heating Operation Range		Cut in/Cut out in Heating Mode	
	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)	Min (° F)	Max (° F)	Cut in (° F)	Cut out (° F)
MXZ-B Models								
MXZ-2B20NA-1	14	115	14	10.4	6	75	N.A	N.A
MXZ-2B20NA-2	14	115	14	10.4	6	75	5	1.4
MXZ-3B24NA-1	14	115	14	10.4	6	75	5	1.4
MXZ-3B30NA-1	14	115	14	10.4	6	75	5	1.4
MXZ-4B36NA-1	14	115	14	10.4	6	75	5	1.4
MXZ-5B42NA	14	115	14	10.4	6	75	N.A	N.A
MXZ-8B48NA	23	115	N.A	N.A	5	70	N.A	N.A
MXZ-C Models								
MXZ-3C24NA	14	115	14	10.4	5	75	5	1.4
MXZ-3C30NA	14	115	14	10.4	5	75	5	1.4
MXZ-4C36NA	14	115	14	10.4	5	75	5	1.4
MXZ-5C42NA	14	115	14	10.4	5	75	5	1.4
MXZ-2C20NA2	14	115	14	10.4	5	75	5	1.4
MXZ-3C24NA2	14	115	14	10.4	5	75	5	1.4
MXZ-3C30NA2	14	115	14	10.4	5	75	5	1.4
MXZ-4C36NA2	14	115	14	10.4	5	75	5	1.4
MXZ-5C42NA2	14	115	14	10.4	5	75	5	1.4
MXZ-8C48NA	23	115	N.A	N.A	-4	70	N.A	N.A
MXZ-8C60NA	23	115	N.A	N.A	-4	70	N.A	N.A
H2i® MXZ-C Models								
MXZ-2C20NAHZ	14	115	14	10.4	-13	75	-14	-18
MXZ-3C24NAHZ	14	115	14	10.4	-13	75	-14	-18
MXZ-3C30NAHZ	14	115	14	10.4	-13	75	-14	-18
MXZ-2C20NAHZ2	14	115	14	10.4	-13	75	-14	-18
MXZ-3C24NAHZ2	14	115	14	10.4	-13	75	-14	-18
MXZ-3C30NAHZ2	14	115	14	10.4	-13	75	-14	-18
MXZ-4C36NAHZ	23	115	N.A	N.A	-13	70	N.A	N.A
MXZ-5C42NAHZ	23	115	N.A	N.A	-13	70	N.A	N.A
MXZ-8C48NAHZ	23	115	N.A	N.A	-13	70	N.A	N.A



1340 Satellite Boulevard, Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com