MITSUBISHI ELECTRIC

Mr. SLIM®
Split-ductless A/C and Heat Pumps

SUBMITTAL DATA: MSZ-FE12NA. . . . . .12,000 BTU/H WALL-MOUNTED INDOOR UNIT FOR MXZ MULTI-ZONE HEAT-PUMP SYSTEMS

Job Name: Location: Date:

Purchaser: Engineer:

Submitted to: For ☐ Reference ☐ Approval ☐ Construction

System Designation: Schedule No.:

GENERAL FEATURES

- Highly energy-efficient system with quiet operation
- Updated sleek, compact indoor unit design
- Includes Standard, Platinum Deodorizing, and Anti-allergy Enzyme Filters for a complete air purifying system
- "Powerful Mode" function permits system to temporarily run at a lower/higher temperature with an increased fan speed, which quickly brings the room to the optimum comfort level
- Integrated i-see sensor automatically detects room air temperature
- Autochangeover for cooling and heating
- Wireless remote controller
- Limited warranty: five years on parts and defects and seven years on compressors

OPTIONAL ACCESSORIES

Indoor Unit

- ◘ Condensate Pump (SI3100-230; 230V)
- ◘ Replacement Platinum Deodorizing Filter (MAC-308FT)
- ◘ Replacement Anti-allergy Enzyme Filters (MAC-418FT; MERV 8)

Controller Options

- ◘ Wall-mounted Wired Controller (PAR-21MAA; req. MAC-3971F)
- ◘ MA Contact Terminal Interface (MAC-397IF)
- ◘ M-NET Control Adapter (MAC-399IF)
- ◘ Remote Temperature Sensor (M21-JKO-307)
- ◘ Lockdown Bracket for Handheld Controller (RCMKP1CB)

Cooling Capacity* . . . . . .12,000 Btu/h
Heating Capacity* . . . . . .13,600 Btu/h

* Rating Conditions (Cooling) - Indoor: 80°F (27°C) DB, 67°F (19°C) WB; Outdoor: 95°F (35°C) DB, 75°F (24°C) WB.
(Heating at 47°F) - Indoor: 70°F (21°C) DB, 60°F (16°C) WB; Outdoor: 47°F (8°C) DB, 43°F (6°C) WB.
(For data on specific indoor units [all ducted, all non-ducted, and both ducted and non-ducted] combinations, see the MXZ Technical and Service Manual.)

Electrical Requirements

Power Supply . . . . . .208 / 230V, 1-Phase, 60 Hz
MCA . . . . . 1 A



Indoor Unit: MSZ-FE12NA



Wireless Remote Controller

Voltage
Indoor - Outdoor S1-S2 . . . . . .AC 208 / 230V
Indoor - Outdoor S2-S3 . . . . . DC 12-24V

Fan Motor . . . . . .0.76 F.L.A.

Airflow
Cooling (Lo - Med - Hi - Powerful) . . . . . 162 - 226 - 381 - 410 Dry CFM
144 - 202 - 305 - 367 Wet CFM
Heating (Lo - Med - Hi - Powerful) . . . . . 166 - 240 - 399 - 420 Dry CFM
Sound Pressure Level (Lo - Med - Hi - Powerful)
Cooling . . . . . 22 - 33 - 43 - 45 dB(A)
Heating . . . . . 22 - 33 - 43 - 44 dB(A)

DIMENSIONS	UNIT INCHES / MM
W	31-7/16 / 799
D	10-1/8 / 257
H	11-5/8 / 295

Weight . . . . . .27 lbs. / 12 kg

External Finish . . . . . .Munsell No. 1.0Y 9.2 / 0.2
Field Drainpipe Size O.D. . . . . .5/8" / 15.88 mm

Refrigerant Type R410A
Refrigerant Pipe Size O.D.
Gas Side . . . . . .3/8" / 9.52 mm
Liquid Side. . . . . .1/4" / 6.35 mm
Connection Method . . . . . .Flared

MXZ-B SERIES HEAT-PUMP OUTDOOR UNITS



Outdoor Unit: MXZ-4B36NA


MXZ-B MULTI-ZONE SYSTEMS CAN INCLUDE:

- Ducted Indoor Units:
  SEZ-KD09,12,15,18NA, PEAD-A24AA
- Nonducted Indoor Units:
  MSZ-GE06,09,12,15,18,24NA, MSZ-FE09,12,18NA, MFZ-KA09,12,18NA, PCA-A24KA, SLZ-KA09,12,15NA, and PLA-A12,18,24BA
- A combination of both Ducted and Nonducted Indoor Units

Refer to the separate submittal forms for the MSZ-GE, MSZ-FE, MFZ-KA, SEZ-KD, SLZ-KA, PEAD, PCA, PLA Indoor Units, and MXZ Outdoor Units.



MSZ-GE



SEZ-KD and PEAD-A24



MSZ-FE



MFZ-KA



PCA-KA




SLZ-KA and PLA-ABA

INVERTER R410A

DIMENSIONS: MSZ-FE12NA

Unit: inch



Piping	Insulation	ø1-3/8 O.D
	Liquid line	ø1/4 19-11/16 (Flared connection ø1/4)
	Gas line	ø3/8 16-15/16 (Flared connection ø3/8)
Drain hose		Insulation ø1-1/8 O.D Connected part ø5/8 O.D

AHRI CERTIFIED™ www.ahridirectory.org
Unitary Small HP
AHRI Standard 210/240
Certification applies only when the complete system is listed with AHRI

ETL LISTED®

ENERGY STAR PARTNER

MITSUBISHI ELECTRIC

HVAC Advanced Products Division
3400 Lawrenceville Suwanee Rd
Suwanee, GA 30024
Tele: 678-376-2900 • Fax: 800-889-9904
Toll Free: 800-433-4822 (#3)
www.mehvac.com

Specifications are subject to change without notice.

 © MITSUBISHI ELECTRIC / HVAC 2011