

Job Name:	
System Reference:	Date:



Indoor Unit: PCA-A30KA6



Outdoor Unit: PUZ-A30NHA6 (-BS)

UNIT OPTION:

- ☐ Standard Model.....PUZ-A30NHA6
- ☐ Seacoast (BS) Model.....PUZ-A30NHA6-BS

ACCESSORIES:

Indoor Unit

- ☐ Condensate Pump (BlueDiamond X87-711/721; 115/230V)
- ☐ Condensate Pump (Sauermann SI30-115/230; 115/230V)
- ☐ High-Efficiency Filter (PAC-SH89KF-E)
- ☐ iSee Sensor (PAC-SH91MK-E)
- ☐ Disconnect Switch (TAZ-MS303)

Outdoor Unit

- ☐ Wind Baffle (WB-PA2)*
- *Allows operation to 0° F (-18° C).
- ☐ Air Outlet Guide (PAC-SG59SG-E)
- ☐ Mounting Base (QSMS1201)
- ☐ Wall Bracket (QSWB2000M-1)

Controls

- ☐ Wireless Controller (MHK1)
- ☐ Advanced Wired Controller (PAR-31MAA)
- ☐ Simple Wired Controller (PAC-YT53CRAU)
- ☐ M-NET Adapter (PAC-SF83MA-E)
- ☐ Temperature Sensor (PAC-SE41TS)

SPECIFICATIONS:

Rated Conditions (Capacity / Input)*		
Cooling	Btu/h / W	30,000 / 3,760
Heating at 47° F	Btu/h / W	32,000 / 3,210
Heating at 17° F	Btu/h / W	23,000 / 2,940

* Rating Conditions per AHRI Standard:
Cooling | Indoor: 80° F (27° C)DB / 67° F (19° C)WB; Outdoor: 95° F (35° C)DB / 75° F (24° C)WB
Heating at 47°F | Indoor: 70° F (21° C)DB / 60° F (16° C)WB; Outdoor: 47° F (8° C)DB / 43° F (6° C)WB
Heating at 17° F | Indoor: 70° F (21° C)DB / 60° F (16° C)WB; Outdoor: 17° F (-8° C)DB / 15° F (-9° C)WB

Capacity Range		
Cooling	Btu/h	12,000 - 30,000
Heating at 47° F	Btu/h	12,000 - 34,000

Operating Range	
Cooling	0° F** to 115° F (-18° C to 46° C) DB
Heating	12° F to 70° F (-11° C to 21° C) DB

** The minimum temperature will be 23° F (-5° C) DB if optional wind baffle accessory is not installed.

AHRI Efficiency Ratings	
EER	8.0
SEER	14.5
HSPF	9.2
COP at 47° F	2.92
COP at 17° F	2.29

Electrical Power Requirements	208 / 230V, 1-Phase, 60 Hz
-------------------------------	----------------------------

Minimum Circuit Ampacity (MCA)		
Indoor / Outdoor	A	1 / 25

Indoor Unit		
Blower Motor (ECM)	F.L.A.	0.54
Blower Motor Output	W	95
SHF / Moisture Removal		0.69 / 8.3 pt./h

Outdoor Unit		
Compressor		DC INVERTER-driven Twin Rotary
Fan Motor (ECM)	F.L.A.	0.75
MOCP	A	40

Airflow Rate (Low-M1-M2-Hi)			
Indoor (Cooling)	DRY	CFM	565-600-635-705
	WET		530-565-600-670
Outdoor	DRY		1,940

Sound Pressure Level			
Indoor (Low-M1-M2-Hi)		dB(A)	35-37-39-41
Outdoor	Cooling		48
	Heating		50

External Dimensions		
Indoor (H x W x D)	In.(mm)	9-1/16 x 50-3/8 x 26-3/4 (230 x 1,280 x 680)
Outdoor (H x W x D)		37-1/8 x 37-3/8 x 13 + 1-3/16 (943 x 950 x 330 + 30)

Net Weight		
Indoor	Lbs.(kg)	71 (32)
Outdoor		165 (75)

External Finish	
Indoor	Munsel No. 6.4Y 8.9/0.4
Outdoor	Munsell No. 3Y 7.8 / 1.1

Refrigerant	R410A ; 6lbs., 10oz.
-------------	----------------------


Refrigerant Piping (Flared)		
Liquid (High Pressure)	In.(mm)	3/8 (9.52)
Gas (Low Pressure)		5/8 (15.88)
Maximum Total Refrigerant Pipe Length	Ft. (m)	165 (50)
Maximum Vertical Separation	Ft. (m)	100 (30)

DIMENSIONS: PCA-A30KA6 & PUZ-A30NHA6 (-BS)

PCA-A30KA6


[FRONT VIEW
LOOKING THROUGH THE UNIT]

Unit: inch (mm)



PUZ-A30NHA6 (-BS)

Unit: mm (inch)



NOTES:
SEACOAST PROTECTION

- External Outer Panel: Phosphate coating + Acrylic-Enamel coating
- Fan Motor Support: Epoxy resin coating (at edge face)
- Separator Assembly ; Valve Bed: Epoxy resin coating (at edge face)
- Screws (used outer side): Zinc nickel coating 5µm + Polyvinylidene chloride coating

“Blue Fin” treatment is an anti-corrosion treatment that is applied to the condenser coil to protect it against airborne contaminants..



COOLING & HEATING

1340 Satellite Boulevard. Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com

