

Job Name: _____

Location: _____

Drawing Reference: _____

Schedule No. _____

System No.: _____

Date: _____

OUTDOOR VRFZ HEAT RECOVERY SYSTEM FEATURES

- 3-phase, 208/230V
- Modular variable refrigerant flow zoning (VRFZ) systems; smaller capacity units can be piped together to form a single, large-capacity two-pipe system
- Required Twinning Kit allows for easy field piping connection
- Selectable fan static, 0.12 or 0.24"WG external static pressure; factory set to 0"WG
- Max. Total Refrigerant Piping Length: 1,804' (P72,96), 1,969' (P120,144,168), 2,461' (P192), 2,625' (P216,240), 3,280' (P264,288); Max. Refrigerant Line Length: 541'; Max. Control Wiring Length: 1,650'
- Connects to CITY MULTI indoor units; controlled via CITY MULTI Controls Network (CMCN)
- External finish: Pre-coated Galvanized-steel Sheets
- Operating Temperature Range
Cooling (Outdoor): 23° ~ 115°F (-5° ~ +46°C) DB
Heating (Outdoor): -4° ~ +60°F (-20° ~ +16°C) WB



PURY-P144TJMU-A PURY-P144TJMU-A

INVERTER


**OPTIONAL PARTS**

- ☐ Twinning Kit*.....CMY-R100XLVBK
- ☐ Branch Joint (T-Branch: ≤ 72,000 Btu/h).....CMY-Y102S-G2
- ☐ Branch Joint (T-Branch: 73,000-144,000 Btu/h).....CMY-Y102L-G2
- ☐ Branch Joint (T-Branch: 145,000-234,000 Btu/h).....CMY-Y202-G2
- ☐ Joint Adapter (Port Connector > 54,000 Btu/h).....CMY-R160J
- ☐ Main BC Controller.....CMB-1016NU-HA
- ☐ Sub BC Controller.....CMB-P104/108NU-GB/1016NU-HB
- * Twinning Kit is necessary to combine the refrigerant flows of the modules and is included in the outdoor unit set.

Specifications		System	Module 1	Module 2
Unit Type		PURY-P288TSJMU-A	PURY-P144TJMU-A	PURY-P144TJMU-A
Nominal Cooling Capacity	Btu/h	288,000	144,000	144,000
Nominal Heating Capacity	Btu/h	320,000	160,000	160,000
External Dimensions (H x W x D)	In. / mm	Refer to Module Data	65 x 68-15/16 x 29-15/16 / 1,650 x 1,750 x 760	65 x 68-15/16 x 29-15/16 / 1,650 x 1,750 x 760
Net Weight	Lbs. / kg	1,390 / 630	695 / 315	695 / 315
Electrical Power Requirements	Voltage, Phase, Hertz	Refer to Module Data**	208 / 230V, 3-phase, 60Hz	
Cooling Power Input	kW	25.61	Refer to System Data	
Heating Power Input	kW	27.19		
Cooling Current (208/230V)	R.L.A.	78.9 / 71.4	Refer to System Data	
Heating Current (208/230V)	R.L.A.	83.8 / 75.8		
Minimum Circuit Ampacity (MCA)**	A	Refer to Module Data**	59 / 54**	59 / 54**
Recommended Fuse/Breaker Size**	A	Refer to Module Data**	60**	60**
Maximum Fuse Size**	A	Refer to Module Data**	90 / 80**	90 / 80**
Piping Diameter			Refer to System Data	
From Twinning Kit to Indoor Units (Brazed) (In. / mm)	Liquid (High Pressure)	1-1/8 / 28.58		
	Gas (Low Pressure)	1-3/8 / 34.93		
From Modules to Twinning Kit (Brazed) (In. / mm)	Liquid (High Pressure)	Refer to Module Data	7/8 / 22.2	7/8 / 22.2
	Gas (Low Pressure)		1-1/8 / 28.58	1-1/8 / 28.58
Indoor Unit	Total Capacity	50 to 150% of ODUs	Refer to System Data	
	Model / Quantity	P06 ~ P96 / 2 to 50 (Max. No. Connectable Branches: 48)		
Sound Pressure Levels	dB(A)	64.0	61.0	61.0
Fan		Refer to Module Data		
Type x Quantity			Propeller Fan x 2	
Airflow Rate	CFM		12,010	
Direct-drive Inverter Motor Output	kW		0.92 + 0.92	
Compressor Operating Range		7 to 100%	Refer to System Data	
Compressor Type x Quantity		Refer to Module Data	Inverter-driven Scroll Hermetic x 1	Inverter-driven Scroll Hermetic x 1
Compressor Motor Output	kW		9.5	9.5
Compressor Crankcase Heater	kW		0.045	0.045
Refrigerant		Refer to Module Data	R410A	
Lubricant			MEL32	
High-pressure Protection Device		Refer to Module Data	601 psi / 4.15 MPa	601 psi / 4.15 MPa
Compressor / Fan Protection Device			Overheat Protection / Thermal Switch	Overheat Protection / Thermal Switch
Inverter Protection Device			Overheat / Overcurrent Protection	Overheat / Overcurrent Protection
Blue Fin Anti-corrosion Protection: Cellulose- and polyurethane-resin coating treatment applied to condenser coil that protects it from air contaminants; ≥1um thick: Salt Sprav Test Method - no unusual rust development to 480 hours.				

** Each individual module requires a separate electrical connection. Reference electrical data for each individual module.

Outdoor Unit: PURY-P288TSJMU-A – DIMENSIONS



Front view

Twinning pipe connection size

Package unit name		PURY-P240TSJMU-A(-BS)	PURY-P264TSJMU-A(-BS)	PURY-P288TSJMU-A(-BS)
Component unit name	Outdoor unit 1	PURY-P120TJMU-A(-BS)	PURY-P144TJMU-A(-BS)	PURY-P144TJMU-A(-BS)
	Outdoor unit 2	PURY-P120TJMU-A(-BS)	PURY-P120TJMU-A(-BS)	PURY-P144TJMU-A(-BS)
	Outdoor Twinning Kit(optional parts)	CMY-R100XLVBK		
BC controller~Twinning pipe	High pressure	a	ø28.58(1-1/8)	
	Low pressure	b	ø34.93(1-3/8)	

Note 1. Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.

2. Twinning pipe (High pressure) should not be tilted more than 15 degrees from the horizontal plane.

Be sure to see the Installation Manual for details of Twinning pipe installation.

3. The pipe section before the Twinning pipe (section "a" in the figure) must have at least 500mm(19-11/16) of straight section (*including the straight pipe that is supplied with the Twinning pipe).

4. Only use the Twinning pipe by Mitsubishi (optional parts).

Twinning pipe-Outdoor unit		Unit model	High pressure c or e	Low pressure d or f
	P120		ø19.05(3/4)	ø28.58(1-1/8)
	P144		ø22.2(7/8)	ø28.58(1-1/8)


Unit : mm(in.)

Twinning Kit: CMY-R100XLVBK


CMY-R100XLVBK

unit : inch

Low-pressure pipe twinning kit



High-pressure twinning pipe



*1.Connect by using the connecting pipes (for bottom piping and front piping) that are sold separately.