CITY MULTI®

Model: PVFY-P48E00B

Manufactured for MITSUBISHI ELECTRIC US, INC.

MITSUBISHI ELECTRIC

Job Name:	
Schedule Reference:	Date:



GENERAL FEATURES

- Dual set point functionality
- Increased static capabilities
- Extra set of contacts included on fan relays if energizing economizer is needed
- Concealed air handler can be operated in a vertical or horizontal left airflow position
- Designed specifically for use with CITY MULTI® outdoor units
- Ideal for installations in closets, attics, or equipment rooms where space is limited
- Choice of three fan speeds for optimum comfort
- Highly efficient DC motor and a forward curved blower ensures quiet, consistent fan operation
- Plug-in connection for auxiliary heat with optional relay kit
- Control board includes a condensate overflow switch connection
- Pre-painted heavy-gauge steel cabinets with 1" insulation feature an R-4.2 insulation value

OPTIONS

□ External Heater Adapter……CN24RELAY-KIT-CM3
□ Downflow Conversion Kit…..…….....……DFK-3

SPECIFICATIONS

Capacity*
Cooling…….....48,000 Btu/h
Heating…….....54,000 Btu/h

Power
Power Source…….....1-phase, 208 / 230V, 60Hz
Power Consumption
Cooling…….0.29 / 0.29 kW
Heating…….0.29 / 0.29 kW
Current
Cooling…….....…….1.62 / 1.47 A
Heating…….....…….1.62 / 1.47 A
Minimum Circuit Ampacity (MCA)…….....2.02 A
Maximum Overcurrent Protection (MOCP) Fuse.....…..15 A

External Finish……..…..Pre-painted heavy-gauge steel

External Dimensions
Inches……58-3/4 H x 24-1/2 W x 21-3/4 D
mm……1,492 H x 622 W x 552 D

Net Weight
Unit……..…..……..….....160 lbs. / 73 kg

Coil Type…….....….Cross Fin
(Aluminum Plate Fin and Copper Tube)

Fan
Type x Quantity……..Forward Curved Blower x 1

Airflow Rate (Low - Mid - High).....1,072 - 1,310 - 1,414 CFM

External Static Pressure
In. WG……0.30 / 0.50 / 0.80 (Selectable)

Motor Type……..……High Efficiency DC (ECM)

Refrigerant Piping Dimensions
Liquid (High Pressure)…….....3/8" / 9.52 mm (Brazed)
Gas (Low Pressure)……..5/8" / 15.88 mm (Brazed)

Drain Connections
Primary and Secondary..…..……FPT 3/4" / 19.05 mm

Sound Data (Low - Mid - High)
(measured at medium static setting)
Sound Pressure Levels.....38 - 39 - 39 dB(A)
Sound Power Levels.....52 - 53 - 54 dB(A)

* Cooling / Heating capacity indicated at the maximum value at operation under the following conditions:
Cooling | Indoor : 80° F (27° C) DB / 67° F (19° C) WB
Cooling | Outdoor : 95° F (35° C) DB
Heating | Indoor : 70° F (21° C) DB
Heating | Outdoor : 47° F (8° C) DB / 43° F (6°C) WB


Notes:

R410A

Specifications are subject to change without notice.
© 2013 Mitsubishi Electric US, Inc.

Model: PVFY-P48E00B – DIMENSIONS

Units: Inches



Model	(1) Gas (Low Pressure) (Brazed)	(2) Liquid (High Pressure) (Brazed)	(3) Drain Conn.
PVFY-P48E00B	5/8	3/8	3/4 FPT
PVFY-P54E00B	5/8	3/8	

Intertek

FORM# PVFY-P48E00B - 201301

Specifications are subject to change without notice.

© 2013 Mitsubishi Electric US, Inc.

Manufactured for

MITSUBISHI ELECTRIC
COOLING & HEATING
Live Better

3400 Lawrenceville Suwanee Rd
Suwanee, GA 30024
Tele: 678-376-2900 • Fax: 800-889-9904
Toll Free: 800-433-4822
www.mitsubishipro.com

Specifications are subject to change without notice.