CITYMULTI®

Outdoor Unit: 16-TON PUHY-P192YSKMU-A (-BS)

(Consists of One PUHY-P120YKMU-A (-BS), One PUHY-P72YKMU-A (-BS), and One CMY-Y100CBK3 Twinning Kit)

MITSUBISHI ELECTRIC

Job Name:	
System Reference:	Date:

OUTDOOR VRF HEAT PUMP SYSTEM FEATURES

- INVERTER-driven compressor
- Air-source, heat pump system
- Long line lengths - for details see Engineering Manual
- Connects to CITY MULTI indoor units
- Controlled via CITY MULTI Controls Network

UNIT OPTION

□ Standard Model……..PUHY-P192YSKMU-A
□ Sea Coast (BS) Model……..PUHY-P192YSKMU-A-BS

OPTIONAL PARTS

■ Twinning Kit (required)..... CMY-Y100CBK3
□ Joint Kit.....for details see Pipe Accesories Submittal
□ Header Kit.....for details see Pipe Accesories Submittal
□ Low Ambient Kit .....for details see Low Ambient Kit Submittal
□ Snow/Hail Guards Kit.....for details see Snow/Hail Guards Kit Submittal

Specifications		System	Module 1	Module 2
Unit Type		PUHY-P192YSKMU-A (-BS)	PUHY-P120YKMU-A (-BS)	PUHY-P72YKMU-A (-BS)
Nominal Cooling Capacity (460V)	Btu/h	192,000	120,000	72,000
Nominal Heating Capacity (460V)	Btu/h	215,000	135,000	80,000
Operating Temperature Range *1	Cooling (Outdoor) *2	Refer to Module Data	23~115° F (-5~46° C) DB	
	Heating (Outdoor)		-13~60° F (-25~15.5° C) WB	
External Dimensions (H x W x D)	In. mm	Refer to Module Data	64-31/32 x 68-29/32 x 29-5/32 1,650 x 1,750 x 740	64-31/32 x 36-1/4 x 29-5/32 1,650 x 920 x 740
Net Weight	Lbs. / kg	1,189 (539)	726 (329)	463 (210)
External Finish		Refer to Module Data	Pre-coated galvanized steel sheet	
Electrical Power Requirements	Voltage, Phase, Hertz	Refer to Module Data**	460V, 3-Phase, 60Hz	
Minimum Circuit Ampacity (MCA)	A	Refer to Module Data**	20	12
Maximum Fuse Size	A	Refer to Module Data**	25	15
Piping Diameter				
From Twinning Kit to First Joint or Header (Brazed) (In. / mm)	Liquid (High Pressure)	5/8 (15.88) Brazed	Refer to System Data	
	Gas (Low Pressure)	1-1/8 (28.58) Brazed		
Max. Total Refrigerant Line Length	Ft.	3,280	Refer to System Data	
Max. Refrigerant Line Length (Between ODU & IDU)	Ft.	541		
Max. Control Wiring Length	Ft.	1,650		
Indoor Unit	Total Capacity	50~130% of ODUs	Refer to System Data	
	Model / Quantity	P06~P96/1~41	Refer to System Data	
Sound Pressure Level	dB(A)	62.5	Refer to System Data	
Fan				
Type x Quantity		Refer to Module Data	Propeller fan x 2	Propeller fan x 1
Airflow Rate	CFM		11,300	6,200
External Static Pressure	In. WG (Pa)	Refer to Module Data	Selectable; 0, 0.12 or 0.24"WG; factory set to 0"W.G.	
Compressor Operating Range		6% to 100%	Refer to System Data	
Compressor Type x Quantity		Refer to Module Data	Inverter-driven Scroll Hermetic x 1	Inverter-driven Scroll Hermetic x 1
Refrigerant		Refer to Module Data	R410A; 26 lbs. + 1 oz. (11.8 kg)	R410A; 19 lbs. + 13 oz. (9.0 kg)
Protection Devices	High Pressure	Refer to Module Data	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter Circuit (Comp. / Fan)		Over-current protection	Over-current protection
	Fan Motor		Thermal switch	Thermal switch
AHRI Ratings (Ducted/Non-Ducted)	EER	12.4 / 12.5	Refer to System Data	
	IEER	18.9 / 19.1		
	COP	3.63 / 3.61		

Blue Fin Anti-corrosion Protection: Cellulose- and polyurethane-resin coating treatment applied to condenser coil that protects it from air contaminants
Standard: ≥1µm thick; Salt Spray Test Method - no unusual rust development to 480 hours.
Sea Coast (BS): ≥1µm thick; Salt Spray Test Method - no unusual rust development to 960 hours.

NOTES:

*1. When applying product below -4° F, consult your design engineer for cold climate application best practices, including the use of a backup source for heating.
*2. For details on extended cooling operation range down to -10° F DB, see Low Ambient Kit Submittal.

** Each individual module requires a separate electrical connection. Refer to electrical data for each individual module.


Specifications are subject to change without notice.

© 2016 Mitsubishi Electric US, Inc.

Outdoor Unit: PUHY-P192YSKMU-A (-BS) – DIMENSIONS

PUHY-P192YSKMU-A(-BS)

Unit : mm(in.)



Twinning pipe~Outdoor unit	Unit model	Liquid	Gas
		c or e	d or f
	P72	ø9.52(3/8)	ø22.2(7/8)
	P120	ø12.7(1/2)	ø28.58(1-1/8)

Twinning pipe connection size

Package unit name			PUHY-P192YSKMU-A(-BS)
Component unit name	Outdoor unit 1		PUHY-P120YKMU-A(-BS)
	Outdoor unit 2		PUHY-P72YKMU-A(-BS)
Outdoor Twinning Kit(optional parts)			CMY-Y100CBK3
Indoor unit~Twinning pipe	Liquid	a	ø15.88(5/8)
	Gas	b	ø28.58(1-1/8)


Note 1.Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.
2.Twinning pipes should not be tilted more than 15 degrees from the horizontal plane.
Be sure to see the Installation Manual for details of Twinning pipe installation.
3.The pipe section before the Twinning pipe (sections "a" and "b" in the figure) must have at least 500mm(19-11/16) of straight section (*including the straight pipe that is supplied with the Twinning pipe).
4.Only use the Twinning pipe by Mitsubishi (optional parts).

Specifications are subject to change without notice.

© 2016 Mitsubishi Electric US, Inc.

Model: PUHY-P120YKMU-A (-BS) – DIMENSIONS

Unit : mm(in.)



© 2016 Mitsubishi Electric US, Inc.

Model: PUHY-P72YKMU-A (-BS) – DIMENSIONS

Unit : mm(in.)


Note1. Please refer to the engineering manual for information regarding necessary spacing around the unit and foundation work. Outdoor unit must be mounted at least 12" off the ground or 12" above the highest average snow depth, whichever is greater.
2. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C(248°F).

Connecting pipe specifications

Model	Diameter			
	Refrigerant pipe		Service valve	
	Liquid	Gas	Liquid	Gas
PUHY-P72YKMU	ø9.52 Brazed (3/8) *1	ø22.2 Brazed (7/8) *2	ø9.52 (3/8)	ø28.58 (1-1/8)

*1 Expand the on-site piping and connect to the refrigerant service valve piping.
*2 Use the pipe joint(field supply) and connect to the refrigerant service valve piping.

NO.	Usage		Specifications
①	For pipes	Front through hole	140 × 77 Knockout hole (5-17/32) (3-1/16)
②		Bottom through hole	150 × 94 Knockout hole (5-29/32) (3-23/32)
③	For wires	Front through hole	ø62.7 or ø34.5 Knockout hole (2-15/32) (1-3/8)
④		Front through hole	ø43.7 or ø22.2 Knockout hole (1-3/4) (7/8)
⑤		Bottom through hole	ø65 Knockout hole (2-9/16)
⑥		Bottom through hole	ø52 Knockout hole (2-1/16)
⑦	For transmission cables	Front through hole	ø34 Knockout hole (1-11/32)



Specifications are subject to change without notice.

© 2016 Mitsubishi Electric US, Inc.


Twinning Kit: CMY-Y100CBK3

CMY-Y100CBK3


Ref.: CMY_Y100VBK2_EXD_EUDB_SI

in.


For Gas pipe:



For Liquid pipe:




<Reducer(Accessory)>



ID: Inner Diameter OD: Outer Diameter

Note 1. Reference the attitude angle of the branch pipe below the fig.



The angle of the branch pipe for hign pressure is within ±15° against the horizontal plane.

2. Use the attached pipe to braze the port-opening of the distributer.
3. Pipe diameter is indicated by inside diameter.
4. Only use the Twinning pipe by Mitsubishi (optional parts) .

MITSUBISHI ELECTRIC

COOLING & HEATING

1340 Satellite Boulevard. Suwanee, GA 30024

Toll Free: 800-433-4822 www.mehvac.com

FORM# PUHY-P192YSKMU-A (-BS) - 201605

Specifications are subject to change without notice.

© 2016 Mitsubishi Electric US, Inc.