CITY MULTI® Model: 20-TON PUHY-P240YSJMU-A

MITSUBISHI ELECTRIC

(Consists of Two PUHY-P120YJMU-A and One CMY-Y100VBK2 Twinning Kit)

Job Name: Location:

Drawing Reference: Schedule No.

System No.: Date:

OUTDOOR VRFZ HEAT PUMP SYSTEM FEATURES

- 3-phase, 460V
- Modular variable refrigerant flow zoning (VRFZ) systems; smaller capacity units can be piped together to form a single, large-capacity two-pipe system
- Selectable fan static, 0.12 or 0.24"WG external static pressure; factory set to 0"WG
- Max. Total Refrigerant Line Length: 3,280'; Max. Refrigerant Line Length: 541'; Max. Control Wiring Length: 1,640'
- Connects to CITY MULTI indoor units; controlled via CITY MULTI Controls Network
- External finish: Pre-coated Galvanized-steel Sheets
- Operating Temperature Range
  Cooling (Outdoor): 23° ~ 115°F (-5° ~ +46°C) DB
  Heating (Outdoor): -4° ~ +60°F (-20° ~ +16°C) WB



PUHY-P120YJMU-A PUHY-P120YJMU-A

INVERTER

R410A


OPTIONAL PARTS

- ☐ Twinning Kit*……CMY-Y100VBK2
- ☐ T-Branch Joint (≤ 72,000 Btu/h)……CMY-Y102S-G2
- ☐ T-Branch Joint (73,000-144,000 Btu/h)……CMY-Y102L-G2
- ☐ T-Branch Joint (145,000 - 234,000 Btu/h)……CMY-Y202-G2
- ☐ T-Branch Joint (≥ 235,000 Btu/h)……CMY-Y302-G2
- ☐ Header - 4-Branch (Capacity: ≤ 72,000 Btu/h)……CMY-Y104-G
- ☐ Header - 8-Branch (Capacity: ≤ 144,000 Btu/h)……CMY-Y108-G
- ☐ Header - 10-Branch (Capacity: ≤ 234,000 Btu/h)……CMY-Y1010-G

* Twinning Kit is necessary to combine the refrigerant flows of the modules and is included in the outdoor unit set.

Specifications		System	Module 1	Module 2
Unit Type		**PUHY-P240YSJMU-A**	**PUHY-P120YJMU-A**	**PUHY-P120YJMU-A**
Nominal Cooling Capacity	**Btu/h**	240,000	120,000	120,000
Nominal Heating Capacity	**Btu/h**	270,000	135,000	135,000
External Dimensions (H x W x D)	**In. / mm**	Refer to Module Data	65 x 68-15/16 x 29-15/16 / 1,650 x 1,750 x 760	65 x 68-15/16 x 29-15/16 / 1,650 x 1,750 x 760
Net Weight	**Lbs. / kg**	1,324 / 600	662 / 300	662 / 300
Electrical Power Requirements	**Voltage, Phase, Hertz**	Refer to Module Data**	460V, 3-phase, 60Hz	
Cooling Power Input	**kW**	20.39	Refer to System Data	
Heating Power Input	**kW**	21.44		
Cooling Current (460V)	**R.L.A.**	28.4	Refer to System Data	
Heating Current (460V)	**R.L.A.**	29.8		
Minimum Circuit Ampacity (MCA)**	**A**	Refer to Module Data**	23**	23**
Recommended Fuse/Breaker Size**	**A**	Refer to Module Data**	25**	25**
Maximum Fuse Size**	**A**	Refer to Module Data**	30**	30**
Piping Diameter			Refer to System Data	
From Twinning Kit to Indoor Units (Brazed) (In. / mm)	**Liquid (High Pressure)**	5/8 / 15.88		
	Gas (Low Pressure)	1-1/8 / 28.58		
From Modules to Twinning Kit (Brazed) (In. / mm)	**Liquid (High Pressure)**	Refer to Module Data	1/2 / 12.7	1/2 / 12.7
	Gas (Low Pressure)		7/8 / 22.2	7/8 / 22.2
Indoor Unit	**Total Capacity**	50 to 130% of ODUs	Refer to System Data	
	Model / Quantity	P06 ~ P96 / 2 to 50		
Sound Pressure Levels	**dB(A)**	63.0	60.0	60.0
Fan		Refer to Module Data		
Type x Quantity			Propeller Fan x 2	Propeller Fan x 2
Airflow Rate	**CFM**		12,010	12,010
Direct-drive Inverter Motor Output	**kW**		0.92 + 0.92	0.92 + 0.92
Compressor Operating Range		8 to 100%	Refer to System Data	
Compressor Type x Quantity		Refer to Module Data	Inverter-driven Scroll Hermetic x 1	Inverter-driven Scroll Hermetic x 1
Compressor Motor Output	**kW**		8.1	8.1
Compressor Crankcase Heater	**kW**		0.045	0.045
Refrigerant		Refer to Module Data	R410A	
Lubricant			MEL32	
High-pressure Protection Device		Refer to Module Data	601 psi / 4.15 MPa	601 psi / 4.15 MPa
Compressor / Fan Protection Device			Overheat Protection / Thermal Switch	Overheat Protection / Thermal Switch
Inverter Protection Device			Overheat / Overcurrent Protection	Overheat / Overcurrent Protection
Blue Fin Anti-corrosion Protection: Cellulose- and polyurethane-resin coating treatment applied to condenser coil that protects it from air contaminants; ≥1µm thick; Salt Spray Test Method - no unusual rust development to 480 hours.				

** Each individual module requires a separate electrical connection. Reference electrical data for each individual module.



Twinning pipe connection size

Package unit name			PUHY-P240YSJMU-A(-BS)	PUHY-P264YSJMU-A(-BS)	PUHY-P288YSJMU-A(-BS)
Component unit name	Outdoor unit 1		PUHY-P120YJMU-A(-BS)	PUHY-P144YJMU-A(-BS)	PUHY-P144YJMU-A(-BS)
	Outdoor unit 2		PUHY-P120YJMU-A(-BS)	PUHY-P120YJMU-A(-BS)	PUHY-P144YJMU-A(-BS)
Outdoor Twinning Kit(optional parts)			CMY-Y100VBK2	CMY-Y200VBK2	
Indoor unit~Twinning pipe	Liquid	a	ø15.88(5/8)	ø19.05(3/4)	
	Gas	b	ø28.58(1-1/8)	ø34.93(1-3/8)	

	Unit model	Liquid	Gas
		c or e	d or f
Twinning pipe~Outdoor unit	P120	ø12.7(1/2)	ø22.2(7/8)
	P144	ø12.7(1/2)	ø28.58(1-1/8)

Note 1.Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.
2.Twinning pipes should not be tilted more than 15 degrees from the horizontal plane.
Be sure to see the Installation Manual for details of Twinning pipe installation.
3.The pipe section before the Twinning pipe (sections "a" and "b" in the figure) must have at least 500mm(19-11/16) of straight section (*including the straight pipe that is supplied with the Twinning pipe).
4.Only use the Twinning pipe by Mitsubishi (optional parts).


Unit : mm(in.)

Twinning Kit: CMY-Y100VBK2


CMY-Y100VBK2

Ref.: CMY_Y100VBK2_EXD_EUDB_SI
Inches (mm)


For Gas pipe:



For Liquid pipe:




<Reducer Pipe (Accessory)>



ID: Inner Diameter OD: Outer Diameter

Note 1. Reference the angle of the branch pipe below the fig.




The angle of the branch pipe is within ±15˚against the ground.

2. Use the attached pipe to braze the port-opening of the distributor.
3. Pipe diameter is indicated by inside diameter.

For instructions on piping the units together using the twinning kit, see the Installation Manual.

Modules 1 and 2: PUHY-P120YJMU-A – DIMENSIONS



<Optional parts>
● Connecting pipe
<Gas> · Elbow(ID⌀28.58(1-1/8)XOD⌀28.58(1-1/8))・・・P120,144 1pc.
· Pipe (ID⌀28.58(1-1/8)XOD⌀22.2(7/8))・・・・・・・P120 1pc.
<Liquid> · Pipe (ID⌀12.7(1/2)XOD⌀9.52(3/8))・・・・・・・・・P120 1pc.
· Pipe (ID⌀12.7(1/2)XOD⌀12.7(1/2))・・・・・・・・・P120,144 1pc.

Note1.Please refer to (2/2) for information regarding necessary spacing around the unit and foundation work.
2.At brazing of pipes,wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C(248°F).

NO.	Usage		Specifications
①	For pipes	Front through hole	102 X 72 Knockout hole (4-1/32) (2-27/32)
②		Bottom through hole	150 X 94 Knockout hole (5-29/32) (3-23/32)
③	For wires	Front through hole	ø62.7 or ø34.5 Knockout hole (2-15/32) (1-3/8)
④		Front through hole	ø43.7 or ø22.2 Knockout hole (1-3/4) (7/8)
⑤		Bottom through hole	ø65 Knockout hole (2-9/16)
⑥	For transmission cables	Front through hole	ø34 Knockout hole (1-11/32)

Connecting pipe specifications

Model	Position dimensions for the refrigerant service valve			Connection specifications for the refrigerant service valve *1	
	Liquid A	Gas B		Liquid	Gas
PUHY-P120YJMU	143 (5-21/32)	172 (6-25/32)		ø9.52 Brazed (3/8) (ø12.7 Brazed (1/2) *2 *3	ø22.2 Brazed (7/8)
PUHY-P144YJMU				ø12.7 Brazed (1/2)	ø28.58 Brazed (1-1/8)

*1 Connect by using the connecting pipes (for bottom piping and front piping) that are sold separately.
*2 Indicates dimensions and connection specifications in the case the unit is used in combination with other outdoor units.
*3 Total length≥40m(131ft)

Certificate Number FM33568

Mitsubishi Electric Air Conditioning & Refrigeration Systems Works acquired ISO 9001 certification under Series 9000 of the International Standard Organization (ISO) based on a review of quality warranties for the production of refrigeration and air conditioning equipment.

ISO Authorization System
The ISO 9000 series is a plant authorization system relating to quality warranties as stipulated by the ISO. ISO 9001 certifies quality warranties based on the "design, development, production, installation and auxiliary services" for products built at an authorized plant.

Mitsubishi Electric Air Conditioning & Refrigeration Systems Works acquired environmental management system standard ISO 14001 certification.

The ISO 14000 series is a set of standards applying to environmental protection set by the International Standard Organization (ISO).

Certificate Number EC97J1227

HVAC Advanced Products Division
Mitsubishi Electric & Electronics USA, Inc.
3400 Lawrenceville Suwanee Rd.
Suwanee, GA 30024
Tele: 678-376-2900 • Fax: 800-889-9904
Toll Free: 800-433-4822 (#4)
www.mehvac.com

Specifications are subject to change without notice.

 © MITSUBISHI ELECTRIC / HVAC 2010