

Job Name:

Location:

Drawing Reference:

Schedule No.

System No.:

Date:

OUTDOOR VRFZ HEAT PUMP SYSTEM FEATURES

- 3-phase, 208/230V systems
- Modular variable refrigerant flow zoning (VRFZ) systems; smaller capacity units can be piped together to form a single, large-capacity two-pipe system
- Compact size for each outdoor module; components can be transported through standard-sized doorways for installation
- Selectable fan static, 0.12 or 0.24"WG external static pressure; factory set to 0"WG
- Max. Total Refrigerant Line Length: 3,280'; Max. Refrigerant Line Length: 541'; Max. Control Wiring Length: 1,650'
- Connects to CITY MULTI indoor units; controlled via CITY MULTI Controls Network
- External finish: Pre-coated Galvanized-steel Sheets with thermoset polyester-resin
- Operating Temperature Range
 - Cooling (Outdoor): 23° ~ 109°F (-5° ~ +43°C) DB
 - Heating (Outdoor): -4° ~ +60°F (-20° ~ +16°C) WB



PUHY-P96THMU-A-BS

INVERTER



OPTIONAL PARTS

- ☒ Branch Joint (T-Branch: ≤ 72,000 Btu/h).....CMY-Y102S-G2
- ☐ Branch Joint (T-Branch: 73,000-144,000 Btu/h).....CMY-Y102L-G2
- ☐ Header - 4-Branch (Capacity: ≤ 72,000 Btu/h).....CMY-Y104-G
- ☐ Header - 8-Branch (Capacity: ≤ 144,000 Btu/h).....CMY-Y108-G
- ☐ Header - 10-Branch (Capacity: ≤ 234,000 Btu/h).....CMY-Y1010-G




Specifications		Model Name
Unit Type		PUHY-P96THMU-A-BS
Nominal Cooling Capacity	Btu/h	96,000
Nominal Heating Capacity	Btu/h	108,000
External Dimensions (H x W x D)	In. / mm	65 x 36-1/4 x 29-15/16 / 1,650 x 920 x 760
Net Weight	Lbs. / kg	441 / 200
Electrical Power Requirements	Voltage, Phase, Hertz	208/230V, 3-phase, 60Hz
Cooling Power Input	kW	8.42
Heating Power Input	kW	8.63
Cooling Current (208/230V)	A	25.9 / 23.4
Heating Current (208/230V)	A	26.6 / 24.0
Minimum Circuit Ampacity (MCA)	A	35 / 32
Maximum Overcurrent Protection (MOCP)	A	40 / 40
Piping Diameter (Brazed) (In. / mm)	Liquid (High Pressure)	3/8 / 9.52 (1/2 / 12.7 if total length ≥ 295' / 90 m)
	Gas (Low Pressure)	7/8 / 22.2
Indoor Unit	Total Capacity	50 to 130% of Outdoor Unit Capacity
	Model / Quantity	P06 to P96 / 1 to 20
Sound Pressure Levels	dB(A)	58.0
Fan		
Type x Quantity		Propeller Fan x 1
Airflow Rate	CFM	7,050
Direct-drive Inverter Motor Output	kW	0.92
Compressor Operating Range		13% to 100%
Compressor Type x Quantity		Inverter-driven Scroll Hermetic x 1
Compressor Motor Output	kW	6.8
Compressor Crankcase Heater	kW	0.051
Refrigerant		R410A
Lubricant		MEL32
High-pressure Protection Device		601 psi / 4.15 MPa
Compressor / Fan Protection Device		Overheat Protection / Thermal Switch
Inverter Protection Device		Overheat / Overcurrent Protection
Blue Fin Anti-corrosion Protection: Cellulose- and polyurethane-resin coating treatment applied to condenser coil that protects it from air contaminants; ≥1µm to 1.5µm thick; Salt Spray Test Method - no unusual rust development to 960 hours.		

SEACOAST PROTECTION

- External Panel Base, External Front Panel, Pillar: Alloyed galvanized-steel sheets with thermoset polyester-resin coating on internal and external surfaces
- Compressor Cover: Galvanized-aluminum sheets with thermoset polyester-resin coating on internal and external surfaces
- Electrical Parts Box: Galvanized-aluminum sheets with thermoset polyester-resin coating on external surface
- Fan Motor Support: Galvanized-steel sheets with thermoset polyester-resin coating on internal and external surfaces
- Printed Circuit Board: Epoxy resin with polyurethane-coating on external surface

Model: PUHY-P96THMU-A-BS – DIMENSIONS

Unit : mm(in)



Connecting pipe specifications

Model	Position dimensions for the refrigerant service valve		Connection specifications for the refrigerant service valve *1	
	Liquid A	Gas B	Liquid	Gas
PUHY-P72THMU (-BS)	142 (5-19/32)	170 (6-23/32)	ø9.52 Brazed (3/8)	ø19.05 Brazed (3/4)
PUHY-P96THMU (-BS)		172 (6-25/32)	ø9.52 Brazed (3/8) (ø12.7 Brazed)*2 (1/2)	ø22.2 Brazed (7/8)

*1 Use the connecting pipes (for bottom and front pipes) that are supplied.

*2 Total length ≥ 90m (295')

Accessories

Connecting pipe

Gas	Elbow	(IDø25.4 [1] X ODø25.4 [1]).....P72, P96	1 pc.
	Pipe	(IDø25.4 [1] X ODø19.05 [3/4]).....P72	1 pc.
	Pipe	(IDø25.4 [1] X ODø22.2 [7/8]).....P96	1 pc.
Liquid	Pipe	(IDø9.52 [3/8] X ODø9.52 [3/8]).....P72, P96	1 pc.

Note 1. Refer to the Engineering or Installation manual for information regarding necessary clearance around the unit, and installation site requirements.

2. When brazing the pipes, protect the refrigerant service valve by wrapping it with a wet cloth to keep its temperature under 120°C (248°F).

NO.	Usage		Specifications
①	For pipes	Front access hole	102 X 72 Knockout hole (4-1/32) (2-27/32)
②		Bottom access hole	150 X 92 Knockout hole (5-29/32)(3-5/8)
③	For wires	Front access hole	ø62.7 or ø34.5 Knockout hole (2-15/32) (1-3/8)
④		Front access hole	ø43.7 or ø22.2 Knockout hole (1-3/4) (7/8)
⑤	For transmission cables	Bottom access hole	ø52 Knockout hole (2-1/16)
⑥		Front access hole	ø34 Knockout hole (1-11/32)



Certificate Number FM33568

Mitsubishi Electric Air Conditioning & Refrigeration Systems Works acquired ISO 9001 certification under Series 9000 of the International Standard Organization (ISO) based on a review of quality warranties for the production of refrigeration and air conditioning equipment.

ISO Authorization System

The ISO 9000 series is a plant authorization system relating to quality warranties as stipulated by the ISO. ISO 9001 certifies quality warranties based on the "design, development, production, installation and auxiliary services" for products built at an authorized plant.

Mitsubishi Electric Air Conditioning & Refrigeration Systems Works acquired environmental management system standard ISO 14001 certification.

The ISO 14000 series is a set of standards applying to environmental protection set by the International Standard Organization (ISO).



**MITSUBISHI
ELECTRIC**

HVAC Advanced Products Division

Mitsubishi Electric & Electronics USA, Inc.

3400 Lawrenceville Suwanee Rd.

Suwanee, GA 30024

Tele: 678-376-2900 • Fax: 800-889-9904

Toll Free: 800-433-4822 (#4)

www.mehvac.com

Specifications are subject to change without notice.



Certificate Number EC97J1227