CITYMULTI®

PEFY-P06NMAU-E4
6,000 BTU/H MEDIUM STATIC DUCTED

MITSUBISHI ELECTRIC
HEATING & AIR CONDITIONING

Job Name:

System Reference: Date:

GENERAL FEATURES

- Dual set point functionality
- Multiple fan speed settings
- Auto fan mode
- 9-7/8” (250mm) high for low ceiling heights
- Built-in condensate lift; lifts to 27-9/16” (700 mm)
- Ducted fan coil supporting multiple configurations for flexible installation

Specifications			System
Unit Type			PEFY-P06NMAU-E4
Cooling capacity (Nominal)[1]		BTU/H	6,000
Heating capacity (Nominal)[1]		BTU/H	6,700
Power source		Voltage, Phase, Hertz	208/230V, 1-phase, 60 Hz
Power Consumption	Cooling	kW	0.042
	Heating	kW	0.04
Current	Cooling	A	0.42/0.38
	Heating	A	0.42/0.38
MCA		A	1.75
Maximum Overcurrent Protection (MOCP)		A	15
External finish			Galvanized steel sheet
External Dimensions		In. [mm]	27-9/16 x 28-7/8 x 9-7/8 [700 x 732 x 250]
Net weight		Lbs [kg]	47 [21]
Heat exchanger			Cross fin (Aluminum fin and copper tube)
Fan	Type x quantity		Sirocco fan x 1
	External Static pressure	in.WG	0.14, 0.2, 0.28, 0.4, 0.6 factory set to 0.2 In. WG
	Airflow rate	CFM	212–265–300
	Motor type		DC Motor
	Motor Output	kW	0.085
	Motor FLA	A	1.4
Sound pressure level (Measured in anechoic room)		dB(A)	24–28–30
Air filter			PP Honeycomb fabric
Refrigerant	Type		R410A
Diameter of refrigerant pipe (O.D.)	Liquid (High Pressure)	In. [mm]	1/4 [6.35] Brazed
	Gas (Low Pressure)	In. [mm]	1/2 [12.7] Brazed
Diameter of drain pipe		In. [mm]	O.D. 1-1/4 [32]

NOTES:
[1]Cooling / Heating capacity indicated at the maximum value at operation under the following conditions:
Cooling | Indoor: 80° F (26.7° C) DB / 67° F (19.4° C) WB; Outdoor 95° F (35° C) DB
Heating | Indoor: 70° F (21.1° C) DB; Outdoor 47° F (8.3° C) DB / 43° F (6.1° C) WB

Specifications are subject to change without notice.

© 2022 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

INDOOR UNIT ACCESSORIES: PEFY-P06NMAU-E4

Control Interface	3-Pin Connector	☐ PAC-715AD
	BACnet® and Modbus® Interface	☐ PAC-UKPRC001-CN-1
	CN24 Relay Kit	☐ CN24RELAY-KIT-CM3
	Connector and wire for Operation status/error using CN51	☐ PAC-725AD
	IT Extender	☐ PAC-WHS01IE-E
	kumo station® for kumo cloud®	☐ PAC-WHS01HC-E
	Thermostat Interface	☐ PAC-US444CN-1
	Thermostat Interface	☐ PAC-US445CN-1
	Wireless Interface for kumo cloud®	☐ PAC-USWHS002-WF-2
Remote Sensor	Flush Mount Remote Temperature Sensor	☐ PAC-USSEN002-FM-1
	Flush Mount Temperature Sensor	☐ PAC-USSEN001-FM-1
	Remote Temperature Sensor	☐ PAC-SE41TS-E
	Wireless temperature and humitity sensor for kumo cloud®	☐ PAC-USWHS003-TH-1
Terminal Signal Adapter	Terminal Signal Adapter	☐ PAC-IT51AD-E
Wired Remote Controller	Deluxe Wired MA Remote Controller†	☐ PAR-40MAAU
	Simple MA Remote Controller†	☐ PAC-YT53CRAU-J
	Smart ME Remote Controller - Backlit touchscreen	☐ PAR-U01MEDU-K
	Touch MA Controller†	☐ PAR-CT01MAU-SB
Wireless Remote Controller	kumo touch™ RedLINK™ Wireless Controller	☐ MHK2
	Wireless MA Receiver	☐ PAR-FA32MA-W
	Wireless MA Remote Controller	☐ PAR-FL32MA-E
Condensate	Blue Diamond (Advanced) Mini Condensate Pump w/ Reservoir & Sensor (208/230V) [recommended]	☐ X87-721
	Blue Diamond (MicroBlue) Mini Condensate Pump (110/208/230V) up to 18,000 BTU/H	☐ X86-003
	Blue Diamond MultiTank — collection tank for use with multiple pumps	☐ C21-014
	Blue Diamond Sensor Extension Cable — 15 Ft.	☐ C13-103
	Refco Condensate Pump (100-240 VAC) up to 120,000 BTU/H	☐ COMBI
	Sauermann Condensate Pump	☐ SI30-230
Filter	Filter Box with MERV 13 Filter	☐ FBM2-1-A

© 2022 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

INDOOR UNIT DIMENSIONS: PEFY-P06NMAU-E4

Unit : mm(in.)

Note
1. Use an M10 screw for the suspension bolt (field supply).
2. Keep the service space for maintenance at the bottom.
3. This drawing is for PEFY-P24·27·30NMAU-E4 models, which have 2 fans. PEFY-P06·08·12NMAU-E4 models have 2 fans. PEFY-P15·18NMAU-E4 models have 1 fan. PEFY-P36·48·54NMAU-E4 models have 3 fans.
4. If the inlet duct is used, remove the air filter (supplied with the unit), then install the filter (field supply) at the suction side.
5. Heat air to 0°C (32°F) or higher when taking fresh air with a fresh air intake.

Unit:mm(in.)

Model	① Gas pipe	② Liquid pipe
PEFY-P06,08,12NMAU-E4	Ø12.7 (1/2)	Ø6.35 (1/4)
PEFY-P15,18NMAU-E4		
PEFY-P24,27,30NMAU-E4	Ø15.88 (5/8)	Ø9.52 (3/8)
PEFY-P36,48NMAU-E4		
PEFY-P54NMAU-E4		

Unit:mm(in.)

Model	A	B	C	D	E	F	G
PEFY-P06,08,12NMAU-E4	700 (27-9/16)	754 (29-11/16)	800 (31-1/2)	660 (26)	7	600 (23-5/8)	658 (25-15/16)
PEFY-P15,18NMAU-E4	900 (35-7/16)	954 (37-9/16)	1000 (39-3/8)	860 (33-7/8)	9	800 (31-1/2)	858 (33-13/16)
PEFY-P24,27,30NMAU-E4	1100 (43-5/16)	1154 (45-7/16)	1200 (47-1/4)	1060 (41-3/4)	11	1000 (39-3/8)	1058 (41-11/16)
PEFY-P36,48NMAU-E4	1400 (55-1/8)	1454 (57-1/4)	1500 (59-1/16)	1360 (53-9/16)	14	1300 (51-3/16)	1358 (53-1/2)
PEFY-P54NMAU-E4	1600 (63)	1654 (65-1/8)	1700 (66-15/16)	1560 (61-7/16)	16	1500 (59-1/16)	1558 (61-3/8)



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com

Specifications are subject to change without notice.

© 2022 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.