

CONTENTS

STANDARD MODELS..... 1

 NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED..... 1

 NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED..... 24

 NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED..... 57

PRO-HEAT MODELS..... 155

 NTXMPH36A142AB/NTXMPH36A142AA OPERATIONAL PERFORMANCE NON-DUCTED 155

 NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED 159

 NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED 169

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.4	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.4	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	30	30,000	15 + 15	15,000	15,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	15 + 15	18,500	18,500	0	0	0	0	0	0	3,470	17.0	15.3
2	33	33,000	9 + 24	9,000	24,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 24	11,200	29,700	0	0	0	0	0	0	3,990	19.5	17.6
2	33	33,000	15 + 18	15,000	18,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	15 + 18	18,600	22,300	0	0	0	0	0	0	3,990	19.5	17.6
2	36	36,000	6 + 30	6,000	30,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 30	7,300	37,700	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	12 + 24	12,000	24,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 24	15,000	30,000	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	18 + 18	18,000	18,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	18 + 18	22,500	22,500	0	0	0	0	0	0	4,500	22.0	19.9
2	39	39,000	9 + 30	9,000	30,000	0	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 30	10,500	36,000	0	0	0	0	0	0	4,740	23.1	20.9
2	39	39,000	15 + 24	15,000	24,000	0	0	0	0	0	0	3,680	18.0	16.3
		46,500	15 + 24	17,900	28,600	0	0	0	0	0	0	4,740	23.1	20.9
2	42	42,000	6 + 36	6,000	36,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 36	6,600	41,400	0	0	0	0	0	0	4,980	24.3	22.0
2	42	42,000	12 + 30	12,000	30,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 30	13,500	34,500	0	0	0	0	0	0	4,980	24.3	22.0
2	42	42,000	18 + 24	18,000	24,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	18 + 24	20,600	27,400	0	0	0	0	0	0	4,980	24.3	22.0
2	45	45,000	9 + 36	9,000	36,000	0	0	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 36	9,900	41,100	0	0	0	0	0	0	5,290	25.9	23.4
2	45	45,000	15 + 30	15,000	30,000	0	0	0	0	0	0	4,550	22.2	20.1
		51,000	15 + 30	16,700	34,300	0	0	0	0	0	0	5,290	25.9	23.4
2	48	48,000	12 + 36	12,000	36,000	0	0	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 36	13,100	40,900	0	0	0	0	0	0	5,610	27.4	24.8
2	48	48,000	18 + 30	18,000	30,000	0	0	0	0	0	0	5,070	24.8	22.4
		54,000	18 + 30	19,900	34,100	0	0	0	0	0	0	5,610	27.4	24.8
2	48	48,000	24 + 24	24,000	24,000	0	0	0	0	0	0	5,070	24.8	22.4
		54,000	24 + 24	27,000	27,000	0	0	0	0	0	0	5,610	27.4	24.8
2	51	48,000	15 + 36	14,100	33,900	0	0	0	0	0	0	5,010	24.4	22.1
		54,000	15 + 36	15,400	38,600	0	0	0	0	0	0	5,500	26.9	24.3
2	54	48,000	18 + 36	16,000	32,000	0	0	0	0	0	0	4,940	24.1	21.8
		54,000	18 + 36	17,500	36,500	0	0	0	0	0	0	5,390	26.3	23.8
2	54	48,000	24 + 30	21,300	26,700	0	0	0	0	0	0	4,940	24.1	21.8
		54,000	24 + 30	23,700	30,300	0	0	0	0	0	0	5,390	26.3	23.8
2	60	48,000	24 + 36	19,200	28,800	0	0	0	0	0	0	4,800	23.4	21.2
		54,000	24 + 36	21,100	32,900	0	0	0	0	0	0	5,270	25.7	23.2
2	60	48,000	30 + 30	24,000	24,000	0	0	0	0	0	0	4,800	23.4	21.2
		54,000	30 + 30	27,000	27,000	0	0	0	0	0	0	5,270	25.7	23.2

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	18	18,000	6 + 6 + 6	6,000	6,000	6,000	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 6 + 6	7,200	7,200	7,200	0	0	0	0	0	1,840	9.0	8.1
3	21	21,000	6 + 6 + 9	6,000	6,000	9,000	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 6 + 9	7,200	7,200	10,800	0	0	0	0	0	2,140	10.4	9.5
3	24	24,000	6 + 6 + 12	6,000	6,000	12,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 12	7,200	7,200	14,400	0	0	0	0	0	2,440	11.9	10.8
3	24	24,000	6 + 9 + 9	6,000	9,000	9,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 9 + 9	7,200	10,800	10,800	0	0	0	0	0	2,440	11.9	10.8
3	27	27,000	6 + 6 + 15	6,000	6,000	15,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 15	7,300	7,300	18,200	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	6 + 9 + 12	6,000	9,000	12,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 9 + 12	7,300	10,900	14,600	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	9 + 9 + 9	9,000	9,000	9,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 9 + 9	10,900	10,900	10,900	0	0	0	0	0	2,960	14.4	13.1
3	30	30,000	6 + 6 + 18	6,000	6,000	18,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 18	7,400	7,400	22,100	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 9 + 15	6,000	9,000	15,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 9 + 15	7,400	11,100	18,500	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 12 + 12	6,000	12,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 12 + 12	7,400	14,800	14,800	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	9 + 9 + 12	9,000	9,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	9 + 9 + 12	11,100	11,100	14,800	0	0	0	0	0	3,470	17.0	15.3
3	33	33,000	6 + 9 + 18	6,000	9,000	18,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 18	7,400	11,200	22,300	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	6 + 12 + 15	6,000	12,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 12 + 15	7,400	14,900	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 9 + 15	9,000	9,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 9 + 15	11,200	11,200	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 12 + 12	9,000	12,000	12,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 12 + 12	11,200	14,900	14,900	0	0	0	0	0	3,990	19.5	17.6
3	36	36,000	6 + 6 + 24	6,000	6,000	24,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 24	7,500	7,500	30,000	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 18	11,300	11,300	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 12 + 18	6,000	12,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 12 + 18	7,500	15,000	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 15 + 15	6,000	15,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 15 + 15	7,500	18,800	18,800	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 18	11,300	11,300	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 12 + 15	9,000	12,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 12 + 15	11,300	15,000	18,800	0	0	0	0	0	4,500	22.0	19.9

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	36	36,000	12 + 12 + 12	12,000	12,000	12,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 12 + 12	15,000	15,000	15,000	0	0	0	0	0	4,500	22.0	19.9
3	39	39,000	6 + 9 + 24	6,000	9,000	24,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 24	7,200	10,700	28,600	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	6 + 15 + 18	6,000	15,000	18,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 15 + 18	7,200	17,900	21,500	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	9 + 12 + 18	9,000	12,000	18,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 12 + 18	10,700	14,300	21,500	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	9 + 15 + 15	9,000	15,000	15,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 15 + 15	10,700	17,900	17,900	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	12 + 12 + 15	12,000	12,000	15,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	12 + 12 + 15	14,300	14,300	17,900	0	0	0	0	0	4,740	23.1	20.9
3	42	42,000	6 + 6 + 30	6,000	6,000	30,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 30	6,700	6,700	34,500	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	6 + 12 + 24	6,000	12,000	24,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 12 + 24	6,900	13,700	27,400	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	6 + 18 + 18	6,000	18,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 18 + 18	6,900	20,600	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	9 + 9 + 24	9,000	9,000	24,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 24	10,300	10,300	27,400	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	9 + 15 + 18	9,000	15,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 15 + 18	10,300	17,100	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	12 + 12 + 18	12,000	12,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 12 + 18	13,700	13,700	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	12 + 15 + 15	12,000	15,000	15,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 15 + 15	13,700	17,100	17,100	0	0	0	0	0	4,980	24.3	22.0
3	45	45,000	6 + 9 + 30	6,000	9,000	30,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 9 + 30	6,700	10,000	34,300	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	6 + 15 + 24	6,000	15,000	24,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 15 + 24	6,800	17,000	27,200	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	9 + 12 + 24	9,000	12,000	24,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 12 + 24	10,200	13,600	27,200	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	9 + 18 + 18	9,000	18,000	18,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 18 + 18	10,200	20,400	20,400	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	12 + 15 + 18	12,000	15,000	18,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	12 + 15 + 18	13,600	17,000	20,400	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	15 + 15 + 15	15,000	15,000	15,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	15 + 15 + 15	17,000	17,000	17,000	0	0	0	0	0	5,290	25.9	23.4
3	48	48,000	6 + 6 + 36	6,000	6,000	36,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 36	6,500	6,500	40,900	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	6 + 12 + 30	6,000	12,000	30,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 12 + 30	6,600	13,300	34,100	0	0	0	0	0	5,610	27.4	24.8

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	48	48,000	6 + 18 + 24	6,000	18,000	24,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 18 + 24	6,800	20,300	27,000	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	9 + 9 + 30	9,000	9,000	30,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 9 + 30	10,000	10,000	34,100	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	9 + 15 + 24	9,000	15,000	24,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 15 + 24	10,100	16,900	27,000	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	12 + 12 + 24	12,000	12,000	24,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 12 + 24	13,500	13,500	27,000	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	12 + 18 + 18	12,000	18,000	18,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 18 + 18	13,500	20,300	20,300	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	15 + 15 + 18	15,000	15,000	18,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	15 + 15 + 18	16,900	16,900	20,300	0	0	0	0	0	5,610	27.4	24.8
3	51	48,000	6 + 9 + 36	5,600	8,500	33,900	0	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 36	6,200	9,300	38,600	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	6 + 15 + 30	5,600	14,100	28,200	0	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 15 + 30	6,300	15,700	32,100	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	9 + 12 + 30	8,500	11,300	28,200	0	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 12 + 30	9,400	12,500	32,100	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	9 + 18 + 24	8,500	16,900	22,600	0	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 18 + 24	9,500	19,100	25,400	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	12 + 15 + 24	11,300	14,100	22,600	0	0	0	0	0	5,010	24.4	22.1
		54,000	12 + 15 + 24	12,700	15,900	25,400	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	15 + 18 + 18	14,100	16,900	16,900	0	0	0	0	0	5,010	24.4	22.1
		54,000	15 + 18 + 18	15,900	19,100	19,100	0	0	0	0	0	5,500	26.9	24.3
3	54	48,000	6 + 12 + 36	5,300	10,700	32,000	0	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 12 + 36	5,800	11,700	36,500	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	6 + 18 + 30	5,300	16,000	26,700	0	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 18 + 30	5,900	17,800	30,300	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	6 + 24 + 24	5,300	21,300	21,300	0	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 24 + 24	6,000	24,000	24,000	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	9 + 9 + 36	8,000	8,000	32,000	0	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 36	8,800	8,800	36,500	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	9 + 15 + 30	8,000	13,300	26,700	0	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 15 + 30	8,900	14,800	30,300	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	12 + 12 + 30	10,700	10,700	26,700	0	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 12 + 30	11,800	11,800	30,300	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	12 + 18 + 24	10,700	16,000	21,300	0	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 18 + 24	12,000	18,000	24,000	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	15 + 15 + 24	13,300	13,300	21,300	0	0	0	0	0	4,940	24.1	21.8
		54,000	15 + 15 + 24	15,000	15,000	24,000	0	0	0	0	0	5,390	26.3	23.8
3	57	48,000	6 + 15 + 36	5,100	12,600	30,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 15 + 36	5,500	13,800	34,600	0	0	0	0	0	5,330	26.0	23.5

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	57	48,000	9 + 12 + 36	7,600	10,100	30,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 36	8,300	11,100	34,600	0	0	0	0	0	5,330	26.0	23.5
3	57	48,000	9 + 18 + 30	7,600	15,200	25,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 18 + 30	8,400	16,800	28,800	0	0	0	0	0	5,330	26.0	23.5
3	57	48,000	9 + 24 + 24	7,600	20,200	20,200	0	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 24 + 24	8,500	22,700	22,700	0	0	0	0	0	5,330	26.0	23.5
3	57	48,000	12 + 15 + 30	10,100	12,600	25,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	12 + 15 + 30	11,200	14,000	28,800	0	0	0	0	0	5,330	26.0	23.5
3	60	48,000	6 + 18 + 36	4,800	14,400	28,800	0	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 18 + 36	5,300	15,800	32,900	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	6 + 24 + 30	4,800	19,200	24,000	0	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 24 + 30	5,300	21,300	27,300	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	9 + 15 + 36	7,200	12,000	28,800	0	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 15 + 36	7,900	13,200	32,900	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	12 + 12 + 36	9,600	9,600	28,800	0	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 36	10,500	10,500	32,900	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	12 + 18 + 30	9,600	14,400	24,000	0	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 18 + 30	10,700	16,000	27,300	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	12 + 24 + 24	9,600	19,200	19,200	0	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 24 + 24	10,800	21,600	21,600	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	15 + 15 + 30	12,000	12,000	24,000	0	0	0	0	0	4,800	23.4	21.2
		54,000	15 + 15 + 30	13,300	13,300	27,300	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	18 + 18 + 24	14,400	14,400	19,200	0	0	0	0	0	4,800	23.4	21.2
		54,000	18 + 18 + 24	16,200	16,200	21,600	0	0	0	0	0	5,270	25.7	23.2
4	24	24,000	6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 6 + 6	7,200	7,200	7,200	7,200	0	0	0	0	2,440	11.9	10.8
4	27	27,000	6 + 6 + 6 + 9	6,000	6,000	6,000	9,000	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 6 + 9	7,300	7,300	7,300	10,900	0	0	0	0	2,960	14.4	13.1
4	30	30,000	6 + 6 + 6 + 12	6,000	6,000	6,000	12,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 6 + 12	7,400	7,400	7,400	14,800	0	0	0	0	3,470	17.0	15.3
4	30	30,000	6 + 6 + 9 + 9	6,000	6,000	9,000	9,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 9 + 9	7,400	7,400	11,100	11,100	0	0	0	0	3,470	17.0	15.3
4	33	33,000	6 + 6 + 6 + 15	6,000	6,000	6,000	15,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 6 + 15	7,400	7,400	7,400	18,600	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 6 + 9 + 12	6,000	6,000	9,000	12,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 9 + 12	7,400	7,400	11,200	14,900	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 9 + 9 + 9	6,000	9,000	9,000	9,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 9 + 9	7,400	11,200	11,200	11,200	0	0	0	0	3,990	19.5	17.6
4	36	36,000	6 + 6 + 6 + 18	6,000	6,000	6,000	18,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 18	7,500	7,500	7,500	22,500	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 6 + 9 + 15	6,000	6,000	9,000	15,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 9 + 15	7,500	7,500	11,300	18,800	0	0	0	0	4,500	22.0	19.9

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	36	36,000	6 + 6 + 12 + 12	6,000	6,000	12,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 12 + 12	7,500	7,500	15,000	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 9 + 9 + 12	6,000	9,000	9,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 9 + 9 + 12	7,500	11,300	11,300	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 9 + 9	11,300	11,300	11,300	11,300	0	0	0	0	4,500	22.0	19.9
4	39	39,000	6 + 6 + 9 + 18	6,000	6,000	9,000	18,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 9 + 18	7,200	7,200	10,700	21,500	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 6 + 12 + 15	6,000	6,000	12,000	15,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 12 + 15	7,200	7,200	14,300	17,900	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 9 + 9 + 15	6,000	9,000	9,000	15,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 9 + 15	7,200	10,700	10,700	17,900	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 9 + 12 + 12	6,000	9,000	12,000	12,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 12 + 12	7,200	10,700	14,300	14,300	0	0	0	0	4,740	23.1	20.9
4	39	39,000	9 + 9 + 9 + 12	9,000	9,000	9,000	12,000	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 9 + 9 + 12	10,700	10,700	10,700	14,300	0	0	0	0	4,740	23.1	20.9
4	42	42,000	6 + 6 + 6 + 24	6,000	6,000	6,000	24,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 24	6,900	6,900	6,900	27,400	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 6 + 12 + 18	6,000	6,000	12,000	18,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 12 + 18	6,900	6,900	13,700	20,600	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 6 + 15 + 15	6,000	6,000	15,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 15 + 15	6,900	6,900	17,100	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 9 + 9 + 18	6,000	9,000	9,000	18,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 9 + 18	6,900	10,300	10,300	20,600	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 9 + 12 + 15	6,000	9,000	12,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 12 + 15	6,900	10,300	13,700	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 12 + 12 + 12	6,000	12,000	12,000	12,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 12 + 12 + 12	6,900	13,700	13,700	13,700	0	0	0	0	4,980	24.3	22.0
4	42	42,000	9 + 9 + 9 + 15	9,000	9,000	9,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 9 + 15	10,300	10,300	10,300	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	9 + 9 + 12 + 12	9,000	9,000	12,000	12,000	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 12 + 12	10,300	10,300	13,700	13,700	0	0	0	0	4,980	24.3	22.0
4	45	45,000	6 + 6 + 9 + 24	6,000	6,000	9,000	24,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 9 + 24	6,800	6,800	10,200	27,200	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 6 + 15 + 18	6,000	6,000	15,000	18,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 15 + 18	6,800	6,800	17,000	20,400	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 9 + 12 + 18	6,000	9,000	12,000	18,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 9 + 12 + 18	6,800	10,200	13,600	20,400	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 9 + 15 + 15	6,000	9,000	15,000	15,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 9 + 15 + 15	6,800	10,200	17,000	17,000	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 12 + 12 + 15	6,000	12,000	12,000	15,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 12 + 12 + 15	6,800	13,600	13,600	17,000	0	0	0	0	5,290	25.9	23.4

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	45	45,000	9 + 9 + 9 + 18	9,000	9,000	9,000	18,000	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 9 + 9 + 18	10,200	10,200	10,200	20,400	0	0	0	0	5,290	25.9	23.4
4	45	45,000	9 + 9 + 12 + 15	9,000	9,000	12,000	15,000	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 9 + 12 + 15	10,200	10,200	13,600	17,000	0	0	0	0	5,290	25.9	23.4
4	45	48,000	9 + 12 + 12 + 12	9,600	12,800	12,800	12,800	0	0	0	0	4,550	22.2	20.1
		54,000	9 + 12 + 12 + 12	10,800	14,400	14,400	14,400	0	0	0	0	5,290	25.9	23.4
4	48	48,000	6 + 6 + 6 + 30	6,000	6,000	6,000	30,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 30	6,600	6,600	6,600	34,100	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 6 + 12 + 24	6,000	6,000	12,000	24,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 12 + 24	6,800	6,800	13,500	27,000	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 6 + 18 + 18	6,000	6,000	18,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 18 + 18	6,800	6,800	20,300	20,300	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 9 + 9 + 24	6,000	9,000	9,000	24,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 9 + 24	6,800	10,100	10,100	27,000	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 9 + 15 + 18	6,000	9,000	15,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 15 + 18	6,800	10,100	16,900	20,300	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 12 + 12 + 18	6,000	12,000	12,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 12 + 12 + 18	6,800	13,500	13,500	20,300	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 12 + 15 + 15	6,000	12,000	15,000	15,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 12 + 15 + 15	6,800	13,500	16,900	16,900	0	0	0	0	5,610	27.4	24.8
4	48	48,000	9 + 9 + 12 + 18	9,000	9,000	12,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 9 + 12 + 18	10,100	10,100	13,500	20,300	0	0	0	0	5,610	27.4	24.8
4	48	45,000	9 + 9 + 15 + 15	8,400	8,400	14,100	14,100	0	0	0	0	5,070	24.8	22.4
		51,000	9 + 9 + 15 + 15	9,600	9,600	15,900	15,900	0	0	0	0	5,610	27.4	24.8
4	48	48,000	9 + 12 + 12 + 15	9,000	12,000	12,000	15,000	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 12 + 12 + 15	10,100	13,500	13,500	16,900	0	0	0	0	5,610	27.4	24.8
4	48	48,000	12 + 12 + 12 + 12	12,000	12,000	12,000	12,000	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 12 + 12 + 12	13,500	13,500	13,500	13,500	0	0	0	0	5,610	27.4	24.8
4	51	48,000	6 + 6 + 9 + 30	5,600	5,600	8,500	28,200	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 30	6,300	6,300	9,400	32,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 6 + 15 + 24	5,600	5,600	14,100	22,600	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 15 + 24	6,400	6,400	15,900	25,400	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 9 + 12 + 24	5,600	8,500	11,300	22,600	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 12 + 24	6,400	9,500	12,700	25,400	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 9 + 18 + 18	5,600	8,500	16,900	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 18 + 18	6,400	9,500	19,100	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 12 + 15 + 18	5,600	11,300	14,100	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 12 + 15 + 18	6,400	12,700	15,900	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 15 + 15 + 15	5,600	14,100	14,100	14,100	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 15 + 15 + 15	6,400	15,900	15,900	15,900	0	0	0	0	5,500	26.9	24.3
4	51	48,000	9 + 9 + 9 + 24	8,500	8,500	8,500	22,600	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 9 + 24	9,500	9,500	9,500	25,400	0	0	0	0	5,500	26.9	24.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	51	48,000	9 + 9 + 15 + 18	8,500	8,500	14,100	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 15 + 18	9,500	9,500	15,900	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	9 + 12 + 12 + 18	8,500	11,300	11,300	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 12 + 12 + 18	9,500	12,700	12,700	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	9 + 12 + 15 + 15	8,500	11,300	14,100	14,100	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 12 + 15 + 15	9,500	12,700	15,900	15,900	0	0	0	0	5,500	26.9	24.3
4	51	48,000	12 + 12 + 12 + 15	11,300	11,300	11,300	14,100	0	0	0	0	5,010	24.4	22.1
		54,000	12 + 12 + 12 + 15	12,700	12,700	12,700	15,900	0	0	0	0	5,500	26.9	24.3
4	54	48,000	6 + 6 + 6 + 36	5,300	5,300	5,300	32,000	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 36	5,800	5,800	5,800	36,500	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 6 + 12 + 30	5,300	5,300	10,700	26,700	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 12 + 30	5,900	5,900	11,800	30,300	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 6 + 18 + 24	5,300	5,300	16,000	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 18 + 24	6,000	6,000	18,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 9 + 9 + 30	5,300	8,000	8,000	26,700	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 30	5,900	8,900	8,900	30,300	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 9 + 15 + 24	5,300	8,000	13,300	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 15 + 24	6,000	9,000	15,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 12 + 12 + 24	5,300	10,700	10,700	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 12 + 12 + 24	6,000	12,000	12,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 15 + 15 + 18	5,300	13,300	13,300	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 15 + 15 + 18	6,000	15,000	15,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 9 + 12 + 24	8,000	8,000	10,700	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 12 + 24	9,000	9,000	12,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 9 + 18 + 18	8,000	8,000	16,000	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 18 + 18	9,000	9,000	18,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 12 + 15 + 18	8,000	10,700	13,300	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 12 + 15 + 18	9,000	12,000	15,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 15 + 15 + 15	8,000	13,300	13,300	13,300	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 15 + 15 + 15	9,000	15,000	15,000	15,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	12 + 12 + 12 + 18	10,700	10,700	10,700	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 12 + 12 + 18	12,000	12,000	12,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	12 + 12 + 15 + 15	10,700	10,700	13,300	13,300	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 12 + 15 + 15	12,000	12,000	15,000	15,000	0	0	0	0	5,390	26.3	23.8
4	57	48,000	6 + 6 + 9 + 36	5,100	5,100	7,600	30,300	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 36	5,500	5,500	8,300	34,600	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 6 + 15 + 30	5,100	5,100	12,600	25,300	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 15 + 30	5,600	5,600	14,000	28,800	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 9 + 12 + 30	5,100	7,600	10,100	25,300	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 12 + 30	5,600	8,400	11,200	28,800	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 9 + 18 + 24	5,100	7,600	15,200	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 18 + 24	5,700	8,500	17,100	22,700	0	0	0	0	5,330	26.0	23.5

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	57	48,000	6 + 12 + 15 + 24	5,100	10,100	12,600	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 12 + 15 + 24	5,700	11,400	14,200	22,700	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 9 + 9 + 30	7,600	7,600	7,600	25,300	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 9 + 30	8,400	8,400	8,400	28,800	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 9 + 15 + 24	7,600	7,600	12,600	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 15 + 24	8,500	8,500	14,200	22,700	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 12 + 12 + 24	7,600	10,100	10,100	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 12 + 24	8,500	11,400	11,400	22,700	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 12 + 18 + 18	7,600	10,100	15,200	15,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 18 + 18	8,500	11,400	17,100	17,100	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 15 + 15 + 18	7,600	12,600	12,600	15,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 15 + 15 + 18	8,500	14,200	14,200	17,100	0	0	0	0	5,330	26.0	23.5
4	57	48,000	12 + 12 + 15 + 18	10,100	10,100	12,600	15,200	0	0	0	0	4,870	23.8	21.5
		54,000	12 + 12 + 15 + 18	11,400	11,400	14,200	17,100	0	0	0	0	5,330	26.0	23.5
4	57	48,000	12 + 15 + 15 + 15	10,100	12,600	12,600	12,600	0	0	0	0	4,870	23.8	21.5
		54,000	12 + 15 + 15 + 15	11,400	14,200	14,200	14,200	0	0	0	0	5,330	26.0	23.5
4	60	48,000	6 + 6 + 12 + 36	4,800	4,800	9,600	28,800	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 12 + 36	5,300	5,300	10,500	32,900	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 6 + 18 + 30	4,800	4,800	14,400	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 18 + 30	5,300	5,300	16,000	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 6 + 24 + 24	4,800	4,800	19,200	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 24 + 24	5,400	5,400	21,600	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 9 + 9 + 36	4,800	7,200	7,200	28,800	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 36	5,300	7,900	7,900	32,900	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 9 + 15 + 30	4,800	7,200	12,000	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 15 + 30	5,300	8,000	13,300	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 12 + 12 + 30	4,800	9,600	9,600	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 12 + 12 + 30	5,300	10,700	10,700	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 15 + 15 + 24	4,800	12,000	12,000	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 15 + 15 + 24	5,400	13,500	13,500	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 18 + 18 + 18	4,800	14,400	14,400	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 18 + 18 + 18	5,400	16,200	16,200	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 9 + 12 + 30	7,200	7,200	9,600	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 12 + 30	8,000	8,000	10,700	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 9 + 18 + 24	7,200	7,200	14,400	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 18 + 24	8,100	8,100	16,200	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 12 + 15 + 24	7,200	9,600	12,000	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 12 + 15 + 24	8,100	10,800	13,500	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 15 + 18 + 18	7,200	12,000	14,400	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 15 + 18 + 18	8,100	13,500	16,200	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	12 + 12 + 12 + 24	9,600	9,600	9,600	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 12 + 24	10,800	10,800	10,800	21,600	0	0	0	0	5,270	25.7	23.2

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	60	48,000	12 + 12 + 18 + 18	9,600	9,600	14,400	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 18 + 18	10,800	10,800	16,200	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	12 + 15 + 15 + 18	9,600	12,000	12,000	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 15 + 15 + 18	10,800	13,500	13,500	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	15 + 15 + 15 + 15	12,000	12,000	12,000	12,000	0	0	0	0	4,800	23.4	21.2
		54,000	15 + 15 + 15 + 15	13,500	13,500	13,500	13,500	0	0	0	0	5,270	25.7	23.2
5	30	30,000	6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 6 + 6 + 6	7,400	7,400	7,400	7,400	7,400	0	0	0	3,470	17.0	15.3
5	33	33,000	6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	9,000	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 6 + 6 + 9	7,400	7,400	7,400	7,400	11,200	0	0	0	3,990	19.5	17.6
5	36	36,000	6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	12,000	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 6 + 12	7,500	7,500	7,500	7,500	15,000	0	0	0	4,500	22.0	19.9
5	36	36,000	6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	9,000	9,000	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 9 + 9	7,500	7,500	7,500	11,300	11,300	0	0	0	4,500	22.0	19.9
5	39	39,000	6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	15,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 6 + 15	7,200	7,200	7,200	7,200	17,900	0	0	0	4,740	23.1	20.9
5	39	39,000	6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	9,000	12,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 9 + 12	7,200	7,200	7,200	10,700	14,300	0	0	0	4,740	23.1	20.9
5	39	39,000	6 + 6 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 9 + 9 + 9	7,200	7,200	10,700	10,700	10,700	0	0	0	4,740	23.1	20.9
5	42	42,000	6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	18,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 6 + 18	6,900	6,900	6,900	6,900	20,600	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	9,000	15,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 9 + 15	6,900	6,900	6,900	10,300	17,100	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	12,000	12,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 12 + 12	6,900	6,900	6,900	13,700	13,700	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 9 + 9 + 12	6,000	6,000	9,000	9,000	12,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 9 + 9 + 12	6,900	6,900	10,300	10,300	13,700	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 9 + 9 + 9 + 9	6,000	9,000	9,000	9,000	9,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 9 + 9 + 9	6,900	10,300	10,300	10,300	10,300	0	0	0	4,980	24.3	22.0
5	45	45,000	6 + 6 + 6 + 9 + 18	6,000	6,000	6,000	9,000	18,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 9 + 18	6,800	6,800	6,800	10,200	20,400	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 6 + 6 + 12 + 15	6,000	6,000	6,000	12,000	15,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 12 + 15	6,800	6,800	6,800	13,600	17,000	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 6 + 9 + 9 + 15	6,000	6,000	9,000	9,000	15,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 9 + 9 + 15	6,800	6,800	10,200	10,200	17,000	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 6 + 9 + 12 + 12	6,000	6,000	9,000	12,000	12,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 9 + 12 + 12	6,800	6,800	10,200	13,600	13,600	0	0	0	5,290	25.9	23.4

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	45	45,000	3 + 9 + 9 + 9 + 12	6,000	9,000	9,000	9,000	12,000	0	0	0	4,550	22.2	20.1
		51,000	3 + 9 + 9 + 9 + 12	6,800	10,200	10,200	10,200	13,600	0	0	0	5,290	25.9	23.4
5	45	45,000	9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	0	0	0	4,550	22.2	20.1
		51,000	9 + 9 + 9 + 9 + 9	10,200	10,200	10,200	10,200	10,200	0	0	0	5,290	25.9	23.4
5	48	48,000	3 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	24,000	0	0	0	5,070	24.8	22.4
		54,000	3 + 6 + 6 + 6 + 24	6,800	6,800	6,800	6,800	27,000	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	12,000	18,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 12 + 18	6,800	6,800	6,800	13,500	20,300	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	15,000	15,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 15 + 15	6,800	6,800	6,800	16,900	16,900	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 9 + 9 + 18	6,000	6,000	9,000	9,000	18,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 9 + 9 + 18	6,800	6,800	10,100	10,100	20,300	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 9 + 12 + 15	6,000	6,000	9,000	12,000	15,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 9 + 12 + 15	6,800	6,800	10,100	13,500	16,900	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 12 + 12 + 12	6,000	6,000	12,000	12,000	12,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 12 + 12 + 12	6,800	6,800	13,500	13,500	13,500	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 9 + 9 + 9 + 15	6,000	9,000	9,000	9,000	15,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 9 + 9 + 15	6,800	10,100	10,100	10,100	16,900	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 9 + 9 + 12 + 12	6,000	9,000	9,000	12,000	12,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 9 + 12 + 12	6,800	10,100	10,100	13,500	13,500	0	0	0	5,610	27.4	24.8
5	48	48,000	9 + 9 + 9 + 9 + 12	9,000	9,000	9,000	9,000	12,000	0	0	0	5,070	24.8	22.4
		54,000	9 + 9 + 9 + 9 + 12	10,100	10,100	10,100	10,100	13,500	0	0	0	5,610	27.4	24.8
5	51	48,000	6 + 6 + 6 + 9 + 24	5,600	5,600	5,600	8,500	22,600	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 9 + 24	6,400	6,400	6,400	9,500	25,400	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 6 + 15 + 18	5,600	5,600	5,600	14,100	16,900	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 15 + 18	6,400	6,400	6,400	15,900	19,100	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 9 + 12 + 18	5,600	5,600	8,500	11,300	16,900	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 12 + 18	6,400	6,400	9,500	12,700	19,100	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 9 + 15 + 15	5,600	5,600	8,500	14,100	14,100	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 15 + 15	6,400	6,400	9,500	15,900	15,900	0	0	0	5,500	26.9	24.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	51	48,000	6 + 6 + 12 + 12 + 15	5,600	5,600	11,300	11,300	14,100	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 12 + 12 + 15	6,400	6,400	12,700	12,700	15,900	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 9 + 9 + 9 + 18	5,600	8,500	8,500	8,500	16,900	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 9 + 9 + 18	6,400	9,500	9,500	9,500	19,100	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 9 + 9 + 12 + 15	5,600	8,500	8,500	11,300	14,100	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 9 + 12 + 15	6,400	9,500	9,500	12,700	15,900	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 9 + 12 + 12 + 12	5,600	8,500	11,300	11,300	11,300	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 12 + 12 + 12	6,400	9,500	12,700	12,700	12,700	0	0	0	5,500	26.9	24.3
5	51	48,000	9 + 9 + 9 + 9 + 15	8,500	8,500	8,500	8,500	14,100	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 9 + 9 + 15	9,500	9,500	9,500	9,500	15,900	0	0	0	5,500	26.9	24.3
5	51	48,000	9 + 9 + 9 + 12 + 12	8,500	8,500	8,500	11,300	11,300	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 9 + 12 + 12	9,500	9,500	9,500	12,700	12,700	0	0	0	5,500	26.9	24.3
5	54	48,000	6 + 6 + 6 + 6 + 30	5,300	5,300	5,300	5,300	26,700	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 30	5,900	5,900	5,900	5,900	30,300	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 6 + 12 + 24	5,300	5,300	5,300	10,700	21,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 12 + 24	6,000	6,000	6,000	12,000	24,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 6 + 18 + 18	5,300	5,300	5,300	16,000	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 18 + 18	6,000	6,000	6,000	18,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 9 + 9 + 24	5,300	5,300	8,000	8,000	21,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 9 + 24	6,000	6,000	9,000	9,000	24,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 9 + 15 + 18	5,300	5,300	8,000	13,300	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 15 + 18	6,000	6,000	9,000	15,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 12 + 12 + 18	5,300	5,300	10,700	10,700	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 12 + 12 + 18	6,000	6,000	12,000	12,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 12 + 15 + 15	5,300	5,300	10,700	13,300	13,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 12 + 15 + 15	6,000	6,000	12,000	15,000	15,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 9 + 9 + 12 + 18	5,300	8,000	8,000	10,700	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 12 + 18	6,000	9,000	9,000	12,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 9 + 9 + 15 + 15	5,300	8,000	8,000	13,300	13,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 15 + 15	6,000	9,000	9,000	15,000	15,000	0	0	0	5,390	26.3	23.8

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	54	48,000	6 + 9 + 12 + 12 + 15	5,300	8,000	10,700	10,700	13,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 12 + 12 + 15	6,000	9,000	12,000	12,000	15,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 12 + 12 + 12 + 12	5,300	10,700	10,700	10,700	10,700	0	0	0	4,940	24.1	21.8
		54,000	6 + 12 + 12 + 12 + 12	6,000	12,000	12,000	12,000	12,000	0	0	0	5,390	26.3	23.8
5	54	48,000	9 + 9 + 9 + 9 + 18	8,000	8,000	8,000	8,000	16,000	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 9 + 9 + 18	9,000	9,000	9,000	9,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	9 + 9 + 9 + 12 + 15	8,000	8,000	8,000	10,700	13,300	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 9 + 12 + 15	9,000	9,000	9,000	12,000	15,000	0	0	0	5,390	26.3	23.8
5	54	48,000	9 + 9 + 12 + 12 + 12	8,000	8,000	10,700	10,700	10,700	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 12 + 12 + 12	9,000	9,000	12,000	12,000	12,000	0	0	0	5,390	26.3	23.8
5	57	48,000	6 + 6 + 6 + 9 + 30	5,100	5,100	5,100	7,600	25,300	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 9 + 30	5,600	5,600	5,600	8,400	28,800	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 6 + 15 + 24	5,100	5,100	5,100	12,600	20,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 15 + 24	5,700	5,700	5,700	14,200	22,700	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 9 + 12 + 24	5,100	5,100	7,600	10,100	20,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 12 + 24	5,700	5,700	8,500	11,400	22,700	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 9 + 18 + 18	5,100	5,100	7,600	15,200	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 18 + 18	5,700	5,700	8,500	17,100	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 12 + 15 + 18	5,100	5,100	10,100	12,600	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 12 + 15 + 18	5,700	5,700	11,400	14,200	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 15 + 15 + 15	5,100	5,100	12,600	12,600	12,600	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 15 + 15 + 15	5,700	5,700	14,200	14,200	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 9 + 9 + 9 + 24	5,100	7,600	7,600	7,600	20,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 9 + 9 + 24	5,700	8,500	8,500	8,500	22,700	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 9 + 9 + 15 + 18	5,100	7,600	7,600	12,600	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 9 + 15 + 18	5,700	8,500	8,500	14,200	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 9 + 12 + 12 + 18	5,100	7,600	10,100	10,100	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 12 + 12 + 18	5,700	8,500	11,400	11,400	17,100	0	0	0	5,330	26.0	23.5

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	57	48,000	6 + 9 + 12 + 15 + 15	5,100	7,600	10,100	12,600	12,600	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 12 + 15 + 15	5,700	8,500	11,400	14,200	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 12 + 12 + 12 + 15	5,100	10,100	10,100	10,100	12,600	0	0	0	4,870	23.8	21.5
		54,000	6 + 12 + 12 + 12 + 15	5,700	11,400	11,400	11,400	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 9 + 9 + 12 + 18	7,600	7,600	7,600	10,100	15,200	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 9 + 12 + 18	8,500	8,500	8,500	11,400	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 9 + 9 + 15 + 15	7,600	7,600	7,600	12,600	12,600	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 9 + 15 + 15	8,500	8,500	8,500	14,200	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 9 + 12 + 12 + 15	7,600	7,600	10,100	10,100	12,600	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 12 + 12 + 15	8,500	8,500	11,400	11,400	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 12 + 12 + 12 + 12	7,600	10,100	10,100	10,100	10,100	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 12 + 12 + 12	8,500	11,400	11,400	11,400	11,400	0	0	0	5,330	26.0	23.5
5	60	48,000	5 + 6 + 6 + 6 + 36	4,800	4,800	4,800	4,800	28,800	0	0	0	4,800	23.4	21.2
		54,000	5 + 6 + 6 + 6 + 36	5,300	5,300	5,300	5,300	32,900	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 6 + 6 + 12 + 30	4,800	4,800	4,800	9,600	24,000	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 12 + 30	5,300	5,300	5,300	10,700	27,300	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 6 + 6 + 18 + 24	4,800	4,800	4,800	14,400	19,200	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 18 + 24	5,400	5,400	5,400	16,200	21,600	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 6 + 9 + 9 + 30	4,800	4,800	7,200	7,200	24,000	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 9 + 9 + 30	5,300	5,300	8,000	8,000	27,300	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 6 + 9 + 15 + 24	4,800	4,800	7,200	12,000	19,200	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 9 + 15 + 24	5,400	5,400	8,100	13,500	21,600	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 6 + 12 + 12 + 24	4,800	4,800	9,600	9,600	19,200	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 12 + 12 + 24	5,400	5,400	10,800	10,800	21,600	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 6 + 12 + 18 + 18	4,800	4,800	9,600	14,400	14,400	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 12 + 18 + 18	5,400	5,400	10,800	16,200	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 6 + 15 + 15 + 18	4,800	4,800	12,000	12,000	14,400	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 15 + 15 + 18	5,400	5,400	13,500	13,500	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 9 + 9 + 12 + 24	4,800	7,200	7,200	9,600	19,200	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 12 + 24	5,400	8,100	8,100	10,800	21,600	0	0	0	5,270	25.7	23.2

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	60	48,000	6 + 9 + 9 + 18 + 18	4,800	7,200	7,200	14,400	14,400	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 18 + 18	5,400	8,100	8,100	16,200	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 9 + 12 + 15 + 18	4,800	7,200	9,600	12,000	14,400	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 12 + 15 + 18	5,400	8,100	10,800	13,500	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 9 + 15 + 15 + 15	4,800	7,200	12,000	12,000	12,000	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 15 + 15 + 15	5,400	8,100	13,500	13,500	13,500	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 12 + 12 + 12 + 18	4,800	9,600	9,600	9,600	14,400	0	0	0	4,800	23.4	21.2
		54,000	6 + 12 + 12 + 12 + 18	5,400	10,800	10,800	10,800	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	6 + 12 + 12 + 15 + 15	4,800	9,600	9,600	12,000	12,000	0	0	0	4,800	23.4	21.2
		54,000	6 + 12 + 12 + 15 + 15	5,400	10,800	10,800	13,500	13,500	0	0	0	5,270	25.7	23.2
5	60	48,000	9 + 9 + 9 + 9 + 24	7,200	7,200	7,200	7,200	19,200	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 9 + 9 + 24	8,100	8,100	8,100	8,100	21,600	0	0	0	5,270	25.7	23.2
5	60	48,000	9 + 9 + 9 + 15 + 18	7,200	7,200	7,200	12,000	14,400	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 9 + 15 + 18	8,100	8,100	8,100	13,500	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	9 + 9 + 12 + 12 + 18	7,200	7,200	9,600	9,600	14,400	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 12 + 12 + 18	8,100	8,100	10,800	10,800	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	9 + 9 + 12 + 15 + 15	7,200	7,200	9,600	12,000	12,000	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 12 + 15 + 15	8,100	8,100	10,800	13,500	13,500	0	0	0	5,270	25.7	23.2
5	60	48,000	9 + 12 + 12 + 12 + 15	7,200	9,600	9,600	9,600	12,000	0	0	0	4,800	23.4	21.2
		54,000	9 + 12 + 12 + 12 + 15	8,100	10,800	10,800	10,800	13,500	0	0	0	5,270	25.7	23.2
5	60	48,000	12 + 12 + 12 + 12 + 12	9,600	9,600	9,600	9,600	9,600	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 12 + 12 + 12	10,800	10,800	10,800	10,800	10,800	0	0	0	5,270	25.7	23.2
6	36	36,000	6 + 6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	6,000	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 6 + 6 + 6	7,500	7,500	7,500	7,500	7,500	7,500	0	0	4,500	22.0	19.9
6	39	39,000	6 + 6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	6,000	9,000	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 6 + 6 + 9	7,200	7,200	7,200	7,200	7,200	10,700	0	0	4,740	23.1	20.9
6	42	42,000	6 + 6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	6,000	12,000	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 6 + 6 + 12	6,900	6,900	6,900	6,900	6,900	13,700	0	0	4,980	24.3	22.0

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	42	42,000	6 + 6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	6,000	9,000	9,000	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 6 + 9 + 9	6,900	6,900	6,900	6,900	10,300	10,300	0	0	4,980	24.3	22.0
6	45	45,000	6 + 6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	6,000	15,000	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 6 + 6 + 15	6,800	6,800	6,800	6,800	6,800	17,000	0	0	5,290	25.9	23.4
6	45	45,000	6 + 6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	6,000	9,000	12,000	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 6 + 9 + 12	6,800	6,800	6,800	6,800	10,200	13,600	0	0	5,290	25.9	23.4
6	45	45,000	6 + 6 + 6 + 9 + 9 + 9	6,000	6,000	6,000	9,000	9,000	9,000	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 9 + 9 + 9	6,800	6,800	6,800	10,200	10,200	10,200	0	0	5,290	25.9	23.4
6	48	48,000	6 + 6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	6,000	18,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 6 + 18	6,800	6,800	6,800	6,800	6,800	20,300	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	6,000	9,000	15,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 9 + 15	6,800	6,800	6,800	6,800	10,100	16,900	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	6,000	12,000	12,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 12 + 12	6,800	6,800	6,800	6,800	13,500	13,500	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 6 + 9 + 9 + 12	6,000	6,000	6,000	9,000	9,000	12,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 9 + 9 + 12	6,800	6,800	6,800	10,100	10,100	13,500	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 9 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	9,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 9 + 9 + 9 + 9	6,800	6,800	10,100	10,100	10,100	10,100	0	0	5,610	27.4	24.8
6	51	48,000	6 + 6 + 6 + 6 + 9 + 18	5,600	5,600	5,600	5,600	8,500	16,900	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 9 + 18	6,400	6,400	6,400	6,400	9,500	19,100	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 6 + 6 + 12 + 15	5,600	5,600	5,600	5,600	11,300	14,100	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 12 + 15	6,400	6,400	6,400	6,400	12,700	15,900	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 6 + 9 + 9 + 15	5,600	5,600	5,600	8,500	8,500	14,100	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 9 + 9 + 15	6,400	6,400	6,400	9,500	9,500	15,900	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 6 + 9 + 12 + 12	5,600	5,600	5,600	8,500	11,300	11,300	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 9 + 12 + 12	6,400	6,400	6,400	9,500	12,700	12,700	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 9 + 9 + 9 + 12	5,600	5,600	8,500	8,500	8,500	11,300	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 9 + 9 + 12	6,400	6,400	9,500	9,500	9,500	12,700	0	0	5,500	26.9	24.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of indoor unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	51	48,000	6 + 9 + 9 + 9 + 9 + 9	5,600	8,500	8,500	8,500	8,500	8,500	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 9 + 9 + 9 + 9	6,400	9,500	9,500	9,500	9,500	9,500	0	0	5,500	26.9	24.3
6	54	48,000	6 + 6 + 6 + 6 + 6 + 24	5,300	5,300	5,300	5,300	5,300	21,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	6,000	24,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 6 + 12 + 18	5,300	5,300	5,300	5,300	10,700	16,000	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	6,000	12,000	18,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 6 + 15 + 15	5,300	5,300	5,300	5,300	13,300	13,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	6,000	15,000	15,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 9 + 9 + 18	5,300	5,300	5,300	8,000	8,000	16,000	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 9 + 9 + 18	6,000	6,000	6,000	9,000	9,000	18,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 9 + 12 + 15	5,300	5,300	5,300	8,000	10,700	13,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 9 + 12 + 15	6,000	6,000	6,000	9,000	12,000	15,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 12 + 12 + 12	5,300	5,300	5,300	10,700	10,700	10,700	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 12 + 12 + 12	6,000	6,000	6,000	12,000	12,000	12,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 9 + 9 + 9 + 15	5,300	5,300	8,000	8,000	8,000	13,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 9 + 9 + 15	6,000	6,000	9,000	9,000	9,000	15,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 9 + 9 + 12 + 12	5,300	5,300	8,000	8,000	10,700	10,700	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 9 + 12 + 12	6,000	6,000	9,000	9,000	12,000	12,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 9 + 9 + 9 + 9 + 12	5,300	8,000	8,000	8,000	8,000	10,700	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 9 + 9 + 12	6,000	9,000	9,000	9,000	9,000	12,000	0	0	5,390	26.3	23.8
6	54	48,000	9 + 9 + 9 + 9 + 9 + 9	8,000	8,000	8,000	8,000	8,000	8,000	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	9,000	0	0	5,390	26.3	23.8
6	57	48,000	6 + 6 + 6 + 6 + 9 + 24	5,100	5,100	5,100	5,100	7,600	20,200	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 9 + 24	5,700	5,700	5,700	5,700	8,500	22,700	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 6 + 6 + 15 + 18	5,100	5,100	5,100	5,100	12,600	15,200	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 15 + 18	5,700	5,700	5,700	5,700	14,200	17,100	0	0	5,330	26.0	23.5

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.4	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.4	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.4	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.4	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.4	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.4	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.4	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.4	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3

STANDARD MODELS

NTXMMX48A182AB/NTXMMX48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.4	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.4	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	9	9,000	9	9,000	0	0	0	0	0	0	0	1,110	5.4	4.9
		10,300	9	10,300	0	0	0	0	0	0	0	1,304	6.4	5.8
1	12	12,000	12	12,000	0	0	0	0	0	0	0	1,410	6.9	6.2
		13,600	12	13,600	0	0	0	0	0	0	0	1,548	7.6	6.8
1	15	15,000	15	15,000	0	0	0	0	0	0	0	1,700	8.3	7.5
		16,900	15	16,900	0	0	0	0	0	0	0	1,792	8.7	7.9
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,980	9.6	8.7
		20,200	18	20,200	0	0	0	0	0	0	0	2,036	9.9	9.0
1	24	24,000	24	24,000	0	0	0	0	0	0	0	2,530	12.3	11.1
		26,800	24	26,800	0	0	0	0	0	0	0	2,523	12.3	11.1
1	30	30,000	30	30,000	0	0	0	0	0	0	0	3,060	14.9	13.5
		33,400	30	33,400	0	0	0	0	0	0	0	3,011	14.7	13.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,560	17.3	15.7
		40,000	36	40,000	0	0	0	0	0	0	0	3,499	17.1	15.4
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,980	9.6	8.7
		20,200	9 + 9	10,100	10,100	0	0	0	0	0	0	2,036	9.9	9.0
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	2,260	11.0	9.9
		23,500	9 + 12	10,100	13,400	0	0	0	0	0	0	2,279	11.1	10.1
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	2,530	12.3	11.1
		26,800	9 + 15	10,100	16,800	0	0	0	0	0	0	2,523	12.3	11.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	2,530	12.3	11.1
		26,800	12 + 12	13,400	13,400	0	0	0	0	0	0	2,523	12.3	11.1
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,800	13.6	12.3
		30,100	9 + 18	10,000	20,100	0	0	0	0	0	0	2,767	13.5	12.2
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,800	13.6	12.3
		30,100	12 + 15	13,400	16,700	0	0	0	0	0	0	2,767	13.5	12.2
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	3,060	14.9	13.5
		33,400	12 + 18	13,400	20,000	0	0	0	0	0	0	3,011	14.7	13.3
2	30	30,000	15 + 15	15,000	15,000	0	0	0	0	0	0	3,060	14.9	13.5
		33,400	15 + 15	16,700	16,700	0	0	0	0	0	0	3,011	14.7	13.3
2	33	33,000	9 + 24	9,000	24,000	0	0	0	0	0	0	3,320	16.1	14.6
		36,700	9 + 24	10,000	26,700	0	0	0	0	0	0	3,255	15.9	14.4
2	33	33,000	15 + 18	15,000	18,000	0	0	0	0	0	0	3,320	16.1	14.6
		36,700	15 + 18	16,700	20,000	0	0	0	0	0	0	3,255	15.9	14.4
2	36	36,000	12 + 24	12,000	24,000	0	0	0	0	0	0	3,560	17.3	15.7
		40,000	12 + 24	13,300	26,700	0	0	0	0	0	0	3,499	17.1	15.4
2	36	36,000	18 + 18	18,000	18,000	0	0	0	0	0	0	3,560	17.3	15.7
		40,000	18 + 18	20,000	20,000	0	0	0	0	0	0	3,499	17.1	15.4
2	39	39,000	9 + 30	9,000	30,000	0	0	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 30	9,800	33,400	0	0	0	0	0	0	3,743	18.3	16.5

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	39	39,000	15 + 24	15,000	24,000	0	0	0	0	0	0	3,790	18.4	16.7
		43,200	15 + 24	16,600	26,600	0	0	0	0	0	0	3,743	18.3	16.5
2	42	42,000	12 + 30	12,000	30,000	0	0	0	0	0	0	4,000	19.4	17.6
		46,500	12 + 30	13,100	33,400	0	0	0	0	0	0	3,987	19.5	17.6
2	42	42,000	18 + 24	18,000	24,000	0	0	0	0	0	0	4,000	19.4	17.6
		46,500	18 + 24	19,900	26,600	0	0	0	0	0	0	3,987	19.5	17.6
2	45	45,000	9 + 36	9,000	36,000	0	0	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 36	9,600	40,200	0	0	0	0	0	0	4,231	20.6	18.7
2	45	45,000	15 + 30	15,000	30,000	0	0	0	0	0	0	4,180	20.3	18.4
		49,800	15 + 30	16,300	33,500	0	0	0	0	0	0	4,231	20.6	18.7
2	48	48,000	12 + 36	12,000	36,000	0	0	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 36	12,900	40,200	0	0	0	0	0	0	4,474	21.8	19.8
2	48	48,000	18 + 30	18,000	30,000	0	0	0	0	0	0	4,340	21.1	19.1
		53,100	18 + 30	19,600	33,500	0	0	0	0	0	0	4,474	21.8	19.8
2	48	48,000	24 + 24	24,000	24,000	0	0	0	0	0	0	4,340	21.1	19.1
		53,100	24 + 24	26,600	26,600	0	0	0	0	0	0	4,474	21.8	19.8
2	51	51,000	15 + 36	15,000	36,000	0	0	0	0	0	0	4,480	21.8	19.7
		56,400	15 + 36	16,100	40,300	0	0	0	0	0	0	4,718	23.0	20.8
2	54	54,000	18 + 36	18,000	36,000	0	0	0	0	0	0	4,580	22.3	20.1
		59,700	18 + 36	19,400	40,300	0	0	0	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	54	54,000	24 + 30	24,000	30,000	0	0	0	0	0	0	4,580	22.3	20.1
		59,700	24 + 30	26,200	33,500	0	0	0	0	0	0	4,962	24.2	21.9
2	60	60,000	24 + 36	24,000	36,000	0	0	0	0	0	0	4,680	22.8	20.6
		66,000	24 + 36	25,800	40,200	0	0	0	0	0	0	5,450	26.6	24.1
2	60	60,000	30 + 30	30,000	30,000	0	0	0	0	0	0	4,680	22.8	20.6
		66,000	30 + 30	33,000	33,000	0	0	0	0	0	0	5,450	26.6	24.1
2	66	61,200	30 + 36	27,800	33,400	0	0	0	0	0	0	4,700	22.8	20.7
		67,200	30 + 36	30,300	36,900	0	0	0	0	0	0	5,410	26.4	23.9
2	72	62,400	36 + 36	31,200	31,200	0	0	0	0	0	0	4,700	22.8	20.7
		68,400	36 + 36	34,200	34,200	0	0	0	0	0	0	5,410	26.4	23.9
3	27	27,000	9 + 9 + 9	9,000	9,000	9,000	0	0	0	0	0	2,800	13.6	12.3
		30,100	9 + 9 + 9	10,000	10,000	10,000	0	0	0	0	0	2,767	13.5	12.2
3	30	30,000	9 + 9 + 12	9,000	9,000	12,000	0	0	0	0	0	3,060	14.9	13.5
		33,400	9 + 9 + 12	10,000	10,000	13,400	0	0	0	0	0	3,011	14.7	13.3
3	33	33,000	9 + 9 + 15	9,000	9,000	15,000	0	0	0	0	0	3,320	16.1	14.6
		36,700	9 + 9 + 15	10,000	10,000	16,700	0	0	0	0	0	3,255	15.9	14.4
3	33	33,000	9 + 12 + 12	9,000	12,000	12,000	0	0	0	0	0	3,320	16.1	14.6
		36,700	9 + 12 + 12	10,000	13,300	13,300	0	0	0	0	0	3,255	15.9	14.4
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 9 + 18	10,000	10,000	20,000	0	0	0	0	0	3,499	17.1	15.4

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 9 + 18	10,000	10,000	20,000	0	0	0	0	0	3,499	17.1	15.4
3	36	36,000	9 + 12 + 15	9,000	12,000	15,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 12 + 15	10,000	13,300	16,700	0	0	0	0	0	3,499	17.1	15.4
3	36	36,000	12 + 12 + 12	12,000	12,000	12,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	12 + 12 + 12	13,300	13,300	13,300	0	0	0	0	0	3,499	17.1	15.4
3	39	39,000	9 + 12 + 18	9,000	12,000	18,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 12 + 18	10,000	13,300	19,900	0	0	0	0	0	3,743	18.3	16.5
3	39	39,000	9 + 15 + 15	9,000	15,000	15,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 15 + 15	10,000	16,600	16,600	0	0	0	0	0	3,743	18.3	16.5
3	39	39,000	12 + 12 + 15	12,000	12,000	15,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	12 + 12 + 15	13,300	13,300	16,600	0	0	0	0	0	3,743	18.3	16.5
3	42	42,000	9 + 9 + 24	9,000	9,000	24,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 9 + 24	10,000	10,000	26,600	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	9 + 15 + 18	9,000	15,000	18,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 15 + 18	10,000	16,600	19,900	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	12 + 12 + 18	12,000	12,000	18,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	12 + 12 + 18	13,300	13,300	19,900	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	12 + 15 + 15	12,000	15,000	15,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	12 + 15 + 15	13,300	16,600	16,600	0	0	0	0	0	3,987	19.5	17.6

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	45	45,000	9 + 12 + 24	9,000	12,000	24,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 12 + 24	10,000	13,300	26,600	0	0	0	0	0	4,231	20.6	18.7
3	45	45,000	9 + 18 + 18	9,000	18,000	18,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 18 + 18	10,000	19,900	19,900	0	0	0	0	0	4,231	20.6	18.7
3	45	45,000	12 + 15 + 18	12,000	15,000	18,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	12 + 15 + 18	13,300	16,600	19,900	0	0	0	0	0	4,231	20.6	18.7
3	45	45,000	15 + 15 + 15	15,000	15,000	15,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	15 + 15 + 15	16,600	16,600	16,600	0	0	0	0	0	4,231	20.6	18.7
3	48	48,000	9 + 9 + 30	9,000	9,000	30,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 30	9,800	9,800	33,500	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	9 + 15 + 24	9,000	15,000	24,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 15 + 24	10,000	16,600	26,600	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	12 + 12 + 24	12,000	12,000	24,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 12 + 24	13,300	13,300	26,600	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	12 + 18 + 18	12,000	18,000	18,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 18 + 18	13,300	19,900	19,900	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	15 + 15 + 18	15,000	15,000	18,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	15 + 15 + 18	16,600	16,600	19,900	0	0	0	0	0	4,474	21.8	19.8
3	51	51,000	9 + 12 + 30	9,000	12,000	30,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 12 + 30	9,800	13,100	33,500	0	0	0	0	0	4,718	23.0	20.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	51	51,000	9 + 18 + 24	9,000	18,000	24,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 18 + 24	10,000	19,900	26,500	0	0	0	0	0	4,718	23.0	20.8
3	51	51,000	12 + 15 + 24	12,000	15,000	24,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	12 + 15 + 24	13,300	16,600	26,500	0	0	0	0	0	4,718	23.0	20.8
3	51	51,000	15 + 18 + 18	15,000	18,000	18,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	15 + 18 + 18	16,600	19,900	19,900	0	0	0	0	0	4,718	23.0	20.8
3	54	54,000	9 + 9 + 36	9,000	9,000	36,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 36	9,700	9,700	40,300	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	9 + 15 + 30	9,000	15,000	30,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 15 + 30	9,800	16,400	33,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	12 + 12 + 30	12,000	12,000	30,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 12 + 30	13,100	13,100	33,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	12 + 18 + 24	12,000	18,000	24,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 18 + 24	13,300	19,900	26,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	15 + 15 + 24	15,000	15,000	24,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	15 + 15 + 24	16,600	16,600	26,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	18 + 18 + 18	18,000	18,000	18,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	18 + 18 + 18	19,900	19,900	19,900	0	0	0	0	0	4,962	24.2	21.9
3	57	57,000	9 + 12 + 36	9,000	12,000	36,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 36	9,700	12,900	40,400	0	0	0	0	0	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	57	57,000	9 + 18 + 30	9,000	18,000	30,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 18 + 30	9,800	19,600	33,500	0	0	0	0	0	5,206	25.4	23.0
3	57	57,000	9 + 24 + 24	9,000	24,000	24,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 24 + 24	9,900	26,500	26,500	0	0	0	0	0	5,206	25.4	23.0
3	57	57,000	12 + 15 + 30	12,000	15,000	30,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	12 + 15 + 30	13,100	16,400	33,500	0	0	0	0	0	5,206	25.4	23.0
3	60	60,000	9 + 15 + 36	9,000	15,000	36,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 15 + 36	9,700	16,100	40,200	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	12 + 12 + 36	12,000	12,000	36,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 36	12,900	12,900	40,200	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	12 + 18 + 30	12,000	18,000	30,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 18 + 30	13,000	19,600	33,400	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	12 + 24 + 24	12,000	24,000	24,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 24 + 24	13,200	26,400	26,400	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	15 + 15 + 30	15,000	15,000	30,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	15 + 15 + 30	16,300	16,300	33,400	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	18 + 18 + 24	18,000	18,000	24,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	18 + 18 + 24	19,800	19,800	26,400	0	0	0	0	0	5,450	26.6	24.1
3	63	60,600	9 + 18 + 36	8,700	17,300	34,600	0	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 18 + 36	9,300	18,600	38,700	0	0	0	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	63	60,600	9 + 24 + 30	8,700	23,100	28,900	0	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 24 + 30	9,400	25,100	32,100	0	0	0	0	0	5,430	26.5	24.0
3	63	60,600	12 + 15 + 36	11,500	14,400	34,600	0	0	0	0	0	4,690	22.8	20.6
		66,600	12 + 15 + 36	12,400	15,500	38,700	0	0	0	0	0	5,430	26.5	24.0
3	66	61,200	12 + 18 + 36	11,100	16,700	33,400	0	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 18 + 36	11,900	17,900	37,300	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	12 + 24 + 30	11,100	22,300	27,800	0	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 24 + 30	12,100	24,200	31,000	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	15 + 15 + 36	13,900	13,900	33,400	0	0	0	0	0	4,700	22.8	20.7
		67,200	15 + 15 + 36	14,900	14,900	37,300	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	18 + 18 + 30	16,700	16,700	27,800	0	0	0	0	0	4,700	22.8	20.7
		67,200	18 + 18 + 30	18,100	18,100	31,000	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	18 + 24 + 24	16,700	22,300	22,300	0	0	0	0	0	4,700	22.8	20.7
		67,200	18 + 24 + 24	18,300	24,400	24,400	0	0	0	0	0	5,410	26.4	23.9
3	69	61,800	9 + 24 + 36	8,100	21,500	32,200	0	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 24 + 36	8,700	23,100	36,100	0	0	0	0	0	5,410	26.4	23.9
3	69	61,800	9 + 30 + 30	8,100	26,900	26,900	0	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 30 + 30	8,700	29,600	29,600	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	12 + 24 + 36	10,400	20,800	31,200	0	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 24 + 36	11,200	22,300	34,900	0	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	72	62,400	12 + 30 + 30	10,400	26,000	26,000	0	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 30 + 30	11,200	28,600	28,600	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	18 + 18 + 36	15,600	15,600	31,200	0	0	0	0	0	4,700	22.8	20.7
		68,400	18 + 18 + 36	16,800	16,800	34,900	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	18 + 24 + 30	15,600	20,800	26,000	0	0	0	0	0	4,700	22.8	20.7
		68,400	18 + 24 + 30	16,900	22,600	28,900	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	24 + 24 + 24	20,800	20,800	20,800	0	0	0	0	0	4,700	22.8	20.7
		68,400	24 + 24 + 24	22,800	22,800	22,800	0	0	0	0	0	5,410	26.4	23.9
3	75	63,000	9 + 30 + 36	7,600	25,200	30,200	0	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 30 + 36	8,000	27,500	33,500	0	0	0	0	0	5,410	26.4	23.9
3	78	63,600	12 + 30 + 36	9,800	24,500	29,400	0	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 30 + 36	10,400	26,700	32,500	0	0	0	0	0	5,410	26.4	23.9
3	78	63,600	18 + 24 + 36	14,700	19,600	29,400	0	0	0	0	0	4,690	22.8	20.6
		69,600	18 + 24 + 36	15,800	21,000	32,800	0	0	0	0	0	5,410	26.4	23.9
3	78	63,600	24 + 24 + 30	19,600	19,600	24,500	0	0	0	0	0	4,690	22.8	20.6
		69,600	24 + 24 + 30	21,200	21,200	27,200	0	0	0	0	0	5,410	26.4	23.9
4	36	36,000	9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 9 + 9 + 9	10,000	10,000	10,000	10,000	0	0	0	0	3,499	17.1	15.4
4	39	39,000	9 + 9 + 9 + 12	9,000	9,000	9,000	12,000	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 9 + 9 + 12	10,000	10,000	10,000	13,300	0	0	0	0	3,743	18.3	16.5

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	42	42,000	9 + 9 + 9 + 15	9,000	9,000	9,000	15,000	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 9 + 9 + 15	10,000	10,000	10,000	16,600	0	0	0	0	3,987	19.5	17.6
4	42	42,000	9 + 9 + 12 + 12	9,000	9,000	12,000	12,000	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 9 + 12 + 12	10,000	10,000	13,300	13,300	0	0	0	0	3,987	19.5	17.6
4	45	45,000	9 + 9 + 9 + 18	9,000	9,000	9,000	18,000	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 9 + 9 + 18	10,000	10,000	10,000	19,900	0	0	0	0	4,231	20.6	18.7
4	45	45,000	9 + 9 + 12 + 15	9,000	9,000	12,000	15,000	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 9 + 12 + 15	10,000	10,000	13,300	16,600	0	0	0	0	4,231	20.6	18.7
4	45	48,000	9 + 12 + 12 + 12	9,600	12,800	12,800	12,800	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 12 + 12 + 12	10,000	13,300	13,300	13,300	0	0	0	0	4,231	20.6	18.7
4	48	48,000	9 + 9 + 12 + 18	9,000	9,000	12,000	18,000	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 12 + 18	10,000	10,000	13,300	19,900	0	0	0	0	4,474	21.8	19.8
4	48	45,000	9 + 9 + 15 + 15	8,400	8,400	14,100	14,100	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 15 + 15	10,000	10,000	16,600	16,600	0	0	0	0	4,474	21.8	19.8
4	48	48,000	9 + 12 + 12 + 15	9,000	12,000	12,000	15,000	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 12 + 12 + 15	10,000	13,300	13,300	16,600	0	0	0	0	4,474	21.8	19.8
4	48	48,000	12 + 12 + 12 + 12	12,000	12,000	12,000	12,000	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 12 + 12 + 12	13,300	13,300	13,300	13,300	0	0	0	0	4,474	21.8	19.8
4	51	51,000	9 + 9 + 9 + 24	9,000	9,000	9,000	24,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 9 + 24	10,000	10,000	10,000	26,500	0	0	0	0	4,718	23.0	20.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	51	51,000	9 + 9 + 15 + 18	9,000	9,000	15,000	18,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 15 + 18	10,000	10,000	16,600	19,900	0	0	0	0	4,718	23.0	20.8
4	51	51,000	9 + 12 + 12 + 18	9,000	12,000	12,000	18,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 12 + 12 + 18	10,000	13,300	13,300	19,900	0	0	0	0	4,718	23.0	20.8
4	51	51,000	9 + 12 + 15 + 15	9,000	12,000	15,000	15,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 12 + 15 + 15	10,000	13,300	16,600	16,600	0	0	0	0	4,718	23.0	20.8
4	51	51,000	12 + 12 + 12 + 15	12,000	12,000	12,000	15,000	0	0	0	0	4,480	21.8	19.7
		56,400	12 + 12 + 12 + 15	13,300	13,300	13,300	16,600	0	0	0	0	4,718	23.0	20.8
4	54	54,000	9 + 9 + 12 + 24	9,000	9,000	12,000	24,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 12 + 24	10,000	10,000	13,300	26,500	0	0	0	0	4,962	24.2	21.9
4	54	54,000	9 + 9 + 18 + 18	9,000	9,000	18,000	18,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 18 + 18	10,000	10,000	19,900	19,900	0	0	0	0	4,962	24.2	21.9
4	54	54,000	9 + 12 + 15 + 18	9,000	12,000	15,000	18,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 12 + 15 + 18	10,000	13,300	16,600	19,900	0	0	0	0	4,962	24.2	21.9
4	54	54,000	9 + 15 + 15 + 15	9,000	15,000	15,000	15,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 15 + 15 + 15	10,000	16,600	16,600	16,600	0	0	0	0	4,962	24.2	21.9
4	54	54,000	12 + 12 + 12 + 18	12,000	12,000	12,000	18,000	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 12 + 12 + 18	13,300	13,300	13,300	19,900	0	0	0	0	4,962	24.2	21.9
4	54	54,000	12 + 12 + 15 + 15	12,000	12,000	15,000	15,000	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 12 + 15 + 15	13,300	13,300	16,600	16,600	0	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	57	57,000	9 + 9 + 9 + 30	9,000	9,000	9,000	30,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 30	9,800	9,800	9,800	33,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 9 + 15 + 24	9,000	9,000	15,000	24,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 15 + 24	9,900	9,900	16,600	26,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 12 + 12 + 24	9,000	12,000	12,000	24,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 12 + 24	9,900	13,300	13,300	26,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 12 + 18 + 18	9,000	12,000	18,000	18,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 18 + 18	9,900	13,300	19,900	19,900	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 15 + 15 + 18	9,000	15,000	15,000	18,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 15 + 15 + 18	9,900	16,600	16,600	19,900	0	0	0	0	5,206	25.4	23.0
4	57	57,000	12 + 12 + 15 + 18	12,000	12,000	15,000	18,000	0	0	0	0	4,630	22.5	20.4
		63,000	12 + 12 + 15 + 18	13,300	13,300	16,600	19,900	0	0	0	0	5,206	25.4	23.0
4	57	57,000	12 + 15 + 15 + 15	12,000	15,000	15,000	15,000	0	0	0	0	4,630	22.5	20.4
		63,000	12 + 15 + 15 + 15	13,300	16,600	16,600	16,600	0	0	0	0	5,206	25.4	23.0
4	60	60,000	9 + 9 + 12 + 30	9,000	9,000	12,000	30,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 12 + 30	9,800	9,800	13,000	33,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	9 + 9 + 18 + 24	9,000	9,000	18,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 18 + 24	9,900	9,900	19,800	26,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	9 + 12 + 15 + 24	9,000	12,000	15,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 12 + 15 + 24	9,900	13,200	16,500	26,400	0	0	0	0	5,450	26.6	24.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	60	60,000	9 + 15 + 18 + 18	9,000	15,000	18,000	18,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 15 + 18 + 18	9,900	16,500	19,800	19,800	0	0	0	0	5,450	26.6	24.1
4	60	60,000	12 + 12 + 12 + 24	12,000	12,000	12,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 12 + 24	13,200	13,200	13,200	26,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	12 + 12 + 18 + 18	12,000	12,000	18,000	18,000	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 18 + 18	13,200	13,200	19,800	19,800	0	0	0	0	5,450	26.6	24.1
4	60	60,000	12 + 15 + 15 + 18	12,000	15,000	15,000	18,000	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 15 + 15 + 18	13,200	16,500	16,500	19,800	0	0	0	0	5,450	26.6	24.1
4	60	60,000	15 + 15 + 15 + 15	15,000	15,000	15,000	15,000	0	0	0	0	4,680	22.8	20.6
		66,000	15 + 15 + 15 + 15	16,500	16,500	16,500	16,500	0	0	0	0	5,450	26.6	24.1
4	63	60,600	9 + 9 + 9 + 36	8,700	8,700	8,700	34,600	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 36	9,300	9,300	9,300	38,700	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 9 + 15 + 30	8,700	8,700	14,400	28,900	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 15 + 30	9,400	9,400	15,700	32,100	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 12 + 12 + 30	8,700	11,500	11,500	28,900	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 12 + 30	9,400	12,500	12,500	32,100	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 12 + 18 + 24	8,700	11,500	17,300	23,100	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 18 + 24	9,500	12,700	19,000	25,400	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 15 + 15 + 24	8,700	14,400	14,400	23,100	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 15 + 15 + 24	9,500	15,900	15,900	25,400	0	0	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	63	60,600	9 + 18 + 18 + 18	8,700	17,300	17,300	17,300	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 18 + 18 + 18	9,500	19,000	19,000	19,000	0	0	0	0	5,430	26.5	24.0
4	63	60,600	12 + 12 + 15 + 24	11,500	11,500	14,400	23,100	0	0	0	0	4,690	22.8	20.6
		66,600	12 + 12 + 15 + 24	12,700	12,700	15,900	25,400	0	0	0	0	5,430	26.5	24.0
4	63	60,600	12 + 15 + 18 + 18	11,500	14,400	17,300	17,300	0	0	0	0	4,690	22.8	20.6
		66,600	12 + 15 + 18 + 18	12,700	15,900	19,000	19,000	0	0	0	0	5,430	26.5	24.0
4	63	60,600	15 + 15 + 15 + 18	14,400	14,400	14,400	17,300	0	0	0	0	4,690	22.8	20.6
		66,600	15 + 15 + 15 + 18	15,900	15,900	15,900	19,000	0	0	0	0	5,430	26.5	24.0
4	66	61,200	9 + 9 + 12 + 36	8,300	8,300	11,100	33,400	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 36	9,000	9,000	11,900	37,300	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 9 + 18 + 30	8,300	8,300	16,700	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 18 + 30	9,100	9,100	18,100	31,000	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 9 + 24 + 24	8,300	8,300	22,300	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 24 + 24	9,200	9,200	24,400	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 12 + 15 + 30	8,300	11,100	13,900	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 12 + 15 + 30	9,100	12,100	15,100	31,000	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 15 + 18 + 24	8,300	13,900	16,700	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 15 + 18 + 24	9,200	15,300	18,300	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	12 + 12 + 12 + 30	11,100	11,100	11,100	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 12 + 30	12,100	12,100	12,100	31,000	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	66	61,200	12 + 12 + 18 + 24	11,100	11,100	16,700	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 18 + 24	12,200	12,200	18,300	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	12 + 15 + 15 + 24	11,100	13,900	13,900	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 15 + 15 + 24	12,200	15,300	15,300	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	12 + 18 + 18 + 18	11,100	16,700	16,700	16,700	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 18 + 18 + 18	12,200	18,300	18,300	18,300	0	0	0	0	5,410	26.4	23.9
4	66	61,200	15 + 15 + 18 + 18	13,900	13,900	16,700	16,700	0	0	0	0	4,700	22.8	20.7
		67,200	15 + 15 + 18 + 18	15,300	15,300	18,300	18,300	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 9 + 15 + 36	8,100	8,100	13,400	32,200	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 15 + 36	8,700	8,700	14,400	36,100	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 12 + 12 + 36	8,100	10,700	10,700	32,200	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 12 + 36	8,700	11,500	11,500	36,100	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 12 + 18 + 30	8,100	10,700	16,100	26,900	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 18 + 30	8,700	11,700	17,500	29,900	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 15 + 15 + 30	8,100	13,400	13,400	26,900	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 15 + 15 + 30	8,700	14,600	14,600	29,900	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 18 + 18 + 24	8,100	16,100	16,100	21,500	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 18 + 18 + 24	8,800	17,700	17,700	23,600	0	0	0	0	5,410	26.4	23.9
4	69	61,800	12 + 12 + 15 + 30	10,700	10,700	13,400	26,900	0	0	0	0	4,700	22.8	20.7
		67,800	12 + 12 + 15 + 30	11,700	11,700	14,600	29,900	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	69	61,800	12 + 15 + 18 + 24	10,700	13,400	16,100	21,500	0	0	0	0	4,700	22.8	20.7
		67,800	12 + 15 + 18 + 24	11,800	14,700	17,700	23,600	0	0	0	0	5,410	26.4	23.9
4	69	61,800	15 + 15 + 15 + 24	13,400	13,400	13,400	21,500	0	0	0	0	4,700	22.8	20.7
		67,800	15 + 15 + 15 + 24	14,700	14,700	14,700	23,600	0	0	0	0	5,410	26.4	23.9
4	69	61,800	15 + 18 + 18 + 18	13,400	16,100	16,100	16,100	0	0	0	0	4,700	22.8	20.7
		67,800	15 + 18 + 18 + 18	14,700	17,700	17,700	17,700	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 9 + 18 + 36	7,800	7,800	15,600	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 18 + 36	8,400	8,400	16,800	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 9 + 24 + 30	7,800	7,800	20,800	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 24 + 30	8,500	8,500	22,600	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 12 + 15 + 36	7,800	10,400	13,000	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 12 + 15 + 36	8,400	11,200	14,000	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 15 + 18 + 30	7,800	13,000	15,600	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 15 + 18 + 30	8,500	14,100	16,900	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 15 + 24 + 24	7,800	13,000	20,800	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 15 + 24 + 24	8,600	14,300	22,800	22,800	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 12 + 12 + 36	10,400	10,400	10,400	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 12 + 36	11,200	11,200	11,200	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 12 + 18 + 30	10,400	10,400	15,600	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 18 + 30	11,300	11,300	16,900	28,900	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	72	62,400	12 + 12 + 24 + 24	10,400	10,400	20,800	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 24 + 24	11,400	11,400	22,800	22,800	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 15 + 15 + 30	10,400	13,000	13,000	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 15 + 15 + 30	11,300	14,100	14,100	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 18 + 18 + 24	10,400	15,600	15,600	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 18 + 18 + 24	11,400	17,100	17,100	22,800	0	0	0	0	5,410	26.4	23.9
4	72	62,400	15 + 15 + 18 + 24	13,000	13,000	15,600	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	15 + 15 + 18 + 24	14,300	14,300	17,100	22,800	0	0	0	0	5,410	26.4	23.9
4	72	62,400	18 + 18 + 18 + 18	15,600	15,600	15,600	15,600	0	0	0	0	4,700	22.8	20.7
		68,400	18 + 18 + 18 + 18	17,100	17,100	17,100	17,100	0	0	0	0	5,410	26.4	23.9
4	75	63,000	9 + 12 + 18 + 36	7,600	10,100	15,100	30,200	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 18 + 36	8,100	10,800	16,200	33,800	0	0	0	0	5,410	26.4	23.9
4	75	63,000	9 + 15 + 15 + 36	7,600	12,600	12,600	30,200	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 15 + 15 + 36	8,100	13,500	13,500	33,800	0	0	0	0	5,410	26.4	23.9
4	75	63,000	9 + 18 + 18 + 30	7,600	15,100	15,100	25,200	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 18 + 18 + 30	8,200	16,400	16,400	28,000	0	0	0	0	5,410	26.4	23.9
4	75	63,000	12 + 12 + 15 + 36	10,100	10,100	12,600	30,200	0	0	0	0	4,700	22.8	20.7
		69,000	12 + 12 + 15 + 36	10,800	10,800	13,500	33,800	0	0	0	0	5,410	26.4	23.9
4	75	63,000	12 + 15 + 18 + 30	10,100	12,600	15,100	25,200	0	0	0	0	4,700	22.8	20.7
		69,000	12 + 15 + 18 + 30	10,900	13,700	16,400	28,000	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	75	63,000	15 + 15 + 15 + 30	12,600	12,600	12,600	25,200	0	0	0	0	4,700	22.8	20.7
		69,000	15 + 15 + 15 + 30	13,700	13,700	13,700	28,000	0	0	0	0	5,410	26.4	23.9
4	75	63,000	15 + 18 + 18 + 24	12,600	15,100	15,100	20,200	0	0	0	0	4,700	22.8	20.7
		69,000	15 + 18 + 18 + 24	13,800	16,600	16,600	22,100	0	0	0	0	5,410	26.4	23.9
4	78	63,600	9 + 9 + 24 + 36	7,300	7,300	19,600	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 24 + 36	7,900	7,900	21,000	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	9 + 9 + 30 + 30	7,300	7,300	24,500	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 30 + 30	7,900	7,900	26,900	26,900	0	0	0	0	5,410	26.4	23.9
4	78	63,600	9 + 15 + 18 + 36	7,300	12,200	14,700	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 18 + 36	7,900	13,100	15,800	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	9 + 15 + 24 + 30	7,300	12,200	19,600	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 24 + 30	8,000	13,300	21,200	27,200	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 12 + 18 + 36	9,800	9,800	14,700	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 18 + 36	10,500	10,500	15,800	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 12 + 24 + 30	9,800	9,800	19,600	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 24 + 30	10,600	10,600	21,200	27,200	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 15 + 15 + 36	9,800	12,200	12,200	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 15 + 15 + 36	10,500	13,100	13,100	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 18 + 18 + 30	9,800	14,700	14,700	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 18 + 18 + 30	10,600	15,900	15,900	27,200	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	78	63,600	15 + 15 + 18 + 30	12,200	12,200	14,700	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	15 + 15 + 18 + 30	13,300	13,300	15,900	27,200	0	0	0	0	5,410	26.4	23.9
4	78	63,600	18 + 18 + 18 + 24	14,700	14,700	14,700	19,600	0	0	0	0	4,690	22.8	20.6
		69,600	18 + 18 + 18 + 24	16,100	16,100	16,100	21,400	0	0	0	0	5,410	26.4	23.9
5	45	45,000	9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	0	0	0	4,180	20.3	18.4
		49,800	9 + 9 + 9 + 9 + 9	10,000	10,000	10,000	10,000	10,000	0	0	0	4,231	20.6	18.7
5	48	48,000	9 + 9 + 9 + 9 + 12	9,000	9,000	9,000	9,000	12,000	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 9 + 9 + 12	10,000	10,000	10,000	10,000	13,300	0	0	0	4,474	21.8	19.8
5	51	51,000	9 + 9 + 9 + 9 + 15	9,000	9,000	9,000	9,000	15,000	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 9 + 9 + 15	10,000	10,000	10,000	10,000	16,600	0	0	0	4,718	23.0	20.8
5	51	51,000	9 + 9 + 9 + 12 + 12	9,000	9,000	9,000	12,000	12,000	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 9 + 12 + 12	10,000	10,000	10,000	13,300	13,300	0	0	0	4,718	23.0	20.8
5	54	54,000	9 + 9 + 9 + 9 + 18	9,000	9,000	9,000	9,000	18,000	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 9 + 9 + 18	10,000	10,000	10,000	10,000	19,900	0	0	0	4,962	24.2	21.9
5	54	54,000	9 + 9 + 9 + 12 + 15	9,000	9,000	9,000	12,000	15,000	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 9 + 12 + 15	10,000	10,000	10,000	13,300	16,600	0	0	0	4,962	24.2	21.9
5	54	54,000	9 + 9 + 12 + 12 + 12	9,000	9,000	12,000	12,000	12,000	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 12 + 12 + 12	10,000	10,000	13,300	13,300	13,300	0	0	0	4,962	24.2	21.9
5	57	57,000	9 + 9 + 9 + 12 + 18	9,000	9,000	9,000	12,000	18,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 12 + 18	9,900	9,900	9,900	13,300	19,900	0	0	0	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	57	57,000	9 + 9 + 9 + 15 + 15	9,000	9,000	9,000	15,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 15 + 15	9,900	9,900	9,900	16,600	16,600	0	0	0	5,206	25.4	23.0
5	57	57,000	9 + 9 + 12 + 12 + 15	9,000	9,000	12,000	12,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 12 + 12 + 15	9,900	9,900	13,300	13,300	16,600	0	0	0	5,206	25.4	23.0
5	57	57,000	9 + 12 + 12 + 12 + 12	9,000	12,000	12,000	12,000	12,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 12 + 12 + 12	9,900	13,300	13,300	13,300	13,300	0	0	0	5,206	25.4	23.0
5	60	60,000	9 + 9 + 9 + 9 + 24	9,000	9,000	9,000	9,000	24,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 9 + 24	9,900	9,900	9,900	9,900	26,400	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 9 + 9 + 15 + 18	9,000	9,000	9,000	15,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 15 + 18	9,900	9,900	9,900	16,500	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 9 + 12 + 12 + 18	9,000	9,000	12,000	12,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 12 + 12 + 18	9,900	9,900	13,200	13,200	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 9 + 12 + 15 + 15	9,000	9,000	12,000	15,000	15,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 12 + 15 + 15	9,900	9,900	13,200	16,500	16,500	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 12 + 12 + 12 + 15	9,000	12,000	12,000	12,000	15,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 12 + 12 + 12 + 15	9,900	13,200	13,200	13,200	16,500	0	0	0	5,450	26.6	24.1
5	60	60,000	12 + 12 + 12 + 12 + 12	12,000	12,000	12,000	12,000	12,000	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 12 + 12 + 12	13,200	13,200	13,200	13,200	13,200	0	0	0	5,450	26.6	24.1
5	63	60,600	9 + 9 + 9 + 12 + 24	8,700	8,700	8,700	11,500	23,100	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 12 + 24	9,500	9,500	9,500	12,700	25,400	0	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	63	60,600	9 + 9 + 9 + 18 + 18	8,700	8,700	8,700	17,300	17,300	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 18 + 18	9,500	9,500	9,500	19,000	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 9 + 12 + 15 + 18	8,700	8,700	11,500	14,400	17,300	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 12 + 15 + 18	9,500	9,500	12,700	15,900	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 9 + 15 + 15 + 15	8,700	8,700	14,400	14,400	14,400	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 15 + 15 + 15	9,500	9,500	15,900	15,900	15,900	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 12 + 12 + 12 + 18	8,700	11,500	11,500	11,500	17,300	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 12 + 12 + 18	9,500	12,700	12,700	12,700	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 12 + 12 + 15 + 15	8,700	11,500	11,500	14,400	14,400	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 12 + 15 + 15	9,500	12,700	12,700	15,900	15,900	0	0	0	5,430	26.5	24.0
5	63	60,600	12 + 12 + 12 + 12 + 15	11,500	11,500	11,500	11,500	14,400	0	0	0	4,690	22.8	20.6
		66,600	12 + 12 + 12 + 12 + 15	12,700	12,700	12,700	12,700	15,900	0	0	0	5,430	26.5	24.0
5	66	61,200	9 + 9 + 9 + 9 + 30	8,300	8,300	8,300	8,300	27,800	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 30	9,100	9,100	9,100	9,100	31,000	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 9 + 15 + 24	8,300	8,300	8,300	13,900	22,300	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 15 + 24	9,200	9,200	9,200	15,300	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 12 + 12 + 24	8,300	8,300	11,100	11,100	22,300	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 12 + 24	9,200	9,200	12,200	12,200	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 12 + 18 + 18	8,300	8,300	11,100	16,700	16,700	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 18 + 18	9,200	9,200	12,200	18,300	18,300	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	66	61,200	9 + 9 + 15 + 15 + 18	8,300	8,300	13,900	13,900	16,700	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 15 + 15 + 18	9,200	9,200	15,300	15,300	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 12 + 12 + 15 + 18	8,300	11,100	11,100	13,900	16,700	0	0	0	4,700	22.8	20.7
		67,200	9 + 12 + 12 + 15 + 18	9,200	12,200	12,200	15,300	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 12 + 15 + 15 + 15	8,300	11,100	13,900	13,900	13,900	0	0	0	4,700	22.8	20.7
		67,200	9 + 12 + 15 + 15 + 15	9,200	12,200	15,300	15,300	15,300	0	0	0	5,410	26.4	23.9
5	66	61,200	12 + 12 + 12 + 12 + 18	11,100	11,100	11,100	11,100	16,700	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 12 + 12 + 18	12,200	12,200	12,200	12,200	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	12 + 12 + 12 + 15 + 15	11,100	11,100	11,100	13,900	13,900	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 12 + 15 + 15	12,200	12,200	12,200	15,300	15,300	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 9 + 9 + 12 + 30	8,100	8,100	8,100	10,700	26,900	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 12 + 30	8,700	8,700	8,700	11,700	29,900	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 9 + 9 + 18 + 24	8,100	8,100	8,100	16,100	21,500	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 18 + 24	8,800	8,800	8,800	17,700	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 9 + 12 + 15 + 24	8,100	8,100	10,700	13,400	21,500	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 12 + 15 + 24	8,800	8,800	11,800	14,700	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 12 + 12 + 12 + 24	8,100	10,700	10,700	10,700	21,500	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 12 + 12 + 24	8,800	11,800	11,800	11,800	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 12 + 15 + 15 + 18	8,100	10,700	13,400	13,400	16,100	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 15 + 15 + 18	8,800	11,800	14,700	14,700	17,700	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	69	61,800	9 + 15 + 15 + 15 + 15	8,100	13,400	13,400	13,400	13,400	0	0	0	4,700	22.8	20.7
		67,800	9 + 15 + 15 + 15 + 15	8,800	14,700	14,700	14,700	14,700	0	0	0	5,410	26.4	23.9
5	69	61,800	12 + 12 + 12 + 15 + 18	10,700	10,700	10,700	13,400	16,100	0	0	0	4,700	22.8	20.7
		67,800	12 + 12 + 12 + 15 + 18	11,800	11,800	11,800	14,700	17,700	0	0	0	5,410	26.4	23.9
5	69	61,800	12 + 12 + 15 + 15 + 15	10,700	10,700	13,400	13,400	13,400	0	0	0	4,700	22.8	20.7
		67,800	12 + 12 + 15 + 15 + 15	11,800	11,800	14,700	14,700	14,700	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 9 + 9 + 36	7,800	7,800	7,800	7,800	31,200	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 36	8,400	8,400	8,400	8,400	34,900	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 9 + 15 + 30	7,800	7,800	7,800	13,000	26,000	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 15 + 30	8,500	8,500	8,500	14,100	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 12 + 12 + 30	7,800	7,800	10,400	10,400	26,000	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 12 + 30	8,500	8,500	11,300	11,300	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 12 + 18 + 24	7,800	7,800	10,400	15,600	20,800	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 18 + 24	8,600	8,600	11,400	17,100	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 15 + 15 + 24	7,800	7,800	13,000	13,000	20,800	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 15 + 15 + 24	8,600	8,600	14,300	14,300	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 18 + 18 + 18	7,800	7,800	15,600	15,600	15,600	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 18 + 18 + 18	8,600	8,600	17,100	17,100	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 12 + 12 + 15 + 24	7,800	10,400	10,400	13,000	20,800	0	0	0	4,700	22.8	20.7
		68,400	9 + 12 + 12 + 15 + 24	8,600	11,400	11,400	14,300	22,800	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	72	62,400	9 + 15 + 15 + 15 + 18	7,800	13,000	13,000	13,000	15,600	0	0	0	4,700	22.8	20.7
		68,400	9 + 15 + 15 + 15 + 18	8,600	14,300	14,300	14,300	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	12 + 12 + 12 + 12 + 24	10,400	10,400	10,400	10,400	20,800	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 12 + 12 + 24	11,400	11,400	11,400	11,400	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	12 + 12 + 12 + 18 + 18	10,400	10,400	10,400	15,600	15,600	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 12 + 18 + 18	11,400	11,400	11,400	17,100	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	12 + 12 + 15 + 15 + 18	10,400	10,400	13,000	13,000	15,600	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 15 + 15 + 18	11,400	11,400	14,300	14,300	17,100	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 9 + 12 + 36	7,600	7,600	7,600	10,100	30,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 36	8,100	8,100	8,100	10,800	33,800	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 9 + 18 + 30	7,600	7,600	7,600	15,100	25,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 18 + 30	8,200	8,200	8,200	16,400	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 9 + 24 + 24	7,600	7,600	7,600	20,200	20,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 24 + 24	8,300	8,300	8,300	22,100	22,100	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 12 + 15 + 30	7,600	7,600	10,100	12,600	25,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 12 + 15 + 30	8,200	8,200	10,900	13,700	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 12 + 12 + 12 + 30	7,600	10,100	10,100	10,100	25,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 12 + 12 + 30	8,200	10,900	10,900	10,900	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 12 + 15 + 15 + 24	7,600	10,100	12,600	12,600	20,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 15 + 15 + 24	8,300	11,000	13,800	13,800	22,100	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	75	63,000	9 + 12 + 18 + 18 + 18	7,600	10,100	15,100	15,100	15,100	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 18 + 18 + 18	8,300	11,000	16,600	16,600	16,600	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 15 + 15 + 18 + 18	7,600	12,600	12,600	15,100	15,100	0	0	0	4,700	22.8	20.7
		69,000	9 + 15 + 15 + 18 + 18	8,300	13,800	13,800	16,600	16,600	0	0	0	5,410	26.4	23.9
5	75	63,000	12 + 12 + 12 + 15 + 24	10,100	10,100	10,100	12,600	20,200	0	0	0	4,700	22.8	20.7
		69,000	12 + 12 + 12 + 15 + 24	11,000	11,000	11,000	13,800	22,100	0	0	0	5,410	26.4	23.9
5	75	63,000	12 + 12 + 15 + 18 + 18	10,100	10,100	12,600	15,100	15,100	0	0	0	4,700	22.8	20.7
		69,000	12 + 12 + 15 + 18 + 18	11,000	11,000	13,800	16,600	16,600	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 12 + 18 + 30	7,300	7,300	9,800	14,700	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 18 + 30	8,000	8,000	10,600	15,900	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 9 + 15 + 36	7,300	7,300	7,300	12,200	29,400	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 15 + 36	7,900	7,900	7,900	13,100	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 12 + 12 + 36	7,300	7,300	9,800	9,800	29,400	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 12 + 36	7,900	7,900	10,500	10,500	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 12 + 18 + 30	7,300	7,300	9,800	14,700	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 18 + 30	8,000	8,000	10,600	15,900	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 12 + 24 + 24	7,300	7,300	9,800	19,600	19,600	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 24 + 24	8,000	8,000	10,700	21,400	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 15 + 15 + 30	7,300	7,300	12,200	12,200	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 15 + 15 + 30	8,000	8,000	13,300	13,300	27,200	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	78	63,600	9 + 9 + 18 + 18 + 24	7,300	7,300	14,700	14,700	19,600	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 18 + 18 + 24	8,000	8,000	16,100	16,100	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 12 + 12 + 15 + 30	7,300	9,800	9,800	12,200	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 12 + 12 + 15 + 30	8,000	10,600	10,600	13,300	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 15 + 15 + 15 + 24	7,300	12,200	12,200	12,200	19,600	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 15 + 15 + 24	8,000	13,400	13,400	13,400	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 15 + 18 + 18 + 18	7,300	12,200	14,700	14,700	14,700	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 18 + 18 + 18	8,000	13,400	16,100	16,100	16,100	0	0	0	5,410	26.4	23.9
5	78	63,600	12 + 12 + 12 + 12 + 30	9,800	9,800	9,800	9,800	24,500	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 12 + 12 + 30	10,600	10,600	10,600	10,600	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	12 + 12 + 12 + 18 + 24	9,800	9,800	9,800	14,700	19,600	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 12 + 18 + 24	10,700	10,700	10,700	16,100	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	12 + 12 + 15 + 15 + 24	9,800	9,800	12,200	12,200	19,600	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 15 + 15 + 24	10,700	10,700	13,400	13,400	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	12 + 12 + 18 + 18 + 18	9,800	9,800	14,700	14,700	14,700	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 18 + 18 + 18	10,700	10,700	16,100	16,100	16,100	0	0	0	5,410	26.4	23.9
6	54	54,000	9 + 9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	9,000	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 9 + 9 + 9 + 9	10,000	10,000	10,000	10,000	10,000	10,000	0	0	4,962	24.2	21.9
6	57	57,000	9 + 9 + 9 + 9 + 9 + 12	9,000	9,000	9,000	9,000	9,000	12,000	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 9 + 9 + 12	9,900	9,900	9,900	9,900	9,900	13,300	0	0	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	60	60,000	9 + 9 + 9 + 9 + 9 + 15	9,000	9,000	9,000	9,000	9,000	15,000	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 9 + 9 + 15	9,900	9,900	9,900	9,900	9,900	16,500	0	0	5,450	26.6	24.1
6	60	60,000	9 + 9 + 9 + 9 + 12 + 12	9,000	9,000	9,000	9,000	12,000	12,000	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 9 + 12 + 12	9,900	9,900	9,900	9,900	13,200	13,200	0	0	5,450	26.6	24.1
6	63	60,600	9 + 9 + 9 + 9 + 9 + 18	8,700	8,700	8,700	8,700	8,700	17,300	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 9 + 9 + 18	9,500	9,500	9,500	9,500	9,500	19,000	0	0	5,430	26.5	24.0
6	63	60,600	9 + 9 + 9 + 9 + 12 + 15	8,700	8,700	8,700	8,700	11,500	14,400	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 9 + 12 + 15	9,500	9,500	9,500	9,500	12,700	15,900	0	0	5,430	26.5	24.0
6	63	60,600	9 + 9 + 9 + 12 + 12 + 12	8,700	8,700	8,700	11,500	11,500	11,500	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 12 + 12 + 12	9,500	9,500	9,500	12,700	12,700	12,700	0	0	5,430	26.5	24.0
6	66	61,200	9 + 9 + 9 + 9 + 12 + 18	8,300	8,300	8,300	8,300	11,100	16,700	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 12 + 18	9,200	9,200	9,200	9,200	12,200	18,300	0	0	5,410	26.4	23.9
6	66	61,200	9 + 9 + 9 + 9 + 15 + 15	8,300	8,300	8,300	8,300	13,900	13,900	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 15 + 15	9,200	9,200	9,200	9,200	15,300	15,300	0	0	5,410	26.4	23.9
6	66	61,200	9 + 9 + 9 + 12 + 12 + 15	8,300	8,300	8,300	11,100	11,100	13,900	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 12 + 12 + 15	9,200	9,200	9,200	12,200	12,200	15,300	0	0	5,410	26.4	23.9
6	66	61,200	9 + 9 + 12 + 12 + 12 + 12	8,300	8,300	11,100	11,100	11,100	11,100	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 12 + 12 + 12	9,200	9,200	12,200	12,200	12,200	12,200	0	0	5,410	26.4	23.9
6	69	61,800	9 + 9 + 9 + 9 + 9 + 24	8,100	8,100	8,100	8,100	8,100	21,500	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 9 + 24	8,800	8,800	8,800	8,800	8,800	23,600	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	69	61,800	9 + 9 + 9 + 9 + 15 + 18	8,100	8,100	8,100	8,100	13,400	16,100	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 15 + 18	8,800	8,800	8,800	8,800	14,700	17,700	0	0	5,410	26.4	23.9
6	69	61,800	9 + 9 + 9 + 12 + 12 + 18	8,100	8,100	8,100	10,700	10,700	16,100	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 12 + 12 + 18	8,800	8,800	8,800	11,800	11,800	17,700	0	0	5,410	26.4	23.9
6	69	61,800	9 + 9 + 12 + 12 + 12 + 15	8,100	8,100	10,700	10,700	10,700	13,400	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 12 + 12 + 12 + 15	8,800	8,800	11,800	11,800	11,800	14,700	0	0	5,410	26.4	23.9
6	69	61,800	9 + 12 + 12 + 12 + 12 + 12	8,100	10,700	10,700	10,700	10,700	10,700	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 12 + 12 + 12 + 12	8,800	11,800	11,800	11,800	11,800	11,800	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 9 + 9 + 12 + 24	7,800	7,800	7,800	7,800	10,400	20,800	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 12 + 24	8,600	8,600	8,600	8,600	11,400	22,800	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 9 + 9 + 18 + 18	7,800	7,800	7,800	7,800	15,600	15,600	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 18 + 18	8,600	8,600	8,600	8,600	17,100	17,100	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 9 + 15 + 15 + 15	7,800	7,800	7,800	13,000	13,000	13,000	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 15 + 15 + 15	8,600	8,600	8,600	14,300	14,300	14,300	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 12 + 12 + 12 + 18	7,800	7,800	10,400	10,400	10,400	15,600	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 12 + 12 + 18	8,600	8,600	11,400	11,400	11,400	17,100	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 12 + 12 + 15 + 15	7,800	7,800	10,400	10,400	13,000	13,000	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 12 + 15 + 15	8,600	8,600	11,400	11,400	14,300	14,300	0	0	5,410	26.4	23.9
6	72	62,400	9 + 12 + 12 + 12 + 12 + 15	7,800	10,400	10,400	10,400	10,400	13,000	0	0	4,700	22.8	20.7
		68,400	9 + 12 + 12 + 12 + 12 + 15	8,600	11,400	11,400	11,400	11,400	14,300	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	75	63,000	9 + 9 + 9 + 9 + 9 + 30	7,600	7,600	7,600	7,600	7,600	25,200	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 30	8,200	8,200	8,200	8,200	8,200	28,000	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 9 + 9 + 15 + 24	7,600	7,600	7,600	7,600	12,600	20,200	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 15 + 24	8,300	8,300	8,300	8,300	13,800	22,100	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 9 + 12 + 12 + 24	7,600	7,600	7,600	10,100	10,100	20,200	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 12 + 24	8,300	8,300	8,300	11,000	11,000	22,100	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 9 + 15 + 15 + 18	7,600	7,600	7,600	12,600	12,600	15,100	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 15 + 15 + 18	8,300	8,300	8,300	13,800	13,800	16,600	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 12 + 12 + 15 + 18	7,600	7,600	10,100	10,100	12,600	15,100	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 12 + 12 + 15 + 18	8,300	8,300	11,000	11,000	13,800	16,600	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 12 + 15 + 15 + 15	7,600	7,600	10,100	12,600	12,600	12,600	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 12 + 15 + 15 + 15	8,300	8,300	11,000	13,800	13,800	13,800	0	0	5,410	26.4	23.9
6	75	63,000	9 + 12 + 12 + 12 + 12 + 18	7,600	10,100	10,100	10,100	10,100	15,100	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 12 + 12 + 12 + 18	8,300	11,000	11,000	11,000	11,000	16,600	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 9 + 9 + 12 + 30	7,300	7,300	7,300	7,300	9,800	24,500	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 12 + 30	8,000	8,000	8,000	8,000	10,600	27,200	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 9 + 9 + 18 + 24	7,300	7,300	7,300	7,300	14,700	19,600	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 18 + 24	8,000	8,000	8,000	8,000	16,100	21,400	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 12 + 12 + 12 + 24	7,300	7,300	9,800	9,800	9,800	19,600	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 12 + 12 + 24	8,000	8,000	10,700	10,700	10,700	21,400	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	78	63,600	9 + 9 + 12 + 15 + 15 + 18	7,300	7,300	9,800	12,200	12,200	14,700	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 15 + 15 + 18	8,000	8,000	10,700	13,400	13,400	16,100	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 15 + 15 + 15 + 15	7,300	7,300	12,200	12,200	12,200	12,200	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 15 + 15 + 15 + 15	8,000	8,000	13,400	13,400	13,400	13,400	0	0	5,410	26.4	23.9
7	63	60,600	9 + 9 + 9 + 9 + 9 + 9 + 9	8,700	8,700	8,700	8,700	8,700	8,700	8,700	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 9 + 9 + 9 + 9	9,500	9,500	9,500	9,500	9,500	9,500	9,500	0	5,430	26.5	24.0
7	66	61,200	9 + 9 + 9 + 9 + 9 + 9 + 12	8,300	8,300	8,300	8,300	8,300	8,300	11,100	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 9 + 9 + 12	9,200	9,200	9,200	9,200	9,200	9,200	12,200	0	5,410	26.4	23.9
7	69	61,800	9 + 9 + 9 + 9 + 9 + 9 + 15	8,100	8,100	8,100	8,100	8,100	8,100	13,400	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 9 + 9 + 15	8,800	8,800	8,800	8,800	8,800	8,800	14,700	0	5,410	26.4	23.9
7	69	61,800	9 + 9 + 9 + 9 + 9 + 12 + 12	8,100	8,100	8,100	8,100	8,100	10,700	10,700	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 9 + 12 + 12	8,800	8,800	8,800	8,800	8,800	11,800	11,800	0	5,410	26.4	23.9
7	72	62,400	9 + 9 + 9 + 9 + 9 + 9 + 18	7,800	7,800	7,800	7,800	7,800	7,800	15,600	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 9 + 9 + 18	8,600	8,600	8,600	8,600	8,600	8,600	17,100	0	5,410	26.4	23.9
7	72	62,400	9 + 9 + 9 + 9 + 9 + 12 + 15	7,800	7,800	7,800	7,800	7,800	10,400	13,000	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 9 + 12 + 15	8,600	8,600	8,600	8,600	8,600	11,400	14,300	0	5,410	26.4	23.9
7	72	62,400	9 + 9 + 9 + 9 + 12 + 12 + 12	7,800	7,800	7,800	7,800	10,400	10,400	10,400	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 12 + 12 + 12	8,600	8,600	8,600	8,600	11,400	11,400	11,400	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 9 + 9 + 12 + 18	7,600	7,600	7,600	7,600	7,600	10,100	15,100	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 12 + 18	8,300	8,300	8,300	8,300	8,300	11,000	16,600	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	75	63,000	9 + 9 + 9 + 9 + 9 + 15 + 15	7,600	7,600	7,600	7,600	7,600	12,600	12,600	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 15 + 15	8,300	8,300	8,300	8,300	8,300	13,800	13,800	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 9 + 12 + 12 + 15	7,600	7,600	7,600	7,600	10,100	10,100	12,600	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 12 + 12 + 15	8,300	8,300	8,300	8,300	11,000	11,000	13,800	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 12 + 12 + 12 + 12	7,600	7,600	7,600	10,100	10,100	10,100	10,100	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 12 + 12 + 12	8,300	8,300	8,300	11,000	11,000	11,000	11,000	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 12 + 12 + 12 + 12	7,600	7,600	7,600	10,100	10,100	10,100	10,100	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 12 + 12 + 12	8,300	8,300	8,300	11,000	11,000	11,000	11,000	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 9 + 9 + 9 + 24	7,300	7,300	7,300	7,300	7,300	7,300	19,600	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 9 + 9 + 24	8,000	8,000	8,000	8,000	8,000	8,000	21,400	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 9 + 9 + 15 + 18	7,300	7,300	7,300	7,300	7,300	12,200	14,700	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 9 + 15 + 18	8,000	8,000	8,000	8,000	8,000	13,400	16,100	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 9 + 12 + 12 + 18	7,300	7,300	7,300	7,300	9,800	9,800	14,700	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 12 + 12 + 18	8,000	8,000	8,000	8,000	10,700	10,700	16,100	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 9 + 12 + 15 + 15	7,300	7,300	7,300	7,300	9,800	12,200	12,200	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 12 + 15 + 15	8,000	8,000	8,000	8,000	10,700	13,400	13,400	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 12 + 12 + 12 + 15	7,300	7,300	7,300	9,800	9,800	9,800	12,200	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 12 + 12 + 12 + 15	8,000	8,000	8,000	10,700	10,700	10,700	13,400	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 12 + 12 + 12 + 12 + 12	7,300	7,300	9,800	9,800	9,800	9,800	9,800	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 12 + 12 + 12 + 12	8,000	8,000	10,700	10,700	10,700	10,700	10,700	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	72	62,400	9 + 9 + 9 + 9 + 9 + 9 + 9 + 9	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 9 + 9 + 9 + 9	8,600	8,600	8,600	8,600	8,600	8,600	8,600	8,600	5,410	26.4	23.9
8	75	63,000	9 + 9 + 9 + 9 + 9 + 9 + 9 + 12	7,600	7,600	7,600	7,600	7,600	7,600	7,600	10,100	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 9 + 9 + 12	8,300	8,300	8,300	8,300	8,300	8,300	8,300	11,000	5,410	26.4	23.9
8	78	63,600	9 + 9 + 9 + 9 + 9 + 9 + 9 + 15	7,300	7,300	7,300	7,300	7,300	7,300	7,300	12,200	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 9 + 9 + 9 + 15	8,000	8,000	8,000	8,000	8,000	8,000	8,000	13,400	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	790	3.8	3.5
		7,000	6	7,000	0	0	0	0	0	0	0	1,060	5.2	4.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	1,110	5.4	4.9
		10,300	9	10,300	0	0	0	0	0	0	0	1,304	6.4	5.8
1	12	12,000	12	12,000	0	0	0	0	0	0	0	1,410	6.9	6.2
		13,600	12	13,600	0	0	0	0	0	0	0	1,548	7.6	6.8
1	15	15,000	15	15,000	0	0	0	0	0	0	0	1,700	8.3	7.5
		16,900	15	16,900	0	0	0	0	0	0	0	1,792	8.7	7.9
1	18	18,000	6	18,000	0	0	0	0	0	0	0	1,980	9.6	8.7
		20,200	6	20,200	0	0	0	0	0	0	0	2,036	9.9	9.0
1	24	24,000	6	24,000	0	0	0	0	0	0	0	2,530	12.3	11.1
		26,800	6	26,800	0	0	0	0	0	0	0	2,523	12.3	11.1
1	30	30,000	6	30,000	0	0	0	0	0	0	0	3,060	14.9	13.5
		33,400	6	33,400	0	0	0	0	0	0	0	3,011	14.7	13.3
1	36	36,000	9	36,000	0	0	0	0	0	0	0	3,560	17.3	15.7
		40,000	9	40,000	0	0	0	0	0	0	0	3,499	17.1	15.4
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	1,410	6.9	6.2
		13,600	6 + 6	6,800	6,800	0	0	0	0	0	0	1,548	7.6	6.8
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	1,700	8.3	7.5
		16,900	6 + 9	6,800	10,100	0	0	0	0	0	0	1,792	8.7	7.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,980	9.6	8.7
		20,200	6 + 12	6,700	13,500	0	0	0	0	0	0	2,036	9.9	9.0
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,980	9.6	8.7
		20,200	9 + 9	10,100	10,100	0	0	0	0	0	0	2,036	9.9	9.0
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	2,260	11.0	9.9
		23,500	6 + 15	6,700	16,800	0	0	0	0	0	0	2,279	11.1	10.1
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	2,260	11.0	9.9
		23,500	9 + 12	10,100	13,400	0	0	0	0	0	0	2,279	11.1	10.1
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	2,530	12.3	11.1
		26,800	6 + 18	6,700	20,100	0	0	0	0	0	0	2,523	12.3	11.1
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	2,530	12.3	11.1
		26,800	9 + 15	10,100	16,800	0	0	0	0	0	0	2,523	12.3	11.1
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	2,530	12.3	11.1
		26,800	12 + 12	13,400	13,400	0	0	0	0	0	0	2,523	12.3	11.1
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,800	13.6	12.3
		30,100	9 + 18	10,000	20,100	0	0	0	0	0	0	2,767	13.5	12.2
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,800	13.6	12.3
		30,100	12 + 15	13,400	16,700	0	0	0	0	0	0	2,767	13.5	12.2
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	3,060	14.9	13.5
		33,400	6 + 24	6,700	26,700	0	0	0	0	0	0	3,011	14.7	13.3

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	3,060	14.9	13.5
		33,400	12 + 18	13,400	20,000	0	0	0	0	0	0	3,011	14.7	13.3
2	30	30,000	15 + 15	15,000	15,000	0	0	0	0	0	0	3,060	14.9	13.5
		33,400	15 + 15	16,700	16,700	0	0	0	0	0	0	3,011	14.7	13.3
2	33	33,000	9 + 24	9,000	24,000	0	0	0	0	0	0	3,320	16.1	14.6
		36,700	9 + 24	10,000	26,700	0	0	0	0	0	0	3,255	15.9	14.4
2	33	33,000	15 + 18	15,000	18,000	0	0	0	0	0	0	3,320	16.1	14.6
		36,700	15 + 18	16,700	20,000	0	0	0	0	0	0	3,255	15.9	14.4
2	36	36,000	6 + 30	6,000	30,000	0	0	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 30	6,500	33,500	0	0	0	0	0	0	3,499	17.1	15.4
2	36	36,000	12 + 24	12,000	24,000	0	0	0	0	0	0	3,560	17.3	15.7
		40,000	12 + 24	13,300	26,700	0	0	0	0	0	0	3,499	17.1	15.4
2	36	36,000	18 + 18	18,000	18,000	0	0	0	0	0	0	3,560	17.3	15.7
		40,000	18 + 18	20,000	20,000	0	0	0	0	0	0	3,499	17.1	15.4
2	39	39,000	9 + 30	9,000	30,000	0	0	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 30	9,800	33,400	0	0	0	0	0	0	3,743	18.3	16.5
2	39	39,000	15 + 24	15,000	24,000	0	0	0	0	0	0	3,790	18.4	16.7
		43,200	15 + 24	16,600	26,600	0	0	0	0	0	0	3,743	18.3	16.5
2	42	42,000	6 + 36	6,000	36,000	0	0	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 36	6,400	40,100	0	0	0	0	0	0	3,987	19.5	17.6

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	42	42,000	12 + 30	12,000	30,000	0	0	0	0	0	0	4,000	19.4	17.6
		46,500	12 + 30	13,100	33,400	0	0	0	0	0	0	3,987	19.5	17.6
2	42	42,000	18 + 24	18,000	24,000	0	0	0	0	0	0	4,000	19.4	17.6
		46,500	18 + 24	19,900	26,600	0	0	0	0	0	0	3,987	19.5	17.6
2	45	45,000	9 + 36	9,000	36,000	0	0	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 36	9,600	40,200	0	0	0	0	0	0	4,231	20.6	18.7
2	45	45,000	15 + 30	15,000	30,000	0	0	0	0	0	0	4,180	20.3	18.4
		49,800	15 + 30	16,300	33,500	0	0	0	0	0	0	4,231	20.6	18.7
2	48	48,000	12 + 36	12,000	36,000	0	0	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 36	12,900	40,200	0	0	0	0	0	0	4,474	21.8	19.8
2	48	48,000	18 + 30	18,000	30,000	0	0	0	0	0	0	4,340	21.1	19.1
		53,100	18 + 30	19,600	33,500	0	0	0	0	0	0	4,474	21.8	19.8
2	48	48,000	24 + 24	24,000	24,000	0	0	0	0	0	0	4,340	21.1	19.1
		53,100	24 + 24	26,600	26,600	0	0	0	0	0	0	4,474	21.8	19.8
2	51	51,000	15 + 36	15,000	36,000	0	0	0	0	0	0	4,480	21.8	19.7
		56,400	15 + 36	16,100	40,300	0	0	0	0	0	0	4,718	23.0	20.8
2	54	54,000	18 + 36	18,000	36,000	0	0	0	0	0	0	4,580	22.3	20.1
		59,700	18 + 36	19,400	40,300	0	0	0	0	0	0	4,962	24.2	21.9
2	54	54,000	24 + 30	24,000	30,000	0	0	0	0	0	0	4,580	22.3	20.1
		59,700	24 + 30	26,200	33,500	0	0	0	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	60	60,000	24 + 36	24,000	36,000	0	0	0	0	0	0	4,680	22.8	20.6
		66,000	24 + 36	25,800	40,200	0	0	0	0	0	0	5,450	26.6	24.1
2	60	60,000	30 + 30	30,000	30,000	0	0	0	0	0	0	4,680	22.8	20.6
		66,000	30 + 30	33,000	33,000	0	0	0	0	0	0	5,450	26.6	24.1
2	66	61,200	30 + 36	27,800	33,400	0	0	0	0	0	0	4,700	22.8	20.7
		67,200	30 + 36	30,300	36,900	0	0	0	0	0	0	5,410	26.4	23.9
2	72	62,400	36 + 36	31,200	31,200	0	0	0	0	0	0	4,700	22.8	20.7
		68,400	36 + 36	34,200	34,200	0	0	0	0	0	0	5,410	26.4	23.9
3	18	18,000	6 + 6 + 6	6,000	6,000	6,000	0	0	0	0	0	1,980	9.6	8.7
		20,200	6 + 6 + 6	6,700	6,700	6,700	0	0	0	0	0	2,036	9.9	9.0
3	21	21,000	6 + 6 + 9	6,000	6,000	9,000	0	0	0	0	0	2,260	11.0	9.9
		23,500	6 + 6 + 9	6,700	6,700	10,100	0	0	0	0	0	2,279	11.1	10.1
3	24	24,000	6 + 6 + 12	6,000	6,000	12,000	0	0	0	0	0	2,530	12.3	11.1
		26,800	6 + 6 + 12	6,700	6,700	13,400	0	0	0	0	0	2,523	12.3	11.1
3	24	24,000	6 + 9 + 9	6,000	9,000	9,000	0	0	0	0	0	2,530	12.3	11.1
		26,800	6 + 9 + 9	6,700	10,100	10,100	0	0	0	0	0	2,523	12.3	11.1
3	27	27,000	6 + 6 + 15	6,000	6,000	15,000	0	0	0	0	0	2,800	13.6	12.3
		30,100	6 + 6 + 15	6,700	6,700	16,700	0	0	0	0	0	2,767	13.5	12.2
3	27	27,000	6 + 9 + 12	6,000	9,000	12,000	0	0	0	0	0	2,800	13.6	12.3
		30,100	6 + 9 + 12	6,700	10,000	13,400	0	0	0	0	0	2,767	13.5	12.2

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	27	27,000	9 + 9 + 9	9,000	9,000	9,000	0	0	0	0	0	2,800	13.6	12.3
		30,100	9 + 9 + 9	10,000	10,000	10,000	0	0	0	0	0	2,767	13.5	12.2
3	30	30,000	6 + 6 + 18	6,000	6,000	18,000	0	0	0	0	0	3,060	14.9	13.5
		33,400	6 + 6 + 18	6,700	6,700	20,000	0	0	0	0	0	3,011	14.7	13.3
3	30	30,000	6 + 9 + 15	6,000	9,000	15,000	0	0	0	0	0	3,060	14.9	13.5
		33,400	6 + 9 + 15	6,700	10,000	16,700	0	0	0	0	0	3,011	14.7	13.3
3	30	30,000	6 + 12 + 12	6,000	12,000	12,000	0	0	0	0	0	3,060	14.9	13.5
		33,400	6 + 12 + 12	6,700	13,400	13,400	0	0	0	0	0	3,011	14.7	13.3
3	30	30,000	9 + 9 + 12	9,000	9,000	12,000	0	0	0	0	0	3,060	14.9	13.5
		33,400	9 + 9 + 12	10,000	10,000	13,400	0	0	0	0	0	3,011	14.7	13.3
3	33	33,000	6 + 9 + 18	6,000	9,000	18,000	0	0	0	0	0	3,320	16.1	14.6
		36,700	6 + 9 + 18	6,700	10,000	20,000	0	0	0	0	0	3,255	15.9	14.4
3	33	33,000	6 + 12 + 15	6,000	12,000	15,000	0	0	0	0	0	3,320	16.1	14.6
		36,700	6 + 12 + 15	6,700	13,300	16,700	0	0	0	0	0	3,255	15.9	14.4
3	33	33,000	9 + 9 + 15	9,000	9,000	15,000	0	0	0	0	0	3,320	16.1	14.6
		36,700	9 + 9 + 15	10,000	10,000	16,700	0	0	0	0	0	3,255	15.9	14.4
3	33	33,000	9 + 12 + 12	9,000	12,000	12,000	0	0	0	0	0	3,320	16.1	14.6
		36,700	9 + 12 + 12	10,000	13,300	13,300	0	0	0	0	0	3,255	15.9	14.4
3	36	36,000	6 + 6 + 24	6,000	6,000	24,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 24	6,700	6,700	26,700	0	0	0	0	0	3,499	17.1	15.4

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 9 + 18	10,000	10,000	20,000	0	0	0	0	0	3,499	17.1	15.4
3	36	36,000	6 + 12 + 18	6,000	12,000	18,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 12 + 18	6,700	13,300	20,000	0	0	0	0	0	3,499	17.1	15.4
3	36	36,000	6 + 15 + 15	6,000	15,000	15,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 15 + 15	6,700	16,700	16,700	0	0	0	0	0	3,499	17.1	15.4
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 9 + 18	10,000	10,000	20,000	0	0	0	0	0	3,499	17.1	15.4
3	36	36,000	9 + 12 + 15	9,000	12,000	15,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 12 + 15	10,000	13,300	16,700	0	0	0	0	0	3,499	17.1	15.4
3	36	36,000	12 + 12 + 12	12,000	12,000	12,000	0	0	0	0	0	3,560	17.3	15.7
		40,000	12 + 12 + 12	13,300	13,300	13,300	0	0	0	0	0	3,499	17.1	15.4
3	39	39,000	6 + 9 + 24	6,000	9,000	24,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	6 + 9 + 24	6,600	10,000	26,600	0	0	0	0	0	3,743	18.3	16.5
3	39	39,000	6 + 15 + 18	6,000	15,000	18,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	6 + 15 + 18	6,600	16,600	19,900	0	0	0	0	0	3,743	18.3	16.5
3	39	39,000	9 + 12 + 18	9,000	12,000	18,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 12 + 18	10,000	13,300	19,900	0	0	0	0	0	3,743	18.3	16.5
3	39	39,000	9 + 15 + 15	9,000	15,000	15,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 15 + 15	10,000	16,600	16,600	0	0	0	0	0	3,743	18.3	16.5

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	39	39,000	12 + 12 + 15	12,000	12,000	15,000	0	0	0	0	0	3,790	18.4	16.7
		43,200	12 + 12 + 15	13,300	13,300	16,600	0	0	0	0	0	3,743	18.3	16.5
3	42	42,000	6 + 6 + 30	6,000	6,000	30,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 30	6,500	6,500	33,400	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	6 + 12 + 24	6,000	12,000	24,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 12 + 24	6,600	13,300	26,600	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	6 + 18 + 18	6,000	18,000	18,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 18 + 18	6,600	19,900	19,900	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	9 + 9 + 24	9,000	9,000	24,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 9 + 24	10,000	10,000	26,600	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	9 + 15 + 18	9,000	15,000	18,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 15 + 18	10,000	16,600	19,900	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	12 + 12 + 18	12,000	12,000	18,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	12 + 12 + 18	13,300	13,300	19,900	0	0	0	0	0	3,987	19.5	17.6
3	42	42,000	12 + 15 + 15	12,000	15,000	15,000	0	0	0	0	0	4,000	19.4	17.6
		46,500	12 + 15 + 15	13,300	16,600	16,600	0	0	0	0	0	3,987	19.5	17.6
3	45	45,000	6 + 9 + 30	6,000	9,000	30,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	6 + 9 + 30	6,500	9,800	33,500	0	0	0	0	0	4,231	20.6	18.7
3	45	45,000	6 + 15 + 24	6,000	15,000	24,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	6 + 15 + 24	6,600	16,600	26,600	0	0	0	0	0	4,231	20.6	18.7

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	45	45,000	9 + 12 + 24	9,000	12,000	24,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 12 + 24	10,000	13,300	26,600	0	0	0	0	0	4,231	20.6	18.7
3	45	45,000	9 + 18 + 18	9,000	18,000	18,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 18 + 18	10,000	19,900	19,900	0	0	0	0	0	4,231	20.6	18.7
3	45	45,000	12 + 15 + 18	12,000	15,000	18,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	12 + 15 + 18	13,300	16,600	19,900	0	0	0	0	0	4,231	20.6	18.7
3	45	45,000	15 + 15 + 15	15,000	15,000	15,000	0	0	0	0	0	4,180	20.3	18.4
		49,800	15 + 15 + 15	16,600	16,600	16,600	0	0	0	0	0	4,231	20.6	18.7
3	48	48,000	6 + 6 + 36	6,000	6,000	36,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 36	6,400	6,400	40,200	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	6 + 12 + 30	6,000	12,000	30,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 12 + 30	6,500	13,100	33,500	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	6 + 18 + 24	6,000	18,000	24,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 18 + 24	6,600	19,900	26,600	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	9 + 9 + 30	9,000	9,000	30,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 30	9,800	9,800	33,500	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	9 + 15 + 24	9,000	15,000	24,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 15 + 24	10,000	16,600	26,600	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	12 + 12 + 24	12,000	12,000	24,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 12 + 24	13,300	13,300	26,600	0	0	0	0	0	4,474	21.8	19.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	48	48,000	12 + 18 + 18	12,000	18,000	18,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 18 + 18	13,300	19,900	19,900	0	0	0	0	0	4,474	21.8	19.8
3	48	48,000	15 + 15 + 18	15,000	15,000	18,000	0	0	0	0	0	4,340	21.1	19.1
		53,100	15 + 15 + 18	16,600	16,600	19,900	0	0	0	0	0	4,474	21.8	19.8
3	51	51,000	6 + 9 + 36	6,000	9,000	36,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 9 + 36	6,400	9,700	40,300	0	0	0	0	0	4,718	23.0	20.8
3	51	51,000	6 + 15 + 30	6,000	15,000	30,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 15 + 30	6,500	16,300	33,500	0	0	0	0	0	4,718	23.0	20.8
3	51	51,000	9 + 12 + 30	9,000	12,000	30,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 12 + 30	9,800	13,100	33,500	0	0	0	0	0	4,718	23.0	20.8
3	51	51,000	9 + 18 + 24	9,000	18,000	24,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 18 + 24	10,000	19,900	26,500	0	0	0	0	0	4,718	23.0	20.8
3	51	51,000	12 + 15 + 24	12,000	15,000	24,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	12 + 15 + 24	13,300	16,600	26,500	0	0	0	0	0	4,718	23.0	20.8
3	51	51,000	15 + 18 + 18	15,000	18,000	18,000	0	0	0	0	0	4,480	21.8	19.7
		56,400	15 + 18 + 18	16,600	19,900	19,900	0	0	0	0	0	4,718	23.0	20.8
3	54	54,000	6 + 12 + 36	6,000	12,000	36,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 12 + 36	6,500	12,900	40,300	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	6 + 18 + 30	6,000	18,000	30,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 18 + 30	6,500	19,600	33,500	0	0	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	54	54,000	6 + 24 + 24	6,000	24,000	24,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 24 + 24	6,600	26,500	26,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	9 + 9 + 36	9,000	9,000	36,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 36	9,700	9,700	40,300	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	9 + 15 + 30	9,000	15,000	30,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 15 + 30	9,800	16,400	33,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	12 + 12 + 30	12,000	12,000	30,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 12 + 30	13,100	13,100	33,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	12 + 18 + 24	12,000	18,000	24,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 18 + 24	13,300	19,900	26,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	15 + 15 + 24	15,000	15,000	24,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	15 + 15 + 24	16,600	16,600	26,500	0	0	0	0	0	4,962	24.2	21.9
3	54	54,000	18 + 18 + 18	18,000	18,000	18,000	0	0	0	0	0	4,580	22.3	20.1
		59,700	18 + 18 + 18	19,900	19,900	19,900	0	0	0	0	0	4,962	24.2	21.9
3	57	57,000	6 + 15 + 36	6,000	15,000	36,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	6 + 15 + 36	6,500	16,200	40,400	0	0	0	0	0	5,206	25.4	23.0
3	57	57,000	9 + 12 + 36	9,000	12,000	36,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 36	9,700	12,900	40,400	0	0	0	0	0	5,206	25.4	23.0
3	57	57,000	9 + 18 + 30	9,000	18,000	30,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 18 + 30	9,800	19,600	33,500	0	0	0	0	0	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	57	57,000	9 + 24 + 24	9,000	24,000	24,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 24 + 24	9,900	26,500	26,500	0	0	0	0	0	5,206	25.4	23.0
3	57	57,000	12 + 15 + 30	12,000	15,000	30,000	0	0	0	0	0	4,630	22.5	20.4
		63,000	12 + 15 + 30	13,100	16,400	33,500	0	0	0	0	0	5,206	25.4	23.0
3	60	60,000	6 + 18 + 36	6,000	18,000	36,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 18 + 36	6,400	19,300	40,200	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	6 + 24 + 30	6,000	24,000	30,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 24 + 30	6,500	26,100	33,400	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	9 + 15 + 36	9,000	15,000	36,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 15 + 36	9,700	16,100	40,200	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	12 + 12 + 36	12,000	12,000	36,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 36	12,900	12,900	40,200	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	12 + 18 + 30	12,000	18,000	30,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 18 + 30	13,000	19,600	33,400	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	12 + 24 + 24	12,000	24,000	24,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 24 + 24	13,200	26,400	26,400	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	15 + 15 + 30	15,000	15,000	30,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	15 + 15 + 30	16,300	16,300	33,400	0	0	0	0	0	5,450	26.6	24.1
3	60	60,000	18 + 18 + 24	18,000	18,000	24,000	0	0	0	0	0	4,680	22.8	20.6
		66,000	18 + 18 + 24	19,800	19,800	26,400	0	0	0	0	0	5,450	26.6	24.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	63	60,600	9 + 18 + 36	8,700	17,300	34,600	0	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 18 + 36	9,300	18,600	38,700	0	0	0	0	0	5,430	26.5	24.0
3	63	60,600	9 + 24 + 30	8,700	23,100	28,900	0	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 24 + 30	9,400	25,100	32,100	0	0	0	0	0	5,430	26.5	24.0
3	63	60,600	12 + 15 + 36	11,500	14,400	34,600	0	0	0	0	0	4,690	22.8	20.6
		66,600	12 + 15 + 36	12,400	15,500	38,700	0	0	0	0	0	5,430	26.5	24.0
3	66	61,200	6 + 24 + 36	5,600	22,300	33,400	0	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 24 + 36	6,000	23,900	37,300	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	6 + 30 + 30	5,600	27,800	27,800	0	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 30 + 30	6,000	30,600	30,600	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	12 + 18 + 36	11,100	16,700	33,400	0	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 18 + 36	11,900	17,900	37,300	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	12 + 24 + 30	11,100	22,300	27,800	0	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 24 + 30	12,100	24,200	31,000	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	15 + 15 + 36	13,900	13,900	33,400	0	0	0	0	0	4,700	22.8	20.7
		67,200	15 + 15 + 36	14,900	14,900	37,300	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	18 + 18 + 30	16,700	16,700	27,800	0	0	0	0	0	4,700	22.8	20.7
		67,200	18 + 18 + 30	18,100	18,100	31,000	0	0	0	0	0	5,410	26.4	23.9
3	66	61,200	18 + 24 + 24	16,700	22,300	22,300	0	0	0	0	0	4,700	22.8	20.7
		67,200	18 + 24 + 24	18,300	24,400	24,400	0	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	69	61,800	9 + 24 + 36	8,100	21,500	32,200	0	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 24 + 36	8,700	23,100	36,100	0	0	0	0	0	5,410	26.4	23.9
3	69	61,800	9 + 30 + 30	8,100	26,900	26,900	0	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 30 + 30	8,700	29,600	29,600	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	6 + 30 + 36	5,200	26,000	31,200	0	0	0	0	0	4,700	22.8	20.7
		68,400	6 + 30 + 36	5,500	28,300	34,500	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	12 + 24 + 36	10,400	20,800	31,200	0	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 24 + 36	11,200	22,300	34,900	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	12 + 30 + 30	10,400	26,000	26,000	0	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 30 + 30	11,200	28,600	28,600	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	18 + 18 + 36	15,600	15,600	31,200	0	0	0	0	0	4,700	22.8	20.7
		68,400	18 + 18 + 36	16,800	16,800	34,900	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	18 + 24 + 30	15,600	20,800	26,000	0	0	0	0	0	4,700	22.8	20.7
		68,400	18 + 24 + 30	16,900	22,600	28,900	0	0	0	0	0	5,410	26.4	23.9
3	72	62,400	24 + 24 + 24	20,800	20,800	20,800	0	0	0	0	0	4,700	22.8	20.7
		68,400	24 + 24 + 24	22,800	22,800	22,800	0	0	0	0	0	5,410	26.4	23.9
3	75	63,000	9 + 30 + 36	7,600	25,200	30,200	0	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 30 + 36	8,000	27,500	33,500	0	0	0	0	0	5,410	26.4	23.9
3	78	63,600	6 + 36 + 36	4,900	29,400	29,400	0	0	0	0	0	4,690	22.8	20.6
		69,600	6 + 36 + 36	5,200	32,200	32,200	0	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	78	63,600	12 + 30 + 36	9,800	24,500	29,400	0	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 30 + 36	10,400	26,700	32,500	0	0	0	0	0	5,410	26.4	23.9
3	78	63,600	18 + 24 + 36	14,700	19,600	29,400	0	0	0	0	0	4,690	22.8	20.6
		69,600	18 + 24 + 36	15,800	21,000	32,800	0	0	0	0	0	5,410	26.4	23.9
3	78	63,600	24 + 24 + 30	19,600	19,600	24,500	0	0	0	0	0	4,690	22.8	20.6
		69,600	24 + 24 + 30	21,200	21,200	27,200	0	0	0	0	0	5,410	26.4	23.9
4	24	24,000	6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	0	0	0	0	2,530	12.3	11.1
		26,800	6 + 6 + 6 + 6	6,700	6,700	6,700	6,700	0	0	0	0	2,523	12.3	11.1
4	27	27,000	6 + 6 + 6 + 9	6,000	6,000	6,000	9,000	0	0	0	0	2,800	13.6	12.3
		30,100	6 + 6 + 6 + 9	6,700	6,700	6,700	10,000	0	0	0	0	2,767	13.5	12.2
4	30	30,000	6 + 6 + 6 + 12	6,000	6,000	6,000	12,000	0	0	0	0	3,060	14.9	13.5
		33,400	6 + 6 + 6 + 12	6,700	6,700	6,700	13,400	0	0	0	0	3,011	14.7	13.3
4	30	30,000	6 + 6 + 9 + 9	6,000	6,000	9,000	9,000	0	0	0	0	3,060	14.9	13.5
		33,400	6 + 6 + 9 + 9	6,700	6,700	10,000	10,000	0	0	0	0	3,011	14.7	13.3
4	33	33,000	6 + 6 + 6 + 15	6,000	6,000	6,000	15,000	0	0	0	0	3,320	16.1	14.6
		36,700	6 + 6 + 6 + 15	6,700	6,700	6,700	16,700	0	0	0	0	3,255	15.9	14.4
4	33	33,000	6 + 6 + 9 + 12	6,000	6,000	9,000	12,000	0	0	0	0	3,320	16.1	14.6
		36,700	6 + 6 + 9 + 12	6,700	6,700	10,000	13,300	0	0	0	0	3,255	15.9	14.4
4	33	33,000	6 + 9 + 9 + 9	6,000	9,000	9,000	9,000	0	0	0	0	3,320	16.1	14.6
		36,700	6 + 9 + 9 + 9	6,700	10,000	10,000	10,000	0	0	0	0	3,255	15.9	14.4

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	36	36,000	6 + 6 + 6 + 18	6,000	6,000	6,000	18,000	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 6 + 18	6,700	6,700	6,700	20,000	0	0	0	0	3,499	17.1	15.4
4	36	36,000	6 + 6 + 9 + 15	6,000	6,000	9,000	15,000	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 9 + 15	6,700	6,700	10,000	16,700	0	0	0	0	3,499	17.1	15.4
4	36	36,000	6 + 6 + 12 + 12	6,000	6,000	12,000	12,000	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 12 + 12	6,700	6,700	13,300	13,300	0	0	0	0	3,499	17.1	15.4
4	36	36,000	6 + 9 + 9 + 12	6,000	9,000	9,000	12,000	0	0	0	0	3,560	17.3	15.7
		40,000	6 + 9 + 9 + 12	6,700	10,000	10,000	13,300	0	0	0	0	3,499	17.1	15.4
4	36	36,000	9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	0	0	0	0	3,560	17.3	15.7
		40,000	9 + 9 + 9 + 9	10,000	10,000	10,000	10,000	0	0	0	0	3,499	17.1	15.4
4	39	39,000	6 + 6 + 9 + 18	6,000	6,000	9,000	18,000	0	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 9 + 18	6,600	6,600	10,000	19,900	0	0	0	0	3,743	18.3	16.5
4	39	39,000	6 + 6 + 12 + 15	6,000	6,000	12,000	15,000	0	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 12 + 15	6,600	6,600	13,300	16,600	0	0	0	0	3,743	18.3	16.5
4	39	39,000	6 + 9 + 9 + 15	6,000	9,000	9,000	15,000	0	0	0	0	3,790	18.4	16.7
		43,200	6 + 9 + 9 + 15	6,600	10,000	10,000	16,600	0	0	0	0	3,743	18.3	16.5
4	39	39,000	6 + 9 + 12 + 12	6,000	9,000	12,000	12,000	0	0	0	0	3,790	18.4	16.7
		43,200	6 + 9 + 12 + 12	6,600	10,000	13,300	13,300	0	0	0	0	3,743	18.3	16.5
4	39	39,000	9 + 9 + 9 + 12	9,000	9,000	9,000	12,000	0	0	0	0	3,790	18.4	16.7
		43,200	9 + 9 + 9 + 12	10,000	10,000	10,000	13,300	0	0	0	0	3,743	18.3	16.5

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	42	42,000	6 + 6 + 6 + 24	6,000	6,000	6,000	24,000	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 24	6,600	6,600	6,600	26,600	0	0	0	0	3,987	19.5	17.6
4	42	42,000	6 + 6 + 12 + 18	6,000	6,000	12,000	18,000	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 12 + 18	6,600	6,600	13,300	19,900	0	0	0	0	3,987	19.5	17.6
4	42	42,000	6 + 6 + 15 + 15	6,000	6,000	15,000	15,000	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 15 + 15	6,600	6,600	16,600	16,600	0	0	0	0	3,987	19.5	17.6
4	42	42,000	6 + 9 + 9 + 18	6,000	9,000	9,000	18,000	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 9 + 9 + 18	6,600	10,000	10,000	19,900	0	0	0	0	3,987	19.5	17.6
4	42	42,000	6 + 9 + 12 + 15	6,000	9,000	12,000	15,000	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 9 + 12 + 15	6,600	10,000	13,300	16,600	0	0	0	0	3,987	19.5	17.6
4	42	42,000	6 + 12 + 12 + 12	6,000	12,000	12,000	12,000	0	0	0	0	4,000	19.4	17.6
		46,500	6 + 12 + 12 + 12	6,600	13,300	13,300	13,300	0	0	0	0	3,987	19.5	17.6
4	42	42,000	9 + 9 + 9 + 15	9,000	9,000	9,000	15,000	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 9 + 9 + 15	10,000	10,000	10,000	16,600	0	0	0	0	3,987	19.5	17.6
4	42	42,000	9 + 9 + 12 + 12	9,000	9,000	12,000	12,000	0	0	0	0	4,000	19.4	17.6
		46,500	9 + 9 + 12 + 12	10,000	10,000	13,300	13,300	0	0	0	0	3,987	19.5	17.6
4	45	45,000	6 + 6 + 9 + 24	6,000	6,000	9,000	24,000	0	0	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 9 + 24	6,600	6,600	10,000	26,600	0	0	0	0	4,231	20.6	18.7
4	45	45,000	6 + 6 + 15 + 18	6,000	6,000	15,000	18,000	0	0	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 15 + 18	6,600	6,600	16,600	19,900	0	0	0	0	4,231	20.6	18.7

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	45	45,000	6 + 9 + 12 + 18	6,000	9,000	12,000	18,000	0	0	0	0	4,180	20.3	18.4
		49,800	6 + 9 + 12 + 18	6,600	10,000	13,300	19,900	0	0	0	0	4,231	20.6	18.7
4	45	45,000	6 + 9 + 15 + 15	6,000	9,000	15,000	15,000	0	0	0	0	4,180	20.3	18.4
		49,800	6 + 9 + 15 + 15	6,600	10,000	16,600	16,600	0	0	0	0	4,231	20.6	18.7
4	45	45,000	6 + 12 + 12 + 15	6,000	12,000	12,000	15,000	0	0	0	0	4,180	20.3	18.4
		49,800	6 + 12 + 12 + 15	6,600	13,300	13,300	16,600	0	0	0	0	4,231	20.6	18.7
4	45	45,000	9 + 9 + 9 + 18	9,000	9,000	9,000	18,000	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 9 + 9 + 18	10,000	10,000	10,000	19,900	0	0	0	0	4,231	20.6	18.7
4	45	45,000	9 + 9 + 12 + 15	9,000	9,000	12,000	15,000	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 9 + 12 + 15	10,000	10,000	13,300	16,600	0	0	0	0	4,231	20.6	18.7
4	45	48,000	9 + 12 + 12 + 12	9,600	12,800	12,800	12,800	0	0	0	0	4,180	20.3	18.4
		49,800	9 + 12 + 12 + 12	10,000	13,300	13,300	13,300	0	0	0	0	4,231	20.6	18.7
4	48	48,000	6 + 6 + 6 + 30	6,000	6,000	6,000	30,000	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 30	6,500	6,500	6,500	33,500	0	0	0	0	4,474	21.8	19.8
4	48	48,000	6 + 6 + 12 + 24	6,000	6,000	12,000	24,000	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 12 + 24	6,600	6,600	13,300	26,600	0	0	0	0	4,474	21.8	19.8
4	48	48,000	6 + 6 + 18 + 18	6,000	6,000	18,000	18,000	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 18 + 18	6,600	6,600	19,900	19,900	0	0	0	0	4,474	21.8	19.8
4	48	48,000	6 + 9 + 9 + 24	6,000	9,000	9,000	24,000	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 9 + 9 + 24	6,600	10,000	10,000	26,600	0	0	0	0	4,474	21.8	19.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	48	48,000	6 + 9 + 15 + 18	6,000	9,000	15,000	18,000	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 9 + 15 + 18	6,600	10,000	16,600	19,900	0	0	0	0	4,474	21.8	19.8
4	48	48,000	6 + 12 + 12 + 18	6,000	12,000	12,000	18,000	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 12 + 12 + 18	6,600	13,300	13,300	19,900	0	0	0	0	4,474	21.8	19.8
4	48	48,000	6 + 12 + 15 + 15	6,000	12,000	15,000	15,000	0	0	0	0	4,340	21.1	19.1
		53,100	6 + 12 + 15 + 15	6,600	13,300	16,600	16,600	0	0	0	0	4,474	21.8	19.8
4	48	48,000	9 + 9 + 12 + 18	9,000	9,000	12,000	18,000	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 12 + 18	10,000	10,000	13,300	19,900	0	0	0	0	4,474	21.8	19.8
4	48	45,000	9 + 9 + 15 + 15	8,400	8,400	14,100	14,100	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 15 + 15	10,000	10,000	16,600	16,600	0	0	0	0	4,474	21.8	19.8
4	48	48,000	9 + 12 + 12 + 15	9,000	12,000	12,000	15,000	0	0	0	0	4,340	21.1	19.1
		53,100	9 + 12 + 12 + 15	10,000	13,300	13,300	16,600	0	0	0	0	4,474	21.8	19.8
4	48	48,000	12 + 12 + 12 + 12	12,000	12,000	12,000	12,000	0	0	0	0	4,340	21.1	19.1
		53,100	12 + 12 + 12 + 12	13,300	13,300	13,300	13,300	0	0	0	0	4,474	21.8	19.8
4	51	51,000	6 + 6 + 9 + 30	6,000	6,000	9,000	30,000	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 9 + 30	6,500	6,500	9,800	33,500	0	0	0	0	4,718	23.0	20.8
4	51	51,000	6 + 6 + 15 + 24	6,000	6,000	15,000	24,000	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 15 + 24	6,600	6,600	16,600	26,500	0	0	0	0	4,718	23.0	20.8
4	51	51,000	6 + 9 + 12 + 24	6,000	9,000	12,000	24,000	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 9 + 12 + 24	6,600	10,000	13,300	26,500	0	0	0	0	4,718	23.0	20.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	51	51,000	6 + 9 + 18 + 18	6,000	9,000	18,000	18,000	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 9 + 18 + 18	6,600	10,000	19,900	19,900	0	0	0	0	4,718	23.0	20.8
4	51	51,000	6 + 12 + 15 + 18	6,000	12,000	15,000	18,000	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 12 + 15 + 18	6,600	13,300	16,600	19,900	0	0	0	0	4,718	23.0	20.8
4	51	51,000	6 + 15 + 15 + 15	6,000	15,000	15,000	15,000	0	0	0	0	4,480	21.8	19.7
		56,400	6 + 15 + 15 + 15	6,600	16,600	16,600	16,600	0	0	0	0	4,718	23.0	20.8
4	51	51,000	9 + 9 + 9 + 24	9,000	9,000	9,000	24,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 9 + 24	10,000	10,000	10,000	26,500	0	0	0	0	4,718	23.0	20.8
4	51	51,000	9 + 9 + 15 + 18	9,000	9,000	15,000	18,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 15 + 18	10,000	10,000	16,600	19,900	0	0	0	0	4,718	23.0	20.8
4	51	51,000	9 + 12 + 12 + 18	9,000	12,000	12,000	18,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 12 + 12 + 18	10,000	13,300	13,300	19,900	0	0	0	0	4,718	23.0	20.8
4	51	51,000	9 + 12 + 15 + 15	9,000	12,000	15,000	15,000	0	0	0	0	4,480	21.8	19.7
		56,400	9 + 12 + 15 + 15	10,000	13,300	16,600	16,600	0	0	0	0	4,718	23.0	20.8
4	51	51,000	12 + 12 + 12 + 15	12,000	12,000	12,000	15,000	0	0	0	0	4,480	21.8	19.7
		56,400	12 + 12 + 12 + 15	13,300	13,300	13,300	16,600	0	0	0	0	4,718	23.0	20.8
4	54	54,000	6 + 6 + 6 + 36	6,000	6,000	6,000	36,000	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 36	6,500	6,500	6,500	40,300	0	0	0	0	4,962	24.2	21.9
4	54	54,000	6 + 6 + 12 + 30	6,000	6,000	12,000	30,000	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 12 + 30	6,500	6,500	13,100	33,500	0	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	54	54,000	6 + 6 + 18 + 24	6,000	6,000	18,000	24,000	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 18 + 24	6,600	6,600	19,900	26,500	0	0	0	0	4,962	24.2	21.9
4	54	54,000	6 + 9 + 9 + 30	6,000	9,000	9,000	30,000	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 9 + 9 + 30	6,500	9,800	9,800	33,500	0	0	0	0	4,962	24.2	21.9
4	54	54,000	6 + 9 + 15 + 24	6,000	9,000	15,000	24,000	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 9 + 15 + 24	6,600	10,000	16,600	26,500	0	0	0	0	4,962	24.2	21.9
4	54	54,000	6 + 12 + 12 + 24	6,000	12,000	12,000	24,000	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 12 + 12 + 24	6,600	13,300	13,300	26,500	0	0	0	0	4,962	24.2	21.9
4	54	54,000	6 + 15 + 15 + 18	6,000	15,000	15,000	18,000	0	0	0	0	4,580	22.3	20.1
		59,700	6 + 15 + 15 + 18	6,600	16,600	16,600	19,900	0	0	0	0	4,962	24.2	21.9
4	54	54,000	9 + 9 + 12 + 24	9,000	9,000	12,000	24,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 12 + 24	10,000	10,000	13,300	26,500	0	0	0	0	4,962	24.2	21.9
4	54	54,000	9 + 9 + 18 + 18	9,000	9,000	18,000	18,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 18 + 18	10,000	10,000	19,900	19,900	0	0	0	0	4,962	24.2	21.9
4	54	54,000	9 + 12 + 15 + 18	9,000	12,000	15,000	18,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 12 + 15 + 18	10,000	13,300	16,600	19,900	0	0	0	0	4,962	24.2	21.9
4	54	54,000	9 + 15 + 15 + 15	9,000	15,000	15,000	15,000	0	0	0	0	4,580	22.3	20.1
		59,700	9 + 15 + 15 + 15	10,000	16,600	16,600	16,600	0	0	0	0	4,962	24.2	21.9
4	54	54,000	12 + 12 + 12 + 18	12,000	12,000	12,000	18,000	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 12 + 12 + 18	13,300	13,300	13,300	19,900	0	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	54	54,000	12 + 12 + 15 + 15	12,000	12,000	15,000	15,000	0	0	0	0	4,580	22.3	20.1
		59,700	12 + 12 + 15 + 15	13,300	13,300	16,600	16,600	0	0	0	0	4,962	24.2	21.9
4	57	57,000	6 + 6 + 9 + 36	6,000	6,000	9,000	36,000	0	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 9 + 36	6,500	6,500	9,700	40,400	0	0	0	0	5,206	25.4	23.0
4	57	57,000	6 + 6 + 15 + 30	6,000	6,000	15,000	30,000	0	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 15 + 30	6,500	6,500	16,400	33,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	6 + 9 + 12 + 30	6,000	9,000	12,000	30,000	0	0	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 12 + 30	6,500	9,800	13,100	33,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	6 + 9 + 18 + 24	6,000	9,000	18,000	24,000	0	0	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 18 + 24	6,600	9,900	19,900	26,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	6 + 12 + 15 + 24	6,000	12,000	15,000	24,000	0	0	0	0	4,630	22.5	20.4
		63,000	6 + 12 + 15 + 24	6,600	13,300	16,600	26,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 9 + 9 + 30	9,000	9,000	9,000	30,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 30	9,800	9,800	9,800	33,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 9 + 15 + 24	9,000	9,000	15,000	24,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 15 + 24	9,900	9,900	16,600	26,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 12 + 12 + 24	9,000	12,000	12,000	24,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 12 + 24	9,900	13,300	13,300	26,500	0	0	0	0	5,206	25.4	23.0
4	57	57,000	9 + 12 + 18 + 18	9,000	12,000	18,000	18,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 18 + 18	9,900	13,300	19,900	19,900	0	0	0	0	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	57	57,000	9 + 15 + 15 + 18	9,000	15,000	15,000	18,000	0	0	0	0	4,630	22.5	20.4
		63,000	9 + 15 + 15 + 18	9,900	16,600	16,600	19,900	0	0	0	0	5,206	25.4	23.0
4	57	57,000	12 + 12 + 15 + 18	12,000	12,000	15,000	18,000	0	0	0	0	4,630	22.5	20.4
		63,000	12 + 12 + 15 + 18	13,300	13,300	16,600	19,900	0	0	0	0	5,206	25.4	23.0
4	57	57,000	12 + 15 + 15 + 15	12,000	15,000	15,000	15,000	0	0	0	0	4,630	22.5	20.4
		63,000	12 + 15 + 15 + 15	13,300	16,600	16,600	16,600	0	0	0	0	5,206	25.4	23.0
4	60	60,000	6 + 6 + 12 + 36	6,000	6,000	12,000	36,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 12 + 36	6,400	6,400	12,900	40,200	0	0	0	0	5,450	26.6	24.1
4	60	60,000	6 + 6 + 18 + 30	6,000	6,000	18,000	30,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 18 + 30	6,500	6,500	19,600	33,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	6 + 6 + 24 + 24	6,000	6,000	24,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 24 + 24	6,600	6,600	26,400	26,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	6 + 9 + 9 + 36	6,000	9,000	9,000	36,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 9 + 36	6,400	9,700	9,700	40,200	0	0	0	0	5,450	26.6	24.1
4	60	60,000	6 + 9 + 15 + 30	6,000	9,000	15,000	30,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 15 + 30	6,500	9,800	16,300	33,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	6 + 12 + 12 + 30	6,000	12,000	12,000	30,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 12 + 12 + 30	6,500	13,000	13,000	33,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	6 + 15 + 15 + 24	6,000	15,000	15,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 15 + 15 + 24	6,600	16,500	16,500	26,400	0	0	0	0	5,450	26.6	24.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	60	60,000	6 + 18 + 18 + 18	6,000	18,000	18,000	18,000	0	0	0	0	4,680	22.8	20.6
		66,000	6 + 18 + 18 + 18	6,600	19,800	19,800	19,800	0	0	0	0	5,450	26.6	24.1
4	60	60,000	9 + 9 + 12 + 30	9,000	9,000	12,000	30,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 12 + 30	9,800	9,800	13,000	33,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	9 + 9 + 18 + 24	9,000	9,000	18,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 18 + 24	9,900	9,900	19,800	26,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	9 + 12 + 15 + 24	9,000	12,000	15,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 12 + 15 + 24	9,900	13,200	16,500	26,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	9 + 15 + 18 + 18	9,000	15,000	18,000	18,000	0	0	0	0	4,680	22.8	20.6
		66,000	9 + 15 + 18 + 18	9,900	16,500	19,800	19,800	0	0	0	0	5,450	26.6	24.1
4	60	60,000	12 + 12 + 12 + 24	12,000	12,000	12,000	24,000	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 12 + 24	13,200	13,200	13,200	26,400	0	0	0	0	5,450	26.6	24.1
4	60	60,000	12 + 12 + 18 + 18	12,000	12,000	18,000	18,000	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 18 + 18	13,200	13,200	19,800	19,800	0	0	0	0	5,450	26.6	24.1
4	60	60,000	12 + 15 + 15 + 18	12,000	15,000	15,000	18,000	0	0	0	0	4,680	22.8	20.6
		66,000	12 + 15 + 15 + 18	13,200	16,500	16,500	19,800	0	0	0	0	5,450	26.6	24.1
4	60	60,000	15 + 15 + 15 + 15	15,000	15,000	15,000	15,000	0	0	0	0	4,680	22.8	20.6
		66,000	15 + 15 + 15 + 15	16,500	16,500	16,500	16,500	0	0	0	0	5,450	26.6	24.1
4	63	60,600	6 + 6 + 15 + 36	5,800	5,800	14,400	34,600	0	0	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 15 + 36	6,200	6,200	15,500	38,700	0	0	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	63	60,600	6 + 9 + 12 + 36	5,800	8,700	11,500	34,600	0	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 12 + 36	6,200	9,300	12,400	38,700	0	0	0	0	5,430	26.5	24.0
4	63	60,600	6 + 9 + 18 + 30	5,800	8,700	17,300	28,900	0	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 18 + 30	6,300	9,400	18,800	32,100	0	0	0	0	5,430	26.5	24.0
4	63	60,600	6 + 9 + 24 + 24	5,800	8,700	23,100	23,100	0	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 24 + 24	6,300	9,500	25,400	25,400	0	0	0	0	5,430	26.5	24.0
4	63	60,600	6 + 12 + 15 + 30	5,800	11,500	14,400	28,900	0	0	0	0	4,690	22.8	20.6
		66,600	6 + 12 + 15 + 30	6,300	12,500	15,700	32,100	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 9 + 9 + 36	8,700	8,700	8,700	34,600	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 36	9,300	9,300	9,300	38,700	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 9 + 15 + 30	8,700	8,700	14,400	28,900	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 15 + 30	9,400	9,400	15,700	32,100	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 12 + 12 + 30	8,700	11,500	11,500	28,900	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 12 + 30	9,400	12,500	12,500	32,100	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 12 + 18 + 24	8,700	11,500	17,300	23,100	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 18 + 24	9,500	12,700	19,000	25,400	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 15 + 15 + 24	8,700	14,400	14,400	23,100	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 15 + 15 + 24	9,500	15,900	15,900	25,400	0	0	0	0	5,430	26.5	24.0
4	63	60,600	9 + 18 + 18 + 18	8,700	17,300	17,300	17,300	0	0	0	0	4,690	22.8	20.6
		66,600	9 + 18 + 18 + 18	9,500	19,000	19,000	19,000	0	0	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	63	60,600	12 + 12 + 15 + 24	11,500	11,500	14,400	23,100	0	0	0	0	4,690	22.8	20.6
		66,600	12 + 12 + 15 + 24	12,700	12,700	15,900	25,400	0	0	0	0	5,430	26.5	24.0
4	63	60,600	12 + 15 + 18 + 18	11,500	14,400	17,300	17,300	0	0	0	0	4,690	22.8	20.6
		66,600	12 + 15 + 18 + 18	12,700	15,900	19,000	19,000	0	0	0	0	5,430	26.5	24.0
4	63	60,600	15 + 15 + 15 + 18	14,400	14,400	14,400	17,300	0	0	0	0	4,690	22.8	20.6
		66,600	15 + 15 + 15 + 18	15,900	15,900	15,900	19,000	0	0	0	0	5,430	26.5	24.0
4	66	61,200	6 + 6 + 18 + 36	5,600	5,600	16,700	33,400	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 18 + 36	6,000	6,000	17,900	37,300	0	0	0	0	5,410	26.4	23.9
4	66	61,200	6 + 6 + 24 + 30	5,600	5,600	22,300	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 24 + 30	6,000	6,000	24,200	31,000	0	0	0	0	5,410	26.4	23.9
4	66	61,200	6 + 9 + 15 + 36	5,600	8,300	13,900	33,400	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 15 + 36	6,000	9,000	14,900	37,300	0	0	0	0	5,410	26.4	23.9
4	66	61,200	6 + 12 + 12 + 36	5,600	11,100	11,100	33,400	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 12 + 12 + 36	6,000	11,900	11,900	37,300	0	0	0	0	5,410	26.4	23.9
4	66	61,200	6 + 15 + 15 + 30	5,600	13,900	13,900	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 15 + 15 + 30	6,000	15,100	15,100	31,000	0	0	0	0	5,410	26.4	23.9
4	66	61,200	6 + 18 + 18 + 24	5,600	16,700	16,700	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	6 + 18 + 18 + 24	6,100	18,300	18,300	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 9 + 12 + 36	8,300	8,300	11,100	33,400	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 36	9,000	9,000	11,900	37,300	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	66	61,200	9 + 9 + 18 + 30	8,300	8,300	16,700	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 18 + 30	9,100	9,100	18,100	31,000	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 9 + 24 + 24	8,300	8,300	22,300	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 24 + 24	9,200	9,200	24,400	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 12 + 15 + 30	8,300	11,100	13,900	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 12 + 15 + 30	9,100	12,100	15,100	31,000	0	0	0	0	5,410	26.4	23.9
4	66	61,200	9 + 15 + 18 + 24	8,300	13,900	16,700	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	9 + 15 + 18 + 24	9,200	15,300	18,300	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	12 + 12 + 12 + 30	11,100	11,100	11,100	27,800	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 12 + 30	12,100	12,100	12,100	31,000	0	0	0	0	5,410	26.4	23.9
4	66	61,200	12 + 12 + 18 + 24	11,100	11,100	16,700	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 18 + 24	12,200	12,200	18,300	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	12 + 15 + 15 + 24	11,100	13,900	13,900	22,300	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 15 + 15 + 24	12,200	15,300	15,300	24,400	0	0	0	0	5,410	26.4	23.9
4	66	61,200	12 + 18 + 18 + 18	11,100	16,700	16,700	16,700	0	0	0	0	4,700	22.8	20.7
		67,200	12 + 18 + 18 + 18	12,200	18,300	18,300	18,300	0	0	0	0	5,410	26.4	23.9
4	66	61,200	15 + 15 + 18 + 18	13,900	13,900	16,700	16,700	0	0	0	0	4,700	22.8	20.7
		67,200	15 + 15 + 18 + 18	15,300	15,300	18,300	18,300	0	0	0	0	5,410	26.4	23.9
4	69	61,800	6 + 9 + 18 + 36	5,400	8,100	16,100	32,200	0	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 18 + 36	5,800	8,700	17,300	36,100	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	69	61,800	6 + 9 + 24 + 30	5,400	8,100	21,500	26,900	0	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 24 + 30	5,800	8,700	23,300	29,900	0	0	0	0	5,410	26.4	23.9
4	69	61,800	6 + 12 + 15 + 36	5,400	10,700	13,400	32,200	0	0	0	0	4,700	22.8	20.7
		67,800	6 + 12 + 15 + 36	5,800	11,500	14,400	36,100	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 9 + 15 + 36	8,100	8,100	13,400	32,200	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 15 + 36	8,700	8,700	14,400	36,100	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 12 + 12 + 36	8,100	10,700	10,700	32,200	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 12 + 36	8,700	11,500	11,500	36,100	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 12 + 18 + 30	8,100	10,700	16,100	26,900	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 18 + 30	8,700	11,700	17,500	29,900	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 15 + 15 + 30	8,100	13,400	13,400	26,900	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 15 + 15 + 30	8,700	14,600	14,600	29,900	0	0	0	0	5,410	26.4	23.9
4	69	61,800	9 + 18 + 18 + 24	8,100	16,100	16,100	21,500	0	0	0	0	4,700	22.8	20.7
		67,800	9 + 18 + 18 + 24	8,800	17,700	17,700	23,600	0	0	0	0	5,410	26.4	23.9
4	69	61,800	12 + 12 + 15 + 30	10,700	10,700	13,400	26,900	0	0	0	0	4,700	22.8	20.7
		67,800	12 + 12 + 15 + 30	11,700	11,700	14,600	29,900	0	0	0	0	5,410	26.4	23.9
4	69	61,800	12 + 15 + 18 + 24	10,700	13,400	16,100	21,500	0	0	0	0	4,700	22.8	20.7
		67,800	12 + 15 + 18 + 24	11,800	14,700	17,700	23,600	0	0	0	0	5,410	26.4	23.9
4	69	61,800	15 + 15 + 15 + 24	13,400	13,400	13,400	21,500	0	0	0	0	4,700	22.8	20.7
		67,800	15 + 15 + 15 + 24	14,700	14,700	14,700	23,600	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	69	61,800	15 + 18 + 18 + 18	13,400	16,100	16,100	16,100	0	0	0	0	4,700	22.8	20.7
		67,800	15 + 18 + 18 + 18	14,700	17,700	17,700	17,700	0	0	0	0	5,410	26.4	23.9
4	72	62,400	6 + 6 + 24 + 36	5,200	5,200	20,800	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 24 + 36	5,600	5,600	22,300	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	6 + 6 + 30 + 30	5,200	5,200	26,000	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 30 + 30	5,600	5,600	28,600	28,600	0	0	0	0	5,410	26.4	23.9
4	72	62,400	6 + 15 + 15 + 36	5,200	13,000	13,000	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	6 + 15 + 15 + 36	5,600	14,000	14,000	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	6 + 18 + 18 + 30	5,200	15,600	15,600	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	6 + 18 + 18 + 30	5,600	16,900	16,900	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 9 + 18 + 36	7,800	7,800	15,600	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 18 + 36	8,400	8,400	16,800	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 9 + 24 + 30	7,800	7,800	20,800	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 24 + 30	8,500	8,500	22,600	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 12 + 15 + 36	7,800	10,400	13,000	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 12 + 15 + 36	8,400	11,200	14,000	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 15 + 18 + 30	7,800	13,000	15,600	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 15 + 18 + 30	8,500	14,100	16,900	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	9 + 15 + 24 + 24	7,800	13,000	20,800	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	9 + 15 + 24 + 24	8,600	14,300	22,800	22,800	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	72	62,400	12 + 12 + 12 + 36	10,400	10,400	10,400	31,200	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 12 + 36	11,200	11,200	11,200	34,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 12 + 18 + 30	10,400	10,400	15,600	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 18 + 30	11,300	11,300	16,900	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 12 + 24 + 24	10,400	10,400	20,800	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 24 + 24	11,400	11,400	22,800	22,800	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 15 + 15 + 30	10,400	13,000	13,000	26,000	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 15 + 15 + 30	11,300	14,100	14,100	28,900	0	0	0	0	5,410	26.4	23.9
4	72	62,400	12 + 18 + 18 + 24	10,400	15,600	15,600	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	12 + 18 + 18 + 24	11,400	17,100	17,100	22,800	0	0	0	0	5,410	26.4	23.9
4	72	62,400	15 + 15 + 18 + 24	13,000	13,000	15,600	20,800	0	0	0	0	4,700	22.8	20.7
		68,400	15 + 15 + 18 + 24	14,300	14,300	17,100	22,800	0	0	0	0	5,410	26.4	23.9
4	72	62,400	18 + 18 + 18 + 18	15,600	15,600	15,600	15,600	0	0	0	0	4,700	22.8	20.7
		68,400	18 + 18 + 18 + 18	17,100	17,100	17,100	17,100	0	0	0	0	5,410	26.4	23.9
4	75	63,000	6 + 9 + 24 + 36	5,000	7,600	20,200	30,200	0	0	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 24 + 36	5,400	8,100	21,600	33,800	0	0	0	0	5,410	26.4	23.9
4	75	63,000	6 + 9 + 30 + 30	5,000	7,600	25,200	25,200	0	0	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 30 + 30	5,400	8,100	27,700	27,700	0	0	0	0	5,410	26.4	23.9
4	75	63,000	9 + 12 + 18 + 36	7,600	10,100	15,100	30,200	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 18 + 36	8,100	10,800	16,200	33,800	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	75	63,000	9 + 15 + 15 + 36	7,600	12,600	12,600	30,200	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 15 + 15 + 36	8,100	13,500	13,500	33,800	0	0	0	0	5,410	26.4	23.9
4	75	63,000	9 + 18 + 18 + 30	7,600	15,100	15,100	25,200	0	0	0	0	4,700	22.8	20.7
		69,000	9 + 18 + 18 + 30	8,200	16,400	16,400	28,000	0	0	0	0	5,410	26.4	23.9
4	75	63,000	12 + 12 + 15 + 36	10,100	10,100	12,600	30,200	0	0	0	0	4,700	22.8	20.7
		69,000	12 + 12 + 15 + 36	10,800	10,800	13,500	33,800	0	0	0	0	5,410	26.4	23.9
4	75	63,000	12 + 15 + 18 + 30	10,100	12,600	15,100	25,200	0	0	0	0	4,700	22.8	20.7
		69,000	12 + 15 + 18 + 30	10,900	13,700	16,400	28,000	0	0	0	0	5,410	26.4	23.9
4	75	63,000	15 + 15 + 15 + 30	12,600	12,600	12,600	25,200	0	0	0	0	4,700	22.8	20.7
		69,000	15 + 15 + 15 + 30	13,700	13,700	13,700	28,000	0	0	0	0	5,410	26.4	23.9
4	75	63,000	15 + 18 + 18 + 24	12,600	15,100	15,100	20,200	0	0	0	0	4,700	22.8	20.7
		69,000	15 + 18 + 18 + 24	13,800	16,600	16,600	22,100	0	0	0	0	5,410	26.4	23.9
4	78	63,600	6 + 6 + 30 + 36	4,900	4,900	24,500	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 30 + 36	5,200	5,200	26,700	32,500	0	0	0	0	5,410	26.4	23.9
4	78	63,600	6 + 18 + 18 + 36	4,900	14,700	14,700	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	6 + 18 + 18 + 36	5,300	15,800	15,800	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	6 + 24 + 24 + 24	4,900	19,600	19,600	19,600	0	0	0	0	4,690	22.8	20.6
		69,600	6 + 24 + 24 + 24	5,400	21,400	21,400	21,400	0	0	0	0	5,410	26.4	23.9
4	78	63,600	9 + 9 + 24 + 36	7,300	7,300	19,600	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 24 + 36	7,900	7,900	21,000	32,800	0	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	78	63,600	9 + 9 + 30 + 30	7,300	7,300	24,500	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 30 + 30	7,900	7,900	26,900	26,900	0	0	0	0	5,410	26.4	23.9
4	78	63,600	9 + 15 + 18 + 36	7,300	12,200	14,700	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 18 + 36	7,900	13,100	15,800	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	9 + 15 + 24 + 30	7,300	12,200	19,600	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 24 + 30	8,000	13,300	21,200	27,200	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 12 + 18 + 36	9,800	9,800	14,700	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 18 + 36	10,500	10,500	15,800	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 12 + 24 + 30	9,800	9,800	19,600	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 24 + 30	10,600	10,600	21,200	27,200	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 15 + 15 + 36	9,800	12,200	12,200	29,400	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 15 + 15 + 36	10,500	13,100	13,100	32,800	0	0	0	0	5,410	26.4	23.9
4	78	63,600	12 + 18 + 18 + 30	9,800	14,700	14,700	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	12 + 18 + 18 + 30	10,600	15,900	15,900	27,200	0	0	0	0	5,410	26.4	23.9
4	78	63,600	15 + 15 + 18 + 30	12,200	12,200	14,700	24,500	0	0	0	0	4,690	22.8	20.6
		69,600	15 + 15 + 18 + 30	13,300	13,300	15,900	27,200	0	0	0	0	5,410	26.4	23.9
4	78	63,600	18 + 18 + 18 + 24	14,700	14,700	14,700	19,600	0	0	0	0	4,690	22.8	20.6
		69,600	18 + 18 + 18 + 24	16,100	16,100	16,100	21,400	0	0	0	0	5,410	26.4	23.9
5	30	30,000	6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	0	0	0	3,060	14.9	13.5
		33,400	6 + 6 + 6 + 6 + 6	6,700	6,700	6,700	6,700	6,700	0	0	0	3,011	14.7	13.3

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	33	33,000	6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	9,000	0	0	0	3,320	16.1	14.6
		36,700	6 + 6 + 6 + 6 + 9	6,700	6,700	6,700	6,700	10,000	0	0	0	3,255	15.9	14.4
5	36	36,000	6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	12,000	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 6 + 6 + 12	6,700	6,700	6,700	6,700	13,300	0	0	0	3,499	17.1	15.4
5	36	36,000	6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	9,000	9,000	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 6 + 9 + 9	6,700	6,700	6,700	10,000	10,000	0	0	0	3,499	17.1	15.4
5	39	39,000	6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	15,000	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 6 + 6 + 15	6,600	6,600	6,600	6,600	16,600	0	0	0	3,743	18.3	16.5
5	39	39,000	6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	9,000	12,000	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 6 + 9 + 12	6,600	6,600	6,600	10,000	13,300	0	0	0	3,743	18.3	16.5
5	39	39,000	6 + 6 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 9 + 9 + 9	6,600	6,600	10,000	10,000	10,000	0	0	0	3,743	18.3	16.5
5	42	42,000	6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	18,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 6 + 18	6,600	6,600	6,600	6,600	19,900	0	0	0	3,987	19.5	17.6
5	42	42,000	6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	9,000	15,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 9 + 15	6,600	6,600	6,600	10,000	16,600	0	0	0	3,987	19.5	17.6
5	42	42,000	6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	12,000	12,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 12 + 12	6,600	6,600	6,600	13,300	13,300	0	0	0	3,987	19.5	17.6
5	42	42,000	6 + 6 + 9 + 9 + 12	6,000	6,000	9,000	9,000	12,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 9 + 9 + 12	6,600	6,600	10,000	10,000	13,300	0	0	0	3,987	19.5	17.6

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	33	33,000	6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	9,000	0	0	0	3,320	16.1	14.6
		36,700	6 + 6 + 6 + 6 + 9	6,700	6,700	6,700	6,700	10,000	0	0	0	3,255	15.9	14.4
5	36	36,000	6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	12,000	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 6 + 6 + 12	6,700	6,700	6,700	6,700	13,300	0	0	0	3,499	17.1	15.4
5	36	36,000	6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	9,000	9,000	0	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 6 + 9 + 9	6,700	6,700	6,700	10,000	10,000	0	0	0	3,499	17.1	15.4
5	39	39,000	6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	15,000	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 6 + 6 + 15	6,600	6,600	6,600	6,600	16,600	0	0	0	3,743	18.3	16.5
5	39	39,000	6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	9,000	12,000	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 6 + 9 + 12	6,600	6,600	6,600	10,000	13,300	0	0	0	3,743	18.3	16.5
5	39	39,000	6 + 6 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	0	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 9 + 9 + 9	6,600	6,600	10,000	10,000	10,000	0	0	0	3,743	18.3	16.5
5	42	42,000	6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	18,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 6 + 18	6,600	6,600	6,600	6,600	19,900	0	0	0	3,987	19.5	17.6
5	42	42,000	6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	9,000	15,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 9 + 15	6,600	6,600	6,600	10,000	16,600	0	0	0	3,987	19.5	17.6
5	42	42,000	6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	12,000	12,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 12 + 12	6,600	6,600	6,600	13,300	13,300	0	0	0	3,987	19.5	17.6
5	42	42,000	6 + 6 + 9 + 9 + 12	6,000	6,000	9,000	9,000	12,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 9 + 9 + 12	6,600	6,600	10,000	10,000	13,300	0	0	0	3,987	19.5	17.6

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	42	42,000	6 + 9 + 9 + 9 + 9	6,000	9,000	9,000	9,000	9,000	0	0	0	4,000	19.4	17.6
		46,500	6 + 9 + 9 + 9 + 9	6,600	10,000	10,000	10,000	10,000	0	0	0	3,987	19.5	17.6
5	45	45,000	6 + 6 + 6 + 9 + 18	6,000	6,000	6,000	9,000	18,000	0	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 6 + 9 + 18	6,600	6,600	6,600	10,000	19,900	0	0	0	4,231	20.6	18.7
5	45	45,000	6 + 6 + 6 + 12 + 15	6,000	6,000	6,000	12,000	15,000	0	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 6 + 12 + 15	6,600	6,600	6,600	13,300	16,600	0	0	0	4,231	20.6	18.7
5	45	45,000	6 + 6 + 9 + 9 + 15	6,000	6,000	9,000	9,000	15,000	0	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 9 + 9 + 15	6,600	6,600	10,000	10,000	16,600	0	0	0	4,231	20.6	18.7
5	45	45,000	6 + 6 + 9 + 12 + 12	6,000	6,000	9,000	12,000	12,000	0	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 9 + 12 + 12	6,600	6,600	10,000	13,300	13,300	0	0	0	4,231	20.6	18.7
5	45	45,000	6 + 9 + 9 + 9 + 12	6,000	9,000	9,000	9,000	12,000	0	0	0	4,180	20.3	18.4
		49,800	6 + 9 + 9 + 9 + 12	6,600	10,000	10,000	10,000	13,300	0	0	0	4,231	20.6	18.7
5	45	45,000	9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	0	0	0	4,180	20.3	18.4
		49,800	9 + 9 + 9 + 9 + 9	10,000	10,000	10,000	10,000	10,000	0	0	0	4,231	20.6	18.7
5	48	48,000	6 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	24,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 6 + 24	6,600	6,600	6,600	6,600	26,600	0	0	0	4,474	21.8	19.8
5	48	48,000	6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	12,000	18,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 12 + 18	6,600	6,600	6,600	13,300	19,900	0	0	0	4,474	21.8	19.8
5	48	48,000	6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	15,000	15,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 15 + 15	6,600	6,600	6,600	16,600	16,600	0	0	0	4,474	21.8	19.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	48	48,000	6 + 6 + 9 + 9 + 18	6,000	6,000	9,000	9,000	18,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 9 + 9 + 18	6,600	6,600	10,000	10,000	19,900	0	0	0	4,474	21.8	19.8
5	48	48,000	6 + 6 + 9 + 12 + 15	6,000	6,000	9,000	12,000	15,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 9 + 12 + 15	6,600	6,600	10,000	13,300	16,600	0	0	0	4,474	21.8	19.8
5	48	48,000	6 + 6 + 12 + 12 + 12	6,000	6,000	12,000	12,000	12,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 12 + 12 + 12	6,600	6,600	13,300	13,300	13,300	0	0	0	4,474	21.8	19.8
5	48	48,000	6 + 9 + 9 + 9 + 15	6,000	9,000	9,000	9,000	15,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 9 + 9 + 9 + 15	6,600	10,000	10,000	10,000	16,600	0	0	0	4,474	21.8	19.8
5	48	48,000	6 + 9 + 9 + 12 + 12	6,000	9,000	9,000	12,000	12,000	0	0	0	4,340	21.1	19.1
		53,100	6 + 9 + 9 + 12 + 12	6,600	10,000	10,000	13,300	13,300	0	0	0	4,474	21.8	19.8
5	48	48,000	9 + 9 + 9 + 9 + 12	9,000	9,000	9,000	9,000	12,000	0	0	0	4,340	21.1	19.1
		53,100	9 + 9 + 9 + 9 + 12	10,000	10,000	10,000	10,000	13,300	0	0	0	4,474	21.8	19.8
5	51	51,000	6 + 6 + 6 + 9 + 24	6,000	6,000	6,000	9,000	24,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 9 + 24	6,600	6,600	6,600	10,000	26,500	0	0	0	4,718	23.0	20.8
5	51	51,000	6 + 6 + 6 + 15 + 18	6,000	6,000	6,000	15,000	18,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 15 + 18	6,600	6,600	6,600	16,600	19,900	0	0	0	4,718	23.0	20.8
5	51	51,000	6 + 6 + 9 + 12 + 18	6,000	6,000	9,000	12,000	18,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 9 + 12 + 18	6,600	6,600	10,000	13,300	19,900	0	0	0	4,718	23.0	20.8
5	51	51,000	6 + 6 + 9 + 15 + 15	6,000	6,000	9,000	15,000	15,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 9 + 15 + 15	6,600	6,600	10,000	16,600	16,600	0	0	0	4,718	23.0	20.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	51	51,000	6 + 6 + 12 + 12 + 15	6,000	6,000	12,000	12,000	15,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 12 + 12 + 15	6,600	6,600	13,300	13,300	16,600	0	0	0	4,718	23.0	20.8
5	51	51,000	6 + 9 + 9 + 9 + 18	6,000	9,000	9,000	9,000	18,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 9 + 9 + 9 + 18	6,600	10,000	10,000	10,000	19,900	0	0	0	4,718	23.0	20.8
5	51	51,000	6 + 9 + 9 + 12 + 15	6,000	9,000	9,000	12,000	15,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 9 + 9 + 12 + 15	6,600	10,000	10,000	13,300	16,600	0	0	0	4,718	23.0	20.8
5	51	51,000	6 + 9 + 12 + 12 + 12	6,000	9,000	12,000	12,000	12,000	0	0	0	4,480	21.8	19.7
		56,400	6 + 9 + 12 + 12 + 12	6,600	10,000	13,300	13,300	13,300	0	0	0	4,718	23.0	20.8
5	51	51,000	9 + 9 + 9 + 9 + 15	9,000	9,000	9,000	9,000	15,000	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 9 + 9 + 15	10,000	10,000	10,000	10,000	16,600	0	0	0	4,718	23.0	20.8
5	51	51,000	9 + 9 + 9 + 12 + 12	9,000	9,000	9,000	12,000	12,000	0	0	0	4,480	21.8	19.7
		56,400	9 + 9 + 9 + 12 + 12	10,000	10,000	10,000	13,300	13,300	0	0	0	4,718	23.0	20.8
5	54	54,000	6 + 6 + 6 + 6 + 30	6,000	6,000	6,000	6,000	30,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 30	6,500	6,500	6,500	6,500	33,500	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 6 + 6 + 12 + 24	6,000	6,000	6,000	12,000	24,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 12 + 24	6,600	6,600	6,600	13,300	26,500	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 6 + 6 + 18 + 18	6,000	6,000	6,000	18,000	18,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 18 + 18	6,600	6,600	6,600	19,900	19,900	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 6 + 9 + 9 + 24	6,000	6,000	9,000	9,000	24,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 9 + 9 + 24	6,600	6,600	10,000	10,000	26,500	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	54	54,000	6 + 6 + 9 + 15 + 18	6,000	6,000	9,000	15,000	18,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 9 + 15 + 18	6,600	6,600	10,000	16,600	19,900	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 6 + 12 + 12 + 18	6,000	6,000	12,000	12,000	18,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 12 + 12 + 18	6,600	6,600	13,300	13,300	19,900	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 6 + 12 + 15 + 15	6,000	6,000	12,000	15,000	15,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 12 + 15 + 15	6,600	6,600	13,300	16,600	16,600	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 9 + 9 + 12 + 18	6,000	9,000	9,000	12,000	18,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 9 + 9 + 12 + 18	6,600	10,000	10,000	13,300	19,900	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 9 + 9 + 15 + 15	6,000	9,000	9,000	15,000	15,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 9 + 9 + 15 + 15	6,600	10,000	10,000	16,600	16,600	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 9 + 12 + 12 + 15	6,000	9,000	12,000	12,000	15,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 9 + 12 + 12 + 15	6,600	10,000	13,300	13,300	16,600	0	0	0	4,962	24.2	21.9
5	54	54,000	6 + 12 + 12 + 12 + 12	6,000	12,000	12,000	12,000	12,000	0	0	0	4,580	22.3	20.1
		59,700	6 + 12 + 12 + 12 + 12	6,600	13,300	13,300	13,300	13,300	0	0	0	4,962	24.2	21.9
5	54	54,000	9 + 9 + 9 + 9 + 18	9,000	9,000	9,000	9,000	18,000	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 9 + 9 + 18	10,000	10,000	10,000	10,000	19,900	0	0	0	4,962	24.2	21.9
5	54	54,000	9 + 9 + 9 + 12 + 15	9,000	9,000	9,000	12,000	15,000	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 9 + 12 + 15	10,000	10,000	10,000	13,300	16,600	0	0	0	4,962	24.2	21.9
5	54	54,000	9 + 9 + 12 + 12 + 12	9,000	9,000	12,000	12,000	12,000	0	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 12 + 12 + 12	10,000	10,000	13,300	13,300	13,300	0	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	57	57,000	6 + 6 + 6 + 9 + 30	6,000	6,000	6,000	9,000	30,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 9 + 30	6,500	6,500	6,500	9,800	33,500	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 6 + 6 + 15 + 24	6,000	6,000	6,000	15,000	24,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 15 + 24	6,600	6,600	6,600	16,600	26,500	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 6 + 9 + 12 + 24	6,000	6,000	9,000	12,000	24,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 9 + 12 + 24	6,600	6,600	9,900	13,300	26,500	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 6 + 9 + 18 + 18	6,000	6,000	9,000	18,000	18,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 9 + 18 + 18	6,600	6,600	9,900	19,900	19,900	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 6 + 12 + 15 + 18	6,000	6,000	12,000	15,000	18,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 12 + 15 + 18	6,600	6,600	13,300	16,600	19,900	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 6 + 15 + 15 + 15	6,000	6,000	15,000	15,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 15 + 15 + 15	6,600	6,600	16,600	16,600	16,600	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 9 + 9 + 9 + 24	6,000	9,000	9,000	9,000	24,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 9 + 9 + 24	6,600	9,900	9,900	9,900	26,500	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 9 + 9 + 15 + 18	6,000	9,000	9,000	15,000	18,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 9 + 15 + 18	6,600	9,900	9,900	16,600	19,900	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 9 + 12 + 12 + 18	6,000	9,000	12,000	12,000	18,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 12 + 12 + 18	6,600	9,900	13,300	13,300	19,900	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 9 + 12 + 15 + 15	6,000	9,000	12,000	15,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 12 + 15 + 15	6,600	9,900	13,300	16,600	16,600	0	0	0	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	57	57,000	6 + 9 + 12 + 15 + 15	6,000	9,000	12,000	15,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 12 + 15 + 15	6,600	9,900	13,300	16,600	16,600	0	0	0	5,206	25.4	23.0
5	57	57,000	6 + 12 + 12 + 12 + 15	6,000	12,000	12,000	12,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	6 + 12 + 12 + 12 + 15	6,600	13,300	13,300	13,300	16,600	0	0	0	5,206	25.4	23.0
5	57	57,000	9 + 9 + 9 + 12 + 18	9,000	9,000	9,000	12,000	18,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 12 + 18	9,900	9,900	9,900	13,300	19,900	0	0	0	5,206	25.4	23.0
5	57	57,000	9 + 9 + 9 + 15 + 15	9,000	9,000	9,000	15,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 15 + 15	9,900	9,900	9,900	16,600	16,600	0	0	0	5,206	25.4	23.0
5	57	57,000	9 + 9 + 12 + 12 + 15	9,000	9,000	12,000	12,000	15,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 12 + 12 + 15	9,900	9,900	13,300	13,300	16,600	0	0	0	5,206	25.4	23.0
5	57	57,000	9 + 12 + 12 + 12 + 12	9,000	12,000	12,000	12,000	12,000	0	0	0	4,630	22.5	20.4
		63,000	9 + 12 + 12 + 12 + 12	9,900	13,300	13,300	13,300	13,300	0	0	0	5,206	25.4	23.0
5	60	60,000	6 + 6 + 6 + 6 + 36	6,000	6,000	6,000	6,000	36,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 36	6,400	6,400	6,400	6,400	40,200	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 6 + 6 + 12 + 30	6,000	6,000	6,000	12,000	30,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 12 + 30	6,500	6,500	6,500	13,000	33,400	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 6 + 6 + 18 + 24	6,000	6,000	6,000	18,000	24,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 18 + 24	6,600	6,600	6,600	19,800	26,400	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 6 + 9 + 9 + 30	6,000	6,000	9,000	9,000	30,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 9 + 9 + 30	6,500	6,500	9,800	9,800	33,400	0	0	0	5,450	26.6	24.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	60	60,000	6 + 6 + 9 + 15 + 24	6,000	6,000	9,000	15,000	24,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 9 + 15 + 24	6,600	6,600	9,900	16,500	26,400	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 6 + 12 + 12 + 24	6,000	6,000	12,000	12,000	24,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 12 + 12 + 24	6,600	6,600	13,200	13,200	26,400	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 6 + 12 + 18 + 18	6,000	6,000	12,000	18,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 12 + 18 + 18	6,600	6,600	13,200	19,800	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 6 + 15 + 15 + 18	6,000	6,000	15,000	15,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 15 + 15 + 18	6,600	6,600	16,500	16,500	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 9 + 9 + 12 + 24	6,000	9,000	9,000	12,000	24,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 9 + 12 + 24	6,600	9,900	9,900	13,200	26,400	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 9 + 9 + 18 + 18	6,000	9,000	9,000	18,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 9 + 18 + 18	6,600	9,900	9,900	19,800	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 9 + 12 + 15 + 18	6,000	9,000	12,000	15,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 12 + 15 + 18	6,600	9,900	13,200	16,500	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 9 + 12 + 15 + 18	6,000	9,000	12,000	15,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 12 + 15 + 18	6,600	9,900	13,200	16,500	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 9 + 15 + 15 + 15	6,000	9,000	15,000	15,000	15,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 15 + 15 + 15	6,600	9,900	16,500	16,500	16,500	0	0	0	5,450	26.6	24.1
5	60	60,000	6 + 12 + 12 + 12 + 18	6,000	12,000	12,000	12,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 12 + 12 + 12 + 18	6,600	13,200	13,200	13,200	19,800	0	0	0	5,450	26.6	24.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	60	60,000	6 + 12 + 12 + 15 + 15	6,000	12,000	12,000	15,000	15,000	0	0	0	4,680	22.8	20.6
		66,000	6 + 12 + 12 + 15 + 15	6,600	13,200	13,200	16,500	16,500	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 9 + 9 + 9 + 24	9,000	9,000	9,000	9,000	24,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 9 + 24	9,900	9,900	9,900	9,900	26,400	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 9 + 9 + 15 + 18	9,000	9,000	9,000	15,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 15 + 18	9,900	9,900	9,900	16,500	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 9 + 12 + 12 + 18	9,000	9,000	12,000	12,000	18,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 12 + 12 + 18	9,900	9,900	13,200	13,200	19,800	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 9 + 12 + 15 + 15	9,000	9,000	12,000	15,000	15,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 12 + 15 + 15	9,900	9,900	13,200	16,500	16,500	0	0	0	5,450	26.6	24.1
5	60	60,000	9 + 12 + 12 + 12 + 15	9,000	12,000	12,000	12,000	15,000	0	0	0	4,680	22.8	20.6
		66,000	9 + 12 + 12 + 12 + 15	9,900	13,200	13,200	13,200	16,500	0	0	0	5,450	26.6	24.1
5	60	60,000	12 + 12 + 12 + 12 + 12	12,000	12,000	12,000	12,000	12,000	0	0	0	4,680	22.8	20.6
		66,000	12 + 12 + 12 + 12 + 12	13,200	13,200	13,200	13,200	13,200	0	0	0	5,450	26.6	24.1
5	63	60,600	6 + 6 + 6 + 9 + 36	5,800	5,800	5,800	8,700	34,600	0	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 9 + 36	6,200	6,200	6,200	9,300	38,700	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 6 + 6 + 15 + 30	5,800	5,800	5,800	14,400	28,900	0	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 15 + 30	6,300	6,300	6,300	15,700	32,100	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 6 + 9 + 12 + 30	5,800	5,800	8,700	11,500	28,900	0	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 12 + 30	6,300	6,300	9,400	12,500	32,100	0	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	63	60,600	6 + 6 + 9 + 18 + 24	5,800	5,800	8,700	17,300	23,100	0	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 18 + 24	6,300	6,300	9,500	19,000	25,400	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 6 + 12 + 15 + 24	5,800	5,800	11,500	14,400	23,100	0	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 12 + 15 + 24	6,300	6,300	12,700	15,900	25,400	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 9 + 9 + 9 + 30	5,800	8,700	8,700	8,700	28,900	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 9 + 9 + 30	6,300	9,400	9,400	9,400	32,100	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 9 + 9 + 15 + 24	5,800	8,700	8,700	14,400	23,100	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 9 + 15 + 24	6,300	9,500	9,500	15,900	25,400	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 9 + 12 + 12 + 24	5,800	8,700	11,500	11,500	23,100	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 12 + 12 + 24	6,300	9,500	12,700	12,700	25,400	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 9 + 12 + 18 + 18	5,800	8,700	11,500	17,300	17,300	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 12 + 18 + 18	6,300	9,500	12,700	19,000	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 9 + 15 + 15 + 18	5,800	8,700	14,400	14,400	17,300	0	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 15 + 15 + 18	6,300	9,500	15,900	15,900	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 12 + 12 + 15 + 18	5,800	11,500	11,500	14,400	17,300	0	0	0	4,690	22.8	20.6
		66,600	6 + 12 + 12 + 15 + 18	6,300	12,700	12,700	15,900	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	6 + 12 + 15 + 15 + 15	5,800	11,500	14,400	14,400	14,400	0	0	0	4,690	22.8	20.6
		66,600	6 + 12 + 15 + 15 + 15	6,300	12,700	15,900	15,900	15,900	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 9 + 9 + 12 + 24	8,700	8,700	8,700	11,500	23,100	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 12 + 24	9,500	9,500	9,500	12,700	25,400	0	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	63	60,600	9 + 9 + 9 + 18 + 18	8,700	8,700	8,700	17,300	17,300	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 18 + 18	9,500	9,500	9,500	19,000	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 9 + 12 + 15 + 18	8,700	8,700	11,500	14,400	17,300	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 12 + 15 + 18	9,500	9,500	12,700	15,900	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 9 + 15 + 15 + 15	8,700	8,700	14,400	14,400	14,400	0	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 15 + 15 + 15	9,500	9,500	15,900	15,900	15,900	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 12 + 12 + 12 + 18	8,700	11,500	11,500	11,500	17,300	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 12 + 12 + 18	9,500	12,700	12,700	12,700	19,000	0	0	0	5,430	26.5	24.0
5	63	60,600	9 + 12 + 12 + 15 + 15	8,700	11,500	11,500	14,400	14,400	0	0	0	4,690	22.8	20.6
		66,600	9 + 12 + 12 + 15 + 15	9,500	12,700	12,700	15,900	15,900	0	0	0	5,430	26.5	24.0
5	63	60,600	12 + 12 + 12 + 12 + 15	11,500	11,500	11,500	11,500	14,400	0	0	0	4,690	22.8	20.6
		66,600	12 + 12 + 12 + 12 + 15	12,700	12,700	12,700	12,700	15,900	0	0	0	5,430	26.5	24.0
5	66	61,200	6 + 6 + 6 + 12 + 36	5,600	5,600	5,600	11,100	33,400	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 12 + 36	6,000	6,000	6,000	11,900	37,300	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 6 + 6 + 18 + 30	5,600	5,600	5,600	16,700	27,800	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 18 + 30	6,000	6,000	6,000	18,100	31,000	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 6 + 6 + 24 + 24	5,600	5,600	5,600	22,300	22,300	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 24 + 24	6,100	6,100	6,100	24,400	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 6 + 9 + 9 + 36	5,600	5,600	8,300	8,300	33,400	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 9 + 36	6,000	6,000	9,000	9,000	37,300	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	66	61,200	6 + 6 + 9 + 15 + 30	5,600	5,600	8,300	13,900	27,800	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 15 + 30	6,000	6,000	9,100	15,100	31,000	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 6 + 12 + 12 + 30	5,600	5,600	11,100	11,100	27,800	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 12 + 12 + 30	6,000	6,000	12,100	12,100	31,000	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 6 + 12 + 18 + 24	5,600	5,600	11,100	16,700	22,300	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 12 + 18 + 24	6,100	6,100	12,200	18,300	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 6 + 15 + 15 + 24	5,600	5,600	13,900	13,900	22,300	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 15 + 15 + 24	6,100	6,100	15,300	15,300	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 6 + 18 + 18 + 18	5,600	5,600	16,700	16,700	16,700	0	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 18 + 18 + 18	6,100	6,100	18,300	18,300	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 9 + 9 + 12 + 30	5,600	8,300	8,300	11,100	27,800	0	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 12 + 30	6,000	9,100	9,100	12,100	31,000	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 9 + 9 + 18 + 24	5,600	8,300	8,300	16,700	22,300	0	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 18 + 24	6,100	9,200	9,200	18,300	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 9 + 12 + 15 + 24	5,600	8,300	11,100	13,900	22,300	0	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 12 + 15 + 24	6,100	9,200	12,200	15,300	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 9 + 12 + 15 + 24	5,600	8,300	11,100	13,900	22,300	0	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 12 + 15 + 24	6,100	9,200	12,200	15,300	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 9 + 15 + 18 + 18	5,600	8,300	13,900	16,700	16,700	0	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 15 + 18 + 18	6,100	9,200	15,300	18,300	18,300	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	66	61,200	6 + 12 + 12 + 12 + 24	5,600	11,100	11,100	11,100	22,300	0	0	0	4,700	22.8	20.7
		67,200	6 + 12 + 12 + 12 + 24	6,100	12,200	12,200	12,200	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 12 + 12 + 18 + 18	5,600	11,100	11,100	16,700	16,700	0	0	0	4,700	22.8	20.7
		67,200	6 + 12 + 12 + 18 + 18	6,100	12,200	12,200	18,300	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 12 + 15 + 15 + 18	5,600	11,100	13,900	13,900	16,700	0	0	0	4,700	22.8	20.7
		67,200	6 + 12 + 15 + 15 + 18	6,100	12,200	15,300	15,300	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	6 + 15 + 15 + 15 + 15	5,600	13,900	13,900	13,900	13,900	0	0	0	4,700	22.8	20.7
		67,200	6 + 15 + 15 + 15 + 15	6,100	15,300	15,300	15,300	15,300	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 9 + 9 + 30	8,300	8,300	8,300	8,300	27,800	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 30	9,100	9,100	9,100	9,100	31,000	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 9 + 15 + 24	8,300	8,300	8,300	13,900	22,300	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 15 + 24	9,200	9,200	9,200	15,300	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 12 + 12 + 24	8,300	8,300	11,100	11,100	22,300	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 12 + 24	9,200	9,200	12,200	12,200	24,400	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 12 + 18 + 18	8,300	8,300	11,100	16,700	16,700	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 18 + 18	9,200	9,200	12,200	18,300	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 9 + 15 + 15 + 18	8,300	8,300	13,900	13,900	16,700	0	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 15 + 15 + 18	9,200	9,200	15,300	15,300	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	9 + 12 + 12 + 15 + 18	8,300	11,100	11,100	13,900	16,700	0	0	0	4,700	22.8	20.7
		67,200	9 + 12 + 12 + 15 + 18	9,200	12,200	12,200	15,300	18,300	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	66	61,200	9 + 12 + 15 + 15 + 15	8,300	11,100	13,900	13,900	13,900	0	0	0	4,700	22.8	20.7
		67,200	9 + 12 + 15 + 15 + 15	9,200	12,200	15,300	15,300	15,300	0	0	0	5,410	26.4	23.9
5	66	61,200	12 + 12 + 12 + 12 + 18	11,100	11,100	11,100	11,100	16,700	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 12 + 12 + 18	12,200	12,200	12,200	12,200	18,300	0	0	0	5,410	26.4	23.9
5	66	61,200	12 + 12 + 12 + 15 + 15	11,100	11,100	11,100	13,900	13,900	0	0	0	4,700	22.8	20.7
		67,200	12 + 12 + 12 + 15 + 15	12,200	12,200	12,200	15,300	15,300	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 6 + 6 + 15 + 36	5,400	5,400	5,400	13,400	32,200	0	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 15 + 36	5,800	5,800	5,800	14,400	36,100	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 6 + 9 + 12 + 36	5,400	5,400	8,100	10,700	32,200	0	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 12 + 36	5,800	5,800	8,700	11,500	36,100	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 6 + 9 + 18 + 30	5,400	5,400	8,100	16,100	26,900	0	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 18 + 30	5,800	5,800	8,700	17,500	29,900	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 6 + 9 + 24 + 24	5,400	5,400	8,100	21,500	21,500	0	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 24 + 24	5,900	5,900	8,800	23,600	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 6 + 12 + 15 + 30	5,400	5,400	10,700	13,400	26,900	0	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 12 + 15 + 30	5,800	5,800	11,700	14,600	29,900	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 9 + 9 + 9 + 36	5,400	8,100	8,100	8,100	32,200	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 9 + 36	5,800	8,700	8,700	8,700	36,100	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 9 + 9 + 15 + 30	5,400	8,100	8,100	13,400	26,900	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 15 + 30	5,800	8,700	8,700	14,600	29,900	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	69	61,800	6 + 9 + 12 + 12 + 30	5,400	8,100	10,700	10,700	26,900	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 12 + 12 + 30	5,800	8,700	11,700	11,700	29,900	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 9 + 12 + 18 + 24	5,400	8,100	10,700	16,100	21,500	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 12 + 18 + 24	5,900	8,800	11,800	17,700	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 9 + 15 + 15 + 24	5,400	8,100	13,400	13,400	21,500	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 15 + 15 + 24	5,900	8,800	14,700	14,700	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 9 + 18 + 18 + 18	5,400	8,100	16,100	16,100	16,100	0	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 18 + 18 + 18	5,900	8,800	17,700	17,700	17,700	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 12 + 12 + 15 + 24	5,400	10,700	10,700	13,400	21,500	0	0	0	4,700	22.8	20.7
		67,800	6 + 12 + 12 + 15 + 24	5,900	11,800	11,800	14,700	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	6 + 15 + 15 + 15 + 18	5,400	13,400	13,400	13,400	16,100	0	0	0	4,700	22.8	20.7
		67,800	6 + 15 + 15 + 15 + 18	5,900	14,700	14,700	14,700	17,700	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 9 + 9 + 12 + 30	8,100	8,100	8,100	10,700	26,900	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 12 + 30	8,700	8,700	8,700	11,700	29,900	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 9 + 9 + 18 + 24	8,100	8,100	8,100	16,100	21,500	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 18 + 24	8,800	8,800	8,800	17,700	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 9 + 12 + 15 + 24	8,100	8,100	10,700	13,400	21,500	0	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 12 + 15 + 24	8,800	8,800	11,800	14,700	23,600	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 12 + 12 + 12 + 24	8,100	10,700	10,700	10,700	21,500	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 12 + 12 + 24	8,800	11,800	11,800	11,800	23,600	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	69	61,800	9 + 12 + 15 + 15 + 18	8,100	10,700	13,400	13,400	16,100	0	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 15 + 15 + 18	8,800	11,800	14,700	14,700	17,700	0	0	0	5,410	26.4	23.9
5	69	61,800	9 + 15 + 15 + 15 + 15	8,100	13,400	13,400	13,400	13,400	0	0	0	4,700	22.8	20.7
		67,800	9 + 15 + 15 + 15 + 15	8,800	14,700	14,700	14,700	14,700	0	0	0	5,410	26.4	23.9
5	69	61,800	12 + 12 + 12 + 15 + 18	10,700	10,700	10,700	13,400	16,100	0	0	0	4,700	22.8	20.7
		67,800	12 + 12 + 12 + 15 + 18	11,800	11,800	11,800	14,700	17,700	0	0	0	5,410	26.4	23.9
5	69	61,800	12 + 12 + 15 + 15 + 15	10,700	10,700	13,400	13,400	13,400	0	0	0	4,700	22.8	20.7
		67,800	12 + 12 + 15 + 15 + 15	11,800	11,800	14,700	14,700	14,700	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 6 + 6 + 18 + 36	5,200	5,200	5,200	15,600	31,200	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 18 + 36	5,600	5,600	5,600	16,800	34,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 6 + 6 + 24 + 30	5,200	5,200	5,200	20,800	26,000	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 24 + 30	5,600	5,600	5,600	22,600	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 6 + 9 + 15 + 36	5,200	5,200	7,800	13,000	31,200	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 15 + 36	5,600	5,600	8,400	14,000	34,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 6 + 12 + 12 + 36	5,200	5,200	10,400	10,400	31,200	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 12 + 12 + 36	5,600	5,600	11,200	11,200	34,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 6 + 12 + 18 + 30	5,200	5,200	10,400	15,600	26,000	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 12 + 18 + 30	5,600	5,600	11,300	16,900	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 6 + 12 + 24 + 24	5,200	5,200	10,400	20,800	20,800	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 12 + 24 + 24	5,700	5,700	11,400	22,800	22,800	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	72	62,400	6 + 6 + 15 + 15 + 30	5,200	5,200	13,000	13,000	26,000	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 15 + 15 + 30	5,600	5,600	14,100	14,100	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 6 + 18 + 18 + 24	5,200	5,200	15,600	15,600	20,800	0	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 18 + 18 + 24	5,700	5,700	17,100	17,100	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 9 + 9 + 12 + 36	5,200	7,800	7,800	10,400	31,200	0	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 12 + 36	5,600	8,400	8,400	11,200	34,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 9 + 9 + 18 + 30	5,200	7,800	7,800	15,600	26,000	0	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 18 + 30	5,600	8,500	8,500	16,900	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 9 + 12 + 15 + 30	5,200	7,800	10,400	13,000	26,000	0	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 12 + 15 + 30	5,600	8,500	11,300	14,100	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 9 + 12 + 15 + 30	5,200	7,800	10,400	13,000	26,000	0	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 12 + 15 + 30	5,600	8,500	11,300	14,100	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 9 + 15 + 18 + 24	5,200	7,800	13,000	15,600	20,800	0	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 15 + 18 + 24	5,700	8,600	14,300	17,100	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 12 + 12 + 12 + 30	5,200	10,400	10,400	10,400	26,000	0	0	0	4,700	22.8	20.7
		68,400	6 + 12 + 12 + 12 + 30	5,600	11,300	11,300	11,300	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 12 + 12 + 18 + 24	5,200	10,400	10,400	15,600	20,800	0	0	0	4,700	22.8	20.7
		68,400	6 + 12 + 12 + 18 + 24	5,700	11,400	11,400	17,100	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 12 + 15 + 15 + 24	5,200	10,400	13,000	13,000	20,800	0	0	0	4,700	22.8	20.7
		68,400	6 + 12 + 15 + 15 + 24	5,700	11,400	14,300	14,300	22,800	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	72	62,400	6 + 12 + 18 + 18 + 18	5,200	10,400	15,600	15,600	15,600	0	0	0	4,700	22.8	20.7
		68,400	6 + 12 + 18 + 18 + 18	5,700	11,400	17,100	17,100	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 9 + 9 + 36	7,800	7,800	7,800	7,800	31,200	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 36	8,400	8,400	8,400	8,400	34,900	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 9 + 15 + 30	7,800	7,800	7,800	13,000	26,000	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 15 + 30	8,500	8,500	8,500	14,100	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 12 + 12 + 30	7,800	7,800	10,400	10,400	26,000	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 12 + 30	8,500	8,500	11,300	11,300	28,900	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 12 + 18 + 24	7,800	7,800	10,400	15,600	20,800	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 18 + 24	8,600	8,600	11,400	17,100	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 15 + 15 + 24	7,800	7,800	13,000	13,000	20,800	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 15 + 15 + 24	8,600	8,600	14,300	14,300	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 9 + 18 + 18 + 18	7,800	7,800	15,600	15,600	15,600	0	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 18 + 18 + 18	8,600	8,600	17,100	17,100	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 12 + 12 + 15 + 24	7,800	10,400	10,400	13,000	20,800	0	0	0	4,700	22.8	20.7
		68,400	9 + 12 + 12 + 15 + 24	8,600	11,400	11,400	14,300	22,800	0	0	0	5,410	26.4	23.9
5	72	62,400	9 + 15 + 15 + 15 + 18	7,800	13,000	13,000	13,000	15,600	0	0	0	4,700	22.8	20.7
		68,400	9 + 15 + 15 + 15 + 18	8,600	14,300	14,300	14,300	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	12 + 12 + 12 + 12 + 24	10,400	10,400	10,400	10,400	20,800	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 12 + 12 + 24	11,400	11,400	11,400	11,400	22,800	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	72	62,400	12 + 12 + 12 + 18 + 18	10,400	10,400	10,400	15,600	15,600	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 12 + 18 + 18	11,400	11,400	11,400	17,100	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	12 + 12 + 15 + 15 + 18	10,400	10,400	13,000	13,000	15,600	0	0	0	4,700	22.8	20.7
		68,400	12 + 12 + 15 + 15 + 18	11,400	11,400	14,300	14,300	17,100	0	0	0	5,410	26.4	23.9
5	72	62,400	6 + 9 + 9 + 24 + 24	5,200	7,800	7,800	20,800	20,800	0	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 24 + 24	5,700	8,600	8,600	22,800	22,800	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 6 + 9 + 18 + 36	5,000	5,000	7,600	15,100	30,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 18 + 36	5,400	5,400	8,100	16,200	33,800	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 6 + 9 + 24 + 30	5,000	5,000	7,600	20,200	25,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 24 + 30	5,500	5,500	8,200	21,900	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 6 + 12 + 15 + 36	5,000	5,000	10,100	12,600	30,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 12 + 15 + 36	5,400	5,400	10,800	13,500	33,800	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 9 + 9 + 15 + 36	5,000	7,600	7,600	12,600	30,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 15 + 36	5,400	8,100	8,100	13,500	33,800	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 9 + 12 + 12 + 36	5,000	7,600	10,100	10,100	30,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 12 + 12 + 36	5,400	8,100	10,800	10,800	33,800	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 9 + 15 + 15 + 30	5,000	7,600	12,600	12,600	25,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 15 + 15 + 30	5,500	8,200	13,700	13,700	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 9 + 18 + 18 + 24	5,000	7,600	15,100	15,100	20,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 18 + 18 + 24	5,500	8,300	16,600	16,600	22,100	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	75	63,000	6 + 12 + 12 + 15 + 30	5,000	10,100	10,100	12,600	25,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 12 + 12 + 15 + 30	5,500	10,900	10,900	13,700	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 15 + 15 + 15 + 24	5,000	12,600	12,600	12,600	20,200	0	0	0	4,700	22.8	20.7
		69,000	6 + 15 + 15 + 15 + 24	5,500	13,800	13,800	13,800	22,100	0	0	0	5,410	26.4	23.9
5	75	63,000	6 + 15 + 18 + 18 + 18	5,000	12,600	15,100	15,100	15,100	0	0	0	4,700	22.8	20.7
		69,000	6 + 15 + 18 + 18 + 18	5,500	13,800	16,600	16,600	16,600	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 9 + 12 + 36	7,600	7,600	7,600	10,100	30,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 36	8,100	8,100	8,100	10,800	33,800	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 9 + 18 + 30	7,600	7,600	7,600	15,100	25,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 18 + 30	8,200	8,200	8,200	16,400	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 9 + 24 + 24	7,600	7,600	7,600	20,200	20,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 24 + 24	8,300	8,300	8,300	22,100	22,100	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 9 + 12 + 15 + 30	7,600	7,600	10,100	12,600	25,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 12 + 15 + 30	8,200	8,200	10,900	13,700	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 12 + 12 + 12 + 30	7,600	10,100	10,100	10,100	25,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 12 + 12 + 30	8,200	10,900	10,900	10,900	28,000	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 12 + 15 + 15 + 24	7,600	10,100	12,600	12,600	20,200	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 15 + 15 + 24	8,300	11,000	13,800	13,800	22,100	0	0	0	5,410	26.4	23.9
5	75	63,000	9 + 12 + 18 + 18 + 18	7,600	10,100	15,100	15,100	15,100	0	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 18 + 18 + 18	8,300	11,000	16,600	16,600	16,600	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	75	63,000	9 + 15 + 15 + 18 + 18	7,600	12,600	12,600	15,100	15,100	0	0	0	4,700	22.8	20.7
		69,000	9 + 15 + 15 + 18 + 18	8,300	13,800	13,800	16,600	16,600	0	0	0	5,410	26.4	23.9
5	75	63,000	12 + 12 + 12 + 15 + 24	10,100	10,100	10,100	12,600	20,200	0	0	0	4,700	22.8	20.7
		69,000	12 + 12 + 12 + 15 + 24	11,000	11,000	11,000	13,800	22,100	0	0	0	5,410	26.4	23.9
5	75	63,000	12 + 12 + 15 + 18 + 18	10,100	10,100	12,600	15,100	15,100	0	0	0	4,700	22.8	20.7
		69,000	12 + 12 + 15 + 18 + 18	11,000	11,000	13,800	16,600	16,600	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 6 + 6 + 24 + 36	4,900	4,900	4,900	19,600	29,400	0	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 24 + 36	5,300	5,300	5,300	21,000	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 6 + 6 + 30 + 30	4,900	4,900	4,900	24,500	24,500	0	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 30 + 30	5,300	5,300	5,300	26,900	26,900	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 6 + 12 + 18 + 36	4,900	4,900	9,800	14,700	29,400	0	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 12 + 18 + 36	5,300	5,300	10,500	15,800	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 6 + 12 + 24 + 30	4,900	4,900	9,800	19,600	24,500	0	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 12 + 24 + 30	5,300	5,300	10,600	21,200	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 6 + 15 + 15 + 36	4,900	4,900	12,200	12,200	29,400	0	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 15 + 15 + 36	5,300	5,300	13,100	13,100	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 6 + 18 + 18 + 30	4,900	4,900	14,700	14,700	24,500	0	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 18 + 18 + 30	5,300	5,300	15,900	15,900	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 9 + 9 + 18 + 36	4,900	7,300	7,300	14,700	29,400	0	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 18 + 36	5,300	7,900	7,900	15,800	32,800	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	78	63,600	6 + 9 + 12 + 15 + 36	4,900	7,300	9,800	12,200	29,400	0	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 12 + 15 + 36	5,300	7,900	10,500	13,100	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 12 + 18 + 30	7,300	7,300	9,800	14,700	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 18 + 30	8,000	8,000	10,600	15,900	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 9 + 15 + 18 + 30	4,900	7,300	12,200	14,700	24,500	0	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 15 + 18 + 30	5,300	8,000	13,300	15,900	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 9 + 15 + 24 + 24	4,900	7,300	12,200	19,600	19,600	0	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 15 + 24 + 24	5,400	8,000	13,400	21,400	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 12 + 12 + 12 + 36	4,900	9,800	9,800	9,800	29,400	0	0	0	4,690	22.8	20.6
		69,600	6 + 12 + 12 + 12 + 36	5,300	10,500	10,500	10,500	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 12 + 12 + 18 + 30	4,900	9,800	9,800	14,700	24,500	0	0	0	4,690	22.8	20.6
		69,600	6 + 12 + 12 + 18 + 30	5,300	10,600	10,600	15,900	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 12 + 15 + 15 + 30	4,900	9,800	12,200	12,200	24,500	0	0	0	4,690	22.8	20.6
		69,600	6 + 12 + 15 + 15 + 30	5,300	10,600	13,300	13,300	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 12 + 18 + 18 + 24	4,900	9,800	14,700	14,700	19,600	0	0	0	4,690	22.8	20.6
		69,600	6 + 12 + 18 + 18 + 24	5,400	10,700	16,100	16,100	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	6 + 18 + 18 + 18 + 18	4,900	14,700	14,700	14,700	14,700	0	0	0	4,690	22.8	20.6
		69,600	6 + 18 + 18 + 18 + 18	5,400	16,100	16,100	16,100	16,100	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 9 + 15 + 36	7,300	7,300	7,300	12,200	29,400	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 15 + 36	7,900	7,900	7,900	13,100	32,800	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	78	63,600	9 + 9 + 12 + 12 + 36	7,300	7,300	9,800	9,800	29,400	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 12 + 36	7,900	7,900	10,500	10,500	32,800	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 12 + 18 + 30	7,300	7,300	9,800	14,700	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 18 + 30	8,000	8,000	10,600	15,900	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 12 + 24 + 24	7,300	7,300	9,800	19,600	19,600	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 24 + 24	8,000	8,000	10,700	21,400	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 15 + 15 + 30	7,300	7,300	12,200	12,200	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 15 + 15 + 30	8,000	8,000	13,300	13,300	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 9 + 18 + 18 + 24	7,300	7,300	14,700	14,700	19,600	0	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 18 + 18 + 24	8,000	8,000	16,100	16,100	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 12 + 12 + 15 + 30	7,300	9,800	9,800	12,200	24,500	0	0	0	4,690	22.8	20.6
		69,600	9 + 12 + 12 + 15 + 30	8,000	10,600	10,600	13,300	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 15 + 15 + 15 + 24	7,300	12,200	12,200	12,200	19,600	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 15 + 15 + 24	8,000	13,400	13,400	13,400	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	9 + 15 + 18 + 18 + 18	7,300	12,200	14,700	14,700	14,700	0	0	0	4,690	22.8	20.6
		69,600	9 + 15 + 18 + 18 + 18	8,000	13,400	16,100	16,100	16,100	0	0	0	5,410	26.4	23.9
5	78	63,600	12 + 12 + 12 + 12 + 30	9,800	9,800	9,800	9,800	24,500	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 12 + 12 + 30	10,600	10,600	10,600	10,600	27,200	0	0	0	5,410	26.4	23.9
5	78	63,600	12 + 12 + 12 + 18 + 24	9,800	9,800	9,800	14,700	19,600	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 12 + 18 + 24	10,700	10,700	10,700	16,100	21,400	0	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	78	63,600	12 + 12 + 15 + 15 + 24	9,800	9,800	12,200	12,200	19,600	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 15 + 15 + 24	10,700	10,700	13,400	13,400	21,400	0	0	0	5,410	26.4	23.9
5	78	63,600	12 + 12 + 18 + 18 + 18	9,800	9,800	14,700	14,700	14,700	0	0	0	4,690	22.8	20.6
		69,600	12 + 12 + 18 + 18 + 18	10,700	10,700	16,100	16,100	16,100	0	0	0	5,410	26.4	23.9
6	36	36,000	6 + 6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	6,000	0	0	3,560	17.3	15.7
		40,000	6 + 6 + 6 + 6 + 6 + 6	6,700	6,700	6,700	6,700	6,700	6,700	0	0	3,499	17.1	15.4
6	39	39,000	6 + 6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	6,000	9,000	0	0	3,790	18.4	16.7
		43,200	6 + 6 + 6 + 6 + 6 + 9	6,600	6,600	6,600	6,600	6,600	10,000	0	0	3,743	18.3	16.5
6	42	42,000	6 + 6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	6,000	12,000	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 6 + 6 + 12	6,600	6,600	6,600	6,600	6,600	13,300	0	0	3,987	19.5	17.6
6	42	42,000	6 + 6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	6,000	9,000	9,000	0	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 6 + 9 + 9	6,600	6,600	6,600	6,600	10,000	10,000	0	0	3,987	19.5	17.6
6	45	45,000	6 + 6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	6,000	15,000	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 6 + 6 + 6 + 15	6,600	6,600	6,600	6,600	6,600	16,600	0	0	4,231	20.6	18.7
6	45	45,000	6 + 6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	6,000	9,000	12,000	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 6 + 6 + 9 + 12	6,600	6,600	6,600	6,600	10,000	13,300	0	0	4,231	20.6	18.7
6	45	45,000	6 + 6 + 6 + 9 + 9 + 9	6,000	6,000	6,000	9,000	9,000	9,000	0	0	4,180	20.3	18.4
		49,800	6 + 6 + 6 + 9 + 9 + 9	6,600	6,600	6,600	10,000	10,000	10,000	0	0	4,231	20.6	18.7
6	48	48,000	6 + 6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	6,000	18,000	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 6 + 6 + 18	6,600	6,600	6,600	6,600	6,600	19,900	0	0	4,474	21.8	19.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	48	48,000	6 + 6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	6,000	9,000	15,000	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 6 + 9 + 15	6,600	6,600	6,600	6,600	10,000	16,600	0	0	4,474	21.8	19.8
6	48	48,000	6 + 6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	6,000	12,000	12,000	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 6 + 12 + 12	6,600	6,600	6,600	6,600	13,300	13,300	0	0	4,474	21.8	19.8
6	48	48,000	6 + 6 + 6 + 9 + 9 + 12	6,000	6,000	6,000	9,000	9,000	12,000	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 9 + 9 + 12	6,600	6,600	6,600	10,000	10,000	13,300	0	0	4,474	21.8	19.8
6	48	48,000	6 + 6 + 9 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	9,000	0	0	4,340	21.1	19.1
		53,100	6 + 6 + 9 + 9 + 9 + 9	6,600	6,600	10,000	10,000	10,000	10,000	0	0	4,474	21.8	19.8
6	51	51,000	6 + 6 + 6 + 6 + 9 + 18	6,000	6,000	6,000	6,000	9,000	18,000	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 6 + 9 + 18	6,600	6,600	6,600	6,600	10,000	19,900	0	0	4,718	23.0	20.8
6	51	51,000	6 + 6 + 6 + 6 + 12 + 15	6,000	6,000	6,000	6,000	12,000	15,000	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 6 + 12 + 15	6,600	6,600	6,600	6,600	13,300	16,600	0	0	4,718	23.0	20.8
6	51	51,000	6 + 6 + 6 + 9 + 9 + 15	6,000	6,000	6,000	9,000	9,000	15,000	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 9 + 9 + 15	6,600	6,600	6,600	10,000	10,000	16,600	0	0	4,718	23.0	20.8
6	51	51,000	6 + 6 + 6 + 9 + 12 + 12	6,000	6,000	6,000	9,000	12,000	12,000	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 9 + 12 + 12	6,600	6,600	6,600	10,000	13,300	13,300	0	0	4,718	23.0	20.8
6	51	51,000	6 + 6 + 9 + 9 + 9 + 12	6,000	6,000	9,000	9,000	9,000	12,000	0	0	4,480	21.8	19.7
		56,400	6 + 6 + 9 + 9 + 9 + 12	6,600	6,600	10,000	10,000	10,000	13,300	0	0	4,718	23.0	20.8
6	51	51,000	6 + 9 + 9 + 9 + 9 + 9	6,000	9,000	9,000	9,000	9,000	9,000	0	0	4,480	21.8	19.7
		56,400	6 + 9 + 9 + 9 + 9 + 9	6,600	10,000	10,000	10,000	10,000	10,000	0	0	4,718	23.0	20.8

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	54	54,000	6 + 6 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	6,000	24,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 6 + 24	6,600	6,600	6,600	6,600	6,600	26,500	0	0	4,962	24.2	21.9
6	54	54,000	6 + 6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	6,000	12,000	18,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 12 + 18	6,600	6,600	6,600	6,600	13,300	19,900	0	0	4,962	24.2	21.9
6	54	54,000	6 + 6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	6,000	15,000	15,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 15 + 15	6,600	6,600	6,600	6,600	16,600	16,600	0	0	4,962	24.2	21.9
6	54	54,000	6 + 6 + 6 + 9 + 9 + 18	6,000	6,000	6,000	9,000	9,000	18,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 9 + 9 + 18	6,600	6,600	6,600	10,000	10,000	19,900	0	0	4,962	24.2	21.9
6	54	54,000	6 + 6 + 6 + 9 + 12 + 15	6,000	6,000	6,000	9,000	12,000	15,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 9 + 12 + 15	6,600	6,600	6,600	10,000	13,300	16,600	0	0	4,962	24.2	21.9
6	54	54,000	6 + 6 + 6 + 12 + 12 + 12	6,000	6,000	6,000	12,000	12,000	12,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 12 + 12 + 12	6,600	6,600	6,600	13,300	13,300	13,300	0	0	4,962	24.2	21.9
6	54	54,000	6 + 6 + 9 + 9 + 9 + 15	6,000	6,000	9,000	9,000	9,000	15,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 9 + 9 + 9 + 15	6,600	6,600	10,000	10,000	10,000	16,600	0	0	4,962	24.2	21.9
6	54	54,000	6 + 6 + 9 + 9 + 12 + 12	6,000	6,000	9,000	9,000	12,000	12,000	0	0	4,580	22.3	20.1
		59,700	6 + 6 + 9 + 9 + 12 + 12	6,600	6,600	10,000	10,000	13,300	13,300	0	0	4,962	24.2	21.9
6	54	54,000	6 + 9 + 9 + 9 + 9 + 12	6,000	9,000	9,000	9,000	9,000	12,000	0	0	4,580	22.3	20.1
		59,700	6 + 9 + 9 + 9 + 9 + 12	6,600	10,000	10,000	10,000	10,000	13,300	0	0	4,962	24.2	21.9
6	54	54,000	9 + 9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	9,000	0	0	4,580	22.3	20.1
		59,700	9 + 9 + 9 + 9 + 9 + 9	10,000	10,000	10,000	10,000	10,000	10,000	0	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	57	57,000	6 + 6 + 6 + 6 + 9 + 24	6,000	6,000	6,000	6,000	9,000	24,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 9 + 24	6,600	6,600	6,600	6,600	9,900	26,500	0	0	5,206	25.4	23.0
6	57	57,000	6 + 6 + 6 + 6 + 15 + 18	6,000	6,000	6,000	6,000	15,000	18,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 15 + 18	6,600	6,600	6,600	6,600	16,600	19,900	0	0	5,206	25.4	23.0
6	57	57,000	6 + 6 + 6 + 9 + 12 + 18	6,000	6,000	6,000	9,000	12,000	18,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 9 + 12 + 18	6,600	6,600	6,600	9,900	13,300	19,900	0	0	5,206	25.4	23.0
6	57	57,000	6 + 6 + 6 + 9 + 15 + 15	6,000	6,000	6,000	9,000	15,000	15,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 9 + 15 + 15	6,600	6,600	6,600	9,900	16,600	16,600	0	0	5,206	25.4	23.0
6	57	57,000	6 + 6 + 6 + 12 + 12 + 15	6,000	6,000	6,000	12,000	12,000	15,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 12 + 12 + 15	6,600	6,600	6,600	13,300	13,300	16,600	0	0	5,206	25.4	23.0
6	57	57,000	6 + 6 + 9 + 9 + 9 + 18	6,000	6,000	9,000	9,000	9,000	18,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 9 + 9 + 9 + 18	6,600	6,600	9,900	9,900	9,900	19,900	0	0	5,206	25.4	23.0
6	57	57,000	6 + 6 + 9 + 9 + 12 + 15	6,000	6,000	9,000	9,000	12,000	15,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 9 + 9 + 12 + 15	6,600	6,600	9,900	9,900	13,300	16,600	0	0	5,206	25.4	23.0
6	57	57,000	6 + 6 + 9 + 12 + 12 + 12	6,000	6,000	9,000	12,000	12,000	12,000	0	0	4,630	22.5	20.4
		63,000	6 + 6 + 9 + 12 + 12 + 12	6,600	6,600	9,900	13,300	13,300	13,300	0	0	5,206	25.4	23.0
6	57	57,000	6 + 9 + 9 + 9 + 9 + 15	6,000	9,000	9,000	9,000	9,000	15,000	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 9 + 9 + 9 + 15	6,600	9,900	9,900	9,900	9,900	16,600	0	0	5,206	25.4	23.0
6	57	57,000	6 + 9 + 9 + 9 + 12 + 12	6,000	9,000	9,000	9,000	12,000	12,000	0	0	4,630	22.5	20.4
		63,000	6 + 9 + 9 + 9 + 12 + 12	6,600	9,900	9,900	9,900	13,300	13,300	0	0	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	57	57,000	9 + 9 + 9 + 9 + 9 + 12	9,000	9,000	9,000	9,000	9,000	12,000	0	0	4,630	22.5	20.4
		63,000	9 + 9 + 9 + 9 + 9 + 12	9,900	9,900	9,900	9,900	9,900	13,300	0	0	5,206	25.4	23.0
6	60	60,000	6 + 6 + 6 + 6 + 6 + 30	6,000	6,000	6,000	6,000	6,000	30,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 30	6,500	6,500	6,500	6,500	6,500	33,400	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 6 + 6 + 12 + 24	6,000	6,000	6,000	6,000	12,000	24,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 12 + 24	6,600	6,600	6,600	6,600	13,200	26,400	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 6 + 6 + 18 + 18	6,000	6,000	6,000	6,000	18,000	18,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 18 + 18	6,600	6,600	6,600	6,600	19,800	19,800	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 6 + 9 + 9 + 24	6,000	6,000	6,000	9,000	9,000	24,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 9 + 9 + 24	6,600	6,600	6,600	9,900	9,900	26,400	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 6 + 9 + 15 + 18	6,000	6,000	6,000	9,000	15,000	18,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 9 + 15 + 18	6,600	6,600	6,600	9,900	16,500	19,800	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 6 + 12 + 12 + 18	6,000	6,000	6,000	12,000	12,000	18,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 12 + 12 + 18	6,600	6,600	6,600	13,200	13,200	19,800	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 6 + 12 + 15 + 15	6,000	6,000	6,000	12,000	15,000	15,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 12 + 15 + 15	6,600	6,600	6,600	13,200	16,500	16,500	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 9 + 9 + 12 + 18	6,000	6,000	9,000	9,000	12,000	18,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 9 + 9 + 12 + 18	6,600	6,600	9,900	9,900	13,200	19,800	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 9 + 9 + 15 + 15	6,000	6,000	9,000	9,000	15,000	15,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 9 + 9 + 15 + 15	6,600	6,600	9,900	9,900	16,500	16,500	0	0	5,450	26.6	24.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	60	60,000	6 + 6 + 9 + 12 + 12 + 15	6,000	6,000	9,000	12,000	12,000	15,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 9 + 12 + 12 + 15	6,600	6,600	9,900	13,200	13,200	16,500	0	0	5,450	26.6	24.1
6	60	60,000	6 + 6 + 12 + 12 + 12 + 12	6,000	6,000	12,000	12,000	12,000	12,000	0	0	4,680	22.8	20.6
		66,000	6 + 6 + 12 + 12 + 12 + 12	6,600	6,600	13,200	13,200	13,200	13,200	0	0	5,450	26.6	24.1
6	60	60,000	6 + 9 + 9 + 9 + 9 + 18	6,000	9,000	9,000	9,000	9,000	18,000	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 9 + 9 + 9 + 18	6,600	9,900	9,900	9,900	9,900	19,800	0	0	5,450	26.6	24.1
6	60	60,000	6 + 9 + 9 + 9 + 12 + 15	6,000	9,000	9,000	9,000	12,000	15,000	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 9 + 9 + 12 + 15	6,600	9,900	9,900	9,900	13,200	16,500	0	0	5,450	26.6	24.1
6	60	60,000	6 + 9 + 9 + 12 + 12 + 12	6,000	9,000	9,000	12,000	12,000	12,000	0	0	4,680	22.8	20.6
		66,000	6 + 9 + 9 + 12 + 12 + 12	6,600	9,900	9,900	13,200	13,200	13,200	0	0	5,450	26.6	24.1
6	60	60,000	9 + 9 + 9 + 9 + 9 + 15	9,000	9,000	9,000	9,000	9,000	15,000	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 9 + 9 + 15	9,900	9,900	9,900	9,900	9,900	16,500	0	0	5,450	26.6	24.1
6	60	60,000	9 + 9 + 9 + 9 + 12 + 12	9,000	9,000	9,000	9,000	12,000	12,000	0	0	4,680	22.8	20.6
		66,000	9 + 9 + 9 + 9 + 12 + 12	9,900	9,900	9,900	9,900	13,200	13,200	0	0	5,450	26.6	24.1
6	63	60,600	6 + 6 + 6 + 6 + 9 + 30	5,800	5,800	5,800	5,800	8,700	28,900	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 9 + 30	6,300	6,300	6,300	6,300	9,400	32,100	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 6 + 6 + 15 + 24	5,800	5,800	5,800	5,800	14,400	23,100	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 15 + 24	6,300	6,300	6,300	6,300	15,900	25,400	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 6 + 9 + 12 + 24	5,800	5,800	5,800	8,700	11,500	23,100	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 9 + 12 + 24	6,300	6,300	6,300	9,500	12,700	25,400	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	63	60,600	6 + 6 + 6 + 9 + 18 + 18	5,800	5,800	5,800	8,700	17,300	17,300	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 9 + 18 + 18	6,300	6,300	6,300	9,500	19,000	19,000	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 6 + 12 + 15 + 18	5,800	5,800	5,800	11,500	14,400	17,300	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 12 + 15 + 18	6,300	6,300	6,300	12,700	15,900	19,000	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 6 + 15 + 15 + 15	5,800	5,800	5,800	14,400	14,400	14,400	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 15 + 15 + 15	6,300	6,300	6,300	15,900	15,900	15,900	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 9 + 9 + 9 + 24	5,800	5,800	8,700	8,700	8,700	23,100	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 9 + 9 + 24	6,300	6,300	9,500	9,500	9,500	25,400	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 9 + 9 + 15 + 18	5,800	5,800	8,700	8,700	14,400	17,300	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 9 + 15 + 18	6,300	6,300	9,500	9,500	15,900	19,000	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 9 + 12 + 12 + 18	5,800	5,800	8,700	11,500	11,500	17,300	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 12 + 12 + 18	6,300	6,300	9,500	12,700	12,700	19,000	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 12 + 12 + 12 + 15	5,800	5,800	11,500	11,500	11,500	14,400	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 12 + 12 + 12 + 15	6,300	6,300	12,700	12,700	12,700	15,900	0	0	5,430	26.5	24.0
6	63	60,600	6 + 9 + 9 + 9 + 12 + 18	5,800	8,700	8,700	8,700	11,500	17,300	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 9 + 9 + 12 + 18	6,300	9,500	9,500	9,500	12,700	19,000	0	0	5,430	26.5	24.0
6	63	60,600	6 + 9 + 9 + 9 + 15 + 15	5,800	8,700	8,700	8,700	14,400	14,400	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 9 + 9 + 15 + 15	6,300	9,500	9,500	9,500	15,900	15,900	0	0	5,430	26.5	24.0
6	63	60,600	6 + 9 + 9 + 12 + 12 + 15	5,800	8,700	8,700	11,500	11,500	14,400	0	0	4,690	22.8	20.6
		66,600	6 + 9 + 9 + 12 + 12 + 15	6,300	9,500	9,500	12,700	12,700	15,900	0	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	63	60,600	9 + 9 + 9 + 9 + 9 + 18	8,700	8,700	8,700	8,700	8,700	17,300	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 9 + 9 + 18	9,500	9,500	9,500	9,500	9,500	19,000	0	0	5,430	26.5	24.0
6	63	60,600	9 + 9 + 9 + 9 + 12 + 15	8,700	8,700	8,700	8,700	11,500	14,400	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 9 + 12 + 15	9,500	9,500	9,500	9,500	12,700	15,900	0	0	5,430	26.5	24.0
6	63	60,600	9 + 9 + 9 + 12 + 12 + 12	8,700	8,700	8,700	11,500	11,500	11,500	0	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 12 + 12 + 12	9,500	9,500	9,500	12,700	12,700	12,700	0	0	5,430	26.5	24.0
6	63	60,600	6 + 6 + 9 + 12 + 15 + 15	5,800	5,800	8,700	11,500	14,400	14,400	0	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 12 + 15 + 15	6,300	6,300	9,500	12,700	15,900	15,900	0	0	5,430	26.5	24.0
6	66	61,200	6 + 6 + 6 + 6 + 6 + 36	5,600	5,600	5,600	5,600	5,600	33,400	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 36	6,000	6,000	6,000	6,000	6,000	37,300	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 6 + 6 + 12 + 30	5,600	5,600	5,600	5,600	11,100	27,800	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 12 + 30	6,000	6,000	6,000	6,000	12,100	31,000	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 6 + 6 + 18 + 24	5,600	5,600	5,600	5,600	16,700	22,300	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 18 + 24	6,100	6,100	6,100	6,100	18,300	24,400	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 6 + 9 + 9 + 30	5,600	5,600	5,600	8,300	8,300	27,800	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 9 + 9 + 30	6,000	6,000	6,000	9,100	9,100	31,000	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 6 + 9 + 15 + 24	5,600	5,600	5,600	8,300	13,900	22,300	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 9 + 15 + 24	6,100	6,100	6,100	9,200	15,300	24,400	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 6 + 12 + 12 + 24	5,600	5,600	5,600	11,100	11,100	22,300	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 12 + 12 + 24	6,100	6,100	6,100	12,200	12,200	24,400	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	66	61,200	6 + 6 + 6 + 15 + 15 + 18	5,600	5,600	5,600	13,900	13,900	16,700	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 15 + 15 + 18	6,100	6,100	6,100	15,300	15,300	18,300	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 9 + 9 + 12 + 24	5,600	5,600	8,300	8,300	11,100	22,300	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 9 + 12 + 24	6,100	6,100	9,200	9,200	12,200	24,400	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 9 + 15 + 15 + 15	5,600	5,600	8,300	13,900	13,900	13,900	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 15 + 15 + 15	6,100	6,100	9,200	15,300	15,300	15,300	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 12 + 12 + 12 + 18	5,600	5,600	11,100	11,100	11,100	16,700	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 12 + 12 + 12 + 18	6,100	6,100	12,200	12,200	12,200	18,300	0	0	5,410	26.4	23.9
6	66	61,200	6 + 6 + 12 + 12 + 15 + 15	5,600	5,600	11,100	11,100	13,900	13,900	0	0	4,700	22.8	20.7
		67,200	6 + 6 + 12 + 12 + 15 + 15	6,100	6,100	12,200	12,200	15,300	15,300	0	0	5,410	26.4	23.9
6	66	61,200	6 + 9 + 9 + 9 + 9 + 24	5,600	8,300	8,300	8,300	8,300	22,300	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 9 + 9 + 24	6,100	9,200	9,200	9,200	9,200	24,400	0	0	5,410	26.4	23.9
6	66	61,200	6 + 9 + 9 + 9 + 15 + 18	5,600	8,300	8,300	8,300	13,900	16,700	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 9 + 15 + 18	6,100	9,200	9,200	9,200	15,300	18,300	0	0	5,410	26.4	23.9
6	66	61,200	6 + 9 + 9 + 12 + 12 + 18	5,600	8,300	8,300	11,100	11,100	16,700	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 12 + 12 + 18	6,100	9,200	9,200	12,200	12,200	18,300	0	0	5,410	26.4	23.9
6	66	61,200	6 + 9 + 9 + 12 + 15 + 15	5,600	8,300	8,300	11,100	13,900	13,900	0	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 12 + 15 + 15	6,100	9,200	9,200	12,200	15,300	15,300	0	0	5,410	26.4	23.9
6	66	61,200	9 + 9 + 9 + 9 + 12 + 18	8,300	8,300	8,300	8,300	11,100	16,700	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 12 + 18	9,200	9,200	9,200	9,200	12,200	18,300	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	66	61,200	9 + 9 + 9 + 9 + 15 + 15	8,300	8,300	8,300	8,300	13,900	13,900	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 15 + 15	9,200	9,200	9,200	9,200	15,300	15,300	0	0	5,410	26.4	23.9
6	66	61,200	9 + 9 + 9 + 12 + 12 + 15	8,300	8,300	8,300	11,100	11,100	13,900	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 12 + 12 + 15	9,200	9,200	9,200	12,200	12,200	15,300	0	0	5,410	26.4	23.9
6	66	61,200	9 + 9 + 12 + 12 + 12 + 12	8,300	8,300	11,100	11,100	11,100	11,100	0	0	4,700	22.8	20.7
		67,200	9 + 9 + 12 + 12 + 12 + 12	9,200	9,200	12,200	12,200	12,200	12,200	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 6 + 6 + 9 + 36	5,400	5,400	5,400	5,400	8,100	32,200	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 9 + 36	5,800	5,800	5,800	5,800	8,700	36,100	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 6 + 6 + 15 + 30	5,400	5,400	5,400	5,400	13,400	26,900	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 15 + 30	5,800	5,800	5,800	5,800	14,600	29,900	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 6 + 9 + 12 + 30	5,400	5,400	5,400	8,100	10,700	26,900	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 9 + 12 + 30	5,800	5,800	5,800	8,700	11,700	29,900	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 6 + 9 + 18 + 24	5,400	5,400	5,400	8,100	16,100	21,500	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 9 + 18 + 24	5,900	5,900	5,900	8,800	17,700	23,600	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 6 + 12 + 15 + 24	5,400	5,400	5,400	10,700	13,400	21,500	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 12 + 15 + 24	5,900	5,900	5,900	11,800	14,700	23,600	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 9 + 9 + 9 + 30	5,400	5,400	8,100	8,100	8,100	26,900	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 9 + 9 + 30	5,800	5,800	8,700	8,700	8,700	29,900	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 9 + 9 + 15 + 24	5,400	5,400	8,100	8,100	13,400	21,500	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 9 + 15 + 24	5,900	5,900	8,800	8,800	14,700	23,600	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	69	61,800	6 + 6 + 9 + 12 + 12 + 24	5,400	5,400	8,100	10,700	10,700	21,500	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 12 + 12 + 24	5,900	5,900	8,800	11,800	11,800	23,600	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 9 + 15 + 15 + 18	5,400	5,400	8,100	13,400	13,400	16,100	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 15 + 15 + 18	5,900	5,900	8,800	14,700	14,700	17,700	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 12 + 12 + 15 + 18	5,400	5,400	10,700	10,700	13,400	16,100	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 12 + 12 + 15 + 18	5,900	5,900	11,800	11,800	14,700	17,700	0	0	5,410	26.4	23.9
6	69	61,800	6 + 6 + 12 + 15 + 15 + 15	5,400	5,400	10,700	13,400	13,400	13,400	0	0	4,700	22.8	20.7
		67,800	6 + 6 + 12 + 15 + 15 + 15	5,900	5,900	11,800	14,700	14,700	14,700	0	0	5,410	26.4	23.9
6	69	61,800	6 + 9 + 9 + 9 + 12 + 24	5,400	8,100	8,100	8,100	10,700	21,500	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 9 + 12 + 24	5,900	8,800	8,800	8,800	11,800	23,600	0	0	5,410	26.4	23.9
6	69	61,800	6 + 9 + 9 + 9 + 18 + 18	5,400	8,100	8,100	8,100	16,100	16,100	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 9 + 18 + 18	5,900	8,800	8,800	8,800	17,700	17,700	0	0	5,410	26.4	23.9
6	69	61,800	6 + 9 + 9 + 12 + 15 + 18	5,400	8,100	8,100	10,700	13,400	16,100	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 12 + 15 + 18	5,900	8,800	8,800	11,800	14,700	17,700	0	0	5,410	26.4	23.9
6	69	61,800	6 + 9 + 9 + 15 + 15 + 15	5,400	8,100	8,100	13,400	13,400	13,400	0	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 15 + 15 + 15	5,900	8,800	8,800	14,700	14,700	14,700	0	0	5,410	26.4	23.9
6	69	61,800	9 + 9 + 9 + 9 + 9 + 24	8,100	8,100	8,100	8,100	8,100	21,500	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 9 + 24	8,800	8,800	8,800	8,800	8,800	23,600	0	0	5,410	26.4	23.9
6	69	61,800	9 + 9 + 9 + 9 + 15 + 18	8,100	8,100	8,100	8,100	13,400	16,100	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 15 + 18	8,800	8,800	8,800	8,800	14,700	17,700	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	69	61,800	9 + 9 + 9 + 12 + 12 + 18	8,100	8,100	8,100	10,700	10,700	16,100	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 12 + 12 + 18	8,800	8,800	8,800	11,800	11,800	17,700	0	0	5,410	26.4	23.9
6	69	61,800	9 + 9 + 12 + 12 + 12 + 15	8,100	8,100	10,700	10,700	10,700	13,400	0	0	4,700	22.8	20.7
		67,800	9 + 9 + 12 + 12 + 12 + 15	8,800	8,800	11,800	11,800	11,800	14,700	0	0	5,410	26.4	23.9
6	69	61,800	9 + 12 + 12 + 12 + 12 + 12	8,100	10,700	10,700	10,700	10,700	10,700	0	0	4,700	22.8	20.7
		67,800	9 + 12 + 12 + 12 + 12 + 12	8,800	11,800	11,800	11,800	11,800	11,800	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 6 + 6 + 12 + 36	5,200	5,200	5,200	5,200	10,400	31,200	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 12 + 36	5,600	5,600	5,600	5,600	11,200	34,900	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 6 + 6 + 18 + 30	5,200	5,200	5,200	5,200	15,600	26,000	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 18 + 30	5,600	5,600	5,600	5,600	16,900	28,900	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 6 + 6 + 24 + 24	5,200	5,200	5,200	5,200	20,800	20,800	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 24 + 24	5,700	5,700	5,700	5,700	22,800	22,800	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 6 + 9 + 9 + 36	5,200	5,200	5,200	7,800	7,800	31,200	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 9 + 36	5,600	5,600	5,600	8,400	8,400	34,900	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 6 + 9 + 15 + 30	5,200	5,200	5,200	7,800	13,000	26,000	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 15 + 30	5,600	5,600	5,600	8,500	14,100	28,900	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 6 + 12 + 12 + 30	5,200	5,200	5,200	10,400	10,400	26,000	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 12 + 12 + 30	5,600	5,600	5,600	11,300	11,300	28,900	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 6 + 15 + 15 + 24	5,200	5,200	5,200	13,000	13,000	20,800	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 15 + 15 + 24	5,700	5,700	5,700	14,300	14,300	22,800	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	72	62,400	6 + 6 + 6 + 18 + 18 + 18	5,200	5,200	5,200	15,600	15,600	15,600	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 18 + 18 + 18	5,700	5,700	5,700	17,100	17,100	17,100	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 9 + 9 + 12 + 30	5,200	5,200	7,800	7,800	10,400	26,000	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 9 + 12 + 30	5,600	5,600	8,500	8,500	11,300	28,900	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 12 + 12 + 12 + 24	5,200	5,200	10,400	10,400	10,400	20,800	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 12 + 12 + 12 + 24	5,700	5,700	11,400	11,400	11,400	22,800	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 12 + 15 + 15 + 18	5,200	5,200	10,400	13,000	13,000	15,600	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 12 + 15 + 15 + 18	5,700	5,700	11,400	14,300	14,300	17,100	0	0	5,410	26.4	23.9
6	72	62,400	6 + 6 + 15 + 15 + 15 + 15	5,200	5,200	13,000	13,000	13,000	13,000	0	0	4,700	22.8	20.7
		68,400	6 + 6 + 15 + 15 + 15 + 15	5,700	5,700	14,300	14,300	14,300	14,300	0	0	5,410	26.4	23.9
6	72	62,400	6 + 9 + 9 + 9 + 9 + 30	5,200	7,800	7,800	7,800	7,800	26,000	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 9 + 9 + 30	5,600	8,500	8,500	8,500	8,500	28,900	0	0	5,410	26.4	23.9
6	72	62,400	6 + 9 + 9 + 9 + 15 + 24	5,200	7,800	7,800	7,800	13,000	20,800	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 9 + 15 + 24	5,700	8,600	8,600	8,600	14,300	22,800	0	0	5,410	26.4	23.9
6	72	62,400	6 + 9 + 9 + 12 + 12 + 24	5,200	7,800	7,800	10,400	10,400	20,800	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 12 + 12 + 24	5,700	8,600	8,600	11,400	11,400	22,800	0	0	5,410	26.4	23.9
6	72	62,400	6 + 9 + 9 + 12 + 18 + 18	5,200	7,800	7,800	10,400	15,600	15,600	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 12 + 18 + 18	5,700	8,600	8,600	11,400	17,100	17,100	0	0	5,410	26.4	23.9
6	72	62,400	6 + 9 + 9 + 15 + 15 + 18	5,200	7,800	7,800	13,000	13,000	15,600	0	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 15 + 15 + 18	5,700	8,600	8,600	14,300	14,300	17,100	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	72	62,400	9 + 9 + 9 + 9 + 12 + 24	7,800	7,800	7,800	7,800	10,400	20,800	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 12 + 24	8,600	8,600	8,600	8,600	11,400	22,800	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 9 + 9 + 18 + 18	7,800	7,800	7,800	7,800	15,600	15,600	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 18 + 18	8,600	8,600	8,600	8,600	17,100	17,100	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 9 + 15 + 15 + 15	7,800	7,800	7,800	13,000	13,000	13,000	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 15 + 15 + 15	8,600	8,600	8,600	14,300	14,300	14,300	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 12 + 12 + 12 + 18	7,800	7,800	10,400	10,400	10,400	15,600	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 12 + 12 + 18	8,600	8,600	11,400	11,400	11,400	17,100	0	0	5,410	26.4	23.9
6	72	62,400	9 + 9 + 12 + 12 + 15 + 15	7,800	7,800	10,400	10,400	13,000	13,000	0	0	4,700	22.8	20.7
		68,400	9 + 9 + 12 + 12 + 15 + 15	8,600	8,600	11,400	11,400	14,300	14,300	0	0	5,410	26.4	23.9
6	72	62,400	9 + 12 + 12 + 12 + 12 + 15	7,800	10,400	10,400	10,400	10,400	13,000	0	0	4,700	22.8	20.7
		68,400	9 + 12 + 12 + 12 + 12 + 15	8,600	11,400	11,400	11,400	11,400	14,300	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 6 + 6 + 15 + 36	5,000	5,000	5,000	5,000	12,600	30,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 15 + 36	5,400	5,400	5,400	5,400	13,500	33,800	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 6 + 9 + 12 + 36	5,000	5,000	5,000	7,600	10,100	30,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 12 + 36	5,400	5,400	5,400	8,100	10,800	33,800	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 6 + 9 + 18 + 30	5,000	5,000	5,000	7,600	15,100	25,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 18 + 30	5,500	5,500	5,500	8,200	16,400	28,000	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 6 + 9 + 24 + 24	5,000	5,000	5,000	7,600	20,200	20,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 24 + 24	5,500	5,500	5,500	8,300	22,100	22,100	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	75	63,000	6 + 6 + 6 + 12 + 15 + 30	5,000	5,000	5,000	10,100	12,600	25,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 12 + 15 + 30	5,500	5,500	5,500	10,900	13,700	28,000	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 9 + 9 + 9 + 36	5,000	5,000	7,600	7,600	7,600	30,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 9 + 36	5,400	5,400	8,100	8,100	8,100	33,800	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 9 + 9 + 15 + 30	5,000	5,000	7,600	7,600	12,600	25,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 15 + 30	5,500	5,500	8,200	8,200	13,700	28,000	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 9 + 12 + 12 + 30	5,000	5,000	7,600	10,100	10,100	25,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 12 + 12 + 30	5,500	5,500	8,200	10,900	10,900	28,000	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 9 + 15 + 15 + 24	5,000	5,000	7,600	12,600	12,600	20,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 15 + 15 + 24	5,500	5,500	8,300	13,800	13,800	22,100	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 9 + 18 + 18 + 18	5,000	5,000	7,600	15,100	15,100	15,100	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 18 + 18 + 18	5,500	5,500	8,300	16,600	16,600	16,600	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 12 + 12 + 15 + 24	5,000	5,000	10,100	10,100	12,600	20,200	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 12 + 12 + 15 + 24	5,500	5,500	11,000	11,000	13,800	22,100	0	0	5,410	26.4	23.9
6	75	63,000	6 + 6 + 15 + 15 + 15 + 18	5,000	5,000	12,600	12,600	12,600	15,100	0	0	4,700	22.8	20.7
		69,000	6 + 6 + 15 + 15 + 15 + 18	5,500	5,500	13,800	13,800	13,800	16,600	0	0	5,410	26.4	23.9
6	75	63,000	6 + 9 + 9 + 9 + 12 + 30	5,000	7,600	7,600	7,600	10,100	25,200	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 9 + 12 + 30	5,500	8,200	8,200	8,200	10,900	28,000	0	0	5,410	26.4	23.9
6	75	63,000	6 + 9 + 9 + 9 + 18 + 24	5,000	7,600	7,600	7,600	15,100	20,200	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 9 + 18 + 24	5,500	8,300	8,300	8,300	16,600	22,100	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	75	63,000	6 + 9 + 9 + 12 + 15 + 24	5,000	7,600	7,600	10,100	12,600	20,200	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 12 + 15 + 24	5,500	8,300	8,300	11,000	13,800	22,100	0	0	5,410	26.4	23.9
6	75	63,000	6 + 9 + 9 + 15 + 18 + 18	5,000	7,600	7,600	12,600	15,100	15,100	0	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 15 + 18 + 18	5,500	8,300	8,300	13,800	16,600	16,600	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 9 + 9 + 9 + 30	7,600	7,600	7,600	7,600	7,600	25,200	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 30	8,200	8,200	8,200	8,200	8,200	28,000	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 9 + 9 + 15 + 24	7,600	7,600	7,600	7,600	12,600	20,200	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 15 + 24	8,300	8,300	8,300	8,300	13,800	22,100	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 9 + 12 + 12 + 24	7,600	7,600	7,600	10,100	10,100	20,200	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 12 + 24	8,300	8,300	8,300	11,000	11,000	22,100	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 9 + 15 + 15 + 18	7,600	7,600	7,600	12,600	12,600	15,100	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 15 + 15 + 18	8,300	8,300	8,300	13,800	13,800	16,600	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 12 + 12 + 15 + 18	7,600	7,600	10,100	10,100	12,600	15,100	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 12 + 12 + 15 + 18	8,300	8,300	11,000	11,000	13,800	16,600	0	0	5,410	26.4	23.9
6	75	63,000	9 + 9 + 12 + 15 + 15 + 15	7,600	7,600	10,100	12,600	12,600	12,600	0	0	4,700	22.8	20.7
		69,000	9 + 9 + 12 + 15 + 15 + 15	8,300	8,300	11,000	13,800	13,800	13,800	0	0	5,410	26.4	23.9
6	75	63,000	9 + 12 + 12 + 12 + 12 + 18	7,600	10,100	10,100	10,100	10,100	15,100	0	0	4,700	22.8	20.7
		69,000	9 + 12 + 12 + 12 + 12 + 18	8,300	11,000	11,000	11,000	11,000	16,600	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 6 + 6 + 18 + 36	4,900	4,900	4,900	4,900	14,700	29,400	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 18 + 36	5,300	5,300	5,300	5,300	15,800	32,800	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	78	63,600	6 + 6 + 6 + 6 + 24 + 30	4,900	4,900	4,900	4,900	19,600	24,500	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 24 + 30	5,300	5,300	5,300	5,300	21,200	27,200	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 6 + 9 + 15 + 36	4,900	4,900	4,900	7,300	12,200	29,400	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 9 + 15 + 36	5,300	5,300	5,300	7,900	13,100	32,800	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 6 + 12 + 12 + 36	4,900	4,900	4,900	9,800	9,800	29,400	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 12 + 12 + 36	5,300	5,300	5,300	10,500	10,500	32,800	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 6 + 15 + 15 + 30	4,900	4,900	4,900	12,200	12,200	24,500	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 15 + 15 + 30	5,300	5,300	5,300	13,300	13,300	27,200	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 6 + 18 + 18 + 24	4,900	4,900	4,900	14,700	14,700	19,600	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 18 + 18 + 24	5,400	5,400	5,400	16,100	16,100	21,400	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 9 + 9 + 12 + 36	4,900	4,900	7,300	7,300	9,800	29,400	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 12 + 36	5,300	5,300	7,900	7,900	10,500	32,800	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 12 + 12 + 12 + 30	4,900	4,900	9,800	9,800	9,800	24,500	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 12 + 12 + 12 + 30	5,300	5,300	10,600	10,600	10,600	27,200	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 12 + 15 + 15 + 24	4,900	4,900	9,800	12,200	12,200	19,600	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 12 + 15 + 15 + 24	5,400	5,400	10,700	13,400	13,400	21,400	0	0	5,410	26.4	23.9
6	78	63,600	6 + 6 + 12 + 18 + 18 + 18	4,900	4,900	9,800	14,700	14,700	14,700	0	0	4,690	22.8	20.6
		69,600	6 + 6 + 12 + 18 + 18 + 18	5,400	5,400	10,700	16,100	16,100	16,100	0	0	5,410	26.4	23.9
6	78	63,600	6 + 9 + 9 + 9 + 9 + 36	4,900	7,300	7,300	7,300	7,300	29,400	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 9 + 9 + 36	5,300	7,900	7,900	7,900	7,900	32,800	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	78	63,600	6 + 9 + 9 + 9 + 15 + 30	4,900	7,300	7,300	7,300	12,200	24,500	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 9 + 15 + 30	5,300	8,000	8,000	8,000	13,300	27,200	0	0	5,410	26.4	23.9
6	78	63,600	6 + 9 + 9 + 12 + 12 + 30	4,900	7,300	7,300	9,800	9,800	24,500	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 12 + 12 + 30	5,300	8,000	8,000	10,600	10,600	27,200	0	0	5,410	26.4	23.9
6	78	63,600	6 + 9 + 9 + 12 + 18 + 24	4,900	7,300	7,300	9,800	14,700	19,600	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 12 + 18 + 24	5,400	8,000	8,000	10,700	16,100	21,400	0	0	5,410	26.4	23.9
6	78	63,600	6 + 9 + 9 + 15 + 15 + 24	4,900	7,300	7,300	12,200	12,200	19,600	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 15 + 15 + 24	5,400	8,000	8,000	13,400	13,400	21,400	0	0	5,410	26.4	23.9
6	78	63,600	6 + 9 + 9 + 18 + 18 + 18	4,900	7,300	7,300	14,700	14,700	14,700	0	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 18 + 18 + 18	5,400	8,000	8,000	16,100	16,100	16,100	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 9 + 9 + 12 + 30	7,300	7,300	7,300	7,300	9,800	24,500	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 12 + 30	8,000	8,000	8,000	8,000	10,600	27,200	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 9 + 9 + 18 + 24	7,300	7,300	7,300	7,300	14,700	19,600	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 18 + 24	8,000	8,000	8,000	8,000	16,100	21,400	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 12 + 12 + 12 + 24	7,300	7,300	9,800	9,800	9,800	19,600	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 12 + 12 + 24	8,000	8,000	10,700	10,700	10,700	21,400	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 12 + 15 + 15 + 18	7,300	7,300	9,800	12,200	12,200	14,700	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 15 + 15 + 18	8,000	8,000	10,700	13,400	13,400	16,100	0	0	5,410	26.4	23.9
6	78	63,600	9 + 9 + 15 + 15 + 15 + 15	7,300	7,300	12,200	12,200	12,200	12,200	0	0	4,690	22.8	20.6
		69,600	9 + 9 + 15 + 15 + 15 + 15	8,000	8,000	13,400	13,400	13,400	13,400	0	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	42	48,000	6 + 6 + 6 + 6 + 6 + 6 + 6	6,900	6,900	6,900	6,900	6,900	6,900	6,900	0	4,000	19.4	17.6
		46,500	6 + 6 + 6 + 6 + 6 + 6 + 6	6,600	6,600	6,600	6,600	6,600	6,600	6,600	0	3,987	19.5	17.6
7	45	48,000	6 + 6 + 6 + 6 + 6 + 6 + 9	6,400	6,400	6,400	6,400	6,400	6,400	9,600	0	4,180	20.3	18.4
		49,800	6 + 6 + 6 + 6 + 6 + 6 + 9	6,600	6,600	6,600	6,600	6,600	6,600	10,000	0	4,231	20.6	18.7
7	48	48,000	6 + 6 + 6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	6,000	6,000	12,000	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 6 + 6 + 6 + 12	6,600	6,600	6,600	6,600	6,600	6,600	13,300	0	4,474	21.8	19.8
7	48	48,000	6 + 6 + 6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	6,000	6,000	9,000	9,000	0	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 6 + 6 + 9 + 9	6,600	6,600	6,600	6,600	6,600	10,000	10,000	0	4,474	21.8	19.8
7	51	51,000	6 + 6 + 6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	6,000	6,000	15,000	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 6 + 6 + 6 + 15	6,600	6,600	6,600	6,600	6,600	6,600	16,600	0	4,718	23.0	20.8
7	51	51,000	6 + 6 + 6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	6,000	6,000	9,000	12,000	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 6 + 6 + 9 + 12	6,600	6,600	6,600	6,600	6,600	10,000	13,300	0	4,718	23.0	20.8
7	51	51,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	6,000	6,000	6,000	6,000	9,000	9,000	9,000	0	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	6,600	6,600	6,600	6,600	10,000	10,000	10,000	0	4,718	23.0	20.8
7	54	54,000	6 + 6 + 6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	6,000	6,000	18,000	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 6 + 6 + 18	6,600	6,600	6,600	6,600	6,600	6,600	19,900	0	4,962	24.2	21.9
7	54	54,000	6 + 6 + 6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	6,000	6,000	9,000	15,000	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 6 + 9 + 15	6,600	6,600	6,600	6,600	6,600	10,000	16,600	0	4,962	24.2	21.9
7	54	54,000	6 + 6 + 6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	6,000	6,000	12,000	12,000	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 6 + 12 + 12	6,600	6,600	6,600	6,600	6,600	13,300	13,300	0	4,962	24.2	21.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	54	54,000	6 + 6 + 6 + 6 + 9 + 9 + 12	6,000	6,000	6,000	6,000	9,000	9,000	12,000	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 9 + 9 + 12	6,600	6,600	6,600	6,600	10,000	10,000	13,300	0	4,962	24.2	21.9
7	54	54,000	6 + 6 + 6 + 9 + 9 + 9 + 9	6,000	6,000	6,000	9,000	9,000	9,000	9,000	0	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 9 + 9 + 9 + 9	6,600	6,600	6,600	10,000	10,000	10,000	10,000	0	4,962	24.2	21.9
7	57	57,000	6 + 6 + 6 + 6 + 6 + 9 + 18	6,000	6,000	6,000	6,000	6,000	9,000	18,000	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 6 + 9 + 18	6,600	6,600	6,600	6,600	6,600	9,900	19,900	0	5,206	25.4	23.0
7	57	57,000	6 + 6 + 6 + 6 + 6 + 12 + 15	6,000	6,000	6,000	6,000	6,000	12,000	15,000	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 6 + 12 + 15	6,600	6,600	6,600	6,600	6,600	13,300	16,600	0	5,206	25.4	23.0
7	57	57,000	6 + 6 + 6 + 6 + 9 + 9 + 15	6,000	6,000	6,000	6,000	9,000	9,000	15,000	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 9 + 9 + 15	6,600	6,600	6,600	6,600	9,900	9,900	16,600	0	5,206	25.4	23.0
7	57	57,000	6 + 6 + 6 + 6 + 9 + 12 + 12	6,000	6,000	6,000	6,000	9,000	12,000	12,000	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 9 + 12 + 12	6,600	6,600	6,600	6,600	9,900	13,300	13,300	0	5,206	25.4	23.0
7	57	57,000	6 + 6 + 6 + 9 + 9 + 9 + 12	6,000	6,000	6,000	9,000	9,000	9,000	12,000	0	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 9 + 9 + 9 + 12	6,600	6,600	6,600	9,900	9,900	9,900	13,300	0	5,206	25.4	23.0
7	57	57,000	6 + 6 + 9 + 9 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	9,000	9,000	0	4,630	22.5	20.4
		63,000	6 + 6 + 9 + 9 + 9 + 9 + 9	6,600	6,600	9,900	9,900	9,900	9,900	9,900	0	5,206	25.4	23.0
7	60	60,000	6 + 6 + 6 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	6,000	6,000	24,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 6 + 24	6,600	6,600	6,600	6,600	6,600	6,600	26,400	0	5,450	26.6	24.1
7	60	60,000	6 + 6 + 6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	6,000	6,000	12,000	18,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 12 + 18	6,600	6,600	6,600	6,600	6,600	13,200	19,800	0	5,450	26.6	24.1

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	60	60,000	6 + 6 + 6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	6,000	6,000	15,000	15,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 15 + 15	6,600	6,600	6,600	6,600	6,600	16,500	16,500	0	5,450	26.6	24.1
7	60	60,000	6 + 6 + 6 + 6 + 9 + 9 + 18	6,000	6,000	6,000	6,000	9,000	9,000	18,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 9 + 9 + 18	6,600	6,600	6,600	6,600	9,900	9,900	19,800	0	5,450	26.6	24.1
7	60	60,000	6 + 6 + 6 + 6 + 9 + 12 + 15	6,000	6,000	6,000	6,000	9,000	12,000	15,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 9 + 12 + 15	6,600	6,600	6,600	6,600	9,900	13,200	16,500	0	5,450	26.6	24.1
7	60	60,000	6 + 6 + 6 + 6 + 12 + 12 + 12	6,000	6,000	6,000	6,000	12,000	12,000	12,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 12 + 12 + 12	6,600	6,600	6,600	6,600	13,200	13,200	13,200	0	5,450	26.6	24.1
7	60	60,000	6 + 6 + 6 + 9 + 9 + 9 + 15	6,000	6,000	6,000	9,000	9,000	9,000	15,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 9 + 9 + 9 + 15	6,600	6,600	6,600	9,900	9,900	9,900	16,500	0	5,450	26.6	24.1
7	60	60,000	6 + 6 + 6 + 9 + 9 + 12 + 12	6,000	6,000	6,000	9,000	9,000	12,000	12,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 9 + 9 + 12 + 12	6,600	6,600	6,600	9,900	9,900	13,200	13,200	0	5,450	26.6	24.1
7	60	60,000	6 + 6 + 9 + 9 + 9 + 9 + 12	6,000	6,000	9,000	9,000	9,000	9,000	12,000	0	4,680	22.8	20.6
		66,000	6 + 6 + 9 + 9 + 9 + 9 + 12	6,600	6,600	9,900	9,900	9,900	9,900	13,200	0	5,450	26.6	24.1
7	60	60,000	6 + 9 + 9 + 9 + 9 + 9 + 9	6,000	9,000	9,000	9,000	9,000	9,000	9,000	0	4,680	22.8	20.6
		66,000	6 + 9 + 9 + 9 + 9 + 9 + 9	6,600	9,900	9,900	9,900	9,900	9,900	9,900	0	5,450	26.6	24.1
7	63	60,600	6 + 6 + 6 + 6 + 6 + 9 + 24	5,800	5,800	5,800	5,800	5,800	8,700	23,100	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 6 + 9 + 24	6,300	6,300	6,300	6,300	6,300	9,500	25,400	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 6 + 6 + 6 + 15 + 18	5,800	5,800	5,800	5,800	5,800	14,400	17,300	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 6 + 15 + 18	6,300	6,300	6,300	6,300	6,300	15,900	19,000	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	63	60,600	6 + 6 + 6 + 6 + 9 + 12 + 18	5,800	5,800	5,800	5,800	8,700	11,500	17,300	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 9 + 12 + 18	6,300	6,300	6,300	6,300	9,500	12,700	19,000	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 6 + 6 + 9 + 15 + 15	5,800	5,800	5,800	5,800	8,700	14,400	14,400	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 9 + 15 + 15	6,300	6,300	6,300	6,300	9,500	15,900	15,900	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 6 + 6 + 12 + 12 + 15	5,800	5,800	5,800	5,800	11,500	11,500	14,400	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 12 + 12 + 15	6,300	6,300	6,300	6,300	12,700	12,700	15,900	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 6 + 9 + 9 + 9 + 18	5,800	5,800	5,800	8,700	8,700	8,700	17,300	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 9 + 9 + 9 + 18	6,300	6,300	6,300	9,500	9,500	9,500	19,000	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 6 + 9 + 9 + 12 + 15	5,800	5,800	5,800	8,700	8,700	11,500	14,400	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 9 + 9 + 12 + 15	6,300	6,300	6,300	9,500	9,500	12,700	15,900	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 6 + 9 + 12 + 12 + 12	5,800	5,800	5,800	8,700	11,500	11,500	11,500	0	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 9 + 12 + 12 + 12	6,300	6,300	6,300	9,500	12,700	12,700	12,700	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 9 + 9 + 9 + 9 + 15	5,800	5,800	8,700	8,700	8,700	8,700	14,400	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 9 + 9 + 9 + 15	6,300	6,300	9,500	9,500	9,500	9,500	15,900	0	5,430	26.5	24.0
7	63	60,600	6 + 6 + 9 + 9 + 9 + 12 + 12	5,800	5,800	8,700	8,700	8,700	11,500	11,500	0	4,690	22.8	20.6
		66,600	6 + 6 + 9 + 9 + 9 + 12 + 12	6,300	6,300	9,500	9,500	9,500	12,700	12,700	0	5,430	26.5	24.0
7	63	60,600	6 + 9 + 9 + 9 + 9 + 9 + 12	5,800	8,700	8,700	8,700	8,700	8,700	11,500	0	4,690	22.8	20.6
		66,600	6 + 9 + 9 + 9 + 9 + 9 + 12	6,300	9,500	9,500	9,500	9,500	9,500	12,700	0	5,430	26.5	24.0
7	63	60,600	9 + 9 + 9 + 9 + 9 + 9 + 9	8,700	8,700	8,700	8,700	8,700	8,700	8,700	0	4,690	22.8	20.6
		66,600	9 + 9 + 9 + 9 + 9 + 9 + 9	9,500	9,500	9,500	9,500	9,500	9,500	9,500	0	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	66	61,200	6 + 6 + 6 + 6 + 6 + 6 + 30	5,600	5,600	5,600	5,600	5,600	5,600	27,800	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 6 + 30	6,000	6,000	6,000	6,000	6,000	6,000	31,000	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 6 + 6 + 12 + 24	5,600	5,600	5,600	5,600	5,600	11,100	22,300	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 12 + 24	6,100	6,100	6,100	6,100	6,100	12,200	24,400	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 6 + 6 + 18 + 18	5,600	5,600	5,600	5,600	5,600	16,700	16,700	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 18 + 18	6,100	6,100	6,100	6,100	6,100	18,300	18,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 6 + 9 + 9 + 24	5,600	5,600	5,600	5,600	8,300	8,300	22,300	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 9 + 9 + 24	6,100	6,100	6,100	6,100	9,200	9,200	24,400	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 6 + 9 + 15 + 18	5,600	5,600	5,600	5,600	8,300	13,900	16,700	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 9 + 15 + 18	6,100	6,100	6,100	6,100	9,200	15,300	18,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 6 + 12 + 12 + 18	5,600	5,600	5,600	5,600	11,100	11,100	16,700	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 12 + 12 + 18	6,100	6,100	6,100	6,100	12,200	12,200	18,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 6 + 12 + 15 + 15	5,600	5,600	5,600	5,600	11,100	13,900	13,900	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 12 + 15 + 15	6,100	6,100	6,100	6,100	12,200	15,300	15,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 9 + 9 + 12 + 18	5,600	5,600	5,600	8,300	8,300	11,100	16,700	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 9 + 9 + 12 + 18	6,100	6,100	6,100	9,200	9,200	12,200	18,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 9 + 9 + 15 + 15	5,600	5,600	5,600	8,300	8,300	13,900	13,900	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 9 + 9 + 15 + 15	6,100	6,100	6,100	9,200	9,200	15,300	15,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 6 + 9 + 12 + 12 + 15	5,600	5,600	5,600	8,300	11,100	11,100	13,900	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 9 + 12 + 12 + 15	6,100	6,100	6,100	9,200	12,200	12,200	15,300	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	66	61,200	6 + 6 + 6 + 12 + 12 + 12 + 12	5,600	5,600	5,600	11,100	11,100	11,100	11,100	0	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 12 + 12 + 12 + 12	6,100	6,100	6,100	12,200	12,200	12,200	12,200	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 9 + 9 + 9 + 9 + 18	5,600	5,600	8,300	8,300	8,300	8,300	16,700	0	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 9 + 9 + 9 + 18	6,100	6,100	9,200	9,200	9,200	9,200	18,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 9 + 9 + 9 + 12 + 15	5,600	5,600	8,300	8,300	8,300	11,100	13,900	0	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 9 + 9 + 12 + 15	6,100	6,100	9,200	9,200	9,200	12,200	15,300	0	5,410	26.4	23.9
7	66	61,200	6 + 6 + 9 + 9 + 12 + 12 + 12	5,600	5,600	8,300	8,300	11,100	11,100	11,100	0	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 9 + 12 + 12 + 12	6,100	6,100	9,200	9,200	12,200	12,200	12,200	0	5,410	26.4	23.9
7	66	61,200	6 + 9 + 9 + 9 + 9 + 9 + 15	5,600	8,300	8,300	8,300	8,300	8,300	13,900	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 9 + 9 + 9 + 15	6,100	9,200	9,200	9,200	9,200	9,200	15,300	0	5,410	26.4	23.9
7	66	61,200	6 + 9 + 9 + 9 + 9 + 12 + 12	5,600	8,300	8,300	8,300	8,300	11,100	11,100	0	4,700	22.8	20.7
		67,200	6 + 9 + 9 + 9 + 9 + 12 + 12	6,100	9,200	9,200	9,200	9,200	12,200	12,200	0	5,410	26.4	23.9
7	66	61,200	9 + 9 + 9 + 9 + 9 + 9 + 12	8,300	8,300	8,300	8,300	8,300	8,300	11,100	0	4,700	22.8	20.7
		67,200	9 + 9 + 9 + 9 + 9 + 9 + 12	9,200	9,200	9,200	9,200	9,200	9,200	12,200	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 6 + 6 + 9 + 30	5,400	5,400	5,400	5,400	5,400	8,100	26,900	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 6 + 9 + 30	5,800	5,800	5,800	5,800	5,800	8,700	29,900	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 6 + 6 + 15 + 24	5,400	5,400	5,400	5,400	5,400	13,400	21,500	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 6 + 15 + 24	5,900	5,900	5,900	5,900	5,900	14,700	23,600	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 6 + 9 + 12 + 24	5,400	5,400	5,400	5,400	8,100	10,700	21,500	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 9 + 12 + 24	5,900	5,900	5,900	5,900	8,800	11,800	23,600	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	69	61,800	6 + 6 + 6 + 6 + 9 + 18 + 18	5,400	5,400	5,400	5,400	8,100	16,100	16,100	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 9 + 18 + 18	5,900	5,900	5,900	5,900	8,800	17,700	17,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 6 + 12 + 15 + 18	5,400	5,400	5,400	5,400	10,700	13,400	16,100	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 12 + 15 + 18	5,900	5,900	5,900	5,900	11,800	14,700	17,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 6 + 15 + 15 + 15	5,400	5,400	5,400	5,400	13,400	13,400	13,400	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 15 + 15 + 15	5,900	5,900	5,900	5,900	14,700	14,700	14,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 9 + 9 + 9 + 24	5,400	5,400	5,400	8,100	8,100	8,100	21,500	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 9 + 9 + 9 + 24	5,900	5,900	5,900	8,800	8,800	8,800	23,600	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 9 + 9 + 15 + 18	5,400	5,400	5,400	8,100	8,100	13,400	16,100	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 9 + 9 + 15 + 18	5,900	5,900	5,900	8,800	8,800	14,700	17,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 9 + 12 + 12 + 18	5,400	5,400	5,400	8,100	10,700	10,700	16,100	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 9 + 12 + 12 + 18	5,900	5,900	5,900	8,800	11,800	11,800	17,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 6 + 12 + 12 + 12 + 15	5,400	5,400	5,400	10,700	10,700	10,700	13,400	0	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 12 + 12 + 12 + 15	5,900	5,900	5,900	11,800	11,800	11,800	14,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 9 + 9 + 9 + 12 + 18	5,400	5,400	8,100	8,100	8,100	10,700	16,100	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 9 + 9 + 12 + 18	5,900	5,900	8,800	8,800	8,800	11,800	17,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 9 + 9 + 9 + 15 + 15	5,400	5,400	8,100	8,100	8,100	13,400	13,400	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 9 + 9 + 15 + 15	5,900	5,900	8,800	8,800	8,800	14,700	14,700	0	5,410	26.4	23.9
7	69	61,800	6 + 6 + 9 + 9 + 12 + 12 + 15	5,400	5,400	8,100	8,100	10,700	10,700	13,400	0	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 9 + 12 + 12 + 15	5,900	5,900	8,800	8,800	11,800	11,800	14,700	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	69	61,800	6 + 9 + 9 + 9 + 9 + 9 + 18	5,400	8,100	8,100	8,100	8,100	8,100	16,100	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 9 + 9 + 9 + 18	5,900	8,800	8,800	8,800	8,800	8,800	17,700	0	5,410	26.4	23.9
7	69	61,800	6 + 9 + 9 + 9 + 9 + 12 + 15	5,400	8,100	8,100	8,100	8,100	10,700	13,400	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 9 + 9 + 12 + 15	5,900	8,800	8,800	8,800	8,800	11,800	14,700	0	5,410	26.4	23.9
7	69	61,800	6 + 9 + 9 + 9 + 12 + 12 + 12	5,400	8,100	8,100	8,100	10,700	10,700	10,700	0	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 9 + 12 + 12 + 12	5,900	8,800	8,800	8,800	11,800	11,800	11,800	0	5,410	26.4	23.9
7	69	61,800	9 + 9 + 9 + 9 + 9 + 9 + 15	8,100	8,100	8,100	8,100	8,100	8,100	13,400	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 9 + 9 + 15	8,800	8,800	8,800	8,800	8,800	8,800	14,700	0	5,410	26.4	23.9
7	69	61,800	9 + 9 + 9 + 9 + 9 + 12 + 12	8,100	8,100	8,100	8,100	8,100	10,700	10,700	0	4,700	22.8	20.7
		67,800	9 + 9 + 9 + 9 + 9 + 12 + 12	8,800	8,800	8,800	8,800	8,800	11,800	11,800	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 6 + 6 + 6 + 36	5,200	5,200	5,200	5,200	5,200	5,200	31,200	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 6 + 36	5,600	5,600	5,600	5,600	5,600	5,600	34,900	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 6 + 6 + 12 + 30	5,200	5,200	5,200	5,200	5,200	10,400	26,000	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 12 + 30	5,600	5,600	5,600	5,600	5,600	11,300	28,900	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 6 + 6 + 18 + 24	5,200	5,200	5,200	5,200	5,200	15,600	20,800	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 18 + 24	5,700	5,700	5,700	5,700	5,700	17,100	22,800	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 6 + 9 + 9 + 30	5,200	5,200	5,200	5,200	7,800	7,800	26,000	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 9 + 9 + 30	5,600	5,600	5,600	5,600	8,500	8,500	28,900	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 6 + 9 + 15 + 24	5,200	5,200	5,200	5,200	7,800	13,000	20,800	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 9 + 15 + 24	5,700	5,700	5,700	5,700	8,600	14,300	22,800	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	72	62,400	6 + 6 + 6 + 6 + 12 + 12 + 24	5,200	5,200	5,200	5,200	10,400	10,400	20,800	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 12 + 12 + 24	5,700	5,700	5,700	5,700	11,400	11,400	22,800	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 6 + 12 + 18 + 18	5,200	5,200	5,200	5,200	10,400	15,600	15,600	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 12 + 18 + 18	5,700	5,700	5,700	5,700	11,400	17,100	17,100	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 6 + 15 + 15 + 18	5,200	5,200	5,200	5,200	13,000	13,000	15,600	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 15 + 15 + 18	5,700	5,700	5,700	5,700	14,300	14,300	17,100	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 9 + 9 + 12 + 24	5,200	5,200	5,200	7,800	7,800	10,400	20,800	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 9 + 12 + 24	5,700	5,700	5,700	8,600	8,600	11,400	22,800	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 9 + 9 + 18 + 18	5,200	5,200	5,200	7,800	7,800	15,600	15,600	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 9 + 18 + 18	5,700	5,700	5,700	8,600	8,600	17,100	17,100	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 9 + 15 + 15 + 15	5,200	5,200	5,200	7,800	13,000	13,000	13,000	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 15 + 15 + 15	5,700	5,700	5,700	8,600	14,300	14,300	14,300	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 12 + 12 + 12 + 18	5,200	5,200	5,200	10,400	10,400	10,400	15,600	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 12 + 12 + 12 + 18	5,700	5,700	5,700	11,400	11,400	11,400	17,100	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 6 + 12 + 12 + 15 + 15	5,200	5,200	5,200	10,400	10,400	13,000	13,000	0	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 12 + 12 + 15 + 15	5,700	5,700	5,700	11,400	11,400	14,300	14,300	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 9 + 9 + 9 + 9 + 24	5,200	5,200	7,800	7,800	7,800	7,800	20,800	0	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 9 + 9 + 9 + 24	5,700	5,700	8,600	8,600	8,600	8,600	22,800	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 9 + 9 + 9 + 15 + 18	5,200	5,200	7,800	7,800	7,800	13,000	15,600	0	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 9 + 9 + 15 + 18	5,700	5,700	8,600	8,600	8,600	14,300	17,100	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	72	62,400	6 + 6 + 9 + 9 + 12 + 12 + 18	5,200	5,200	7,800	7,800	10,400	10,400	15,600	0	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 9 + 12 + 12 + 18	5,700	5,700	8,600	8,600	11,400	11,400	17,100	0	5,410	26.4	23.9
7	72	62,400	6 + 6 + 9 + 9 + 12 + 15 + 15	5,200	5,200	7,800	7,800	10,400	13,000	13,000	0	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 9 + 12 + 15 + 15	5,700	5,700	8,600	8,600	11,400	14,300	14,300	0	5,410	26.4	23.9
7	72	62,400	6 + 9 + 9 + 9 + 9 + 12 + 18	5,200	7,800	7,800	7,800	7,800	10,400	15,600	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 9 + 9 + 12 + 18	5,700	8,600	8,600	8,600	8,600	11,400	17,100	0	5,410	26.4	23.9
7	72	62,400	6 + 9 + 9 + 9 + 9 + 15 + 15	5,200	7,800	7,800	7,800	7,800	13,000	13,000	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 9 + 9 + 15 + 15	5,700	8,600	8,600	8,600	8,600	14,300	14,300	0	5,410	26.4	23.9
7	72	62,400	6 + 9 + 9 + 9 + 12 + 12 + 15	5,200	7,800	7,800	7,800	10,400	10,400	13,000	0	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 9 + 12 + 12 + 15	5,700	8,600	8,600	8,600	11,400	11,400	14,300	0	5,410	26.4	23.9
7	72	62,400	9 + 9 + 9 + 9 + 9 + 9 + 18	7,800	7,800	7,800	7,800	7,800	7,800	15,600	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 9 + 9 + 18	8,600	8,600	8,600	8,600	8,600	8,600	17,100	0	5,410	26.4	23.9
7	72	62,400	9 + 9 + 9 + 9 + 9 + 12 + 15	7,800	7,800	7,800	7,800	7,800	10,400	13,000	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 9 + 12 + 15	8,600	8,600	8,600	8,600	8,600	11,400	14,300	0	5,410	26.4	23.9
7	72	62,400	9 + 9 + 9 + 9 + 12 + 12 + 12	7,800	7,800	7,800	7,800	10,400	10,400	10,400	0	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 12 + 12 + 12	8,600	8,600	8,600	8,600	11,400	11,400	11,400	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 6 + 6 + 9 + 36	5,000	5,000	5,000	5,000	5,000	7,600	30,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 6 + 9 + 36	5,400	5,400	5,400	5,400	5,400	8,100	33,800	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 6 + 6 + 15 + 30	5,000	5,000	5,000	5,000	5,000	12,600	25,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 6 + 15 + 30	5,500	5,500	5,500	5,500	5,500	13,700	28,000	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	75	63,000	6 + 6 + 6 + 6 + 9 + 12 + 30	5,000	5,000	5,000	5,000	7,600	10,100	25,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 9 + 12 + 30	5,500	5,500	5,500	5,500	8,200	10,900	28,000	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 6 + 9 + 18 + 24	5,000	5,000	5,000	5,000	7,600	15,100	20,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 9 + 18 + 24	5,500	5,500	5,500	5,500	8,300	16,600	22,100	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 6 + 12 + 15 + 24	5,000	5,000	5,000	5,000	10,100	12,600	20,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 12 + 15 + 24	5,500	5,500	5,500	5,500	11,000	13,800	22,100	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 6 + 15 + 18 + 18	5,000	5,000	5,000	5,000	12,600	15,100	15,100	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 15 + 18 + 18	5,500	5,500	5,500	5,500	13,800	16,600	16,600	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 9 + 9 + 9 + 30	5,000	5,000	5,000	7,600	7,600	7,600	25,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 9 + 9 + 30	5,500	5,500	5,500	8,200	8,200	8,200	28,000	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 9 + 9 + 15 + 24	5,000	5,000	5,000	7,600	7,600	12,600	20,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 9 + 15 + 24	5,500	5,500	5,500	8,300	8,300	13,800	22,100	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 9 + 12 + 12 + 24	5,000	5,000	5,000	7,600	10,100	10,100	20,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 12 + 12 + 24	5,500	5,500	5,500	8,300	11,000	11,000	22,100	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 9 + 15 + 15 + 18	5,000	5,000	5,000	7,600	12,600	12,600	15,100	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 15 + 15 + 18	5,500	5,500	5,500	8,300	13,800	13,800	16,600	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 12 + 12 + 15 + 18	5,000	5,000	5,000	10,100	10,100	12,600	15,100	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 12 + 12 + 15 + 18	5,500	5,500	5,500	11,000	11,000	13,800	16,600	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 6 + 12 + 15 + 15 + 15	5,000	5,000	5,000	10,100	12,600	12,600	12,600	0	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 12 + 15 + 15 + 15	5,500	5,500	5,500	11,000	13,800	13,800	13,800	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	75	63,000	6 + 6 + 9 + 9 + 9 + 12 + 24	5,000	5,000	7,600	7,600	7,600	10,100	20,200	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 9 + 12 + 24	5,500	5,500	8,300	8,300	8,300	11,000	22,100	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 9 + 9 + 9 + 18 + 18	5,000	5,000	7,600	7,600	7,600	15,100	15,100	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 9 + 18 + 18	5,500	5,500	8,300	8,300	8,300	16,600	16,600	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 9 + 9 + 12 + 15 + 18	5,000	5,000	7,600	7,600	10,100	12,600	15,100	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 12 + 15 + 18	5,500	5,500	8,300	8,300	11,000	13,800	16,600	0	5,410	26.4	23.9
7	75	63,000	6 + 6 + 9 + 9 + 15 + 15 + 15	5,000	5,000	7,600	7,600	12,600	12,600	12,600	0	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 15 + 15 + 15	5,500	5,500	8,300	8,300	13,800	13,800	13,800	0	5,410	26.4	23.9
7	75	63,000	6 + 9 + 9 + 9 + 9 + 9 + 24	5,000	7,600	7,600	7,600	7,600	7,600	20,200	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 9 + 9 + 9 + 24	5,500	8,300	8,300	8,300	8,300	8,300	22,100	0	5,410	26.4	23.9
7	75	63,000	6 + 9 + 9 + 9 + 9 + 15 + 18	5,000	7,600	7,600	7,600	7,600	12,600	15,100	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 9 + 9 + 15 + 18	5,500	8,300	8,300	8,300	8,300	13,800	16,600	0	5,410	26.4	23.9
7	75	63,000	6 + 9 + 9 + 9 + 12 + 12 + 18	5,000	7,600	7,600	7,600	10,100	10,100	15,100	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 9 + 12 + 12 + 18	5,500	8,300	8,300	8,300	11,000	11,000	16,600	0	5,410	26.4	23.9
7	75	63,000	6 + 9 + 9 + 9 + 12 + 15 + 15	5,000	7,600	7,600	7,600	10,100	12,600	12,600	0	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 9 + 12 + 15 + 15	5,500	8,300	8,300	8,300	11,000	13,800	13,800	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 9 + 9 + 12 + 18	7,600	7,600	7,600	7,600	7,600	10,100	15,100	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 12 + 18	8,300	8,300	8,300	8,300	8,300	11,000	16,600	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 9 + 9 + 15 + 15	7,600	7,600	7,600	7,600	7,600	12,600	12,600	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 15 + 15	8,300	8,300	8,300	8,300	8,300	13,800	13,800	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	75	63,000	9 + 9 + 9 + 9 + 12 + 12 + 15	7,600	7,600	7,600	7,600	10,100	10,100	12,600	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 12 + 12 + 15	8,300	8,300	8,300	8,300	11,000	11,000	13,800	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 12 + 12 + 12 + 12	7,600	7,600	7,600	10,100	10,100	10,100	10,100	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 12 + 12 + 12	8,300	8,300	8,300	11,000	11,000	11,000	11,000	0	5,410	26.4	23.9
7	75	63,000	9 + 9 + 9 + 12 + 12 + 12 + 12	7,600	7,600	7,600	10,100	10,100	10,100	10,100	0	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 12 + 12 + 12 + 12	8,300	8,300	8,300	11,000	11,000	11,000	11,000	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 6 + 6 + 6 + 12 + 36	4,900	4,900	4,900	4,900	4,900	9,800	29,400	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 12 + 36	5,300	5,300	5,300	5,300	5,300	10,500	32,800	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 6 + 6 + 6 + 18 + 30	4,900	4,900	4,900	4,900	4,900	14,700	24,500	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 18 + 30	5,300	5,300	5,300	5,300	5,300	15,900	27,200	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 6 + 6 + 6 + 24 + 24	4,900	4,900	4,900	4,900	4,900	19,600	19,600	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 24 + 24	5,400	5,400	5,400	5,400	5,400	21,400	21,400	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 6 + 6 + 9 + 9 + 36	4,900	4,900	4,900	4,900	7,300	7,300	29,400	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 9 + 9 + 36	5,300	5,300	5,300	5,300	7,900	7,900	32,800	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 6 + 6 + 9 + 15 + 30	4,900	4,900	4,900	4,900	7,300	12,200	24,500	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 9 + 15 + 30	5,300	5,300	5,300	5,300	8,000	13,300	27,200	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 6 + 6 + 12 + 12 + 30	4,900	4,900	4,900	4,900	9,800	9,800	24,500	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 12 + 12 + 30	5,300	5,300	5,300	5,300	10,600	10,600	27,200	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 6 + 6 + 12 + 18 + 24	4,900	4,900	4,900	4,900	9,800	14,700	19,600	0	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 12 + 18 + 24	5,400	5,400	5,400	5,400	10,700	16,100	21,400	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	78	63,600	6 + 6 + 9 + 9 + 9 + 15 + 24	4,900	4,900	7,300	7,300	7,300	12,200	19,600	0	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 9 + 15 + 24	5,400	5,400	8,000	8,000	8,000	13,400	21,400	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 9 + 9 + 12 + 12 + 24	4,900	4,900	7,300	7,300	9,800	9,800	19,600	0	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 12 + 12 + 24	5,400	5,400	8,000	8,000	10,700	10,700	21,400	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 9 + 9 + 12 + 18 + 18	4,900	4,900	7,300	7,300	9,800	14,700	14,700	0	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 12 + 18 + 18	5,400	5,400	8,000	8,000	10,700	16,100	16,100	0	5,410	26.4	23.9
7	78	63,600	6 + 6 + 9 + 9 + 15 + 15 + 18	4,900	4,900	7,300	7,300	12,200	12,200	14,700	0	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 15 + 15 + 18	5,400	5,400	8,000	8,000	13,400	13,400	16,100	0	5,410	26.4	23.9
7	78	63,600	6 + 9 + 9 + 9 + 9 + 12 + 24	4,900	7,300	7,300	7,300	7,300	9,800	19,600	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 9 + 9 + 12 + 24	5,400	8,000	8,000	8,000	8,000	10,700	21,400	0	5,410	26.4	23.9
7	78	63,600	6 + 9 + 9 + 9 + 9 + 18 + 18	4,900	7,300	7,300	7,300	7,300	14,700	14,700	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 9 + 9 + 18 + 18	5,400	8,000	8,000	8,000	8,000	16,100	16,100	0	5,410	26.4	23.9
7	78	63,600	6 + 9 + 9 + 9 + 12 + 15 + 18	4,900	7,300	7,300	7,300	9,800	12,200	14,700	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 9 + 12 + 15 + 18	5,400	8,000	8,000	8,000	10,700	13,400	16,100	0	5,410	26.4	23.9
7	78	63,600	6 + 9 + 9 + 9 + 15 + 15 + 15	4,900	7,300	7,300	7,300	12,200	12,200	12,200	0	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 9 + 15 + 15 + 15	5,400	8,000	8,000	8,000	13,400	13,400	13,400	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 9 + 9 + 9 + 24	7,300	7,300	7,300	7,300	7,300	7,300	19,600	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 9 + 9 + 24	8,000	8,000	8,000	8,000	8,000	8,000	21,400	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 9 + 9 + 15 + 18	7,300	7,300	7,300	7,300	7,300	12,200	14,700	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 9 + 15 + 18	8,000	8,000	8,000	8,000	8,000	13,400	16,100	0	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	78	63,600	9 + 9 + 9 + 9 + 12 + 12 + 18	7,300	7,300	7,300	7,300	9,800	9,800	14,700	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 12 + 12 + 18	8,000	8,000	8,000	8,000	10,700	10,700	16,100	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 9 + 12 + 15 + 15	7,300	7,300	7,300	7,300	9,800	12,200	12,200	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 12 + 15 + 15	8,000	8,000	8,000	8,000	10,700	13,400	13,400	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 9 + 12 + 12 + 12 + 15	7,300	7,300	7,300	9,800	9,800	9,800	12,200	0	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 12 + 12 + 12 + 15	8,000	8,000	8,000	10,700	10,700	10,700	13,400	0	5,410	26.4	23.9
7	78	63,600	9 + 9 + 12 + 12 + 12 + 12 + 12	7,300	7,300	9,800	9,800	9,800	9,800	9,800	0	4,690	22.8	20.6
		69,600	9 + 9 + 12 + 12 + 12 + 12 + 12	8,000	8,000	10,700	10,700	10,700	10,700	10,700	0	5,410	26.4	23.9
8	48	48,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	6,000	6,000	6,000	4,340	21.1	19.1
		53,100	6 + 6 + 6 + 6 + 6 + 6 + 6 + 6	6,600	6,600	6,600	6,600	6,600	6,600	6,600	6,600	4,474	21.8	19.8
8	51	51,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	6,000	6,000	6,000	9,000	4,480	21.8	19.7
		56,400	6 + 6 + 6 + 6 + 6 + 6 + 6 + 9	6,600	6,600	6,600	6,600	6,600	6,600	6,600	10,000	4,718	23.0	20.8
8	54	54,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	6,000	6,000	6,000	12,000	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 6 + 6 + 6 + 12	6,600	6,600	6,600	6,600	6,600	6,600	6,600	13,300	4,962	24.2	21.9
8	54	54,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	6,000	6,000	6,000	9,000	9,000	4,580	22.3	20.1
		59,700	6 + 6 + 6 + 6 + 6 + 6 + 9 + 9	6,600	6,600	6,600	6,600	6,600	6,600	10,000	10,000	4,962	24.2	21.9
8	57	57,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	6,000	6,000	6,000	15,000	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 15	6,600	6,600	6,600	6,600	6,600	6,600	6,600	16,600	5,206	25.4	23.0
8	57	57,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	6,000	6,000	6,000	9,000	12,000	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 12	6,600	6,600	6,600	6,600	6,600	6,600	9,900	13,300	5,206	25.4	23.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	57	57,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	6,000	6,000	6,000	6,000	6,000	9,000	9,000	9,000	4,630	22.5	20.4
		63,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	6,600	6,600	6,600	6,600	6,600	9,900	9,900	9,900	5,206	25.4	23.0
8	60	60,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	6,000	6,000	6,000	18,000	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 18	6,600	6,600	6,600	6,600	6,600	6,600	6,600	19,800	5,450	26.6	24.1
8	60	60,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	6,000	6,000	6,000	9,000	15,000	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 15	6,600	6,600	6,600	6,600	6,600	6,600	9,900	16,500	5,450	26.6	24.1
8	60	60,000	6 + 6 + 6 + 6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	6,000	6,000	6,000	12,000	12,000	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 6 + 12 + 12	6,600	6,600	6,600	6,600	6,600	6,600	13,200	13,200	5,450	26.6	24.1
8	60	60,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 12	6,000	6,000	6,000	6,000	6,000	9,000	9,000	12,000	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 12	6,600	6,600	6,600	6,600	6,600	9,900	9,900	13,200	5,450	26.6	24.1
8	60	60,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	6,000	6,000	6,000	6,000	9,000	9,000	9,000	9,000	4,680	22.8	20.6
		66,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	6,600	6,600	6,600	6,600	9,900	9,900	9,900	9,900	5,450	26.6	24.1
8	63	60,600	6 + 6 + 6 + 6 + 6 + 6 + 9 + 18	5,800	5,800	5,800	5,800	5,800	5,800	8,700	17,300	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 6 + 6 + 9 + 18	6,300	6,300	6,300	6,300	6,300	6,300	9,500	19,000	5,430	26.5	24.0
8	63	60,600	6 + 6 + 6 + 6 + 6 + 6 + 12 + 15	5,800	5,800	5,800	5,800	5,800	5,800	11,500	14,400	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 6 + 6 + 12 + 15	6,300	6,300	6,300	6,300	6,300	6,300	12,700	15,900	5,430	26.5	24.0
8	63	60,600	6 + 6 + 6 + 6 + 6 + 9 + 9 + 15	5,800	5,800	5,800	5,800	5,800	8,700	8,700	14,400	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 6 + 9 + 9 + 15	6,300	6,300	6,300	6,300	6,300	9,500	9,500	15,900	5,430	26.5	24.0
8	63	60,600	6 + 6 + 6 + 6 + 6 + 9 + 12 + 12	5,800	5,800	5,800	5,800	5,800	8,700	11,500	11,500	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 6 + 9 + 12 + 12	6,300	6,300	6,300	6,300	6,300	9,500	12,700	12,700	5,430	26.5	24.0

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	63	60,600	6 + 6 + 6 + 6 + 9 + 9 + 9 + 12	5,800	5,800	5,800	5,800	8,700	8,700	8,700	11,500	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 6 + 9 + 9 + 9 + 12	6,300	6,300	6,300	6,300	9,500	9,500	9,500	12,700	5,430	26.5	24.0
8	63	60,600	6 + 6 + 6 + 9 + 9 + 9 + 9 + 9	5,800	5,800	5,800	8,700	8,700	8,700	8,700	8,700	4,690	22.8	20.6
		66,600	6 + 6 + 6 + 9 + 9 + 9 + 9 + 9	6,300	6,300	6,300	9,500	9,500	9,500	9,500	9,500	5,430	26.5	24.0
8	66	61,200	6 + 6 + 6 + 6 + 6 + 6 + 6 + 24	5,600	5,600	5,600	5,600	5,600	5,600	5,600	22,300	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 6 + 6 + 24	6,100	6,100	6,100	6,100	6,100	6,100	6,100	24,400	5,410	26.4	23.9
8	66	61,200	6 + 6 + 6 + 6 + 6 + 6 + 12 + 18	5,600	5,600	5,600	5,600	5,600	5,600	11,100	16,700	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 6 + 12 + 18	6,100	6,100	6,100	6,100	6,100	6,100	12,200	18,300	5,410	26.4	23.9
8	66	61,200	6 + 6 + 6 + 6 + 6 + 6 + 15 + 15	5,600	5,600	5,600	5,600	5,600	5,600	13,900	13,900	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 6 + 15 + 15	6,100	6,100	6,100	6,100	6,100	6,100	15,300	15,300	5,410	26.4	23.9
8	66	61,200	6 + 6 + 6 + 6 + 6 + 9 + 9 + 18	5,600	5,600	5,600	5,600	5,600	8,300	8,300	16,700	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 9 + 9 + 18	6,100	6,100	6,100	6,100	6,100	9,200	9,200	18,300	5,410	26.4	23.9
8	66	61,200	6 + 6 + 6 + 6 + 6 + 9 + 12 + 15	5,600	5,600	5,600	5,600	5,600	8,300	11,100	13,900	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 9 + 12 + 15	6,100	6,100	6,100	6,100	6,100	9,200	12,200	15,300	5,410	26.4	23.9
8	66	61,200	6 + 6 + 6 + 6 + 6 + 12 + 12 + 12	5,600	5,600	5,600	5,600	5,600	11,100	11,100	11,100	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 6 + 12 + 12 + 12	6,100	6,100	6,100	6,100	6,100	12,200	12,200	12,200	5,410	26.4	23.9
8	66	61,200	6 + 6 + 6 + 6 + 9 + 9 + 9 + 15	5,600	5,600	5,600	5,600	8,300	8,300	8,300	13,900	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 9 + 9 + 9 + 15	6,100	6,100	6,100	6,100	9,200	9,200	9,200	15,300	5,410	26.4	23.9
8	66	61,200	6 + 6 + 6 + 6 + 9 + 9 + 12 + 12	5,600	5,600	5,600	5,600	8,300	8,300	11,100	11,100	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 6 + 9 + 9 + 12 + 12	6,100	6,100	6,100	6,100	9,200	9,200	12,200	12,200	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	66	61,200	6 + 6 + 6 + 9 + 9 + 9 + 9 + 12	5,600	5,600	5,600	8,300	8,300	8,300	8,300	11,100	4,700	22.8	20.7
		67,200	6 + 6 + 6 + 9 + 9 + 9 + 9 + 12	6,100	6,100	6,100	9,200	9,200	9,200	9,200	12,200	5,410	26.4	23.9
8	66	61,200	6 + 6 + 9 + 9 + 9 + 9 + 9 + 9	5,600	5,600	8,300	8,300	8,300	8,300	8,300	8,300	4,700	22.8	20.7
		67,200	6 + 6 + 9 + 9 + 9 + 9 + 9 + 9	6,100	6,100	9,200	9,200	9,200	9,200	9,200	9,200	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 6 + 6 + 6 + 9 + 24	5,400	5,400	5,400	5,400	5,400	5,400	8,100	21,500	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 6 + 6 + 9 + 24	5,900	5,900	5,900	5,900	5,900	5,900	8,800	23,600	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 6 + 6 + 6 + 15 + 18	5,400	5,400	5,400	5,400	5,400	5,400	13,400	16,100	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 6 + 6 + 15 + 18	5,900	5,900	5,900	5,900	5,900	5,900	14,700	17,700	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 6 + 6 + 9 + 12 + 18	5,400	5,400	5,400	5,400	5,400	8,100	10,700	16,100	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 6 + 9 + 12 + 18	5,900	5,900	5,900	5,900	5,900	8,800	11,800	17,700	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 6 + 6 + 9 + 15 + 15	5,400	5,400	5,400	5,400	5,400	8,100	13,400	13,400	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 6 + 9 + 15 + 15	5,900	5,900	5,900	5,900	5,900	8,800	14,700	14,700	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 6 + 6 + 12 + 12 + 15	5,400	5,400	5,400	5,400	5,400	10,700	10,700	13,400	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 6 + 12 + 12 + 15	5,900	5,900	5,900	5,900	5,900	11,800	11,800	14,700	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 6 + 9 + 9 + 9 + 18	5,400	5,400	5,400	5,400	8,100	8,100	8,100	16,100	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 9 + 9 + 9 + 18	5,900	5,900	5,900	5,900	8,800	8,800	8,800	17,700	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 6 + 9 + 9 + 12 + 15	5,400	5,400	5,400	5,400	8,100	8,100	10,700	13,400	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 6 + 9 + 9 + 12 + 15	5,900	5,900	5,900	5,900	8,800	8,800	11,800	14,700	5,410	26.4	23.9
8	69	61,800	6 + 6 + 6 + 9 + 9 + 9 + 9 + 15	5,400	5,400	5,400	8,100	8,100	8,100	8,100	13,400	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 9 + 9 + 9 + 9 + 15	5,900	5,900	5,900	8,800	8,800	8,800	8,800	14,700	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	69	61,800	6 + 6 + 6 + 9 + 9 + 9 + 12 + 12	5,400	5,400	5,400	8,100	8,100	8,100	10,700	10,700	4,700	22.8	20.7
		67,800	6 + 6 + 6 + 9 + 9 + 9 + 12 + 12	5,900	5,900	5,900	8,800	8,800	8,800	11,800	11,800	5,410	26.4	23.9
8	69	61,800	6 + 6 + 9 + 9 + 9 + 9 + 9 + 12	5,400	5,400	8,100	8,100	8,100	8,100	8,100	10,700	4,700	22.8	20.7
		67,800	6 + 6 + 9 + 9 + 9 + 9 + 9 + 12	5,900	5,900	8,800	8,800	8,800	8,800	8,800	11,800	5,410	26.4	23.9
8	69	61,800	6 + 9 + 9 + 9 + 9 + 9 + 9 + 9	5,400	8,100	8,100	8,100	8,100	8,100	8,100	8,100	4,700	22.8	20.7
		67,800	6 + 9 + 9 + 9 + 9 + 9 + 9 + 9	5,900	8,800	8,800	8,800	8,800	8,800	8,800	8,800	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 6 + 6 + 6 + 6 + 30	5,200	5,200	5,200	5,200	5,200	5,200	5,200	26,000	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 6 + 6 + 30	5,600	5,600	5,600	5,600	5,600	5,600	5,600	28,900	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 6 + 6 + 6 + 12 + 24	5,200	5,200	5,200	5,200	5,200	5,200	10,400	20,800	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 6 + 12 + 24	5,700	5,700	5,700	5,700	5,700	5,700	11,400	22,800	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 6 + 6 + 6 + 18 + 18	5,200	5,200	5,200	5,200	5,200	5,200	15,600	15,600	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 6 + 18 + 18	5,700	5,700	5,700	5,700	5,700	5,700	17,100	17,100	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 6 + 6 + 9 + 9 + 24	5,200	5,200	5,200	5,200	5,200	7,800	7,800	20,800	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 9 + 9 + 24	5,700	5,700	5,700	5,700	5,700	8,600	8,600	22,800	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 6 + 6 + 9 + 15 + 18	5,200	5,200	5,200	5,200	5,200	7,800	13,000	15,600	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 9 + 15 + 18	5,700	5,700	5,700	5,700	5,700	8,600	14,300	17,100	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 6 + 6 + 12 + 12 + 18	5,200	5,200	5,200	5,200	5,200	10,400	10,400	15,600	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 6 + 12 + 12 + 18	5,700	5,700	5,700	5,700	5,700	11,400	11,400	17,100	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 6 + 9 + 9 + 12 + 18	5,200	5,200	5,200	5,200	7,800	7,800	10,400	15,600	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 9 + 9 + 12 + 18	5,700	5,700	5,700	5,700	8,600	8,600	11,400	17,100	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	72	62,400	6 + 6 + 6 + 6 + 9 + 9 + 15 + 15	5,200	5,200	5,200	5,200	7,800	7,800	13,000	13,000	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 6 + 9 + 9 + 15 + 15	5,700	5,700	5,700	5,700	8,600	8,600	14,300	14,300	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 9 + 9 + 9 + 9 + 18	5,200	5,200	5,200	7,800	7,800	7,800	7,800	15,600	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 9 + 9 + 9 + 18	5,700	5,700	5,700	8,600	8,600	8,600	8,600	17,100	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 9 + 9 + 9 + 12 + 15	5,200	5,200	5,200	7,800	7,800	7,800	10,400	13,000	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 9 + 9 + 12 + 15	5,700	5,700	5,700	8,600	8,600	8,600	11,400	14,300	5,410	26.4	23.9
8	72	62,400	6 + 6 + 6 + 9 + 9 + 12 + 12 + 12	5,200	5,200	5,200	7,800	7,800	10,400	10,400	10,400	4,700	22.8	20.7
		68,400	6 + 6 + 6 + 9 + 9 + 12 + 12 + 12	5,700	5,700	5,700	8,600	8,600	11,400	11,400	11,400	5,410	26.4	23.9
8	72	62,400	6 + 6 + 9 + 9 + 9 + 9 + 9 + 15	5,200	5,200	7,800	7,800	7,800	7,800	7,800	13,000	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 9 + 9 + 9 + 9 + 15	5,700	5,700	8,600	8,600	8,600	8,600	8,600	14,300	5,410	26.4	23.9
8	72	62,400	6 + 6 + 9 + 9 + 9 + 9 + 12 + 12	5,200	5,200	7,800	7,800	7,800	7,800	10,400	10,400	4,700	22.8	20.7
		68,400	6 + 6 + 9 + 9 + 9 + 9 + 12 + 12	5,700	5,700	8,600	8,600	8,600	8,600	11,400	11,400	5,410	26.4	23.9
8	72	62,400	6 + 9 + 9 + 9 + 9 + 9 + 9 + 12	5,200	7,800	7,800	7,800	7,800	7,800	7,800	10,400	4,700	22.8	20.7
		68,400	6 + 9 + 9 + 9 + 9 + 9 + 9 + 12	5,700	8,600	8,600	8,600	8,600	8,600	8,600	11,400	5,410	26.4	23.9
8	72	62,400	9 + 9 + 9 + 9 + 9 + 9 + 9 + 9	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	4,700	22.8	20.7
		68,400	9 + 9 + 9 + 9 + 9 + 9 + 9 + 9	8,600	8,600	8,600	8,600	8,600	8,600	8,600	8,600	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 30	5,000	5,000	5,000	5,000	5,000	5,000	7,600	25,200	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 30	5,500	5,500	5,500	5,500	5,500	5,500	8,200	28,000	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 6 + 6 + 6 + 15 + 24	5,000	5,000	5,000	5,000	5,000	5,000	12,600	20,200	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 6 + 6 + 15 + 24	5,500	5,500	5,500	5,500	5,500	5,500	13,800	22,100	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	75	63,000	6 + 6 + 6 + 6 + 6 + 9 + 12 + 24	5,000	5,000	5,000	5,000	5,000	7,600	10,100	20,200	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 6 + 9 + 12 + 24	5,500	5,500	5,500	5,500	5,500	8,300	11,000	22,100	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 6 + 6 + 9 + 18 + 18	5,000	5,000	5,000	5,000	5,000	7,600	15,100	15,100	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 6 + 9 + 18 + 18	5,500	5,500	5,500	5,500	5,500	8,300	16,600	16,600	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 6 + 6 + 15 + 15 + 15	5,000	5,000	5,000	5,000	5,000	12,600	12,600	12,600	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 6 + 15 + 15 + 15	5,500	5,500	5,500	5,500	5,500	13,800	13,800	13,800	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 6 + 9 + 9 + 9 + 24	5,000	5,000	5,000	5,000	7,600	7,600	7,600	20,200	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 9 + 9 + 9 + 24	5,500	5,500	5,500	5,500	8,300	8,300	8,300	22,100	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 6 + 9 + 9 + 15 + 18	5,000	5,000	5,000	5,000	7,600	7,600	12,600	15,100	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 6 + 9 + 9 + 15 + 18	5,500	5,500	5,500	5,500	8,300	8,300	13,800	16,600	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 9 + 9 + 9 + 12 + 18	5,000	5,000	5,000	7,600	7,600	7,600	10,100	15,100	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 9 + 9 + 12 + 18	5,500	5,500	5,500	8,300	8,300	8,300	11,000	16,600	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 9 + 9 + 9 + 15 + 15	5,000	5,000	5,000	7,600	7,600	7,600	12,600	12,600	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 9 + 9 + 15 + 15	5,500	5,500	5,500	8,300	8,300	8,300	13,800	13,800	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 9 + 9 + 12 + 12 + 15	5,000	5,000	5,000	7,600	7,600	10,100	10,100	12,600	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 9 + 12 + 12 + 15	5,500	5,500	5,500	8,300	8,300	11,000	11,000	13,800	5,410	26.4	23.9
8	75	63,000	6 + 6 + 6 + 9 + 12 + 12 + 12 + 12	5,000	5,000	5,000	7,600	10,100	10,100	10,100	10,100	4,700	22.8	20.7
		69,000	6 + 6 + 6 + 9 + 12 + 12 + 12 + 12	5,500	5,500	5,500	8,300	11,000	11,000	11,000	11,000	5,410	26.4	23.9
8	75	63,000	6 + 6 + 9 + 9 + 9 + 9 + 9 + 18	5,000	5,000	7,600	7,600	7,600	7,600	7,600	15,100	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 9 + 9 + 9 + 18	5,500	5,500	8,300	8,300	8,300	8,300	8,300	16,600	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	75	63,000	6 + 6 + 9 + 9 + 9 + 9 + 12 + 15	5,000	5,000	7,600	7,600	7,600	7,600	10,100	12,600	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 9 + 9 + 12 + 15	5,500	5,500	8,300	8,300	8,300	8,300	11,000	13,800	5,410	26.4	23.9
8	75	63,000	6 + 6 + 9 + 9 + 9 + 12 + 12 + 12	5,000	5,000	7,600	7,600	7,600	10,100	10,100	10,100	4,700	22.8	20.7
		69,000	6 + 6 + 9 + 9 + 9 + 12 + 12 + 12	5,500	5,500	8,300	8,300	8,300	11,000	11,000	11,000	5,410	26.4	23.9
8	75	63,000	6 + 9 + 9 + 9 + 9 + 9 + 9 + 15	5,000	7,600	7,600	7,600	7,600	7,600	7,600	12,600	4,700	22.8	20.7
		69,000	6 + 9 + 9 + 9 + 9 + 9 + 9 + 15	5,500	8,300	8,300	8,300	8,300	8,300	8,300	13,800	5,410	26.4	23.9
8	75	63,000	9 + 9 + 9 + 9 + 9 + 9 + 9 + 12	7,600	7,600	7,600	7,600	7,600	7,600	7,600	10,100	4,700	22.8	20.7
		69,000	9 + 9 + 9 + 9 + 9 + 9 + 9 + 12	8,300	8,300	8,300	8,300	8,300	8,300	8,300	11,000	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 6 + 6 + 6 + 36	4,900	4,900	4,900	4,900	4,900	4,900	4,900	29,400	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 6 + 6 + 36	5,300	5,300	5,300	5,300	5,300	5,300	5,300	32,800	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 6 + 6 + 12 + 30	4,900	4,900	4,900	4,900	4,900	4,900	9,800	24,500	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 6 + 12 + 30	5,300	5,300	5,300	5,300	5,300	5,300	10,600	27,200	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 6 + 6 + 18 + 24	4,900	4,900	4,900	4,900	4,900	4,900	14,700	19,600	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 6 + 18 + 24	5,400	5,400	5,400	5,400	5,400	5,400	16,100	21,400	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 6 + 9 + 9 + 30	4,900	4,900	4,900	4,900	4,900	7,300	7,300	24,500	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 9 + 9 + 30	5,300	5,300	5,300	5,300	5,300	8,000	8,000	27,200	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 6 + 9 + 15 + 24	4,900	4,900	4,900	4,900	4,900	7,300	12,200	19,600	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 9 + 15 + 24	5,400	5,400	5,400	5,400	5,400	8,000	13,400	21,400	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 6 + 12 + 12 + 24	4,900	4,900	4,900	4,900	4,900	9,800	9,800	19,600	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 12 + 12 + 24	5,400	5,400	5,400	5,400	5,400	10,700	10,700	21,400	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	78	63,600	6 + 6 + 6 + 6 + 6 + 15 + 15 + 18	4,900	4,900	4,900	4,900	4,900	12,200	12,200	14,700	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 6 + 15 + 15 + 18	5,400	5,400	5,400	5,400	5,400	13,400	13,400	16,100	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 9 + 9 + 12 + 24	4,900	4,900	4,900	4,900	7,300	7,300	9,800	19,600	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 9 + 9 + 12 + 24	5,400	5,400	5,400	5,400	8,000	8,000	10,700	21,400	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 6 + 9 + 9 + 18 + 18	4,900	4,900	4,900	4,900	7,300	7,300	14,700	14,700	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 6 + 9 + 9 + 18 + 18	5,400	5,400	5,400	5,400	8,000	8,000	16,100	16,100	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 9 + 9 + 9 + 9 + 24	4,900	4,900	4,900	7,300	7,300	7,300	7,300	19,600	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 9 + 9 + 9 + 9 + 24	5,400	5,400	5,400	8,000	8,000	8,000	8,000	21,400	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 9 + 9 + 9 + 15 + 18	4,900	4,900	4,900	7,300	7,300	7,300	12,200	14,700	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 9 + 9 + 9 + 15 + 18	5,400	5,400	5,400	8,000	8,000	8,000	13,400	16,100	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 9 + 9 + 12 + 12 + 18	4,900	4,900	4,900	7,300	7,300	9,800	9,800	14,700	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 9 + 9 + 12 + 12 + 18	5,400	5,400	5,400	8,000	8,000	10,700	10,700	16,100	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 9 + 12 + 12 + 12 + 15	4,900	4,900	4,900	7,300	9,800	9,800	9,800	12,200	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 9 + 12 + 12 + 12 + 15	5,400	5,400	5,400	8,000	10,700	10,700	10,700	13,400	5,410	26.4	23.9
8	78	63,600	6 + 6 + 6 + 12 + 12 + 12 + 12 + 12	4,900	4,900	4,900	9,800	9,800	9,800	9,800	9,800	4,690	22.8	20.6
		69,600	6 + 6 + 6 + 12 + 12 + 12 + 12 + 12	5,400	5,400	5,400	10,700	10,700	10,700	10,700	10,700	5,410	26.4	23.9
8	78	63,600	6 + 6 + 9 + 9 + 9 + 9 + 12 + 18	4,900	4,900	7,300	7,300	7,300	7,300	9,800	14,700	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 9 + 9 + 12 + 18	5,400	5,400	8,000	8,000	8,000	8,000	10,700	16,100	5,410	26.4	23.9
8	78	63,600	6 + 6 + 9 + 9 + 9 + 9 + 15 + 15	4,900	4,900	7,300	7,300	7,300	7,300	12,200	12,200	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 9 + 9 + 15 + 15	5,400	5,400	8,000	8,000	8,000	8,000	13,400	13,400	5,410	26.4	23.9

STANDARD MODELS

NTXMMX60A182AB/NTXMMX60A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	78	63,600	6 + 6 + 9 + 9 + 9 + 12 + 12 + 15	4,900	4,900	7,300	7,300	7,300	9,800	9,800	12,200	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 9 + 12 + 12 + 15	5,400	5,400	8,000	8,000	8,000	10,700	10,700	13,400	5,410	26.4	23.9
8	78	63,600	6 + 6 + 9 + 9 + 12 + 12 + 12 + 12	4,900	4,900	7,300	7,300	9,800	9,800	9,800	9,800	4,690	22.8	20.6
		69,600	6 + 6 + 9 + 9 + 12 + 12 + 12 + 12	5,400	5,400	8,000	8,000	10,700	10,700	10,700	10,700	5,410	26.4	23.9
8	78	63,600	6 + 9 + 9 + 9 + 9 + 9 + 9 + 18	4,900	7,300	7,300	7,300	7,300	7,300	7,300	14,700	4,690	22.8	20.6
		69,600	6 + 9 + 9 + 9 + 9 + 9 + 9 + 18	5,400	8,000	8,000	8,000	8,000	8,000	8,000	16,100	5,410	26.4	23.9
8	78	63,600	9 + 9 + 9 + 9 + 9 + 9 + 9 + 15	7,300	7,300	7,300	7,300	7,300	7,300	7,300	12,200	4,690	22.8	20.6
		69,600	9 + 9 + 9 + 9 + 9 + 9 + 9 + 15	8,000	8,000	8,000	8,000	8,000	8,000	8,000	13,400	5,410	26.4	23.9

PRO-HEAT MODELS

NTXMPH36A142AB/NTXMPH36A142AA OPERATIONAL PERFORMANCE NON-DUCTED

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.5	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.5	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	15 + 15	15,000	15,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	15 + 15	18,500	18,500	0	0	0	0	0	0	3,470	17.0	15.3
2	33	33,000	9 + 24	9,000	24,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 24	11,200	29,700	0	0	0	0	0	0	3,990	19.5	17.6
2	33	33,000	15 + 18	15,000	18,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	15 + 18	18,600	22,300	0	0	0	0	0	0	3,990	19.5	17.6
2	36	36,000	6 + 30	6,000	30,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 30	7,300	37,700	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	12 + 24	12,000	24,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 24	15,000	30,000	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	18 + 18	18,000	18,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	18 + 18	22,500	22,500	0	0	0	0	0	0	4,500	22.0	19.9
2	39	36,000	9 + 30	8,300	27,700	0	0	0	0	0	0	3,080	15.0	13.6
		45,000	9 + 30	10,200	34,800	0	0	0	0	0	0	4,350	21.3	19.2
2	39	36,000	15 + 24	13,800	22,200	0	0	0	0	0	0	3,080	15.0	13.6
		45,000	15 + 24	17,300	27,700	0	0	0	0	0	0	4,350	21.3	19.2
2	42	36,000	6 + 36	5,100	30,900	0	0	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 36	6,200	38,800	0	0	0	0	0	0	4,200	20.5	18.6

PRO-HEAT MODELS

NTXMPH36A142AB/NTXMPH36A142AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	42	36,000	12 + 30	10,300	25,700	0	0	0	0	0	0	2,820	13.8	12.5
		45,000	12 + 30	12,600	32,400	0	0	0	0	0	0	4,200	20.5	18.6
2	42	36,000	18 + 24	15,400	20,600	0	0	0	0	0	0	2,820	13.8	12.5
		45,000	18 + 24	19,300	25,700	0	0	0	0	0	0	4,200	20.5	18.6
2	45	36,000	9 + 36	7,200	28,800	0	0	0	0	0	0	2,630	12.8	11.6
		45,000	9 + 36	8,700	36,300	0	0	0	0	0	0	4,010	19.6	17.7
2	45	36,000	15 + 30	12,000	24,000	0	0	0	0	0	0	2,630	12.8	11.6
		45,000	15 + 30	14,800	30,200	0	0	0	0	0	0	4,010	19.6	17.7
3	18	18,000	6 + 6 + 6	6,000	6,000	6,000	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 6 + 6	7,200	7,200	7,200	0	0	0	0	0	1,840	9.0	8.1
3	21	21,000	6 + 6 + 9	6,000	6,000	9,000	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 6 + 9	7,200	7,200	10,800	0	0	0	0	0	2,140	10.5	9.5
3	24	24,000	6 + 6 + 12	6,000	6,000	12,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 12	7,200	7,200	14,400	0	0	0	0	0	2,440	11.9	10.8
3	24	24,000	6 + 9 + 9	6,000	9,000	9,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 9 + 9	7,200	10,800	10,800	0	0	0	0	0	2,440	11.9	10.8
3	27	27,000	6 + 6 + 15	6,000	6,000	15,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 15	7,300	7,300	18,200	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	6 + 9 + 12	6,000	9,000	12,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 9 + 12	7,300	10,900	14,600	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	9 + 9 + 9	9,000	9,000	9,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 9 + 9	10,900	10,900	10,900	0	0	0	0	0	2,960	14.4	13.1
3	30	30,000	6 + 6 + 18	6,000	6,000	18,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 18	7,400	7,400	22,100	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 9 + 15	6,000	9,000	15,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 9 + 15	7,400	11,100	18,500	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 12 + 12	6,000	12,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 12 + 12	7,400	14,800	14,800	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	9 + 9 + 12	9,000	9,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	9 + 9 + 12	11,100	11,100	14,800	0	0	0	0	0	3,470	17.0	15.3
3	33	33,000	6 + 9 + 18	6,000	9,000	18,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 18	7,400	11,200	22,300	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	6 + 12 + 15	6,000	12,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 12 + 15	7,400	14,900	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 9 + 15	9,000	9,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 9 + 15	11,200	11,200	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 12 + 12	9,000	12,000	12,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 12 + 12	11,200	14,900	14,900	0	0	0	0	0	3,990	19.5	17.6
3	36	36,000	6 + 6 + 24	6,000	6,000	24,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 24	7,500	7,500	30,000	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 12 + 18	6,000	12,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 12 + 18	7,500	15,000	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 15 + 15	6,000	15,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 15 + 15	7,500	18,800	18,800	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 18	11,300	11,300	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 12 + 15	9,000	12,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 12 + 15	11,300	15,000	18,800	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	12 + 12 + 12	12,000	12,000	12,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 12 + 12	15,000	15,000	15,000	0	0	0	0	0	4,500	22.0	19.9
3	39	36,000	6 + 9 + 24	5,500	8,300	22,200	0	0	0	0	0	3,080	15.0	13.6
		45,000	6 + 9 + 24	6,900	10,400	27,700	0	0	0	0	0	4,350	21.3	19.2
3	39	36,000	6 + 15 + 18	5,500	13,800	16,600	0	0	0	0	0	3,080	15.0	13.6
		45,000	6 + 15 + 18	6,900	17,300	20,800	0	0	0	0	0	4,350	21.3	19.2
3	39	36,000	9 + 12 + 18	8,300	11,100	16,600	0	0	0	0	0	3,080	15.0	13.6
		45,000	9 + 12 + 18	10,400	13,800	20,800	0	0	0	0	0	4,350	21.3	19.2
3	39	36,000	9 + 15 + 15	8,300	13,800	13,800	0	0	0	0	0	3,080	15.0	13.6
		45,000	9 + 15 + 15	10,400	17,300	17,300	0	0	0	0	0	4,350	21.3	19.2
3	39	36,000	12 + 12 + 15	11,100	11,100	13,800	0	0	0	0	0	3,080	15.0	13.6
		45,000	12 + 12 + 15	13,800	13,800	17,300	0	0	0	0	0	4,350	21.3	19.2

PRO-HEAT MODELS

NTXMPH36A142AB/NTXMPH36A142AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	42	36,000	6 + 6 + 30	5,100	5,100	25,700	0	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 6 + 30	6,300	6,300	32,400	0	0	0	0	0	4,200	20.5	18.6
3	42	36,000	6 + 12 + 24	5,100	10,300	20,600	0	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 12 + 24	6,400	12,900	25,700	0	0	0	0	0	4,200	20.5	18.6
3	42	36,000	6 + 18 + 18	5,100	15,400	15,400	0	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 18 + 18	6,400	19,300	19,300	0	0	0	0	0	4,200	20.5	18.6
3	42	36,000	9 + 9 + 24	7,700	7,700	20,600	0	0	0	0	0	2,820	13.8	12.5
		45,000	9 + 9 + 24	9,600	9,600	25,700	0	0	0	0	0	4,200	20.5	18.6
3	42	36,000	9 + 15 + 18	7,700	12,900	15,400	0	0	0	0	0	2,820	13.8	12.5
		45,000	9 + 15 + 18	9,600	16,100	19,300	0	0	0	0	0	4,200	20.5	18.6
3	42	36,000	12 + 12 + 18	10,300	10,300	15,400	0	0	0	0	0	2,820	13.8	12.5
		45,000	12 + 12 + 18	12,900	12,900	19,300	0	0	0	0	0	4,200	20.5	18.6
3	42	36,000	12 + 15 + 15	10,300	12,900	12,900	0	0	0	0	0	2,820	13.8	12.5
		45,000	12 + 15 + 15	12,900	16,100	16,100	0	0	0	0	0	4,200	20.5	18.6
3	45	36,000	6 + 9 + 30	4,800	7,200	24,000	0	0	0	0	0	2,630	12.8	11.6
		45,000	6 + 9 + 30	5,900	8,900	30,200	0	0	0	0	0	4,010	19.6	17.7
3	45	36,000	6 + 15 + 24	4,800	12,000	19,200	0	0	0	0	0	2,630	12.8	11.6
		45,000	6 + 15 + 24	6,000	15,000	24,000	0	0	0	0	0	4,010	19.6	17.7
3	45	36,000	9 + 12 + 24	7,200	9,600	19,200	0	0	0	0	0	2,630	12.8	11.6
		45,000	9 + 12 + 24	9,000	12,000	24,000	0	0	0	0	0	4,010	19.6	17.7
3	45	36,000	9 + 18 + 18	7,200	14,400	14,400	0	0	0	0	0	2,630	12.8	11.6
		45,000	9 + 18 + 18	9,000	18,000	18,000	0	0	0	0	0	4,010	19.6	17.7
3	45	36,000	12 + 15 + 18	9,600	12,000	14,400	0	0	0	0	0	2,630	12.8	11.6
		45,000	12 + 15 + 18	12,000	15,000	18,000	0	0	0	0	0	4,010	19.6	17.7
3	45	36,000	15 + 15 + 15	12,000	12,000	12,000	0	0	0	0	0	2,630	12.8	11.6
		45,000	15 + 15 + 15	15,000	15,000	15,000	0	0	0	0	0	4,010	19.6	17.7
4	24	24,000	6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 6 + 6	7,200	7,200	7,200	7,200	0	0	0	0	2,440	11.9	10.8
4	27	27,000	6 + 6 + 6 + 9	6,000	6,000	6,000	9,000	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 6 + 9	7,300	7,300	7,300	10,900	0	0	0	0	2,960	14.4	13.1
4	30	30,000	6 + 6 + 6 + 12	6,000	6,000	6,000	12,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 6 + 12	7,400	7,400	7,400	14,800	0	0	0	0	3,470	17.0	15.3
4	30	30,000	6 + 6 + 9 + 9	6,000	6,000	9,000	9,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 9 + 9	7,400	7,400	11,100	11,100	0	0	0	0	3,470	17.0	15.3
4	33	33,000	6 + 6 + 6 + 15	6,000	6,000	6,000	15,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 6 + 15	7,400	7,400	7,400	18,600	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 6 + 9 + 12	6,000	6,000	9,000	12,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 9 + 12	7,400	7,400	11,200	14,900	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 9 + 9 + 9	6,000	9,000	9,000	9,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 9 + 9	7,400	11,200	11,200	11,200	0	0	0	0	3,990	19.5	17.6
4	36	36,000	6 + 6 + 6 + 18	6,000	6,000	6,000	18,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 18	7,500	7,500	7,500	22,500	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 6 + 9 + 15	6,000	6,000	9,000	15,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 9 + 15	7,500	7,500	11,300	18,800	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 6 + 12 + 12	6,000	6,000	12,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 12 + 12	7,500	7,500	15,000	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 9 + 9 + 12	6,000	9,000	9,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 9 + 9 + 12	7,500	11,300	11,300	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 9 + 9	11,300	11,300	11,300	11,300	0	0	0	0	4,500	22.0	19.9
4	39	36,000	6 + 6 + 9 + 18	5,500	5,500	8,300	16,600	0	0	0	0	3,080	15.0	13.6
		45,000	6 + 6 + 9 + 18	6,900	6,900	10,400	20,800	0	0	0	0	4,350	21.3	19.2
4	39	36,000	6 + 6 + 12 + 15	5,500	5,500	11,100	13,800	0	0	0	0	3,080	15.0	13.6
		45,000	6 + 6 + 12 + 15	6,900	6,900	13,800	17,300	0	0	0	0	4,350	21.3	19.2
4	39	36,000	6 + 9 + 9 + 15	5,500	8,300	8,300	13,800	0	0	0	0	3,080	15.0	13.6
		45,000	6 + 9 + 9 + 15	6,900	10,400	10,400	17,300	0	0	0	0	4,350	21.3	19.2
4	39	36,000	6 + 9 + 12 + 12	5,500	8,300	11,100	11,100	0	0	0	0	3,080	15.0	13.6
		45,000	6 + 9 + 12 + 12	6,900	10,400	13,800	13,800	0	0	0	0	4,350	21.3	19.2
4	39	36,000	9 + 9 + 9 + 12	8,300	8,300	8,300	11,100	0	0	0	0	3,080	15.0	13.6
		45,000	9 + 9 + 9 + 12	10,400	10,400	10,400	13,800	0	0	0	0	4,350	21.3	19.2

PRO-HEAT MODELS

NTXMPH36A142AB/NTXMPH36A142AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	42	36,000	6 + 6 + 6 + 24	5,100	5,100	5,100	20,600	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 6 + 6 + 24	6,400	6,400	6,400	25,700	0	0	0	0	4,200	20.5	18.6
4	42	36,000	6 + 6 + 12 + 18	5,100	5,100	10,300	15,400	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 6 + 12 + 18	6,400	6,400	12,900	19,300	0	0	0	0	4,200	20.5	18.6
4	42	36,000	6 + 6 + 15 + 15	5,100	5,100	12,900	12,900	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 6 + 15 + 15	6,400	6,400	16,100	16,100	0	0	0	0	4,200	20.5	18.6
4	42	36,000	6 + 9 + 9 + 18	5,100	7,700	7,700	15,400	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 9 + 9 + 18	6,400	9,600	9,600	19,300	0	0	0	0	4,200	20.5	18.6
4	42	36,000	6 + 9 + 12 + 15	5,100	7,700	10,300	12,900	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 9 + 12 + 15	6,400	9,600	12,900	16,100	0	0	0	0	4,200	20.5	18.6
4	42	36,000	6 + 12 + 12 + 12	5,100	10,300	10,300	10,300	0	0	0	0	2,820	13.8	12.5
		45,000	6 + 12 + 12 + 12	6,400	12,900	12,900	12,900	0	0	0	0	4,200	20.5	18.6
4	42	36,000	9 + 9 + 9 + 15	7,700	7,700	7,700	12,900	0	0	0	0	2,820	13.8	12.5
		45,000	9 + 9 + 9 + 15	9,600	9,600	9,600	16,100	0	0	0	0	4,200	20.5	18.6
4	42	36,000	9 + 9 + 12 + 12	7,700	7,700	10,300	10,300	0	0	0	0	2,820	13.8	12.5
		45,000	9 + 9 + 12 + 12	9,600	9,600	12,900	12,900	0	0	0	0	4,200	20.5	18.6
4	45	36,000	6 + 6 + 9 + 24	4,800	4,800	7,200	19,200	0	0	0	0	2,630	12.8	11.6
		45,000	6 + 6 + 9 + 24	6,000	6,000	9,000	24,000	0	0	0	0	4,010	19.6	17.7
4	45	36,000	6 + 6 + 15 + 18	4,800	4,800	12,000	14,400	0	0	0	0	2,630	12.8	11.6
		45,000	6 + 6 + 15 + 18	6,000	6,000	15,000	18,000	0	0	0	0	4,010	19.6	17.7
4	45	36,000	6 + 9 + 12 + 18	4,800	7,200	9,600	14,400	0	0	0	0	2,630	12.8	11.6
		45,000	6 + 9 + 12 + 18	6,000	9,000	12,000	18,000	0	0	0	0	4,010	19.6	17.7
4	45	36,000	6 + 12 + 12 + 15	4,800	9,600	9,600	12,000	0	0	0	0	2,630	12.8	11.6
		45,000	6 + 12 + 12 + 15	6,000	12,000	12,000	15,000	0	0	0	0	4,010	19.6	17.7
4	45	36,000	9 + 9 + 9 + 18	7,200	7,200	7,200	14,400	0	0	0	0	2,630	12.8	11.6
		45,000	9 + 9 + 9 + 18	9,000	9,000	9,000	18,000	0	0	0	0	4,010	19.6	17.7
4	45	36,000	9 + 9 + 12 + 15	7,200	7,200	9,600	12,000	0	0	0	0	2,630	12.8	11.6
		45,000	9 + 9 + 12 + 15	9,000	9,000	12,000	15,000	0	0	0	0	4,010	19.6	17.7
4	45	36,000	6 + 9 + 15 + 15	4,800	7,200	12,000	12,000	0	0	0	0	2,630	12.8	11.6
		45,000	6 + 9 + 15 + 15	6,000	9,000	15,000	15,000	0	0	0	0	4,010	19.6	17.7
4	45	36,000	9 + 12 + 12 + 12	7,200	9,600	9,600	9,600	0	0	0	0	2,630	12.8	11.6
		45,000	9 + 12 + 12 + 12	9,000	12,000	12,000	12,000	0	0	0	0	4,010	19.6	17.7

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.5	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.5	9.5
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	15 + 15	15,000	15,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	15 + 15	18,500	18,500	0	0	0	0	0	0	3,470	17.0	15.3
2	33	33,000	9 + 24	9,000	24,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 24	11,200	29,700	0	0	0	0	0	0	3,990	19.5	17.6
2	33	33,000	15 + 18	15,000	18,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	15 + 18	18,600	22,300	0	0	0	0	0	0	3,990	19.5	17.6
2	36	36,000	6 + 30	6,000	30,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 30	7,300	37,700	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	12 + 24	12,000	24,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 24	15,000	30,000	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	18 + 18	18,000	18,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	18 + 18	22,500	22,500	0	0	0	0	0	0	4,500	22.0	19.9
2	39	39,000	9 + 30	9,000	30,000	0	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 30	10,500	36,000	0	0	0	0	0	0	4,740	23.1	20.9
2	39	39,000	15 + 24	15,000	24,000	0	0	0	0	0	0	3,680	18.0	16.3
		46,500	15 + 24	17,900	28,600	0	0	0	0	0	0	4,740	23.1	20.9
2	42	42,000	6 + 36	6,000	36,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 36	6,600	41,400	0	0	0	0	0	0	4,980	24.3	22.0

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
2	42	42,000	12 + 30	12,000	30,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 30	13,500	34,500	0	0	0	0	0	0	4,980	24.3	22.0
2	42	42,000	18 + 24	18,000	24,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	18 + 24	20,600	27,400	0	0	0	0	0	0	4,980	24.3	22.0
2	45	42,000	9 + 36	8,400	33,600	0	0	0	0	0	0	3,740	18.3	16.5
		48,000	9 + 36	9,300	38,700	0	0	0	0	0	0	4,670	22.8	20.6
2	45	42,000	15 + 30	14,000	28,000	0	0	0	0	0	0	3,740	18.3	16.5
		48,000	15 + 30	15,700	32,300	0	0	0	0	0	0	4,670	22.8	20.6
2	48	42,000	12 + 36	10,500	31,500	0	0	0	0	0	0	3,460	16.9	15.3
		48,000	12 + 36	11,600	36,400	0	0	0	0	0	0	4,370	21.4	19.3
2	48	42,000	18 + 30	15,800	26,300	0	0	0	0	0	0	3,460	16.9	15.3
		48,000	18 + 30	17,700	30,300	0	0	0	0	0	0	4,370	21.4	19.3
2	48	42,000	24 + 24	21,000	21,000	0	0	0	0	0	0	3,460	16.9	15.3
		48,000	24 + 24	24,000	24,000	0	0	0	0	0	0	4,370	21.4	19.3
2	51	42,000	15 + 36	12,400	29,600	0	0	0	0	0	0	3,430	16.7	15.1
		48,000	15 + 36	13,700	34,300	0	0	0	0	0	0	4,320	21.1	19.1
2	54	42,000	18 + 36	14,000	28,000	0	0	0	0	0	0	3,400	16.6	15.0
		48,000	18 + 36	15,600	32,400	0	0	0	0	0	0	4,270	20.9	18.9
2	54	42,000	24 + 30	18,700	23,300	0	0	0	0	0	0	3,400	16.6	15.0
		48,000	24 + 30	21,000	27,000	0	0	0	0	0	0	4,270	20.9	18.9
3	18	18,000	6 + 6 + 6	6,000	6,000	6,000	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 6 + 6	7,200	7,200	7,200	0	0	0	0	0	1,840	9.0	8.1
3	21	21,000	6 + 6 + 9	6,000	6,000	9,000	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 6 + 9	7,200	7,200	10,800	0	0	0	0	0	2,140	10.5	9.5
3	24	24,000	6 + 6 + 12	6,000	6,000	12,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 12	7,200	7,200	14,400	0	0	0	0	0	2,440	11.9	10.8
3	24	24,000	6 + 9 + 9	6,000	9,000	9,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 9 + 9	7,200	10,800	10,800	0	0	0	0	0	2,440	11.9	10.8
3	27	27,000	6 + 6 + 15	6,000	6,000	15,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 15	7,300	7,300	18,200	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	6 + 9 + 12	6,000	9,000	12,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 9 + 12	7,300	10,900	14,600	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	9 + 9 + 9	9,000	9,000	9,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 9 + 9	10,900	10,900	10,900	0	0	0	0	0	2,960	14.4	13.1
3	30	30,000	6 + 6 + 18	6,000	6,000	18,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 18	7,400	7,400	22,100	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 9 + 15	6,000	9,000	15,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 9 + 15	7,400	11,100	18,500	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 12 + 12	6,000	12,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 12 + 12	7,400	14,800	14,800	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	9 + 9 + 12	9,000	9,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	9 + 9 + 12	11,100	11,100	14,800	0	0	0	0	0	3,470	17.0	15.3
3	33	33,000	6 + 9 + 18	6,000	9,000	18,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 18	7,400	11,200	22,300	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	6 + 12 + 15	6,000	12,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 12 + 15	7,400	14,900	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 9 + 15	9,000	9,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 9 + 15	11,200	11,200	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 12 + 12	9,000	12,000	12,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 12 + 12	11,200	14,900	14,900	0	0	0	0	0	3,990	19.5	17.6
3	36	36,000	6 + 6 + 24	6,000	6,000	24,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 24	7,500	7,500	30,000	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 12 + 18	6,000	12,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 12 + 18	7,500	15,000	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 15 + 15	6,000	15,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 15 + 15	7,500	18,800	18,800	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 18	11,300	11,300	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 12 + 15	9,000	12,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 12 + 15	11,300	15,000	18,800	0	0	0	0	0	4,500	22.0	19.9

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	36	36,000	12 + 12 + 12	12,000	12,000	12,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 12 + 12	15,000	15,000	15,000	0	0	0	0	0	4,500	22.0	19.9
3	39	39,000	6 + 9 + 24	6,000	9,000	24,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 24	7,200	10,700	28,600	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	6 + 15 + 18	6,000	15,000	18,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 15 + 18	7,200	17,900	21,500	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	9 + 12 + 18	9,000	12,000	18,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 12 + 18	10,700	14,300	21,500	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	9 + 15 + 15	9,000	15,000	15,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 15 + 15	10,700	17,900	17,900	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	12 + 12 + 15	12,000	12,000	15,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	12 + 12 + 15	14,300	14,300	17,900	0	0	0	0	0	4,740	23.1	20.9
3	42	42,000	6 + 6 + 30	6,000	6,000	30,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 30	6,700	6,700	34,500	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	6 + 12 + 24	6,000	12,000	24,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 12 + 24	6,900	13,700	27,400	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	6 + 18 + 18	6,000	18,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 18 + 18	6,900	20,600	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	9 + 9 + 24	9,000	9,000	24,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 24	10,300	10,300	27,400	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	9 + 15 + 18	9,000	15,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 15 + 18	10,300	17,100	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	12 + 12 + 18	12,000	12,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 12 + 18	13,700	13,700	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	12 + 15 + 15	12,000	15,000	15,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 15 + 15	13,700	17,100	17,100	0	0	0	0	0	4,980	24.3	22.0
3	45	42,000	6 + 9 + 30	5,600	8,400	28,000	0	0	0	0	0	3,740	18.3	16.5
		48,000	6 + 9 + 30	6,300	9,400	32,300	0	0	0	0	0	4,670	22.8	20.6
3	45	42,000	6 + 15 + 24	5,600	14,000	22,400	0	0	0	0	0	3,740	18.3	16.5
		48,000	6 + 15 + 24	6,400	16,000	25,600	0	0	0	0	0	4,670	22.8	20.6
3	45	42,000	9 + 12 + 24	8,400	11,200	22,400	0	0	0	0	0	3,740	18.3	16.5
		48,000	9 + 12 + 24	9,600	12,800	25,600	0	0	0	0	0	4,670	22.8	20.6
3	45	42,000	9 + 18 + 18	8,400	16,800	16,800	0	0	0	0	0	3,740	18.3	16.5
		48,000	9 + 18 + 18	9,600	19,200	19,200	0	0	0	0	0	4,670	22.8	20.6
3	45	42,000	12 + 15 + 18	11,200	14,000	16,800	0	0	0	0	0	3,740	18.3	16.5
		48,000	12 + 15 + 18	12,800	16,000	19,200	0	0	0	0	0	4,670	22.8	20.6
3	45	42,000	15 + 15 + 15	14,000	14,000	14,000	0	0	0	0	0	3,740	18.3	16.5
		48,000	15 + 15 + 15	16,000	16,000	16,000	0	0	0	0	0	4,670	22.8	20.6
3	48	42,000	6 + 6 + 36	5,300	5,300	31,500	0	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 36	5,800	5,800	36,400	0	0	0	0	0	4,370	21.4	19.3
3	48	42,000	6 + 12 + 30	5,300	10,500	26,300	0	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 12 + 30	5,900	11,800	30,300	0	0	0	0	0	4,370	21.4	19.3
3	48	42,000	6 + 18 + 24	5,300	15,800	21,000	0	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 18 + 24	6,000	18,000	24,000	0	0	0	0	0	4,370	21.4	19.3
3	48	42,000	9 + 9 + 30	7,900	7,900	26,300	0	0	0	0	0	3,460	16.9	15.3
		48,000	9 + 9 + 30	8,900	8,900	30,300	0	0	0	0	0	4,370	21.4	19.3
3	48	42,000	9 + 15 + 24	7,900	13,100	21,000	0	0	0	0	0	3,460	16.9	15.3
		48,000	9 + 15 + 24	9,000	15,000	24,000	0	0	0	0	0	4,370	21.4	19.3
3	48	42,000	12 + 12 + 24	10,500	10,500	21,000	0	0	0	0	0	3,460	16.9	15.3
		48,000	12 + 12 + 24	12,000	12,000	24,000	0	0	0	0	0	4,370	21.4	19.3
3	48	42,000	12 + 18 + 18	10,500	15,800	15,800	0	0	0	0	0	3,460	16.9	15.3
		48,000	12 + 18 + 18	12,000	18,000	18,000	0	0	0	0	0	4,370	21.4	19.3
3	48	42,000	15 + 15 + 18	13,100	13,100	15,800	0	0	0	0	0	3,460	16.9	15.3
		48,000	15 + 15 + 18	15,000	15,000	18,000	0	0	0	0	0	4,370	21.4	19.3
3	51	42,000	6 + 9 + 36	4,900	7,400	29,600	0	0	0	0	0	3,430	16.7	15.1
		48,000	6 + 9 + 36	5,500	8,200	34,300	0	0	0	0	0	4,320	21.1	19.1
3	51	42,000	6 + 15 + 30	4,900	12,400	24,700	0	0	0	0	0	3,430	16.7	15.1
		48,000	6 + 15 + 30	5,600	13,900	28,500	0	0	0	0	0	4,320	21.1	19.1
3	51	42,000	9 + 12 + 30	7,400	9,900	24,700	0	0	0	0	0	3,430	16.7	15.1
		48,000	9 + 12 + 30	8,300	11,100	28,500	0	0	0	0	0	4,320	21.1	19.1

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	51	42,000	9 + 18 + 24	7,400	14,800	19,800	0	0	0	0	0	3,430	16.7	15.1
		48,000	9 + 18 + 24	8,500	16,900	22,600	0	0	0	0	0	4,320	21.1	19.1
3	51	42,000	12 + 15 + 24	9,900	12,400	19,800	0	0	0	0	0	3,430	16.7	15.1
		48,000	12 + 15 + 24	11,300	14,100	22,600	0	0	0	0	0	4,320	21.1	19.1
3	51	42,000	15 + 18 + 18	12,400	14,800	14,800	0	0	0	0	0	3,430	16.7	15.1
		48,000	15 + 18 + 18	14,100	16,900	16,900	0	0	0	0	0	4,320	21.1	19.1
3	54	42,000	6 + 12 + 36	4,700	9,300	28,000	0	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 12 + 36	5,200	10,400	32,400	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	6 + 18 + 30	4,700	14,000	23,300	0	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 18 + 30	5,300	15,800	27,000	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	6 + 24 + 24	4,700	18,700	18,700	0	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 24 + 24	5,300	21,300	21,300	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	9 + 9 + 36	7,000	7,000	28,000	0	0	0	0	0	3,400	16.6	15.0
		48,000	9 + 9 + 36	7,800	7,800	32,400	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	9 + 15 + 30	7,000	11,700	23,300	0	0	0	0	0	3,400	16.6	15.0
		48,000	9 + 15 + 30	7,900	13,200	27,000	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	12 + 12 + 30	9,300	9,300	23,300	0	0	0	0	0	3,400	16.6	15.0
		48,000	12 + 12 + 30	10,500	10,500	27,000	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	12 + 18 + 24	9,300	14,000	18,700	0	0	0	0	0	3,400	16.6	15.0
		48,000	12 + 18 + 24	10,700	16,000	21,300	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	15 + 15 + 24	11,700	11,700	18,700	0	0	0	0	0	3,400	16.6	15.0
		48,000	15 + 15 + 24	13,300	13,300	21,300	0	0	0	0	0	4,270	20.9	18.9
3	54	42,000	18 + 18 + 18	14,000	14,000	14,000	0	0	0	0	0	3,400	16.6	15.0
		48,000	18 + 18 + 18	16,000	16,000	16,000	0	0	0	0	0	4,270	20.9	18.9
4	24	24,000	6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 6 + 6	7,200	7,200	7,200	7,200	0	0	0	0	2,440	11.9	10.8
4	27	27,000	6 + 6 + 6 + 9	6,000	6,000	6,000	9,000	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 6 + 9	7,300	7,300	7,300	10,900	0	0	0	0	2,960	14.4	13.1
4	30	30,000	6 + 6 + 6 + 12	6,000	6,000	6,000	12,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 6 + 12	7,400	7,400	7,400	14,800	0	0	0	0	3,470	17.0	15.3
4	30	30,000	6 + 6 + 9 + 9	6,000	6,000	9,000	9,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 9 + 9	7,400	7,400	11,100	11,100	0	0	0	0	3,470	17.0	15.3
4	33	33,000	6 + 6 + 6 + 15	6,000	6,000	6,000	15,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 6 + 15	7,400	7,400	7,400	18,600	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 6 + 9 + 12	6,000	6,000	9,000	12,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 9 + 12	7,400	7,400	11,200	14,900	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 9 + 9 + 9	6,000	9,000	9,000	9,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 9 + 9	7,400	11,200	11,200	11,200	0	0	0	0	3,990	19.5	17.6
4	36	36,000	6 + 6 + 6 + 18	6,000	6,000	6,000	18,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 18	7,500	7,500	7,500	22,500	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 6 + 9 + 15	6,000	6,000	9,000	15,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 9 + 15	7,500	7,500	11,300	18,800	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 6 + 12 + 12	6,000	6,000	12,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 12 + 12	7,500	7,500	15,000	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 9 + 9 + 12	6,000	9,000	9,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 9 + 9 + 12	7,500	11,300	11,300	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 9 + 9	11,300	11,300	11,300	11,300	0	0	0	0	4,500	22.0	19.9
4	39	39,000	6 + 6 + 9 + 18	6,000	6,000	9,000	18,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 9 + 18	7,200	7,200	10,700	21,500	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 6 + 12 + 15	6,000	6,000	12,000	15,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 12 + 15	7,200	7,200	14,300	17,900	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 9 + 9 + 15	6,000	9,000	9,000	15,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 9 + 15	7,200	10,700	10,700	17,900	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 9 + 12 + 12	6,000	9,000	12,000	12,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 12 + 12	7,200	10,700	14,300	14,300	0	0	0	0	4,740	23.1	20.9

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	39	39,000	9 + 9 + 9 + 12	9,000	9,000	9,000	12,000	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 9 + 9 + 12	10,700	10,700	10,700	14,300	0	0	0	0	4,740	23.1	20.9
4	42	42,000	6 + 6 + 6 + 24	6,000	6,000	6,000	24,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 24	6,900	6,900	6,900	27,400	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 6 + 12 + 18	6,000	6,000	12,000	18,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 12 + 18	6,900	6,900	13,700	20,600	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 6 + 15 + 15	6,000	6,000	15,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 15 + 15	6,900	6,900	17,100	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 9 + 9 + 18	6,000	9,000	9,000	18,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 9 + 18	6,900	10,300	10,300	20,600	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 9 + 12 + 15	6,000	9,000	12,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 12 + 15	6,900	10,300	13,700	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 12 + 12 + 12	6,000	12,000	12,000	12,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 12 + 12 + 12	6,900	13,700	13,700	13,700	0	0	0	0	4,980	24.3	22.0
4	42	42,000	9 + 9 + 9 + 15	9,000	9,000	9,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 9 + 15	10,300	10,300	10,300	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	9 + 9 + 12 + 12	9,000	9,000	12,000	12,000	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 12 + 12	10,300	10,300	13,700	13,700	0	0	0	0	4,980	24.3	22.0
4	45	42,000	6 + 6 + 9 + 24	5,600	5,600	8,400	22,400	0	0	0	0	3,740	18.3	16.5
		48,000	6 + 6 + 9 + 24	6,400	6,400	9,600	25,600	0	0	0	0	4,670	22.8	20.6
4	45	42,000	6 + 6 + 15 + 18	5,600	5,600	14,000	16,800	0	0	0	0	3,740	18.3	16.5
		48,000	6 + 6 + 15 + 18	6,400	6,400	16,000	19,200	0	0	0	0	4,670	22.8	20.6
4	45	42,000	6 + 9 + 12 + 18	5,600	8,400	11,200	16,800	0	0	0	0	3,740	18.3	16.5
		48,000	6 + 9 + 12 + 18	6,400	9,600	12,800	19,200	0	0	0	0	4,670	22.8	20.6
4	45	42,000	6 + 9 + 15 + 15	5,600	8,400	14,000	14,000	0	0	0	0	3,740	18.3	16.5
		48,000	6 + 9 + 15 + 15	6,400	9,600	16,000	16,000	0	0	0	0	4,670	22.8	20.6
4	45	42,000	6 + 12 + 12 + 15	5,600	11,200	11,200	14,000	0	0	0	0	3,740	18.3	16.5
		48,000	6 + 12 + 12 + 15	6,400	12,800	12,800	16,000	0	0	0	0	4,670	22.8	20.6
4	45	42,000	9 + 9 + 9 + 18	8,400	8,400	8,400	16,800	0	0	0	0	3,740	18.3	16.5
		48,000	9 + 9 + 9 + 18	9,600	9,600	9,600	19,200	0	0	0	0	4,670	22.8	20.6
4	45	42,000	9 + 9 + 12 + 15	8,400	8,400	11,200	14,000	0	0	0	0	3,740	18.3	16.5
		48,000	9 + 9 + 12 + 15	9,600	9,600	12,800	16,000	0	0	0	0	4,670	22.8	20.6
4	45	42,000	9 + 12 + 12 + 12	8,400	11,200	11,200	11,200	0	0	0	0	3,740	18.3	16.5
		48,000	9 + 12 + 12 + 12	9,600	12,800	12,800	12,800	0	0	0	0	4,670	22.8	20.6
4	48	42,000	6 + 6 + 6 + 30	5,300	5,300	5,300	26,300	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 6 + 30	5,900	5,900	5,900	30,300	0	0	0	0	4,370	21.4	19.3
4	48	42,000	6 + 6 + 12 + 24	5,300	5,300	10,500	21,000	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 12 + 24	6,000	6,000	12,000	24,000	0	0	0	0	4,370	21.4	19.3
4	48	42,000	6 + 6 + 18 + 18	5,300	5,300	15,800	15,800	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 18 + 18	6,000	6,000	18,000	18,000	0	0	0	0	4,370	21.4	19.3
4	48	42,000	6 + 9 + 9 + 24	5,300	7,900	7,900	21,000	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 9 + 9 + 24	6,000	9,000	9,000	24,000	0	0	0	0	4,370	21.4	19.3
4	48	42,000	6 + 9 + 15 + 18	5,300	7,900	13,100	15,800	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 9 + 15 + 18	6,000	9,000	15,000	18,000	0	0	0	0	4,370	21.4	19.3
4	48	42,000	6 + 12 + 12 + 18	5,300	10,500	10,500	15,800	0	0	0	0	3,460	16.9	15.3
		48,000	6 + 12 + 12 + 18	6,000	12,000	12,000	18,000	0	0	0	0	4,370	21.4	19.3
4	48	42,000	9 + 9 + 12 + 18	7,900	7,900	10,500	15,800	0	0	0	0	3,460	16.9	15.3
		48,000	9 + 9 + 12 + 18	9,000	9,000	12,000	18,000	0	0	0	0	4,370	21.4	19.3

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	48	42,000	9 + 12 + 12 + 15	7,900	10,500	10,500	13,100	0	0	0	0	3,460	16.9	15.3
		48,000	9 + 12 + 12 + 15	9,000	12,000	12,000	15,000	0	0	0	0	4,370	21.4	19.3
4	48	42,000	12 + 12 + 12 + 12	10,500	10,500	10,500	10,500	0	0	0	0	3,460	16.9	15.3
		48,000	12 + 12 + 12 + 12	12,000	12,000	12,000	12,000	0	0	0	0	4,370	21.4	19.3
4	51	42,000	6 + 6 + 9 + 30	4,900	4,900	7,400	24,700	0	0	0	0	3,430	16.7	15.1
		48,000	6 + 6 + 9 + 30	5,600	5,600	8,300	28,500	0	0	0	0	4,320	21.1	19.1
4	51	42,000	6 + 6 + 15 + 24	4,900	4,900	12,400	19,800	0	0	0	0	3,430	16.7	15.1
		48,000	6 + 6 + 15 + 24	5,600	5,600	14,100	22,600	0	0	0	0	4,320	21.1	19.1
4	51	42,000	6 + 9 + 12 + 24	4,900	7,400	9,900	19,800	0	0	0	0	3,430	16.7	15.1
		48,000	6 + 9 + 12 + 24	5,600	8,500	11,300	22,600	0	0	0	0	4,320	21.1	19.1
4	51	42,000	6 + 9 + 18 + 18	4,900	7,400	14,800	14,800	0	0	0	0	3,430	16.7	15.1
		48,000	6 + 9 + 18 + 18	5,600	8,500	16,900	16,900	0	0	0	0	4,320	21.1	19.1
4	51	42,000	6 + 15 + 15 + 15	4,900	12,400	12,400	12,400	0	0	0	0	3,430	16.7	15.1
		48,000	6 + 15 + 15 + 15	5,600	14,100	14,100	14,100	0	0	0	0	4,320	21.1	19.1
4	51	42,000	9 + 9 + 9 + 24	7,400	7,400	7,400	19,800	0	0	0	0	3,430	16.7	15.1
		48,000	9 + 9 + 9 + 24	8,500	8,500	8,500	22,600	0	0	0	0	4,320	21.1	19.1
4	51	42,000	9 + 12 + 12 + 18	7,400	9,900	9,900	14,800	0	0	0	0	3,430	16.7	15.1
		48,000	9 + 12 + 12 + 18	8,500	11,300	11,300	16,900	0	0	0	0	4,320	21.1	19.1
4	51	42,000	12 + 12 + 12 + 15	9,900	9,900	9,900	12,400	0	0	0	0	3,430	16.7	15.1
		48,000	12 + 12 + 12 + 15	11,300	11,300	11,300	14,100	0	0	0	0	4,320	21.1	19.1
4	51	42,000	9 + 9 + 15 + 18	7,400	7,400	12,400	14,800	0	0	0	0	3,430	16.7	15.1
		48,000	9 + 9 + 15 + 18	8,500	8,500	14,100	16,900	0	0	0	0	4,320	21.1	19.1
4	54	42,000	6 + 6 + 6 + 36	4,700	4,700	4,700	28,000	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 6 + 36	5,200	5,200	5,200	32,400	0	0	0	0	4,270	20.9	18.9
4	54	42,000	6 + 6 + 12 + 30	4,700	4,700	9,300	23,300	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 12 + 30	5,300	5,300	10,500	27,000	0	0	0	0	4,270	20.9	18.9
4	54	42,000	6 + 6 + 18 + 24	4,700	4,700	14,000	18,700	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 18 + 24	5,300	5,300	16,000	21,300	0	0	0	0	4,270	20.9	18.9
4	54	42,000	6 + 9 + 9 + 30	4,700	7,000	7,000	23,300	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 9 + 9 + 30	5,300	7,900	7,900	27,000	0	0	0	0	4,270	20.9	18.9
4	54	42,000	6 + 9 + 15 + 24	4,700	7,000	11,700	18,700	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 9 + 15 + 24	5,300	8,000	13,300	21,300	0	0	0	0	4,270	20.9	18.9
4	54	42,000	6 + 12 + 12 + 24	4,700	9,300	9,300	18,700	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 12 + 12 + 24	5,300	10,700	10,700	21,300	0	0	0	0	4,270	20.9	18.9
4	54	42,000	6 + 15 + 15 + 18	4,700	11,700	11,700	14,000	0	0	0	0	3,400	16.6	15.0
		48,000	6 + 15 + 15 + 18	5,300	13,300	13,300	16,000	0	0	0	0	4,270	20.9	18.9
4	54	42,000	9 + 9 + 12 + 24	7,000	7,000	9,300	18,700	0	0	0	0	3,400	16.6	15.0
		48,000	9 + 9 + 12 + 24	8,000	8,000	10,700	21,300	0	0	0	0	4,270	20.9	18.9
4	54	42,000	12 + 12 + 15 + 15	9,300	9,300	11,700	11,700	0	0	0	0	3,400	16.6	15.0
		48,000	12 + 12 + 15 + 15	10,700	10,700	13,300	13,300	0	0	0	0	4,270	20.9	18.9
5	30	30,000	6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 6 + 6 + 6	7,400	7,400	7,400	7,400	7,400	0	0	0	3,470	17.0	15.3

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	33	33,000	6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	9,000	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 6 + 6 + 9	7,400	7,400	7,400	7,400	11,200	0	0	0	3,990	19.5	17.6
5	36	36,000	6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	12,000	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 6 + 12	7,500	7,500	7,500	7,500	15,000	0	0	0	4,500	22.0	19.9
5	36	36,000	6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	9,000	9,000	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 9 + 9	7,500	7,500	7,500	11,300	11,300	0	0	0	4,500	22.0	19.9
5	39	39,000	6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	15,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 6 + 15	7,200	7,200	7,200	7,200	17,900	0	0	0	4,740	23.1	20.9
5	39	39,000	6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	9,000	12,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 9 + 12	7,200	7,200	7,200	10,700	14,300	0	0	0	4,740	23.1	20.9
5	39	39,000	6 + 6 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 9 + 9 + 9	7,200	7,200	10,700	10,700	10,700	0	0	0	4,740	23.1	20.9
5	42	42,000	6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	18,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 6 + 18	6,900	6,900	6,900	6,900	20,600	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	9,000	15,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 9 + 15	6,900	6,900	6,900	10,300	17,100	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	12,000	12,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 12 + 12	6,900	6,900	6,900	13,700	13,700	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 9 + 9 + 12	6,000	6,000	9,000	9,000	12,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 9 + 9 + 12	6,900	6,900	10,300	10,300	13,700	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 9 + 9 + 9 + 9	6,000	9,000	9,000	9,000	9,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 9 + 9 + 9	6,900	10,300	10,300	10,300	10,300	0	0	0	4,980	24.3	22.0
5	45	42,000	6 + 6 + 6 + 9 + 18	5,600	5,600	5,600	8,400	16,800	0	0	0	3,740	18.3	16.5
		48,000	6 + 6 + 6 + 9 + 18	6,400	6,400	6,400	9,600	19,200	0	0	0	4,670	22.8	20.6
5	45	42,000	6 + 6 + 6 + 12 + 15	5,600	5,600	5,600	11,200	14,000	0	0	0	3,740	18.3	16.5
		48,000	6 + 6 + 6 + 12 + 15	6,400	6,400	6,400	12,800	16,000	0	0	0	4,670	22.8	20.6
5	45	42,000	6 + 6 + 9 + 9 + 15	5,600	5,600	8,400	8,400	14,000	0	0	0	3,740	18.3	16.5
		48,000	6 + 6 + 9 + 9 + 15	6,400	6,400	9,600	9,600	16,000	0	0	0	4,670	22.8	20.6

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	45	42,000	6 + 6 + 9 + 12 + 12	5,600	5,600	8,400	11,200	11,200	0	0	0	3,740	18.3	16.5
		48,000	6 + 6 + 9 + 12 + 12	6,400	6,400	9,600	12,800	12,800	0	0	0	4,670	22.8	20.6
5	45	42,000	6 + 9 + 9 + 9 + 12	5,600	8,400	8,400	8,400	11,200	0	0	0	3,740	18.3	16.5
		48,000	6 + 9 + 9 + 9 + 12	6,400	9,600	9,600	9,600	12,800	0	0	0	4,670	22.8	20.6
5	45	42,000	9 + 9 + 9 + 9 + 9	8,400	8,400	8,400	8,400	8,400	0	0	0	3,740	18.3	16.5
		48,000	9 + 9 + 9 + 9 + 9	9,600	9,600	9,600	9,600	9,600	0	0	0	4,670	22.8	20.6
5	48	42,000	6 + 6 + 6 + 6 + 24	5,300	5,300	5,300	5,300	21,000	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	24,000	0	0	0	4,370	21.4	19.3
5	48	42,000	6 + 6 + 6 + 12 + 18	5,300	5,300	5,300	10,500	15,800	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	12,000	18,000	0	0	0	4,370	21.4	19.3
5	48	42,000	6 + 6 + 6 + 15 + 15	5,300	5,300	5,300	13,100	13,100	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	15,000	15,000	0	0	0	4,370	21.4	19.3
5	48	42,000	6 + 6 + 9 + 9 + 18	5,300	5,300	7,900	7,900	15,800	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 9 + 9 + 18	6,000	6,000	9,000	9,000	18,000	0	0	0	4,370	21.4	19.3
5	48	42,000	6 + 6 + 9 + 12 + 15	5,300	5,300	7,900	10,500	13,100	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 9 + 12 + 15	6,000	6,000	9,000	12,000	15,000	0	0	0	4,370	21.4	19.3
5	48	42,000	6 + 6 + 12 + 12 + 12	5,300	5,300	10,500	10,500	10,500	0	0	0	3,460	16.9	15.3
		48,000	6 + 6 + 12 + 12 + 12	6,000	6,000	12,000	12,000	12,000	0	0	0	4,370	21.4	19.3
5	48	42,000	6 + 9 + 9 + 9 + 15	5,300	7,900	7,900	7,900	13,100	0	0	0	3,460	16.9	15.3
		48,000	6 + 9 + 9 + 9 + 15	6,000	9,000	9,000	9,000	15,000	0	0	0	4,370	21.4	19.3
5	48	42,000	6 + 9 + 9 + 12 + 12	5,300	7,900	7,900	10,500	10,500	0	0	0	3,460	16.9	15.3
		48,000	6 + 9 + 9 + 12 + 12	6,000	9,000	9,000	12,000	12,000	0	0	0	4,370	21.4	19.3
5	48	42,000	9 + 9 + 9 + 9 + 12	7,900	7,900	7,900	7,900	10,500	0	0	0	3,460	16.9	15.3
		48,000	9 + 9 + 9 + 9 + 12	9,000	9,000	9,000	9,000	12,000	0	0	0	4,370	21.4	19.3
5	51	42,000	6 + 6 + 6 + 9 + 24	4,900	4,900	4,900	7,400	19,800	0	0	0	3,430	16.7	15.1
		48,000	6 + 6 + 6 + 9 + 24	5,600	5,600	5,600	8,500	22,600	0	0	0	4,320	21.1	19.1
5	51	42,000	6 + 6 + 6 + 15 + 18	4,900	4,900	4,900	12,400	14,800	0	0	0	3,430	16.7	15.1
		48,000	6 + 6 + 6 + 15 + 18	5,600	5,600	5,600	14,100	16,900	0	0	0	4,320	21.1	19.1

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	51	42,000	6 + 6 + 9 + 12 + 18	4,900	4,900	7,400	9,900	14,800	0	0	0	3,430	16.7	15.1
		48,000	6 + 6 + 9 + 12 + 18	5,600	5,600	8,500	11,300	16,900	0	0	0	4,320	21.1	19.1
5	51	42,000	6 + 6 + 9 + 15 + 15	4,900	4,900	7,400	12,400	12,400	0	0	0	3,430	16.7	15.1
		48,000	6 + 6 + 9 + 15 + 15	5,600	5,600	8,500	14,100	14,100	0	0	0	4,320	21.1	19.1
5	51	42,000	6 + 6 + 12 + 12 + 15	4,900	4,900	9,900	9,900	12,400	0	0	0	3,430	16.7	15.1
		48,000	6 + 6 + 12 + 12 + 15	5,600	5,600	11,300	11,300	14,100	0	0	0	4,320	21.1	19.1
5	51	42,000	6 + 9 + 9 + 9 + 18	4,900	7,400	7,400	7,400	14,800	0	0	0	3,430	16.7	15.1
		48,000	6 + 9 + 9 + 9 + 18	5,600	8,500	8,500	8,500	16,900	0	0	0	4,320	21.1	19.1
5	51	42,000	6 + 9 + 9 + 12 + 15	4,900	7,400	7,400	9,900	12,400	0	0	0	3,430	16.7	15.1
		48,000	6 + 9 + 9 + 12 + 15	5,600	8,500	8,500	11,300	14,100	0	0	0	4,320	21.1	19.1
5	51	42,000	6 + 9 + 12 + 12 + 12	4,900	7,400	9,900	9,900	9,900	0	0	0	3,430	16.7	15.1
		48,000	6 + 9 + 12 + 12 + 12	5,600	8,500	11,300	11,300	11,300	0	0	0	4,320	21.1	19.1
5	51	42,000	9 + 9 + 9 + 9 + 15	7,400	7,400	7,400	7,400	12,400	0	0	0	3,430	16.7	15.1
		48,000	9 + 9 + 9 + 9 + 15	8,500	8,500	8,500	8,500	14,100	0	0	0	4,320	21.1	19.1
5	51	42,000	9 + 9 + 9 + 12 + 12	7,400	7,400	7,400	9,900	9,900	0	0	0	3,430	16.7	15.1
		48,000	9 + 9 + 9 + 12 + 12	8,500	8,500	8,500	11,300	11,300	0	0	0	4,320	21.1	19.1
5	54	42,000	6 + 6 + 6 + 6 + 30	4,700	4,700	4,700	4,700	23,300	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 6 + 6 + 30	5,300	5,300	5,300	5,300	27,000	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 6 + 6 + 12 + 24	4,700	4,700	4,700	9,300	18,700	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 6 + 12 + 24	5,300	5,300	5,300	10,700	21,300	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 6 + 6 + 18 + 18	4,700	4,700	4,700	14,000	14,000	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 6 + 18 + 18	5,300	5,300	5,300	16,000	16,000	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 6 + 9 + 9 + 24	4,700	4,700	7,000	7,000	18,700	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 9 + 9 + 24	5,300	5,300	8,000	8,000	21,300	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 6 + 9 + 15 + 18	4,700	4,700	7,000	11,700	14,000	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 9 + 15 + 18	5,300	5,300	8,000	13,300	16,000	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 6 + 12 + 12 + 18	4,700	4,700	9,300	9,300	14,000	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 12 + 12 + 18	5,300	5,300	10,700	10,700	16,000	0	0	0	4,270	20.9	18.9

PRO-HEAT MODELS

NTXMPH42A152AB/NTXMPH42A152AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	54	42,000	6 + 6 + 12 + 15 + 15	4,700	4,700	9,300	11,700	11,700	0	0	0	3,400	16.6	15.0
		48,000	6 + 6 + 12 + 15 + 15	5,300	5,300	10,700	13,300	13,300	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 9 + 9 + 12 + 18	4,700	7,000	7,000	9,300	14,000	0	0	0	3,400	16.6	15.0
		48,000	6 + 9 + 9 + 12 + 18	5,300	8,000	8,000	10,700	16,000	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 9 + 9 + 15 + 15	4,700	7,000	7,000	11,700	11,700	0	0	0	3,400	16.6	15.0
		48,000	6 + 9 + 9 + 15 + 15	5,300	8,000	8,000	13,300	13,300	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 9 + 12 + 12 + 15	4,700	7,000	9,300	9,300	11,700	0	0	0	3,400	16.6	15.0
		48,000	6 + 9 + 12 + 12 + 15	5,300	8,000	10,700	10,700	13,300	0	0	0	4,270	20.9	18.9
5	54	42,000	6 + 12 + 12 + 12 + 12	4,700	9,300	9,300	9,300	9,300	0	0	0	3,400	16.6	15.0
		48,000	6 + 12 + 12 + 12 + 12	5,300	10,700	10,700	10,700	10,700	0	0	0	4,270	20.9	18.9
5	54	42,000	9 + 9 + 9 + 9 + 18	7,000	7,000	7,000	7,000	14,000	0	0	0	3,400	16.6	15.0
		48,000	9 + 9 + 9 + 9 + 18	8,000	8,000	8,000	8,000	16,000	0	0	0	4,270	20.9	18.9
5	54	42,000	9 + 9 + 9 + 12 + 15	7,000	7,000	7,000	9,300	11,700	0	0	0	3,400	16.6	15.0
		48,000	9 + 9 + 9 + 12 + 15	8,000	8,000	8,000	10,700	13,300	0	0	0	4,270	20.9	18.9
5	54	42,000	9 + 9 + 12 + 12 + 12	7,000	7,000	9,300	9,300	9,300	0	0	0	3,400	16.6	15.0
		48,000	9 + 9 + 12 + 12 + 12	8,000	8,000	10,700	10,700	10,700	0	0	0	4,270	20.9	18.9

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
1	6	6,000	6	6,000	0	0	0	0	0	0	0	600	2.9	2.7
		7,200	6	7,200	0	0	0	0	0	0	0	600	2.9	2.7
1	9	9,000	9	9,000	0	0	0	0	0	0	0	690	3.4	3.1
		10,800	9	10,800	0	0	0	0	0	0	0	910	4.5	4.0
1	12	12,000	12	12,000	0	0	0	0	0	0	0	780	3.8	3.5
		14,400	12	14,400	0	0	0	0	0	0	0	1,230	6.0	5.4
2	12	12,000	6 + 6	6,000	6,000	0	0	0	0	0	0	780	3.8	3.5
		14,400	6 + 6	7,200	7,200	0	0	0	0	0	0	1,230	6.0	5.4
1	15	15,000	15	15,000	0	0	0	0	0	0	0	980	4.8	4.3
		18,000	15	18,000	0	0	0	0	0	0	0	1,530	7.5	6.8
2	15	15,000	6 + 9	6,000	9,000	0	0	0	0	0	0	980	4.8	4.3
		18,000	6 + 9	7,200	10,800	0	0	0	0	0	0	1,530	7.5	6.8
1	18	18,000	18	18,000	0	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	18	21,600	0	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	6 + 12	6,000	12,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 12	7,200	14,400	0	0	0	0	0	0	1,840	9.0	8.1
2	18	18,000	9 + 9	9,000	9,000	0	0	0	0	0	0	1,170	5.7	5.2
		21,600	9 + 9	10,800	10,800	0	0	0	0	0	0	1,840	9.0	8.1
3	18	18,000	6 + 6 + 6	6,000	6,000	6,000	0	0	0	0	0	1,170	5.7	5.2
		21,600	6 + 6 + 6	7,200	7,200	7,200	0	0	0	0	0	1,840	9.0	8.1
2	21	21,000	6 + 15	6,000	15,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 15	7,200	18,000	0	0	0	0	0	0	2,140	10.4	9.5
2	21	21,000	9 + 12	9,000	12,000	0	0	0	0	0	0	1,370	6.7	6.0
		25,200	9 + 12	10,800	14,400	0	0	0	0	0	0	2,140	10.4	9.5
3	21	21,000	6 + 6 + 9	6,000	6,000	9,000	0	0	0	0	0	1,370	6.7	6.0
		25,200	6 + 6 + 9	7,200	7,200	10,800	0	0	0	0	0	2,140	10.4	9.5
1	24	24,000	24	24,000	0	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	24	28,800	0	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	6 + 18	6,000	18,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 18	7,200	21,600	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	9 + 15	9,000	15,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	9 + 15	10,800	18,000	0	0	0	0	0	0	2,440	11.9	10.8
2	24	24,000	12 + 12	12,000	12,000	0	0	0	0	0	0	1,560	7.6	6.9
		28,800	12 + 12	14,400	14,400	0	0	0	0	0	0	2,440	11.9	10.8
3	24	24,000	6 + 6 + 12	6,000	6,000	12,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 12	7,200	7,200	14,400	0	0	0	0	0	2,440	11.9	10.8
3	24	24,000	6 + 9 + 9	6,000	9,000	9,000	0	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 9 + 9	7,200	10,800	10,800	0	0	0	0	0	2,440	11.9	10.8
4	24	24,000	6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	0	0	0	0	1,560	7.6	6.9
		28,800	6 + 6 + 6 + 6	7,200	7,200	7,200	7,200	0	0	0	0	2,440	11.9	10.8
2	27	27,000	9 + 18	9,000	18,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 18	10,900	21,900	0	0	0	0	0	0	2,960	14.4	13.1
2	27	27,000	12 + 15	12,000	15,000	0	0	0	0	0	0	2,010	9.8	8.9
		32,800	12 + 15	14,600	18,200	0	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	6 + 6 + 15	6,000	6,000	15,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 15	7,300	7,300	18,200	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	6 + 9 + 12	6,000	9,000	12,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 9 + 12	7,300	10,900	14,600	0	0	0	0	0	2,960	14.4	13.1
3	27	27,000	9 + 9 + 9	9,000	9,000	9,000	0	0	0	0	0	2,010	9.8	8.9
		32,800	9 + 9 + 9	10,900	10,900	10,900	0	0	0	0	0	2,960	14.4	13.1
4	27	27,000	6 + 6 + 6 + 9	6,000	6,000	6,000	9,000	0	0	0	0	2,010	9.8	8.9
		32,800	6 + 6 + 6 + 9	7,300	7,300	7,300	10,900	0	0	0	0	2,960	14.4	13.1
1	30	30,000	30	30,000	0	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	30	36,900	0	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	6 + 24	6,000	24,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 24	7,400	29,500	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	12 + 18	12,000	18,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	12 + 18	14,800	22,100	0	0	0	0	0	0	3,470	17.0	15.3
2	30	30,000	15 + 15	15,000	15,000	0	0	0	0	0	0	2,450	12.0	10.8
		36,900	15 + 15	18,500	18,500	0	0	0	0	0	0	3,470	17.0	15.3

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	30	30,000	6 + 6 + 18	6,000	6,000	18,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 18	7,400	7,400	22,100	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 9 + 15	6,000	9,000	15,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 9 + 15	7,400	11,100	18,500	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	6 + 12 + 12	6,000	12,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 12 + 12	7,400	14,800	14,800	0	0	0	0	0	3,470	17.0	15.3
3	30	30,000	9 + 9 + 12	9,000	9,000	12,000	0	0	0	0	0	2,450	12.0	10.8
		36,900	9 + 9 + 12	11,100	11,100	14,800	0	0	0	0	0	3,470	17.0	15.3
4	30	30,000	6 + 6 + 6 + 12	6,000	6,000	6,000	12,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 6 + 12	7,400	7,400	7,400	14,800	0	0	0	0	3,470	17.0	15.3
4	30	30,000	6 + 6 + 9 + 9	6,000	6,000	9,000	9,000	0	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 9 + 9	7,400	7,400	11,100	11,100	0	0	0	0	3,470	17.0	15.3
5	30	30,000	6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	0	0	0	2,450	12.0	10.8
		36,900	6 + 6 + 6 + 6 + 6	7,400	7,400	7,400	7,400	7,400	0	0	0	3,470	17.0	15.3
2	33	33,000	9 + 24	9,000	24,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 24	11,200	29,700	0	0	0	0	0	0	3,990	19.5	17.6
2	33	33,000	15 + 18	15,000	18,000	0	0	0	0	0	0	2,900	14.1	12.8
		40,900	15 + 18	18,600	22,300	0	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	6 + 9 + 18	6,000	9,000	18,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 18	7,400	11,200	22,300	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	6 + 12 + 15	6,000	12,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 12 + 15	7,400	14,900	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 9 + 15	9,000	9,000	15,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 9 + 15	11,200	11,200	18,600	0	0	0	0	0	3,990	19.5	17.6
3	33	33,000	9 + 12 + 12	9,000	12,000	12,000	0	0	0	0	0	2,900	14.1	12.8
		40,900	9 + 12 + 12	11,200	14,900	14,900	0	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 6 + 6 + 15	6,000	6,000	6,000	15,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 6 + 15	7,400	7,400	7,400	18,600	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 6 + 9 + 12	6,000	6,000	9,000	12,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 9 + 12	7,400	7,400	11,200	14,900	0	0	0	0	3,990	19.5	17.6
4	33	33,000	6 + 9 + 9 + 9	6,000	9,000	9,000	9,000	0	0	0	0	2,900	14.1	12.8
		40,900	6 + 9 + 9 + 9	7,400	11,200	11,200	11,200	0	0	0	0	3,990	19.5	17.6
5	33	33,000	6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	9,000	0	0	0	2,900	14.1	12.8
		40,900	6 + 6 + 6 + 6 + 9	7,400	7,400	7,400	7,400	11,200	0	0	0	3,990	19.5	17.6
1	36	36,000	36	36,000	0	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	36	45,000	0	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	6 + 30	6,000	30,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 30	7,500	37,700	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	12 + 24	12,000	24,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 24	15,000	30,000	0	0	0	0	0	0	4,500	22.0	19.9
2	36	36,000	18 + 18	18,000	18,000	0	0	0	0	0	0	3,340	16.3	14.8
		45,000	18 + 18	22,500	22,500	0	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 6 + 24	6,000	6,000	24,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 24	7,500	7,500	30,000	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 18	11,300	11,300	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 12 + 18	6,000	12,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 12 + 18	7,500	15,000	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	6 + 15 + 15	6,000	15,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 15 + 15	7,500	18,800	18,800	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 9 + 18	9,000	9,000	18,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 18	11,300	11,300	22,500	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	9 + 12 + 15	9,000	12,000	15,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 12 + 15	11,300	15,000	18,800	0	0	0	0	0	4,500	22.0	19.9
3	36	36,000	12 + 12 + 12	12,000	12,000	12,000	0	0	0	0	0	3,340	16.3	14.8
		45,000	12 + 12 + 12	15,000	15,000	15,000	0	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 6 + 6 + 18	6,000	6,000	6,000	18,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 18	7,500	7,500	7,500	22,500	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 6 + 9 + 15	6,000	6,000	9,000	15,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 9 + 15	7,500	7,500	11,300	18,800	0	0	0	0	4,500	22.0	19.9

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
4	36	36,000	6 + 6 + 12 + 12	6,000	6,000	12,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 12 + 12	7,500	7,500	15,000	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	6 + 9 + 9 + 12	6,000	9,000	9,000	12,000	0	0	0	0	3,340	16.3	14.8
		45,000	6 + 9 + 9 + 12	7,500	11,300	11,300	15,000	0	0	0	0	4,500	22.0	19.9
4	36	36,000	9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	0	0	0	0	3,340	16.3	14.8
		45,000	9 + 9 + 9 + 9	11,300	11,300	11,300	11,300	0	0	0	0	4,500	22.0	19.9
5	36	36,000	6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	12,000	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 6 + 12	7,500	7,500	7,500	7,500	15,000	0	0	0	4,500	22.0	19.9
5	36	36,000	6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	9,000	9,000	0	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 9 + 9	7,500	7,500	7,500	11,300	11,300	0	0	0	4,500	22.0	19.9
6	36	36,000	6 + 6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	6,000	0	0	3,340	16.3	14.8
		45,000	6 + 6 + 6 + 6 + 6 + 6	7,500	7,500	7,500	7,500	7,500	7,500	0	0	4,500	22.0	19.9
2	39	39,000	9 + 30	9,000	30,000	0	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 30	10,500	36,000	0	0	0	0	0	0	4,740	23.1	20.9
2	39	39,000	15 + 24	15,000	24,000	0	0	0	0	0	0	3,680	18.0	16.3
		46,500	15 + 24	17,900	28,600	0	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	6 + 9 + 24	6,000	9,000	24,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 24	7,200	10,700	28,600	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	6 + 15 + 18	6,000	15,000	18,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 15 + 18	7,200	17,900	21,500	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	9 + 12 + 18	9,000	12,000	18,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 12 + 18	10,700	14,300	21,500	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	9 + 15 + 15	9,000	15,000	15,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 15 + 15	10,700	17,900	17,900	0	0	0	0	0	4,740	23.1	20.9
3	39	39,000	12 + 12 + 15	12,000	12,000	15,000	0	0	0	0	0	3,680	18.0	16.3
		46,500	12 + 12 + 15	14,300	14,300	17,900	0	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 6 + 9 + 18	6,000	6,000	9,000	18,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 9 + 18	7,200	7,200	10,700	21,500	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 6 + 12 + 15	6,000	6,000	12,000	15,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 12 + 15	7,200	7,200	14,300	17,900	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 9 + 9 + 15	6,000	9,000	9,000	15,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 9 + 15	7,200	10,700	10,700	17,900	0	0	0	0	4,740	23.1	20.9
4	39	39,000	6 + 9 + 12 + 12	6,000	9,000	12,000	12,000	0	0	0	0	3,680	18.0	16.3
		46,500	6 + 9 + 12 + 12	7,200	10,700	14,300	14,300	0	0	0	0	4,740	23.1	20.9
4	39	39,000	9 + 9 + 9 + 12	9,000	9,000	9,000	12,000	0	0	0	0	3,680	18.0	16.3
		46,500	9 + 9 + 9 + 12	10,700	10,700	10,700	14,300	0	0	0	0	4,740	23.1	20.9
5	39	39,000	6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	15,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 6 + 15	7,200	7,200	7,200	7,200	17,900	0	0	0	4,740	23.1	20.9
5	39	39,000	6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	9,000	12,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 9 + 12	7,200	7,200	7,200	10,700	14,300	0	0	0	4,740	23.1	20.9
5	39	39,000	6 + 6 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	0	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 9 + 9 + 9	7,200	7,200	10,700	10,700	10,700	0	0	0	4,740	23.1	20.9
6	39	39,000	6 + 6 + 6 + 6 + 6 + 9	6,000	6,000	6,000	6,000	6,000	9,000	0	0	3,680	18.0	16.3
		46,500	6 + 6 + 6 + 6 + 6 + 9	7,200	7,200	7,200	7,200	7,200	10,700	0	0	4,740	23.1	20.9
2	42	42,000	6 + 36	6,000	36,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 36	6,600	41,400	0	0	0	0	0	0	4,980	24.3	22.0
2	42	42,000	12 + 30	12,000	30,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 30	13,500	34,500	0	0	0	0	0	0	4,980	24.3	22.0
2	42	42,000	18 + 24	18,000	24,000	0	0	0	0	0	0	4,020	19.6	17.8
		48,000	18 + 24	20,600	27,400	0	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	6 + 6 + 30	6,000	6,000	30,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 30	6,700	6,700	34,500	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	6 + 12 + 24	6,000	12,000	24,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 12 + 24	6,900	13,700	27,400	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	6 + 18 + 18	6,000	18,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 18 + 18	6,900	20,600	20,600	0	0	0	0	0	4,980	24.3	22.0

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	42	42,000	9 + 9 + 24	9,000	9,000	24,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 24	10,300	10,300	27,400	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	9 + 15 + 18	9,000	15,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 15 + 18	10,300	17,100	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	12 + 12 + 18	12,000	12,000	18,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 12 + 18	13,700	13,700	20,600	0	0	0	0	0	4,980	24.3	22.0
3	42	42,000	12 + 15 + 15	12,000	15,000	15,000	0	0	0	0	0	4,020	19.6	17.8
		48,000	12 + 15 + 15	13,700	17,100	17,100	0	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 6 + 6 + 24	6,000	6,000	6,000	24,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 24	6,900	6,900	6,900	27,400	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 6 + 12 + 18	6,000	6,000	12,000	18,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 12 + 18	6,900	6,900	13,700	20,600	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 6 + 15 + 15	6,000	6,000	15,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 15 + 15	6,900	6,900	17,100	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 9 + 9 + 18	6,000	9,000	9,000	18,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 9 + 18	6,900	10,300	10,300	20,600	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 9 + 12 + 15	6,000	9,000	12,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 12 + 15	6,900	10,300	13,700	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	6 + 12 + 12 + 12	6,000	12,000	12,000	12,000	0	0	0	0	4,020	19.6	17.8
		48,000	6 + 12 + 12 + 12	6,900	13,700	13,700	13,700	0	0	0	0	4,980	24.3	22.0
4	42	42,000	9 + 9 + 9 + 15	9,000	9,000	9,000	15,000	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 9 + 15	10,300	10,300	10,300	17,100	0	0	0	0	4,980	24.3	22.0
4	42	42,000	9 + 9 + 12 + 12	9,000	9,000	12,000	12,000	0	0	0	0	4,020	19.6	17.8
		48,000	9 + 9 + 12 + 12	10,300	10,300	13,700	13,700	0	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	18,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 6 + 18	6,900	6,900	6,900	6,900	20,600	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	9,000	15,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 9 + 15	6,900	6,900	6,900	10,300	17,100	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	12,000	12,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 12 + 12	6,900	6,900	6,900	13,700	13,700	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 6 + 9 + 9 + 12	6,000	6,000	9,000	9,000	12,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 9 + 9 + 12	6,900	6,900	10,300	10,300	13,700	0	0	0	4,980	24.3	22.0
5	42	42,000	6 + 9 + 9 + 9 + 9	6,000	9,000	9,000	9,000	9,000	0	0	0	4,020	19.6	17.8
		48,000	6 + 9 + 9 + 9 + 9	6,900	10,300	10,300	10,300	10,300	0	0	0	4,980	24.3	22.0
6	42	42,000	6 + 6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	6,000	12,000	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 6 + 6 + 12	6,900	6,900	6,900	6,900	6,900	13,700	0	0	4,980	24.3	22.0
6	42	42,000	6 + 6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	6,000	9,000	9,000	0	0	4,020	19.6	17.8
		48,000	6 + 6 + 6 + 6 + 9 + 9	6,900	6,900	6,900	6,900	10,300	10,300	0	0	4,980	24.3	22.0
7	42	48,000	6 + 6 + 6 + 6 + 6 + 6 + 6	6,900	6,900	6,900	6,900	6,900	6,900	6,900	0	4,020	19.6	17.8
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 6	7,700	7,700	7,700	7,700	7,700	7,700	7,700	0	4,980	24.3	22.0
2	45	45,000	9 + 36	9,000	36,000	0	0	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 36	9,900	41,100	0	0	0	0	0	0	5,290	25.9	23.4
2	45	45,000	15 + 30	15,000	30,000	0	0	0	0	0	0	4,550	22.2	20.1
		51,000	15 + 30	16,700	34,300	0	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	6 + 9 + 30	6,000	9,000	30,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 9 + 30	6,700	10,000	34,300	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	6 + 15 + 24	6,000	15,000	24,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 15 + 24	6,800	17,000	27,200	0	0	0	0	0	5,290	25.9	23.4

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
3	45	45,000	9 + 12 + 24	9,000	12,000	24,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 12 + 24	10,200	13,600	27,200	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	9 + 18 + 18	9,000	18,000	18,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 18 + 18	10,200	20,400	20,400	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	12 + 15 + 18	12,000	15,000	18,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	12 + 15 + 18	13,600	17,000	20,400	0	0	0	0	0	5,290	25.9	23.4
3	45	45,000	15 + 15 + 15	15,000	15,000	15,000	0	0	0	0	0	4,550	22.2	20.1
		51,000	15 + 15 + 15	17,000	17,000	17,000	0	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 6 + 9 + 24	6,000	6,000	9,000	24,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 9 + 24	6,800	6,800	10,200	27,200	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 6 + 15 + 18	6,000	6,000	15,000	18,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 15 + 18	6,800	6,800	17,000	20,400	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 9 + 12 + 18	6,000	9,000	12,000	18,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 9 + 12 + 18	6,800	10,200	13,600	20,400	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 9 + 15 + 15	6,000	9,000	15,000	15,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 9 + 15 + 15	6,800	10,200	17,000	17,000	0	0	0	0	5,290	25.9	23.4
4	45	45,000	6 + 12 + 12 + 15	6,000	12,000	12,000	15,000	0	0	0	0	4,550	22.2	20.1
		51,000	6 + 12 + 12 + 15	6,800	13,600	13,600	17,000	0	0	0	0	5,290	25.9	23.4
4	45	45,000	9 + 9 + 9 + 18	9,000	9,000	9,000	18,000	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 9 + 9 + 18	10,200	10,200	10,200	20,400	0	0	0	0	5,290	25.9	23.4
4	45	45,000	9 + 9 + 12 + 15	9,000	9,000	12,000	15,000	0	0	0	0	4,550	22.2	20.1
		51,000	9 + 9 + 12 + 15	10,200	10,200	13,600	17,000	0	0	0	0	5,290	25.9	23.4
4	45	48,000	9 + 12 + 12 + 12	9,600	12,800	12,800	12,800	0	0	0	0	4,550	22.2	20.1
		54,000	9 + 12 + 12 + 12	10,800	14,400	14,400	14,400	0	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 6 + 6 + 9 + 18	6,000	6,000	6,000	9,000	18,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 9 + 18	6,800	6,800	6,800	10,200	20,400	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 6 + 6 + 12 + 15	6,000	6,000	6,000	12,000	15,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 12 + 15	6,800	6,800	6,800	13,600	17,000	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 6 + 9 + 9 + 15	6,000	6,000	9,000	9,000	15,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 9 + 9 + 15	6,800	6,800	10,200	10,200	17,000	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 6 + 9 + 12 + 12	6,000	6,000	9,000	12,000	12,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 9 + 12 + 12	6,800	6,800	10,200	13,600	13,600	0	0	0	5,290	25.9	23.4
5	45	45,000	6 + 9 + 9 + 9 + 12	6,000	9,000	9,000	9,000	12,000	0	0	0	4,550	22.2	20.1
		51,000	6 + 9 + 9 + 9 + 12	6,800	10,200	10,200	10,200	13,600	0	0	0	5,290	25.9	23.4
5	45	45,000	9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	0	0	0	4,550	22.2	20.1
		51,000	9 + 9 + 9 + 9 + 9	10,200	10,200	10,200	10,200	10,200	0	0	0	5,290	25.9	23.4
6	45	45,000	6 + 6 + 6 + 6 + 6 + 15	6,000	6,000	6,000	6,000	6,000	15,000	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 6 + 6 + 15	6,800	6,800	6,800	6,800	6,800	17,000	0	0	5,290	25.9	23.4
6	45	45,000	6 + 6 + 6 + 6 + 9 + 12	6,000	6,000	6,000	6,000	9,000	12,000	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 6 + 9 + 12	6,800	6,800	6,800	6,800	10,200	13,600	0	0	5,290	25.9	23.4
6	45	45,000	6 + 6 + 6 + 9 + 9 + 9	6,000	6,000	6,000	9,000	9,000	9,000	0	0	4,550	22.2	20.1
		51,000	6 + 6 + 6 + 9 + 9 + 9	6,800	6,800	6,800	10,200	10,200	10,200	0	0	5,290	25.9	23.4

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	45	48,000	6 + 6 + 6 + 6 + 6 + 6 + 9	6,400	6,400	6,400	6,400	6,400	6,400	9,600	0	4,550	22.2	20.1
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 9	7,200	7,200	7,200	7,200	7,200	7,200	10,800	0	5,290	25.9	23.4
2	48	48,000	12 + 36	12,000	36,000	0	0	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 36	13,100	40,900	0	0	0	0	0	0	5,610	27.4	24.8
2	48	48,000	18 + 30	18,000	30,000	0	0	0	0	0	0	5,070	24.8	22.4
		54,000	18 + 30	19,900	34,100	0	0	0	0	0	0	5,610	27.4	24.8
2	48	48,000	24 + 24	24,000	24,000	0	0	0	0	0	0	5,070	24.8	22.4
		54,000	24 + 24	27,000	27,000	0	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	6 + 6 + 36	6,000	6,000	36,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 36	6,500	6,500	40,900	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	6 + 12 + 30	6,000	12,000	30,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 12 + 30	6,600	13,300	34,100	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	6 + 18 + 24	6,000	18,000	24,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 18 + 24	6,800	20,300	27,000	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	9 + 9 + 30	9,000	9,000	30,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 9 + 30	10,000	10,000	34,100	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	9 + 15 + 24	9,000	15,000	24,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 15 + 24	10,100	16,900	27,000	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	12 + 12 + 24	12,000	12,000	24,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 12 + 24	13,500	13,500	27,000	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	12 + 18 + 18	12,000	18,000	18,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 18 + 18	13,500	20,300	20,300	0	0	0	0	0	5,610	27.4	24.8
3	48	48,000	15 + 15 + 18	15,000	15,000	18,000	0	0	0	0	0	5,070	24.8	22.4
		54,000	15 + 15 + 18	16,900	16,900	20,300	0	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 6 + 6 + 30	6,000	6,000	6,000	30,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 30	6,600	6,600	6,600	34,100	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 6 + 12 + 24	6,000	6,000	12,000	24,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 12 + 24	6,800	6,800	13,500	27,000	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 6 + 18 + 18	6,000	6,000	18,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 18 + 18	6,800	6,800	20,300	20,300	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 9 + 9 + 24	6,000	9,000	9,000	24,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 9 + 24	6,800	10,100	10,100	27,000	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 9 + 15 + 18	6,000	9,000	15,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 15 + 18	6,800	10,100	16,900	20,300	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 12 + 12 + 18	6,000	12,000	12,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 12 + 12 + 18	6,800	13,500	13,500	20,300	0	0	0	0	5,610	27.4	24.8
4	48	48,000	6 + 12 + 15 + 15	6,000	12,000	15,000	15,000	0	0	0	0	5,070	24.8	22.4
		54,000	6 + 12 + 15 + 15	6,800	13,500	16,900	16,900	0	0	0	0	5,610	27.4	24.8
4	48	48,000	9 + 9 + 12 + 18	9,000	9,000	12,000	18,000	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 9 + 12 + 18	10,100	10,100	13,500	20,300	0	0	0	0	5,610	27.4	24.8
4	48	45,000	9 + 9 + 15 + 15	8,400	8,400	14,100	14,100	0	0	0	0	5,070	24.8	22.4
		51,000	9 + 9 + 15 + 15	9,600	9,600	15,900	15,900	0	0	0	0	5,610	27.4	24.8
4	48	48,000	9 + 12 + 12 + 15	9,000	12,000	12,000	15,000	0	0	0	0	5,070	24.8	22.4
		54,000	9 + 12 + 12 + 15	10,100	13,500	13,500	16,900	0	0	0	0	5,610	27.4	24.8
4	48	48,000	12 + 12 + 12 + 12	12,000	12,000	12,000	12,000	0	0	0	0	5,070	24.8	22.4
		54,000	12 + 12 + 12 + 12	13,500	13,500	13,500	13,500	0	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	24,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 24	6,800	6,800	6,800	6,800	27,000	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	12,000	18,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 12 + 18	6,800	6,800	6,800	13,500	20,300	0	0	0	5,610	27.4	24.8

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	48	48,000	6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	15,000	15,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 15 + 15	6,800	6,800	6,800	16,900	16,900	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 9 + 9 + 18	6,000	6,000	9,000	9,000	18,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 9 + 9 + 18	6,800	6,800	10,100	10,100	20,300	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 9 + 12 + 15	6,000	6,000	9,000	12,000	15,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 9 + 12 + 15	6,800	6,800	10,100	13,500	16,900	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 6 + 12 + 12 + 12	6,000	6,000	12,000	12,000	12,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 12 + 12 + 12	6,800	6,800	13,500	13,500	13,500	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 9 + 9 + 9 + 15	6,000	9,000	9,000	9,000	15,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 9 + 9 + 15	6,800	10,100	10,100	10,100	16,900	0	0	0	5,610	27.4	24.8
5	48	48,000	6 + 9 + 9 + 12 + 12	6,000	9,000	9,000	12,000	12,000	0	0	0	5,070	24.8	22.4
		54,000	6 + 9 + 9 + 12 + 12	6,800	10,100	10,100	13,500	13,500	0	0	0	5,610	27.4	24.8
5	48	48,000	9 + 9 + 9 + 9 + 12	9,000	9,000	9,000	9,000	12,000	0	0	0	5,070	24.8	22.4
		54,000	9 + 9 + 9 + 9 + 12	10,100	10,100	10,100	10,100	13,500	0	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	6,000	18,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 6 + 18	6,800	6,800	6,800	6,800	6,800	20,300	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	6,000	9,000	15,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 9 + 15	6,800	6,800	6,800	6,800	10,100	16,900	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	6,000	12,000	12,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 12 + 12	6,800	6,800	6,800	6,800	13,500	13,500	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 6 + 9 + 9 + 12	6,000	6,000	6,000	9,000	9,000	12,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 9 + 9 + 12	6,800	6,800	6,800	10,100	10,100	13,500	0	0	5,610	27.4	24.8
6	48	48,000	6 + 6 + 9 + 9 + 9 + 9	6,000	6,000	9,000	9,000	9,000	9,000	0	0	5,070	24.8	22.4
		54,000	6 + 6 + 9 + 9 + 9 + 9	6,800	6,800	10,100	10,100	10,100	10,100	0	0	5,610	27.4	24.8
7	48	48,000	6 + 6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	6,000	6,000	12,000	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 6 + 12	6,800	6,800	6,800	6,800	6,800	6,800	13,500	0	5,610	27.4	24.8
7	48	48,000	6 + 6 + 6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	6,000	6,000	9,000	9,000	0	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 6 + 9 + 9	6,800	6,800	6,800	6,800	6,800	10,100	10,100	0	5,610	27.4	24.8

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	48	48,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 6	6,000	6,000	6,000	6,000	6,000	6,000	6,000	6,000	5,070	24.8	22.4
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 6	6,800	6,800	6,800	6,800	6,800	6,800	6,800	6,800	5,610	27.4	24.8
2	51	48,000	15 + 36	14,100	33,900	0	0	0	0	0	0	5,010	24.4	22.1
		54,000	15 + 36	15,400	38,600	0	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	6 + 9 + 36	5,600	8,500	33,900	0	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 36	6,200	9,300	38,600	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	6 + 15 + 30	5,600	14,100	28,200	0	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 15 + 30	6,300	15,700	32,100	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	9 + 12 + 30	8,500	11,300	28,200	0	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 12 + 30	9,400	12,500	32,100	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	9 + 18 + 24	8,500	16,900	22,600	0	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 18 + 24	9,500	19,100	25,400	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	12 + 15 + 24	11,300	14,100	22,600	0	0	0	0	0	5,010	24.4	22.1
		54,000	12 + 15 + 24	12,700	15,900	25,400	0	0	0	0	0	5,500	26.9	24.3
3	51	48,000	15 + 18 + 18	14,100	16,900	16,900	0	0	0	0	0	5,010	24.4	22.1
		54,000	15 + 18 + 18	15,900	19,100	19,100	0	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 6 + 9 + 30	5,600	5,600	8,500	28,200	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 30	6,300	6,300	9,400	32,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 6 + 15 + 24	5,600	5,600	14,100	22,600	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 15 + 24	6,400	6,400	15,900	25,400	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 9 + 12 + 24	5,600	8,500	11,300	22,600	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 12 + 24	6,400	9,500	12,700	25,400	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 9 + 18 + 18	5,600	8,500	16,900	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 18 + 18	6,400	9,500	19,100	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 12 + 15 + 18	5,600	11,300	14,100	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 12 + 15 + 18	6,400	12,700	15,900	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	6 + 15 + 15 + 15	5,600	14,100	14,100	14,100	0	0	0	0	5,010	24.4	22.1
		54,000	6 + 15 + 15 + 15	6,400	15,900	15,900	15,900	0	0	0	0	5,500	26.9	24.3
4	51	48,000	9 + 9 + 9 + 24	8,500	8,500	8,500	22,600	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 9 + 24	9,500	9,500	9,500	25,400	0	0	0	0	5,500	26.9	24.3
4	51	48,000	9 + 9 + 15 + 18	8,500	8,500	14,100	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 15 + 18	9,500	9,500	15,900	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	9 + 12 + 12 + 18	8,500	11,300	11,300	16,900	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 12 + 12 + 18	9,500	12,700	12,700	19,100	0	0	0	0	5,500	26.9	24.3
4	51	48,000	9 + 12 + 15 + 15	8,500	11,300	14,100	14,100	0	0	0	0	5,010	24.4	22.1
		54,000	9 + 12 + 15 + 15	9,500	12,700	15,900	15,900	0	0	0	0	5,500	26.9	24.3
4	51	48,000	12 + 12 + 12 + 15	11,300	11,300	11,300	14,100	0	0	0	0	5,010	24.4	22.1
		54,000	12 + 12 + 12 + 15	12,700	12,700	12,700	15,900	0	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 6 + 9 + 24	5,600	5,600	5,600	8,500	22,600	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 9 + 24	6,400	6,400	6,400	9,500	25,400	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 6 + 15 + 18	5,600	5,600	5,600	14,100	16,900	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 15 + 18	6,400	6,400	6,400	15,900	19,100	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 9 + 12 + 18	5,600	5,600	8,500	11,300	16,900	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 12 + 18	6,400	6,400	9,500	12,700	19,100	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 9 + 15 + 15	5,600	5,600	8,500	14,100	14,100	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 15 + 15	6,400	6,400	9,500	15,900	15,900	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 6 + 12 + 12 + 15	5,600	5,600	11,300	11,300	14,100	0	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 12 + 12 + 15	6,400	6,400	12,700	12,700	15,900	0	0	0	5,500	26.9	24.3

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	51	48,000	6 + 9 + 9 + 9 + 18	5,600	8,500	8,500	8,500	16,900	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 9 + 9 + 18	6,400	9,500	9,500	9,500	19,100	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 9 + 9 + 12 + 15	5,600	8,500	8,500	11,300	14,100	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 9 + 12 + 15	6,400	9,500	9,500	12,700	15,900	0	0	0	5,500	26.9	24.3
5	51	48,000	6 + 9 + 12 + 12 + 12	5,600	8,500	11,300	11,300	11,300	0	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 12 + 12 + 12	6,400	9,500	12,700	12,700	12,700	0	0	0	5,500	26.9	24.3
5	51	48,000	9 + 9 + 9 + 9 + 15	8,500	8,500	8,500	8,500	14,100	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 9 + 9 + 15	9,500	9,500	9,500	9,500	15,900	0	0	0	5,500	26.9	24.3
5	51	48,000	9 + 9 + 9 + 12 + 12	8,500	8,500	8,500	11,300	11,300	0	0	0	5,010	24.4	22.1
		54,000	9 + 9 + 9 + 12 + 12	9,500	9,500	9,500	12,700	12,700	0	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 6 + 6 + 9 + 18	5,600	5,600	5,600	5,600	8,500	16,900	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 9 + 18	6,400	6,400	6,400	6,400	9,500	19,100	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 6 + 6 + 12 + 15	5,600	5,600	5,600	5,600	11,300	14,100	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 12 + 15	6,400	6,400	6,400	6,400	12,700	15,900	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 6 + 9 + 9 + 15	5,600	5,600	5,600	8,500	8,500	14,100	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 9 + 9 + 15	6,400	6,400	6,400	9,500	9,500	15,900	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 6 + 9 + 12 + 12	5,600	5,600	5,600	8,500	11,300	11,300	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 9 + 12 + 12	6,400	6,400	6,400	9,500	12,700	12,700	0	0	5,500	26.9	24.3
6	51	48,000	6 + 6 + 9 + 9 + 9 + 12	5,600	5,600	8,500	8,500	8,500	11,300	0	0	5,010	24.4	22.1
		54,000	6 + 6 + 9 + 9 + 9 + 12	6,400	6,400	9,500	9,500	9,500	12,700	0	0	5,500	26.9	24.3
6	51	48,000	6 + 9 + 9 + 9 + 9 + 9	5,600	8,500	8,500	8,500	8,500	8,500	0	0	5,010	24.4	22.1
		54,000	6 + 9 + 9 + 9 + 9 + 9	6,400	9,500	9,500	9,500	9,500	9,500	0	0	5,500	26.9	24.3
7	51	48,000	6 + 6 + 6 + 6 + 6 + 6 + 15	5,600	5,600	5,600	5,600	5,600	5,600	14,100	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 15	6,400	6,400	6,400	6,400	6,400	6,400	15,900	0	5,500	26.9	24.3
7	51	48,000	6 + 6 + 6 + 6 + 6 + 9 + 12	5,600	5,600	5,600	5,600	5,600	8,500	11,300	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 6 + 9 + 12	6,400	6,400	6,400	6,400	6,400	9,500	12,700	0	5,500	26.9	24.3
7	51	48,000	6 + 6 + 6 + 6 + 9 + 9 + 9	5,600	5,600	5,600	5,600	8,500	8,500	8,500	0	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 9 + 9 + 9	6,400	6,400	6,400	6,400	9,500	9,500	9,500	0	5,500	26.9	24.3

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	51	48,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 9	5,600	5,600	5,600	5,600	5,600	5,600	5,600	8,500	5,010	24.4	22.1
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 9	6,400	6,400	6,400	6,400	6,400	6,400	6,400	9,500	5,500	26.9	24.3
2	54	48,000	18 + 36	16,000	32,000	0	0	0	0	0	0	4,940	24.1	21.8
		54,000	18 + 36	17,500	36,500	0	0	0	0	0	0	5,390	26.3	23.8
2	54	48,000	24 + 30	21,300	26,700	0	0	0	0	0	0	4,940	24.1	21.8
		54,000	24 + 30	23,700	30,300	0	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	6 + 12 + 36	5,300	10,700	32,000	0	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 12 + 36	5,800	11,700	36,500	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	6 + 18 + 30	5,300	16,000	26,700	0	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 18 + 30	5,900	17,800	30,300	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	6 + 24 + 24	5,300	21,300	21,300	0	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 24 + 24	6,000	24,000	24,000	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	9 + 9 + 36	8,000	8,000	32,000	0	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 36	8,800	8,800	36,500	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	9 + 15 + 30	8,000	13,300	26,700	0	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 15 + 30	8,900	14,800	30,300	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	12 + 12 + 30	10,700	10,700	26,700	0	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 12 + 30	11,800	11,800	30,300	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	12 + 18 + 24	10,700	16,000	21,300	0	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 18 + 24	12,000	18,000	24,000	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	15 + 15 + 24	13,300	13,300	21,300	0	0	0	0	0	4,940	24.1	21.8
		54,000	15 + 15 + 24	15,000	15,000	24,000	0	0	0	0	0	5,390	26.3	23.8
3	54	48,000	18 + 18 + 18	16,000	16,000	16,000	0	0	0	0	0	4,940	24.1	21.8
		54,000	18 + 18 + 18	18,000	18,000	18,000	0	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 6 + 6 + 36	5,300	5,300	5,300	32,000	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 36	5,800	5,800	5,800	36,500	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 6 + 12 + 30	5,300	5,300	10,700	26,700	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 12 + 30	5,900	5,900	11,800	30,300	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 6 + 18 + 24	5,300	5,300	16,000	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 18 + 24	6,000	6,000	18,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 9 + 9 + 30	5,300	8,000	8,000	26,700	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 30	5,900	8,900	8,900	30,300	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 9 + 15 + 24	5,300	8,000	13,300	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 15 + 24	6,000	9,000	15,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 12 + 12 + 24	5,300	10,700	10,700	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 12 + 12 + 24	6,000	12,000	12,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	6 + 15 + 15 + 18	5,300	13,300	13,300	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	6 + 15 + 15 + 18	6,000	15,000	15,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 9 + 12 + 24	8,000	8,000	10,700	21,300	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 12 + 24	9,000	9,000	12,000	24,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 9 + 18 + 18	8,000	8,000	16,000	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 18 + 18	9,000	9,000	18,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 12 + 15 + 18	8,000	10,700	13,300	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 12 + 15 + 18	9,000	12,000	15,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	9 + 15 + 15 + 15	8,000	13,300	13,300	13,300	0	0	0	0	4,940	24.1	21.8
		54,000	9 + 15 + 15 + 15	9,000	15,000	15,000	15,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	12 + 12 + 12 + 18	10,700	10,700	10,700	16,000	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 12 + 12 + 18	12,000	12,000	12,000	18,000	0	0	0	0	5,390	26.3	23.8
4	54	48,000	12 + 12 + 15 + 15	10,700	10,700	13,300	13,300	0	0	0	0	4,940	24.1	21.8
		54,000	12 + 12 + 15 + 15	12,000	12,000	15,000	15,000	0	0	0	0	5,390	26.3	23.8
5	54	48,000	5 + 6 + 6 + 6 + 30	5,300	5,300	5,300	5,300	26,700	0	0	0	4,940	24.1	21.8
		54,000	5 + 6 + 6 + 6 + 30	5,900	5,900	5,900	5,900	30,300	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 6 + 12 + 24	5,300	5,300	5,300	10,700	21,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 12 + 24	6,000	6,000	6,000	12,000	24,000	0	0	0	5,390	26.3	23.8

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	54	48,000	6 + 6 + 6 + 18 + 18	5,300	5,300	5,300	16,000	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 18 + 18	6,000	6,000	6,000	18,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 9 + 9 + 24	5,300	5,300	8,000	8,000	21,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 9 + 24	6,000	6,000	9,000	9,000	24,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 9 + 15 + 18	5,300	5,300	8,000	13,300	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 15 + 18	6,000	6,000	9,000	15,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 12 + 12 + 18	5,300	5,300	10,700	10,700	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 12 + 12 + 18	6,000	6,000	12,000	12,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 6 + 12 + 15 + 15	5,300	5,300	10,700	13,300	13,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 12 + 15 + 15	6,000	6,000	12,000	15,000	15,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 9 + 9 + 12 + 18	5,300	8,000	8,000	10,700	16,000	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 12 + 18	6,000	9,000	9,000	12,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 9 + 9 + 15 + 15	5,300	8,000	8,000	13,300	13,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 15 + 15	6,000	9,000	9,000	15,000	15,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 9 + 12 + 12 + 15	5,300	8,000	10,700	10,700	13,300	0	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 12 + 12 + 15	6,000	9,000	12,000	12,000	15,000	0	0	0	5,390	26.3	23.8
5	54	48,000	6 + 12 + 12 + 12 + 12	5,300	10,700	10,700	10,700	10,700	0	0	0	4,940	24.1	21.8
		54,000	6 + 12 + 12 + 12 + 12	6,000	12,000	12,000	12,000	12,000	0	0	0	5,390	26.3	23.8
5	54	48,000	9 + 9 + 9 + 9 + 18	8,000	8,000	8,000	8,000	16,000	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 9 + 9 + 18	9,000	9,000	9,000	9,000	18,000	0	0	0	5,390	26.3	23.8
5	54	48,000	9 + 9 + 9 + 12 + 15	8,000	8,000	8,000	10,700	13,300	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 9 + 12 + 15	9,000	9,000	9,000	12,000	15,000	0	0	0	5,390	26.3	23.8
5	54	48,000	9 + 9 + 12 + 12 + 12	8,000	8,000	10,700	10,700	10,700	0	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 12 + 12 + 12	9,000	9,000	12,000	12,000	12,000	0	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 6 + 6 + 24	5,300	5,300	5,300	5,300	5,300	21,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 6 + 24	6,000	6,000	6,000	6,000	6,000	24,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 6 + 12 + 18	5,300	5,300	5,300	5,300	10,700	16,000	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 12 + 18	6,000	6,000	6,000	6,000	12,000	18,000	0	0	5,390	26.3	23.8

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	54	48,000	6 + 6 + 6 + 6 + 15 + 15	5,300	5,300	5,300	5,300	13,300	13,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 15 + 15	6,000	6,000	6,000	6,000	15,000	15,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 9 + 9 + 18	5,300	5,300	5,300	8,000	8,000	16,000	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 9 + 9 + 18	6,000	6,000	6,000	9,000	9,000	18,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 9 + 12 + 15	5,300	5,300	5,300	8,000	10,700	13,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 9 + 12 + 15	6,000	6,000	6,000	9,000	12,000	15,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 6 + 12 + 12 + 12	5,300	5,300	5,300	10,700	10,700	10,700	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 12 + 12 + 12	6,000	6,000	6,000	12,000	12,000	12,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 9 + 9 + 9 + 15	5,300	5,300	8,000	8,000	8,000	13,300	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 9 + 9 + 15	6,000	6,000	9,000	9,000	9,000	15,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 6 + 9 + 9 + 12 + 12	5,300	5,300	8,000	8,000	10,700	10,700	0	0	4,940	24.1	21.8
		54,000	6 + 6 + 9 + 9 + 12 + 12	6,000	6,000	9,000	9,000	12,000	12,000	0	0	5,390	26.3	23.8
6	54	48,000	6 + 9 + 9 + 9 + 9 + 12	5,300	8,000	8,000	8,000	8,000	10,700	0	0	4,940	24.1	21.8
		54,000	6 + 9 + 9 + 9 + 9 + 12	6,000	9,000	9,000	9,000	9,000	12,000	0	0	5,390	26.3	23.8
6	54	48,000	9 + 9 + 9 + 9 + 9 + 9	8,000	8,000	8,000	8,000	8,000	8,000	0	0	4,940	24.1	21.8
		54,000	9 + 9 + 9 + 9 + 9 + 9	9,000	9,000	9,000	9,000	9,000	9,000	0	0	5,390	26.3	23.8
7	54	48,000	6 + 6 + 6 + 6 + 6 + 18	5,300	5,300	5,300	5,300	5,300	5,300	16,000	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 6 + 18	6,000	6,000	6,000	6,000	6,000	6,000	18,000	0	5,390	26.3	23.8
7	54	48,000	6 + 6 + 6 + 6 + 6 + 9 + 15	5,300	5,300	5,300	5,300	5,300	8,000	13,300	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 6 + 9 + 15	6,000	6,000	6,000	6,000	6,000	9,000	15,000	0	5,390	26.3	23.8
7	54	48,000	6 + 6 + 6 + 6 + 6 + 12 + 12	5,300	5,300	5,300	5,300	5,300	10,700	10,700	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 6 + 12 + 12	6,000	6,000	6,000	6,000	6,000	12,000	12,000	0	5,390	26.3	23.8
7	54	48,000	6 + 6 + 6 + 6 + 9 + 9 + 12	5,300	5,300	5,300	5,300	8,000	8,000	10,700	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 9 + 9 + 12	6,000	6,000	6,000	6,000	9,000	9,000	12,000	0	5,390	26.3	23.8
7	54	48,000	6 + 6 + 6 + 9 + 9 + 9 + 9	5,300	5,300	5,300	8,000	8,000	8,000	8,000	0	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 9 + 9 + 9 + 9	6,000	6,000	6,000	9,000	9,000	9,000	9,000	0	5,390	26.3	23.8
8	54	48,000	6 + 6 + 6 + 6 + 6 + 6 + 12	5,300	5,300	5,300	5,300	5,300	5,300	5,300	10,700	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 12	6,000	6,000	6,000	6,000	6,000	6,000	6,000	12,000	5,390	26.3	23.8

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	54	48,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 9	5,300	5,300	5,300	5,300	5,300	5,300	8,000	8,000	4,940	24.1	21.8
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 9	6,000	6,000	6,000	6,000	6,000	6,000	9,000	9,000	5,390	26.3	23.8
3	57	48,000	6 + 15 + 36	5,100	12,600	30,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 15 + 36	5,500	13,800	34,600	0	0	0	0	0	5,330	26.0	23.5
3	57	48,000	9 + 12 + 36	7,600	10,100	30,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 36	8,300	11,100	34,600	0	0	0	0	0	5,330	26.0	23.5
3	57	48,000	9 + 18 + 30	7,600	15,200	25,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 18 + 30	8,400	16,800	28,800	0	0	0	0	0	5,330	26.0	23.5
3	57	48,000	9 + 24 + 24	7,600	20,200	20,200	0	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 24 + 24	8,500	22,700	22,700	0	0	0	0	0	5,330	26.0	23.5
3	57	48,000	12 + 15 + 30	10,100	12,600	25,300	0	0	0	0	0	4,870	23.8	21.5
		54,000	12 + 15 + 30	11,200	14,000	28,800	0	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 6 + 9 + 36	5,100	5,100	7,600	30,300	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 36	5,500	5,500	8,300	34,600	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 6 + 15 + 30	5,100	5,100	12,600	25,300	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 15 + 30	5,600	5,600	14,000	28,800	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 9 + 12 + 30	5,100	7,600	10,100	25,300	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 12 + 30	5,600	8,400	11,200	28,800	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 9 + 18 + 24	5,100	7,600	15,200	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 18 + 24	5,700	8,500	17,100	22,700	0	0	0	0	5,330	26.0	23.5
4	57	48,000	6 + 12 + 15 + 24	5,100	10,100	12,600	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	6 + 12 + 15 + 24	5,700	11,400	14,200	22,700	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 9 + 9 + 30	7,600	7,600	7,600	25,300	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 9 + 30	8,400	8,400	8,400	28,800	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 9 + 15 + 24	7,600	7,600	12,600	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 15 + 24	8,500	8,500	14,200	22,700	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 12 + 12 + 24	7,600	10,100	10,100	20,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 12 + 24	8,500	11,400	11,400	22,700	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 12 + 18 + 18	7,600	10,100	15,200	15,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 18 + 18	8,500	11,400	17,100	17,100	0	0	0	0	5,330	26.0	23.5
4	57	48,000	9 + 15 + 15 + 18	7,600	12,600	12,600	15,200	0	0	0	0	4,870	23.8	21.5
		54,000	9 + 15 + 15 + 18	8,500	14,200	14,200	17,100	0	0	0	0	5,330	26.0	23.5
4	57	48,000	12 + 12 + 15 + 18	10,100	10,100	12,600	15,200	0	0	0	0	4,870	23.8	21.5
		54,000	12 + 12 + 15 + 18	11,400	11,400	14,200	17,100	0	0	0	0	5,330	26.0	23.5
4	57	48,000	12 + 15 + 15 + 15	10,100	12,600	12,600	12,600	0	0	0	0	4,870	23.8	21.5
		54,000	12 + 15 + 15 + 15	11,400	14,200	14,200	14,200	0	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 6 + 9 + 30	5,100	5,100	5,100	7,600	25,300	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 9 + 30	5,600	5,600	5,600	8,400	28,800	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 6 + 15 + 24	5,100	5,100	5,100	12,600	20,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 15 + 24	5,700	5,700	5,700	14,200	22,700	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 9 + 12 + 24	5,100	5,100	7,600	10,100	20,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 12 + 24	5,700	5,700	8,500	11,400	22,700	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 9 + 18 + 18	5,100	5,100	7,600	15,200	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 18 + 18	5,700	5,700	8,500	17,100	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 12 + 15 + 18	5,100	5,100	10,100	12,600	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 12 + 15 + 18	5,700	5,700	11,400	14,200	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 6 + 15 + 15 + 15	5,100	5,100	12,600	12,600	12,600	0	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 15 + 15 + 15	5,700	5,700	14,200	14,200	14,200	0	0	0	5,330	26.0	23.5

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	57	48,000	6 + 9 + 9 + 9 + 24	5,100	7,600	7,600	7,600	20,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 9 + 9 + 24	5,700	8,500	8,500	8,500	22,700	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 9 + 9 + 15 + 18	5,100	7,600	7,600	12,600	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 9 + 15 + 18	5,700	8,500	8,500	14,200	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 9 + 12 + 12 + 18	5,100	7,600	10,100	10,100	15,200	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 12 + 12 + 18	5,700	8,500	11,400	11,400	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 9 + 12 + 15 + 15	5,100	7,600	10,100	12,600	12,600	0	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 12 + 15 + 15	5,700	8,500	11,400	14,200	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	6 + 12 + 12 + 12 + 15	5,100	10,100	10,100	10,100	12,600	0	0	0	4,870	23.8	21.5
		54,000	6 + 12 + 12 + 12 + 15	5,700	11,400	11,400	11,400	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 9 + 9 + 12 + 18	7,600	7,600	7,600	10,100	15,200	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 9 + 12 + 18	8,500	8,500	8,500	11,400	17,100	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 9 + 9 + 15 + 15	7,600	7,600	7,600	12,600	12,600	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 9 + 15 + 15	8,500	8,500	8,500	14,200	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 9 + 12 + 12 + 15	7,600	7,600	10,100	10,100	12,600	0	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 12 + 12 + 15	8,500	8,500	11,400	11,400	14,200	0	0	0	5,330	26.0	23.5
5	57	48,000	9 + 12 + 12 + 12 + 12	7,600	10,100	10,100	10,100	10,100	0	0	0	4,870	23.8	21.5
		54,000	9 + 12 + 12 + 12 + 12	8,500	11,400	11,400	11,400	11,400	0	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 6 + 6 + 9 + 24	5,100	5,100	5,100	5,100	7,600	20,200	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 9 + 24	5,700	5,700	5,700	5,700	8,500	22,700	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 6 + 6 + 15 + 18	5,100	5,100	5,100	5,100	12,600	15,200	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 15 + 18	5,700	5,700	5,700	5,700	14,200	17,100	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 6 + 9 + 12 + 18	5,100	5,100	5,100	7,600	10,100	15,200	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 9 + 12 + 18	5,700	5,700	5,700	8,500	11,400	17,100	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 6 + 9 + 15 + 15	5,100	5,100	5,100	7,600	12,600	12,600	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 9 + 15 + 15	5,700	5,700	5,700	8,500	14,200	14,200	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 6 + 12 + 12 + 15	5,100	5,100	5,100	10,100	10,100	12,600	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 12 + 12 + 15	5,700	5,700	5,700	11,400	11,400	14,200	0	0	5,330	26.0	23.5

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	57	48,000	6 + 6 + 9 + 9 + 9 + 18	5,100	5,100	7,600	7,600	7,600	15,200	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 9 + 9 + 18	5,700	5,700	8,500	8,500	8,500	17,100	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 9 + 9 + 12 + 15	5,100	5,100	7,600	7,600	10,100	12,600	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 9 + 12 + 15	5,700	5,700	8,500	8,500	11,400	14,200	0	0	5,330	26.0	23.5
6	57	48,000	6 + 6 + 9 + 12 + 12 + 12	5,100	5,100	7,600	10,100	10,100	10,100	0	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 12 + 12 + 12	5,700	5,700	8,500	11,400	11,400	11,400	0	0	5,330	26.0	23.5
6	57	48,000	6 + 9 + 9 + 9 + 9 + 15	5,100	7,600	7,600	7,600	7,600	12,600	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 9 + 9 + 9 + 15	5,700	8,500	8,500	8,500	8,500	14,200	0	0	5,330	26.0	23.5
6	57	48,000	6 + 9 + 9 + 9 + 12 + 12	5,100	7,600	7,600	7,600	10,100	10,100	0	0	4,870	23.8	21.5
		54,000	6 + 9 + 9 + 9 + 12 + 12	5,700	8,500	8,500	8,500	11,400	11,400	0	0	5,330	26.0	23.5
6	57	48,000	9 + 9 + 9 + 9 + 9 + 12	7,600	7,600	7,600	7,600	7,600	10,100	0	0	4,870	23.8	21.5
		54,000	9 + 9 + 9 + 9 + 9 + 12	8,500	8,500	8,500	8,500	8,500	11,400	0	0	5,330	26.0	23.5
7	57	48,000	6 + 6 + 6 + 6 + 6 + 9 + 18	5,100	5,100	5,100	5,100	5,100	7,600	15,200	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 6 + 9 + 18	5,700	5,700	5,700	5,700	5,700	8,500	17,100	0	5,330	26.0	23.5
7	57	48,000	6 + 6 + 6 + 6 + 6 + 12 + 15	5,100	5,100	5,100	5,100	5,100	10,100	12,600	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 6 + 12 + 15	5,700	5,700	5,700	5,700	5,700	11,400	14,200	0	5,330	26.0	23.5
7	57	48,000	6 + 6 + 6 + 6 + 9 + 9 + 15	5,100	5,100	5,100	5,100	7,600	7,600	12,600	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 9 + 9 + 15	5,700	5,700	5,700	5,700	8,500	8,500	14,200	0	5,330	26.0	23.5
7	57	48,000	6 + 6 + 6 + 6 + 9 + 12 + 12	5,100	5,100	5,100	5,100	7,600	10,100	10,100	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 9 + 12 + 12	5,700	5,700	5,700	5,700	8,500	11,400	11,400	0	5,330	26.0	23.5
7	57	48,000	6 + 6 + 6 + 9 + 9 + 9 + 12	5,100	5,100	5,100	7,600	7,600	7,600	10,100	0	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 9 + 9 + 9 + 12	5,700	5,700	5,700	8,500	8,500	8,500	11,400	0	5,330	26.0	23.5
7	57	48,000	6 + 6 + 9 + 9 + 9 + 9 + 9	5,100	5,100	7,600	7,600	7,600	7,600	7,600	0	4,870	23.8	21.5
		54,000	6 + 6 + 9 + 9 + 9 + 9 + 9	5,700	5,700	8,500	8,500	8,500	8,500	8,500	0	5,330	26.0	23.5
8	57	48,000	6 + 6 + 6 + 6 + 6 + 6 + 15	5,100	5,100	5,100	5,100	5,100	5,100	5,100	12,600	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 15	5,700	5,700	5,700	5,700	5,700	5,700	5,700	14,200	5,330	26.0	23.5
8	57	48,000	6 + 6 + 6 + 6 + 6 + 9 + 12	5,100	5,100	5,100	5,100	5,100	5,100	7,600	10,100	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 6 + 9 + 12	5,700	5,700	5,700	5,700	5,700	5,700	8,500	11,400	5,330	26.0	23.5

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
8	57	48,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	5,100	5,100	5,100	5,100	5,100	7,600	7,600	7,600	4,870	23.8	21.5
		54,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 9	5,700	5,700	5,700	5,700	5,700	8,500	8,500	8,500	5,330	26.0	23.5
2	60	48,000	24 + 36	19,200	28,800	0	0	0	0	0	0	4,800	23.4	21.2
		54,000	24 + 36	21,100	32,900	0	0	0	0	0	0	5,270	25.7	23.2
2	60	48,000	30 + 30	24,000	24,000	0	0	0	0	0	0	4,800	23.4	21.2
		54,000	30 + 30	27,000	27,000	0	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	6 + 18 + 36	4,800	14,400	28,800	0	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 18 + 36	5,300	15,800	32,900	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	6 + 24 + 30	4,800	19,200	24,000	0	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 24 + 30	5,300	21,300	27,300	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	9 + 15 + 36	7,200	12,000	28,800	0	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 15 + 36	7,900	13,200	32,900	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	12 + 12 + 36	9,600	9,600	28,800	0	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 36	10,500	10,500	32,900	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	12 + 18 + 30	9,600	14,400	24,000	0	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 18 + 30	10,700	16,000	27,300	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	12 + 24 + 24	9,600	19,200	19,200	0	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 24 + 24	10,800	21,600	21,600	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	15 + 15 + 30	12,000	12,000	24,000	0	0	0	0	0	4,800	23.4	21.2
		54,000	15 + 15 + 30	13,300	13,300	27,300	0	0	0	0	0	5,270	25.7	23.2
3	60	48,000	18 + 18 + 24	14,400	14,400	19,200	0	0	0	0	0	4,800	23.4	21.2
		54,000	18 + 18 + 24	16,200	16,200	21,600	0	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 6 + 12 + 36	4,800	4,800	9,600	28,800	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 12 + 36	5,300	5,300	10,500	32,900	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 6 + 18 + 30	4,800	4,800	14,400	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 18 + 30	5,300	5,300	16,000	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 6 + 24 + 24	4,800	4,800	19,200	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 24 + 24	5,400	5,400	21,600	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 9 + 9 + 36	4,800	7,200	7,200	28,800	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 36	5,300	7,900	7,900	32,900	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 9 + 15 + 30	4,800	7,200	12,000	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 15 + 30	5,300	8,000	13,300	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 12 + 12 + 30	4,800	9,600	9,600	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 12 + 12 + 30	5,300	10,700	10,700	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 15 + 15 + 24	4,800	12,000	12,000	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 15 + 15 + 24	5,400	13,500	13,500	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	6 + 18 + 18 + 18	4,800	14,400	14,400	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	6 + 18 + 18 + 18	5,400	16,200	16,200	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 9 + 12 + 30	7,200	7,200	9,600	24,000	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 12 + 30	8,000	8,000	10,700	27,300	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 9 + 18 + 24	7,200	7,200	14,400	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 18 + 24	8,100	8,100	16,200	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 12 + 15 + 24	7,200	9,600	12,000	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 12 + 15 + 24	8,100	10,800	13,500	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	9 + 15 + 18 + 18	7,200	12,000	14,400	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	9 + 15 + 18 + 18	8,100	13,500	16,200	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	12 + 12 + 12 + 24	9,600	9,600	9,600	19,200	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 12 + 24	10,800	10,800	10,800	21,600	0	0	0	0	5,270	25.7	23.2
4	60	48,000	12 + 12 + 18 + 18	9,600	9,600	14,400	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 18 + 18	10,800	10,800	16,200	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	12 + 15 + 15 + 18	9,600	12,000	12,000	14,400	0	0	0	0	4,800	23.4	21.2
		54,000	12 + 15 + 15 + 18	10,800	13,500	13,500	16,200	0	0	0	0	5,270	25.7	23.2
4	60	48,000	15 + 15 + 15 + 15	12,000	12,000	12,000	12,000	0	0	0	0	4,800	23.4	21.2
		54,000	15 + 15 + 15 + 15	13,500	13,500	13,500	13,500	0	0	0	0	5,270	25.7	23.2
5	60	48,000	3 + 6 + 6 + 6 + 36	4,800	4,800	4,800	4,800	28,800	0	0	0	4,800	23.4	21.2
		54,000	3 + 6 + 6 + 6 + 36	5,300	5,300	5,300	5,300	32,900	0	0	0	5,270	25.7	23.2

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
5	60	48,000	9 + 9 + 12 + 12 + 18	7,200	7,200	9,600	9,600	14,400	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 12 + 12 + 18	8,100	8,100	10,800	10,800	16,200	0	0	0	5,270	25.7	23.2
5	60	48,000	9 + 9 + 12 + 15 + 15	7,200	7,200	9,600	12,000	12,000	0	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 12 + 15 + 15	8,100	8,100	10,800	13,500	13,500	0	0	0	5,270	25.7	23.2
5	60	48,000	9 + 12 + 12 + 12 + 15	7,200	9,600	9,600	9,600	12,000	0	0	0	4,800	23.4	21.2
		54,000	9 + 12 + 12 + 12 + 15	8,100	10,800	10,800	10,800	13,500	0	0	0	5,270	25.7	23.2
5	60	48,000	12 + 12 + 12 + 12 + 12	9,600	9,600	9,600	9,600	9,600	0	0	0	4,800	23.4	21.2
		54,000	12 + 12 + 12 + 12 + 12	10,800	10,800	10,800	10,800	10,800	0	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 6 + 6 + 6 + 30	4,800	4,800	4,800	4,800	4,800	24,000	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 30	5,300	5,300	5,300	5,300	5,300	27,300	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 6 + 6 + 12 + 24	4,800	4,800	4,800	4,800	9,600	19,200	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 12 + 24	5,400	5,400	5,400	5,400	10,800	21,600	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 6 + 6 + 18 + 18	4,800	4,800	4,800	4,800	14,400	14,400	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 18 + 18	5,400	5,400	5,400	5,400	16,200	16,200	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 6 + 9 + 9 + 24	4,800	4,800	4,800	7,200	7,200	19,200	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 9 + 9 + 24	5,400	5,400	5,400	8,100	8,100	21,600	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 6 + 9 + 15 + 18	4,800	4,800	4,800	7,200	12,000	14,400	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 9 + 15 + 18	5,400	5,400	5,400	8,100	13,500	16,200	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 6 + 12 + 12 + 18	4,800	4,800	4,800	9,600	9,600	14,400	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 12 + 12 + 18	5,400	5,400	5,400	10,800	10,800	16,200	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 6 + 12 + 15 + 15	4,800	4,800	4,800	9,600	12,000	12,000	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 12 + 15 + 15	5,400	5,400	5,400	10,800	13,500	13,500	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 9 + 9 + 12 + 18	4,800	4,800	7,200	7,200	9,600	14,400	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 9 + 9 + 12 + 18	5,400	5,400	8,100	8,100	10,800	16,200	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 9 + 9 + 15 + 15	4,800	4,800	7,200	7,200	12,000	12,000	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 9 + 9 + 15 + 15	5,400	5,400	8,100	8,100	13,500	13,500	0	0	5,270	25.7	23.2
6	60	48,000	6 + 6 + 9 + 12 + 12 + 15	4,800	4,800	7,200	9,600	9,600	12,000	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 9 + 12 + 12 + 15	5,400	5,400	8,100	10,800	10,800	13,500	0	0	5,270	25.7	23.2

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
6	60	48,000	6 + 6 + 12 + 12 + 12 + 12	4,800	4,800	9,600	9,600	9,600	9,600	0	0	4,800	23.4	21.2
		54,000	6 + 6 + 12 + 12 + 12 + 12	5,400	5,400	10,800	10,800	10,800	10,800	0	0	5,270	25.7	23.2
6	60	48,000	6 + 9 + 9 + 9 + 9 + 18	4,800	7,200	7,200	7,200	7,200	14,400	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 9 + 9 + 18	5,400	8,100	8,100	8,100	8,100	16,200	0	0	5,270	25.7	23.2
6	60	48,000	6 + 9 + 9 + 9 + 12 + 15	4,800	7,200	7,200	7,200	9,600	12,000	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 9 + 12 + 15	5,400	8,100	8,100	8,100	10,800	13,500	0	0	5,270	25.7	23.2
6	60	48,000	6 + 9 + 9 + 12 + 12 + 12	4,800	7,200	7,200	9,600	9,600	9,600	0	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 12 + 12 + 12	5,400	8,100	8,100	10,800	10,800	10,800	0	0	5,270	25.7	23.2
6	60	48,000	9 + 9 + 9 + 9 + 9 + 15	7,200	7,200	7,200	7,200	7,200	12,000	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 9 + 9 + 9 + 15	8,100	8,100	8,100	8,100	8,100	13,500	0	0	5,270	25.7	23.2
6	60	48,000	9 + 9 + 9 + 9 + 12 + 12	7,200	7,200	7,200	7,200	9,600	9,600	0	0	4,800	23.4	21.2
		54,000	9 + 9 + 9 + 9 + 12 + 12	8,100	8,100	8,100	8,100	10,800	10,800	0	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 6 + 6 + 6 + 24	4,800	4,800	4,800	4,800	4,800	4,800	19,200	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 24	5,400	5,400	5,400	5,400	5,400	5,400	21,600	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 6 + 6 + 12 + 18	4,800	4,800	4,800	4,800	4,800	9,600	14,400	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 12 + 18	5,400	5,400	5,400	5,400	5,400	10,800	16,200	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 6 + 6 + 15 + 15	4,800	4,800	4,800	4,800	4,800	12,000	12,000	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 15 + 15	5,400	5,400	5,400	5,400	5,400	13,500	13,500	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 6 + 9 + 9 + 18	4,800	4,800	4,800	4,800	7,200	7,200	14,400	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 9 + 9 + 18	5,400	5,400	5,400	5,400	8,100	8,100	16,200	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 6 + 9 + 12 + 15	4,800	4,800	4,800	4,800	7,200	9,600	12,000	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 9 + 12 + 15	5,400	5,400	5,400	5,400	8,100	10,800	13,500	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 6 + 12 + 12 + 12	4,800	4,800	4,800	4,800	9,600	9,600	9,600	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 12 + 12 + 12	5,400	5,400	5,400	5,400	10,800	10,800	10,800	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 9 + 9 + 9 + 15	4,800	4,800	4,800	7,200	7,200	7,200	12,000	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 9 + 9 + 9 + 15	5,400	5,400	5,400	8,100	8,100	8,100	13,500	0	5,270	25.7	23.2
7	60	48,000	6 + 6 + 6 + 9 + 9 + 12 + 12	4,800	4,800	4,800	7,200	7,200	9,600	9,600	0	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 9 + 9 + 12 + 12	5,400	5,400	5,400	8,100	8,100	10,800	10,800	0	5,270	25.7	23.2

PRO-HEAT MODELS

NTXMPH48A182AB/NTXMPH48A182AA OPERATIONAL PERFORMANCE NON-DUCTED, cont.

# of Indoor Unit	Total Nominal Capacity (x1000) [KBTU/H]	TTL Indoor unit Capacity [BTU/H]	Operational [KBTU/H] Performance for Indoor Unit Combination (x1000)	IDU1 capacity [BTU/H]	IDU2 capacity [BTU/H]	IDU3 capacity [BTU/H]	IDU4 capacity [BTU/H]	IDU5 capacity [BTU/H]	IDU6 capacity [BTU/H]	IDU7 capacity [BTU/H]	IDU8 capacity [BTU/H]	Total Input [W]	Operating current (208V) [A]	Operating current (230V) [A]
7	60	48,000	6 + 6 + 9 + 9 + 9 + 9 + 12	4,800	4,800	7,200	7,200	7,200	7,200	9,600	0	4,800	23.4	21.2
		54,000	6 + 6 + 9 + 9 + 9 + 9 + 12	5,400	5,400	8,100	8,100	8,100	8,100	10,800	0	5,270	25.7	23.2
7	60	48,000	6 + 9 + 9 + 9 + 9 + 9 + 9	4,800	7,200	7,200	7,200	7,200	7,200	7,200	0	4,800	23.4	21.2
		54,000	6 + 9 + 9 + 9 + 9 + 9 + 9	5,400	8,100	8,100	8,100	8,100	8,100	8,100	0	5,270	25.7	23.2
8	60	48,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 18	4,800	4,800	4,800	4,800	4,800	4,800	4,800	14,400	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 6 + 18	5,400	5,400	5,400	5,400	5,400	5,400	5,400	16,200	5,270	25.7	23.2
8	60	48,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 15	4,800	4,800	4,800	4,800	4,800	4,800	7,200	12,000	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 9 + 15	5,400	5,400	5,400	5,400	5,400	5,400	8,100	13,500	5,270	25.7	23.2
8	60	48,000	6 + 6 + 6 + 6 + 6 + 6 + 12 + 12	4,800	4,800	4,800	4,800	4,800	4,800	9,600	9,600	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 6 + 12 + 12	5,400	5,400	5,400	5,400	5,400	5,400	10,800	10,800	5,270	25.7	23.2
8	60	48,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 12	4,800	4,800	4,800	4,800	4,800	7,200	7,200	9,600	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 6 + 9 + 9 + 12	5,400	5,400	5,400	5,400	5,400	8,100	8,100	10,800	5,270	25.7	23.2
8	60	48,000	6 + 6 + 6 + 6 + 9 + 9 + 9 + 9	4,800	4,800	4,800	4,800	7,200	7,200	7,200	7,200	4,800	23.4	21.2
		54,000	6 + 6 + 6 + 6 + 9 + 9 + 9 + 9	5,400	5,400	5,400	5,400	8,100	8,100	8,100	8,100	5,270	25.7	23.2