CITYMULTI®

6-TON PURY-HP72YNU-A1

MITSUBISHI ELECTRIC
HEATING & AIR CONDITIONING

Job Name:

System Reference: Date:

460V OUTDOOR VRF HEAT RECOVERY SYSTEM



ACCESSORIES

☑ Big Foot Stand.....for details see Big Foot Stands submittals
☑ BC Controller (Required).....for details see BC Controller Submittals
☑ Joint Kit.....for details see Pipe Accessories Submittal
☑ Snow/Hail Guards Kit.....for details see Snow/Hail Guards Kit Submittal

Specifications			System
Unit Type			PURY-HP72YNU-A1
Cooling Capacity (Nominal)		BTU/H	72,000
Heating Capacity (Nominal)		BTU/H	80,000
Guaranteed Operating Range	Cooling	°F [°C]	23~126 [-5.0~52.0]
	Heating	°F [°C]	-22~60 [-30.0~15.5]
Extended Operating Range	Heating	°F [°C]	-27.4~60 [-33.0~15.5]
External Dimensions (H x W x D)		In. [mm]	71-5/8 x 49-1/4 x 29-3/8 [1,818 x 1,250 x 745]
Net Weight		Lbs. [kg]	644 [292]
External Finish			Pre-coated galvanized steel sheet [MUNSELL 3Y 7.8/1.1 or similar]
Electrical Power Requirements	Voltage, Phase, Hertz, Power Tolerance		460V, 3-phase, 60 Hz, ±10%
Minimum Circuit Ampacity		A	25.0
Maximum Overcurrent Protection		A	40
Recommended Fuse Size		A	25
Recommended Minimum Wire Size		AWG [mm]	10 [5.3]
SCCR		kA	5
Refrigerant Piping Diameter	Liquid (High Pressure)	In. [mm]	5/8 [15.88] Brazed
	Gas (Low Pressure)	In. [mm]	3/4 [19.05] Brazed
Max. Total Refrigerant Line Length		Ft.	1,804
Max. Refrigerant Line Length (Between ODU & IDU)		Ft.	541
Max. Control Wiring Length		Ft.	1,640
Indoor Unit Connectable	Total Capacity		50.0~150.0% of outdoor unit capacity
	Model/Quantity		P04~P96/1.0~18.0
Sound Pressure Levels		dB(A)	56.5/58.0
Sound Power Levels		dB(A)	75.5/77.0
FAN[4]	Type x Quantity		Propeller fan x 2
	Fan Motor Output	kW	0.46+0.46
	Airflow Rate	CFM	6,700
	External Static Pressure	In. WG	Selectable; 0.00, 0.12, 0.24, 0.32, In. WG; factory set to 0 In. WG
Compressor Operating Range			15.0% to 100.0%
Compressor	Type x Quantity		Inverter scroll hermetic compressor x 1
Refrigerant	Type x Original Charge		R410A x 21.0 lbs + 9.0 oz [9.8 kg]
Protection Devices	High Pressure Protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter Circuit (Comp./Fan)		Over-heat protection, Over-current protection
AHRI Ratings (Ducted/Non-ducted)	EER		11.6/12.1
	IEER		21.7/22.8
	COP		3.76/4.09
	SCHE		25.9/25.5

NOTES:
Nominal cooling conditions (Test conditions are based on AHRI 1230-2023)
Indoor: 80°FD.B./67°FW.B. (26.7°CD.B./19.4°CW.B.), Outdoor: 95°FD.B. (35°CD.B.)
Nominal heating conditions (Test conditions are based on AHRI 1230-2023)
Indoor: 70°FD.B. (21.1°CD.B.), Outdoor: 47°FD.B./43°FW.B. (8.3°CD.B./6.1°CW.B.)

[1]Harsh weather environments may demand performance enhancing equipment. Ask your Mitsubishi Electric representative for more details about your region
[2]For details on extended cooling operation range down to -10° F DB, see Low Ambient Kit Submittal
[3]When applying product below -4°F, consult your design engineer for cold climate application best practices, including the use of a backup source for heating
[4]Unit will continue to operate in extended operating range, but capacity is not guaranteed

Specifications are subject to change without notice.

© 2024 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

OUTDOOR UNIT: PURY-HP72YNU-A1 – DIMENSIONS

PURY-HP72, 96, 120T/YNU-A1


Unit: mm (in.)

Connecting pipe specifications

Model	Diameter			
	Refrigerant pipe *1		Service valve	
	High pressure	Low pressure	High pressure	Low pressure
HP72	φ15.88(5/8) Brazed	φ19.05(3/4) Brazed	φ28.58(1-1/8)	φ28.58(1-1/8)
HP96	φ19.05(3/4) Brazed	φ22.2(7/8) Brazed	φ28.58(1-1/8)	φ28.58(1-1/8)
HP120	φ19.05(3/4) Brazed	φ28.58(1-1/8) Brazed	φ28.58(1-1/8)	φ28.58(1-1/8)

*1 Connect the refrigerant pipe to the service valve according to the installation Manual.

NO.	Usage		Specifications
①	For pipes	Front through hole	1(Ø(5-7/8) X 84(3-5/16) Knockout hole
②		Bottom through hole	130(5-15/16) X 94(3-3/4) Knockout hole
③	For wires	Front through hole	φ62.7(2-1/2) or φ34.5(1-3/8) Knockout hole
④		Front through hole	φ43.7(1-3/4) or φ22.2(7/8) Knockout hole
⑤		Bottom through hole	φ65(2-9/16) Knockout hole
⑥		Bottom through hole	φ52(2-1/16) Knockout hole
⑦	For transmission cables	Front through hole	φ34(1-3/8) Knockout hole
⑧		Bottom through hole	φ34(1-3/8) Knockout hole



1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com

FORM# PURY-HP72YNU-A1 - 202404

Specifications are subject to change without notice.

© 2024 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.