

Job Name:

Location:

Drawing Reference:

Schedule No.

System No.:

Date:

OUTDOOR VRFZ HEAT PUMP SYSTEM FEATURES

- 3-phase, 208 / 230V
- Modular variable refrigerant flow zoning (VRFZ) systems; smaller capacity units can be piped together to form a single, large-capacity two-pipe system
- Required Twinning Kit allows for easy field piping connection
- Selectable fan static, 0.12 or 0.24"WG external static pressure; factory set to 0"WG
- Max. Total Refrigerant Line Length: 3,280'; Max. Refrigerant Line Length: 541'; Max. Control Wiring Length: 1,640'
- Connects to CITY MULTI indoor units; controlled via CITY MULTI Controls Network
- External finish: Pre-coated Galvanized-steel Sheets
- Operating Temperature Range
 - Cooling (Outdoor): 23° ~ 115°F (-5° ~ +46°C) DB
 - Heating (Outdoor): -4° ~ +60°F (-20° ~ +16°C) WB



PUHY-P120TJMU-A PUHY-P120TJMU-A PUHY-P96TJMU-A

INVERTER


**OPTIONAL PARTS**

- ☐ Twinning Kit* CMY-Y300VBK2
 - ☐ T-Branch Joint (≤ 72,000 Btu/h).....CMY-Y102S-G2
 - ☐ T-Branch Joint (73,000-144,000 Btu/h).....CMY-Y102L-G2
 - ☐ T-Branch Joint (145,000 - 234,000 Btu/h).....CMY-Y202-G2
 - ☐ T-Branch Joint (≥ 235,000 Btu/h).....CMY-Y302-G2
 - ☐ Header - 4-Branch (Capacity: ≤ 72,000 Btu/h).....CMY-Y104-G
 - ☐ Header - 8-Branch (Capacity: ≤ 144,000 Btu/h).....CMY-Y108-G
 - ☐ Header - 10-Branch (Capacity: ≤ 234,000 Btu/h).....CMY-Y1010-G
- * Twinning Kit is necessary to combine the refrigerant flows of the modules and is included in the outdoor unit set.

Specifications		System	Module 1	Module 2	Module 3
Unit Type		PUHY-P336TSJMU-A	PUHY-P120TJMU-A	PUHY-P120TJMU-A	PUHY-P96TJMU-A
Nominal Cooling Capacity	Btu/h	336,000	120,000	120,000	96,000
Nominal Heating Capacity	Btu/h	378,000	135,000	135,000	108,000
External Dimensions (H x W x D)	In. / mm	Refer to Module Data	65 x 68-15/16 x 29-15/16 / 1,650 x 1,750 x 760	65 x 68-15/16 x 29-15/16 / 1,650 x 1,750 x 760	65 x 48-1/16 x 29-15/16 / 1,650 x 1,220 x 760
Net Weight	Lbs. / kg	1,755 / 795	629 / 285	629 / 285	497 / 225
Electrical Power Requirements	Voltage, Phase, Hertz	Refer to Module Data**	208 / 230V, 3-phase, 60Hz		
Cooling Power Input	kW	28.58	Refer to System Data		
Heating Power Input	kW	30.24			
Cooling Current (208/230V)	R.L.A.	88.1 / 79.7	Refer to System Data		
Heating Current (208/230V)	R.L.A.	93.2 / 84.3			
Minimum Circuit Ampacity (MCA)**	A	Refer to Module Data**	49 / 46**	49 / 46**	36 / 34**
Recommended Fuse/Breaker Size**	A	Refer to Module Data**	50**	50**	40**
Maximum Fuse Size**	A	Refer to Module Data**	70 / 60**	70 / 60**	50 / 50**
Piping Diameter					
From Twinning Kit to Indoor Units (Braze) (In. / mm)	Liquid (High Pressure)	3/4 / 19.05	Refer to System Data		
	Gas (Low Pressure)	1-5/8 / 41.28			
From Modules to Twinning Kit (Braze) (In. / mm)	Liquid (High Pressure)	Refer to Module Data	1/2 / 12.7	1/2 / 12.7	3/8 / 9.52
	Gas (Low Pressure)		7/8 / 22.2	7/8 / 22.2	7/8 / 22.2
Indoor Unit	Total Capacity	50 to 130% of ODUs	Refer to System Data		
	Model / Quantity	P06 ~ P96 / 2 to 50			
Sound Pressure Levels	dB(A)	64.5	60.0	60.0	58.0
Fan		Refer to Module Data			
Type x Quantity			Propeller Fan x 2	Propeller Fan x 2	Propeller Fan x 1
Airflow Rate	CFM		12,010	12,010	6,180
Direct-drive Inverter Motor Output	kW		0.92 + 0.92	0.92 + 0.92	0.92
Compressor Operating Range		7 to 100%	Refer to System Data		
Compressor Type x Quantity		Refer to Module Data	Inverter-driven Scroll Hermetic x 1 for Each Module		
Compressor Motor Output	kW		8.1	8.1	6.8
Compressor Crankcase Heater	kW		0.045	0.045	0.045
Refrigerant			R410A		
Lubricant		Refer to Module Data	MEL32		
High-pressure Protection Device		Refer to Module Data	601 psi / 4.15 MPa	601 psi / 4.15 MPa	601 psi / 4.15 MPa
Compressor / Fan Protection Device			Overheat Protection / Thermal Switch		
Inverter Protection Device			Overheat / Overcurrent Protection		
Blue Fin Anti-corrosion Protection: Cellulose- and polyurethane-resin coating treatment applied to condenser coil that protects it from air contaminants; ≥1µm thick; Salt Spray Test Method - no unusual rust development to 480 hours.					

** Each individual module requires a separate electrical connection. Reference electrical data for each individual module.

Outdoor Unit: PUHY-P336TSJMU-A – DIMENSIONS



Front view

Left view

Twining pipe connection size

Package unit name		PUHY-P336TSJMU-A(-BS)	PUHY-P360TSJMU-A(-BS)
Component unit name	Outdoor unit 1	PUHY-P120TJMU-A(-BS)	PUHY-P144TJMU-A(-BS)
	Outdoor unit 2	PUHY-P120TJMU-A(-BS)	PUHY-P120TJMU-A(-BS)
	Outdoor unit 3	PUHY-P96TJMU-A(-BS)	PUHY-P96TJMU-A(-BS)
Outdoor Twining Kit(optional parts)		CNY-Y300VBK2	
Indoor unit-Twining pipe 2	Liquid a	ø19.05(3/4)	
	Gas b	ø41.28(1-5/8)	
Twining pipe 1-Twining pipe 2	Liquid c	ø19.05(3/4)	
	Gas d	ø34.93(1-3/8)	

Twining pipe-Outdoor unit	Unit model		Liquid	Gas
	P96		e or g or i ø3.52(3/8)	f or h or j ø22.2(7/8)
	P120		ø12.7(1/2)	ø22.2(7/8)
	P144		ø12.7(1/2)	ø28.58(1-1/8)


- Note 1. Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.
2. Twining pipes should not be tilted more than 15 degrees from the horizontal plane.
Be sure to see the Installation Manual for details of Twining pipe installation.
3. The pipe section before the Twining pipe (sections "a", "b", "c" and "d" in the figure) must have at least 500mm(19-11/16) of straight section
(*including the straight pipe that is supplied with the Twining pipe).
4. Only use the Twining pipe by Mitsubishi (optional parts).

Unit : mm(in.)


Twinning Kit: CMY-Y300VBK2

CMY-Y300VBK2 Twinning Kit

For Gas pipe:




For Liquid pipe:




Reducer (Accessory)

Inches



ID: Inner Diameter OD: Outer Diameter

Note 1. Reference the angle of the branch pipe below the fig.




The angle of the branch pipe is within $\pm 15^\circ$ against the ground.

2. Use the attached pipe to braze the port-opening of the distributor.
3. Pipe diameter is indicated by inside diameter.

For instructions on piping the units together using the twinning kit, see the Installation Manual.

Modules 1 and 2: PUHY-P120TJMU-A – DIMENSIONS



NO.	Usage	Specifications
①	For pipes	Front through hole 102 X 72 Knockout hole (4-1/32) (2-7/32)
②		Bottom through hole 150 X 94 Knockout hole (5-29/32) (3-23/32)
③	For wires	Front through hole ø62.7 or ø34.5 Knockout hole (2-15/32) (1-3/8)
④		Front through hole ø43.7 or ø22.2 Knockout hole (1-3/4) (7/8)
⑤		Bottom through hole ø65 Knockout hole (2-9/16)
⑥	For transmission cables	Front through hole ø34 Knockout hole (1-11/32)

Note 1: Please refer to (2/2) for information regarding necessary spacing around the unit and foundation work.

2: All brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C(248°F).

<Optional parts>
 ● Connecting pipe
 <Gas> Elbow (IDø28.58(1-1/8)XODø28.58(1-1/8)).....P120, 144 1pc.
 Pipe (IDø28.58(1-1/8)XODø22.2(7/8)).....P120 1pc.
 <Liquid> Pipe (IDø12.7(1/2)XODø6.52(3/8)).....P120 1pc.
 Pipe (IDø12.7(1/2)XODø12.7(1/2)).....P120, 144 1pc.


Left side view

Model		Position dimensions for the refrigerant service valve		Connection specifications for the refrigerant service valve *1	
		Liquid	Gas	Liquid	Gas
PUHY-P120TJMU	143 (5-21/32)	172 (6-25/32)		ø9.52 Brazed (3/8)	ø22.2 Brazed (7/8)
				ø12.7 Brazed (1/2) *2-3	
PUHY-P144TJMU				ø12.7 Brazed (1/2)	ø28.58 Brazed (1-1/8)

*1 Connect by using the connecting pipes (for bottom piping and front piping) that are sold separately.


*2 Indicates dimensions and connection specifications in the case the unit is that are sold separately.

*3 Total length $\geq 40\text{m}(131\text{ft})$



Unit : mm(in.)


Module 3: PUHY-P96TJMU-A – DIMENSIONS



- <Optional parts>
 ● Connecting pipe
 <Gas>
 - Elbow (Dø25.4)(XODø25.4)(1) 1pc.
 - Pipe (Dø25.4)(XODø22.7)(18) 1pc.
 <Liquid>
 - Pipe (Dø8.52)(3/8)(XODø8.52)(3/8) 1pc.
 - Pipe (Dø8.52)(3/8)(XODø12.7)(12) 1pc.

Note 1. Please refer to (2/2) for information regarding necessary spacing around the unit and foundation work.
 2. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120 °C(248°F).

NO.	Usage	Specifications
①	Front through hole	102 X 72 Knockout hole (4-1/32) (2-27/32)
②	Bottom through hole	150 X 94 Knockout hole (5-29/32) (3-23/32)
③	Front through hole	ø62.7 or ø34.5 Knockout hole (2-15/32) (1-3/8)
④	Front through hole	ø45.7 or ø22.2 Knockout hole (1-3/4) (7/8)
⑤	Bottom through hole	ø65 Knockout hole (2-9/16)
⑥	Front through hole	ø34 Knockout hole (1-11/32)



Model	Position dimensions for the refrigerant service valve		Connection specifications for the refrigerant service valve *1	
	Liquid	Gas	Liquid	Gas
PUHY-P96TJMU	158 (6-1/4)	172 (6-25/32)	ø9.52 Brazed (3/8) (1/2) *2	ø22.2 Brazed (7/8)

*1 Connected by using the connecting pipes (for bottom piping and front piping) that are sold separately.
 *2 Total length ≥ 90m(295ft)

Unit : mm(in.)



Mitsubishi Electric Air Conditioning & Refrigeration Systems Works acquired ISO 9001 certification under Series 9000 of the International Standard Organization (ISO) based on a review of quality warranties for the production of refrigeration and air conditioning equipment.

ISO Authorization System
 The ISO 9000 series is a plant authorization system relating to quality warranties as stipulated by the ISO. ISO 9001 certifies quality warranties based on the "design, development, production, installation and auxiliary services" for products built at an authorized plant.



Mitsubishi Electric Air Conditioning & Refrigeration Systems Works acquired environmental management system standard ISO 14001 certification.

The ISO 14000 series is a set of standards applying to environmental protection set by the International Standard Organization (ISO).



HVAC Advanced Products Division
 Mitsubishi Electric & Electronics USA, Inc.
 3400 Lawrenceville Suwanee Rd.
 Suwanee, GA 30024

Tele: 678-376-2900 • Fax: 800-889-9904
 Toll Free: 800-433-4822 (#4)
 www.mehvac.com

Specifications are subject to change without notice.