CITYMULTI®

26-TON PURY-P312YSNU-A(-BS)

MITSUBISHI ELECTRIC
HEATING & AIR CONDITIONING

Job Name:

System Reference: Date:

460V OUTDOOR VRF HEAT RECOVERY SYSTEM



UNIT OPTION

☑ Standard Model PURY-P312YSNU-A

☑ Seacoast (BS) Model PURY-P312YSNU-A-BS

ACCESSORIES

☑ Big Foot Stand ..... for details see Big Foot Stands submittals

☑ Twinning Kit (Required) CMY-R300NCBK

☑ BC Controller (Required) ..... for details see BC Controller Submittals

☑ Joint Kit ..... for details see Pipe Accessories Submittal

☑ Low Ambient Kit ..... for details see Low Ambient Kit Submittal

☑ Panel Heater Kit ..... for details see Panel Heater Kit Submittal

☑ Snow/Hail Guards Kit ..... for details see Snow/Hail Guards Kit Submittal

Specifications			System
Unit Type			PURY-P312YSNU-A(-BS)
Cooling Capacity (Nominal)		BTU/H	312,000
Heating Capacity (Nominal)		BTU/H	350,000
Net Weight		Lbs. [kg]	1,456 [660]
Refrigerant Piping Diameter	Liquid (High Pressure)	In. [mm]	1-1/8 [28.58] Brazed
	Gas (Low Pressure)	In. [mm]	1-5/8 [41.28] Brazed
Max. Total Refrigerant Line Length		Ft.	3,116
Max. Refrigerant Line Length (Between ODU & IDU)		Ft.	541
Max. Control Wiring Length		Ft.	1,640
Indoor Unit Connectable	Total Capacity		50.0~150.0% of outdoor unit capacity
	Model/Quantity		P04~P96/2.0~50.0
Sound Pressure Levels		dB(A)	67.0/69.0
Sound Power Levels		dB(A)	87.0/88.5
Compressor Operating Range			7.5% to 100.0%
AHRI Ratings (Ducted/Non-ducted)	EER		9.0/9.2
	IEER		18.1/19.7
	COP		3.2/3.36
	SCHE		20.6/23.8

Specifications			Module 1	Module 2
Unit Type			PURY-P168YNU-A(-BS)	PURY-P144YNU-A(-BS)
Cooling Capacity (Nominal)		BTU/H	168,000	144,000
Heating Capacity (Nominal)		BTU/H	188,000	160,000
Guaranteed Operating Range[1]	Cooling[2]	ºF [ºC]	23~126 [-5.0~52.0]	23~126 [-5.0~52.0]
Guaranteed Operating Range	Heating	ºF [ºC]	-13~60 [-25.0~15.5]	-13~60 [-25.0~15.5]
Extended Operating Range	Heating	ºF [ºC]	-18.0~60 [-18.0~15.5]	-18.0~60 [-18.0~15.5]
External Dimensions (H x W x D)		In. [mm]	71-5/8 x 68-15/16 x 29-3/16 [1,818 x 1,750 x 740]	71-5/8 x 48-7/8 x 29-3/16 [1,818 x 1,240 x 740]
Net Weight		Lbs. [kg]	774 [351]	682 [309]
External Finish			Pre-coated galvanized steel sheet (+powder coating for -BS type) [MUNSELL 5Y 8/1]	Pre-coated galvanized steel sheet (+powder coating for -BS type) [MUNSELL 5Y 8/1]
Electrical Power Requirements	Voltage, Phase, Hertz, Power Tolerance		460V, 3-phase, 60 Hz, ±10%	460V, 3-phase, 60 Hz, ±10%
Minimum Circuit Ampacity		A	32.0	28.0
Maximum Overcurrent Protection		A	50	45
Recommended Fuse Size		A	40	30
Recommended Minimum Wire Size		AWG [mm]	8 [8.4]	10 [5.3]
SCCR		kA	5	5
FAN[4]	Type x Quantity		Propeller fan x 2	Propeller fan x 2
	Airflow Rate	CFM	14,850	9,550
	External Static Pressure	In. WG	Selectable; 0.00, 0.12, 0.24, 0.32, In. WG; factory set to 0 In. WG	Selectable; 0.00, 0.12, 0.24, 0.32, In. WG; factory set to 0 In. WG
Compressor	Type x Quantity		Inverter scroll hermetic compressor x 1	Inverter scroll hermetic compressor x 1
Refrigerant	Type x Original Charge		R410A x 23.0 lbs + 12.0 oz [10.8 kg]	R410A x 23.0 lbs + 12.0 oz [10.8 kg]
Protection Devices	High Pressure Protection		High pressure sensor, High pressure switch at 4.15 MPa (601 psi)	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)
	Inverter Circuit (Comp./Fan)		Over-heat protection, Over-current protection	Over-heat protection, Over-current protection

NOTES:
Nominal cooling conditions (Test conditions are based on AHRI 1230-2023)
Indoor: 80°FD.B./67°FW.B. (26.7°CD.B./19.4°CW.B.), Outdoor: 95°FD.B. (35°CD.B.)
Nominal heating conditions (Test conditions are based on AHRI 1230-2023)
Indoor: 70°FD.B. (21.1°CD.B.), Outdoor: 47°FD.B./43°FW.B. (8.3°CD.B./6.1°CW.B.)

[1]Harsh weather environments may demand performance enhancing equipment. Ask your Mitsubishi Electric representative for more details about your region
[2]For details on extended cooling operation range down to -10° F DB, see Low Ambient Kit Submittal
[3]When applying product below -4°F, consult your design engineer for cold climate application best practices, including the use of a backup source for heating
[4]Unit will continue to operate in extended operating range, but capacity is not guaranteed


Specifications are subject to change without notice.

© 2024 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

OUTDOOR UNIT: PURY-P312YSNU-A(-BS) – DIMENSIONS

PURY-P312YSNU-A(-BS)

Unit: mm(in)



		Unit model	High pressure c or e	Low pressure d or f
Twinning pipe–Outdoor unit		P144	ø22.2(7/8)	ø28.58(1-1/8)
		P168	ø22.2(7/8)	ø28.58(1-1/8)

Twinning pipe connection size

Package unit name		PURY-P312YSNU-A(-BS)
Component unit name	Outdoor unit 1	PURY-P168YNU-A(-BS)
	Outdoor unit 2	PURY-P144YNU-A(-BS)
Outdoor Twinning Kit(optional parts)		CMY-R300NCBK
BC controller ~Twinning pipe	High pressure | a	ø28.58(1-1/8)
	Low pressure | b	ø41.28(1-5/8)

Note 1. Connect the pipes as shown in the figure above. Refer to the table above for the pipe size.
2. Twinning pipes should not be tilted more than 15 degrees from the horizontal plane.
Be sure to see the Installation Manual for details of Twinning pipe installation.
3. The pipe section before the Twinning pipe (section "a"and "b"in the figure) must have at least 500mm(19-11/16) of straight section (*including the straight pipe that is supplied with the Twinning pipe).
4. Only use the Twinning pipe by Mitsubishi (optional parts).

NOTES:
SEACOAST PROTECTION
Anti-corrosion Protection: A coating treatment is applied to condenser coil for protection from air contaminants.
Standard: Salt Spray Test Method - no unusual rust development to 480 hours.
Sea Coast (BS): Salt Spray Test Method (JRA 9002) - no unusual rust development to 960 hours.


Specifications are subject to change without notice.

© 2024 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

MODULE 1: PURY-P168YNU-A(-BS) – DIMENSIONS

PURY-P168YNU-A(-BS)

Unit: mm(in)



NOTES:
SEACOAST PROTECTION
Anti-corrosion Protection: A coating treatment is applied to condenser coil for protection from air contaminants.
Standard: Salt Spray Test Method - no unusual rust development to 480 hours.
Sea Coast (BS): Salt Spray Test Method (JRA 9002) - no unusual rust development to 960 hours.

Specifications are subject to change without notice.

© 2024 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

MODULE 2: PURY-P144YNU-A(-BS) – DIMENSIONS

PURY-P96,120,144YNU-A(-BS)

Unit: mm(in)


Note 1. At brazing of pipes, wrap the refrigerant service valve with wet cloth and keep the temperature of refrigerant service valve under 120°C(248°F).

Connecting pipe specifications

Model	Diameter			
	Refrigerant pipe		Service valve	
	High pressure	Low pressure	High pressure	Low pressure
P96	ø19.05(3/4) Brazed *1	ø22.2(7/8) Brazed *1	ø28.58(1-1/8)	ø28.58(1-1/8)
P120				
P144	ø22.2(7/8) Brazed *1	ø28.58(1-1/8) Brazed		

*1 Connect the refrigerant pipe to the service valve according to the Installation Manual.

NO.	Usage		Specifications
①	For pipes	Front through hole	148(5-7/8) × 84(3-5/16) Knockout hole
②		Bottom through hole	150(5-15/16) × 94(3-3/4) Knockout hole
③	For wires	Front through hole	ø62.7(2-1/2) or ø34.5(1-3/8) Knockout hole
④		Front through hole	ø43.7(1-3/4) or ø22.2(7/8) Knockout hole
⑤		Bottom through hole	ø65(2-9/16) Knockout hole
⑥		Bottom through hole	ø52(2-1/16) Knockout hole
⑦	For transmission cables	Front through hole	ø34(1-3/8) Knockout hole
⑧		Bottom through hole	ø34(1-3/8) Knockout hole



NOTES:
SEACOAST PROTECTION
Anti-corrosion Protection: A coating treatment is applied to condenser coil for protection from air contaminants.
Standard: Salt Spray Test Method - no unusual rust development to 480 hours.
Sea Coast (BS): Salt Spray Test Method (JRA 9002) - no unusual rust development to 960 hours.

Specifications are subject to change without notice.


© 2024 Mitsubishi Electric Trane HVAC US LLC. All rights reserved.

TWINNING KIT: CMY-R300NCBK – DIMENSIONS

CMY-R300NCBK

Unit: mm (in.)


Note:
1. Refer to the figure below for the installation position of the twinning pipe.




Slope of the twinning pipes are at an angle within ±15° to the horizontal plane.

2. Use the attached pipe to braze the port-opening of the twinning pipe.
3. Pipe diameter is indicated by inside diameter.


Low-pressure twinning pipe




<Deformed pipe(Accessory)>




High-pressure twinning pipe



<Deformed pipe(Accessory)>



Note 1. Reference the attitude angle of the twinning pipe below the fig.



The angle of the twinning pipe is within ±15° against the horizontal plane.

2. Use the attached pipe to braze the port-opening of the twinning pipe.
3. Pipe diameter is indicated by inside diameter.
4. Only use the Twinning pipe by Mitsubishi (optional parts) .

1340 Satellite Boulevard Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com

FORM# PURY-P312YSNU-A - 202404