

Subject: MCR-10063, Fix errors in CY73-01 (Inter-Multics File Transfer Facility Manual)

Author: Eric Swenson

Date: May 25, 2019

Problem Description

There are several typos in the Inter-Multics File Transfer Facility Reference Manual, CY73-01. First, the pathname of the default TTF is incorrect. It is specified as:

```
>udd>SysAdmin>admin>TTF
```

But this was changed (several releases back) to:

```
>udd>SysAdmin>admin>TTF.ttf
```

Additionally, several of the examples use incorrect syntax for directives in the CMF — they are missing a trailing semicolon (;).

Finally, in the section “Subchannel Access Control Segment”, the example uses the “add_names” command, while this command is actually “add_name”.

Ticket <http://multics-trac.swenson.org/ticket/142> describes this issue.

Proposed Changes

Add an errata info segment for CY73 with the following content:

```
2019-05-25 CY73-01 (Inter-Multics File Transfer Facility Reference Manual)
Errata Information for MR12.7
```

pg 2-2: Change the paragraph:

```
The pathname of the TTF is usually:
```

```
>udd>SysAdmin>admin>TTF
```

to:

```
The pathname of the TTF is usually:
```

```
>udd>SysAdmin>admin>TTF.ttf
```

pg 2-3: Under "Example 1", add a semicolon (;) to the end of the additional_info directive so that it reads:

```
additional_info: "type= host, connect_timeout= none,
                 rts_mode= no";
```

Also add a semicolon (;) in "Example 2" at the end of the additional_info directive.

pg 2-4: Under "Example 1", add a semicolon (;) at the end of the additional_info directive.

Under "Example 2", add a semicolon (;) at the end of the additional_info directive.

pg 2-6: Under "Example", add a semicolon (;) at the end of the terminal_type

directive, so that it reads:

```
name: b.h203;
  service: multiplexer;
  multiplexer_type: hasp;
  baud: 4800;
  line_type: SSC;
  terminal_type: IMFT_HASP_HOST;
```

pg 2-7: In the "Example" at the top of the page, add a semicolon (;) at the end of the line_type directive and correct the indentation so that the example reads:

```
name: b.h203.opr;
  service: slave;
  line_type: BSC;
```

pg 2-26: Under the section "Subchannel Access Control Segment", 5th paragraph, change:

```
add_names >scl>rcp>x.hNNN.sub1.acs =.=.sub2.= =.=.sub3.=
=.=.sub4.=
```

to:

```
add_name >scl>rcp>x.hNNN.sub1.acs =.=.sub2.= =.=.sub3.= =.=.sub4.=
```

Documentation

No documentation is required except that the errata will be listed in the Software Release Bulletin in the next Multics release.

Testing

No testing required.

Version History

Date	Revision	Author	Comment
2019-05-25	1.0	Eric Swenson	Initial revision of the MCR.