









## **Jaw Crusher**

- · Semi hydraulic Jaw Adjust
- High Capacity 960mm x 600mm opening
- Reverse crushing capability

# Feeder/Hopper

- Capacity: 3 cubic metre
- 800mm wide
- Hardox lined
- Declined feeder floor to assist material flow
- Wireless Radio control

# **Discharge Conveyor**

- 1000mm wide
- 3000mm discharge height
- Low maintenance design

Hydraulic stabilisation legs

Machine weight 28,000kg

Required Power 400v 3phase

### Contact us:

Unit 10a, Enterprise Park, Drumquin Rd, Castlederg, Co. Tyrone, N. Ireland, BT81 7PX

**T.** +44 28 8167 8571 **E.** info@omegacrusher.com

# mega **JasoM**













<sup>\*</sup>Details may change on final Specification

# MAIN DISCHARGE CONVEYOR 1000mm wide belt 3000m discharge height for large stockpiles Hydraulic folding for ease of transport **Electric drive motor** Spoke tail drum H. 3298 W. 3000 L. 11,390 WEIGHT. 28,000 KGS Self-cleaning spoke tail drum. **CRUSHER BOX** Single toggle Size: 960mm x 600mm **VIBRATING FEEDER** Speed 280 rpm 800mm wide Drive Electric 90kw vibrating feeder Adjustable with tie back Feeder floor has a rod and spring 5-degree angle to help in material flow Crusher can be run in both forward and in reverse. **Automatic stop start** as crusher fills Operator remote TRUCK MOUNTING control on/off. **POINT (5TH WHEEL PIN)** Always on electric drive motors, for higher efficiency. HYDRAULIC JACKING **FEED HOPPER** LEGS BOTH FRONT AND **REAR FOR EASE OF SET UP** · 3.8 cubic metre hopper. Which can be filled by excavator or wheeled loader 960mm opening into SIDE DISCHARGE CONVEYOR jaw crusher 700mm wide belt Fitted with side 2000m discharge height for large support legs. stockpiles of natural fines Hydraulic folding for ease of transport **Electric drive motor** Self-cleaning spoke tail drum.

T. +44 28 8167 8571
W. info@omegacrusher.com
www.omegacrusher.com

TWIN AXLES FOR EASE OF MOVEMENT, THE AXLES ARE ON SPRING SUSPENSION

