



TUB GRINDER

Like all Diamond Z Grinders, the DZT8000 Series offers extreme attention to safety, along with being easy to use and maintain.

FEATURES

- ◆ Radio remote control
- ◆ Tool box
- ◆ Choice of screens
- ◆ Engine cover
- ◆ Fluid coupling mill drive.
- ◆ Wheeled or tracked
- ◆ Diesel or electric
- ◆ All track mounted machines come with 24" (600mm) wide pads, other options available





SPECIFICATIONS	DZT8000	DZT8000TKT
Power	CAT® C27 1,050 HP Tier 4	CAT® C27 1,050 HP Tier 4
Transmission	Fluid Coupling Drive	Fluid Coupling Drive
Transport dimensions (L x W x H)	40'-1" x 11'-11" x 13'-7" (12.21m x 3.63m x 4.16m)	45'-7" x 11'-11" x 13'-7" (13.89m x 3.63m x 4.16m)
Operating dimensions (L x W x H)	65'-4" x 14'-0" x 18'-0" (19.93m x 4.26m x 5.48m)	49'-11" x 14'-0" x 13'-0" (14.96m x 4.26m x 3.96m)
Weight	77,000 lbs. (34,926.58 kg)	96,000 lbs. (44,905.60 kg)
Mill feed opening (W x H)	32.5" x 60" (9.93m x 18.28m)	32.5" x 60" (9.93m x 18.28m)
Screen area	4,800 sq. in. (30,967.68 sq. cm)	4,800 sq. in. (30,967.68 sq. cm)
Production	Up to 120 TPH/480 YPH	Up to 120 TPH/480 YPH

All information subject to change without notice. Please reconfirm any critical details. Production rates based on customer reports, actual throughput will vary depending on on-site specifics.