



◀◀◀◀◀ DZ4065TK

HIGH CAPACITY TRACKED STACKER

The Diamond Z DZ4065TK sets the standard for high capacity, high mobility stackers. The DZ4065TK comes with an impressive array of features, including a large hopper, full-length guarding, an easily accessible engine bay, an impact section under the feeder and an adjustable feeder height. When the DZ4065TK arrives at a job site, it takes only a few minutes to set up and get to work. As is the case with all Diamond Z stackers, the DZ4065TK features a setback design for maximum stockpiling.

At 65' (19.8m) long, the DZ4065TK is the entry point for Diamond Z tracked stackers, which are also available in 80' (24.3m), 100' (30.4m) and custom lengths.

FEATURES

- ◆ Hydraulic folding head section for transport minimizing setup time
- ◆ Hydraulically adjustable discharge height up to 27' 5" (8.4m)
- ◆ Hydraulically adjustable feed in height to compliment crushing and screening plants
- ◆ 67hp (50kw) giving a rating of up to 550USTPH (500TPH)
- ◆ 11' 4" (3.5m) tracks for superior maneuverability & stability
- ◆ Fuel efficient hydraulics system
- ◆ User friendly hydraulic controls
- ◆ Hopper HARDOX™ liners
- ◆ Heavy duty impact bed





SPECIFICATIONS		DZ4065TK	
Engine	Cat 2.2 67hp (50kw) Tier 4 Final	Weight	23,148 lbs (10,500kg approx.)
Transport Height	8' 3" (2.5m)	Stockpile Height	25' 10" (7.88m)
Transport Length	39' 9" (12.1m)	Stockpile Capacity	1,180 yd ³ (902m ³)
Transport Width	7' 8" (2.34m)	Production	550 USTPH (500 TPH)

All information subject to change without notice. Please reconfirm any critical details. Productions rates based on customer reports, actual throughput will vary depending on on-site specifics.