





SPECIFICATIONS	DZH3000	DZH3000TKT
Power	CAT® C15 580 HP Tier 4	CAT® C18 765 HP Tier 4
Transmission	Fluid Coupling Drive	Fluid Coupling Drive
Transport dimensions (L x W x H)	37'-1" x 10'-5" x 13'-3" (11.30m x 3.17m x 4.01m)	37'-1" x 10'-5" x 13'-3" (11.30m x 3.17m x 4.01m)
Operating dimensions (L x W x H)	52'-1" x 10'-5" x 15'-0" (15.9 x 3.17m x 4.57m)	52'-1" x 10'-5" x 15'-0" (15.9 x 3.17m x 4.57m)
Weight	63,000 lbs. (28,576.29 kg)	75,000 lbs. (34,019.4 kg)
Mill feed opening (W x H)	59" x 32" (18m x 9.7m)	59" x 32" (18m x 9.7m)
Screen area	3,146 sq. in. (20,296.73 sq. cm)	3,146 sq in (20,296.73 sq. cm)
Production	Up to 84 TPH/335 YPH	Up to 84 TPH/335 YPH

All information subject to change without notice. Please reconfirm any critical details. Productions rates based on customer reports, actual throughput will vary depending on on-site specifics.