## POLYKEN®

## Premium UL 181B-FX Listed Duct Tape

557

	Backing	Backing:	Printed Polyethylene Coated Cloth			
	Adhesive	Adhesive:	Rubber			
		Liner: N	/Α			
		Colors: M	letallic, Black, Silver			
		Specifications: UL 181B-FX Listed				
	Rep vos *	Standard Si	<b>zes:</b> 48mm x 55M, 72mm x 55M			
Applications						
A superior closure system for use on UL Listed Challengir						
flexible, non-metallic air duct			and repair applications			
Features & Benefits						
High strength PE Coated Cloth Backing Tough and durable Conference all la terminate for an effective						
Aggressive Natural Rubber Adhesive			Conformable to wrap ducts for an effective seal Excellent bond to sheet metal and other surfaces			
			High strength to withstand vertical pull from the			

UL181B-FX Listed
UL181B-FX Listed
Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
Low VOC Content
Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values						
	Standard UOM	Metric UOM	Test Method			
Total Thickness	14.0 mils	0.356 mm	ASTM D-1000			
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101			
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101			
Tensile Strength	29 lb/in	50.79 N/cm	ASTM D-1000			
Smoke Developed	15		ASTM E-84			
Flame Spread	15		ASTM E-84			
Operating Temperature	40 to 200 °F	4 to 93 °C				
VOC Content	<1 g/L					

Recommended Storage Conditions: 60-80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.polyken.com