


Class 300 (XS/XH)

FIG. 3161

90° Elbow



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

FIGURE 3161 - 90° ELBOW

Nominal Size	Dimension A	Approx. Wt. Each
<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1/4	0.94	0.20
8	23.88	0.09
3/8	1.06	0.29
10	26.92	0.13
1/2	1.25	0.47
15	31.75	0.21
3/4	1.44	0.66
20	36.58	0.30
1	1.63	1.20
25	41.40	0.54
1 1/4	1.94	1.90
32	49.28	0.86
1 1/2	2.13	2.50
40	54.10	1.13
2	2.50	4.20
50	63.50	1.91
2 1/2	2.94	5.30
65	74.68	2.40
3	3.38	9.70
80	85.85	4.40
4	4.50	16.00
100	114.30	7.26

MATERIAL SPECIFICATIONS

Dimensions: Fittings: ASME B16.3
 Unions: ASME B16.39
 Bushings/Plugs: ASME B16.14

Material: ASTM A-197

Finish: Black or Hot Dip Galvanized per ASTM A153 Class A

Threads: NPT per ASME B1.20.1

Pressure Ratings: Fittings: ASME B16.3
 Unions: ASME B16.39
 Bushings/Plugs: ASME B16.14

Pressure Testing: All malleable iron fittings are tested for through wall porosity using an air under water process.

Agency Approvals: All malleable iron fittings and unions are UL/ULC Listed and FM Approved.

PROJECT INFORMATION

APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	