


## Class 300 (XS/XH)

# FIG. 3164

## Straight Tee



For Listings/Approval Details and Limitations, visit our website at [www.anvilintl.com](http://www.anvilintl.com) or contact an Anvil® Sales Representative.

### FIGURE 3164 - STRAIGHT TEE

Nominal Size	Dimension A	Approx. Wt. Each
<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1/4	1.31	0.27
8	33.27	0.12
3/8	1.06	0.42
10	26.92	0.19
1/2	1.25	0.65
15	31.75	0.29
3/4	1.44	1.10
20	36.58	0.50
1	1.63	1.60
25	41.40	0.73
1 1/4	1.94	2.50
32	49.28	1.13
1 1/2	2.13	3.40
40	54.10	1.54
2	2.50	5.20
50	63.50	2.36
2 1/2	2.94	8.00
65	74.68	3.63
3	3.38	13.00
80	85.85	5.90
4	4.50	24.00
100	114.30	10.89

### MATERIAL SPECIFICATIONS

Dimensions: Fittings: ASME B16.3  
 Unions: ASME B16.39  
 Bushings/Plugs: ASME B16.14

Material: ASTM A-197

Finish: Black or Hot Dip Galvanized per ASTM A153 Class A

Threads: NPT per ASME B1.20.1

Pressure Ratings: Fittings: ASME B16.3  
 Unions: ASME B16.39  
 Bushings/Plugs: ASME B16.14

Pressure Testing: All malleable iron fittings are tested for through wall porosity using an air under water process.

Agency Approvals: All malleable iron fittings and unions are UL/ULC Listed and FM Approved.

### PROJECT INFORMATION

### APPROVAL STAMP

Project:	<input type="checkbox"/> Approved
Address:	<input type="checkbox"/> Approved as noted
Contractor:	<input type="checkbox"/> Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	