



# Lead Free\*

## 95LF SERIES

### Stop and Waste Ball Valve

<b>Job Name:</b>	<b>Contractor:</b>
<b>Job Location:</b>	<b>P.O. Number:</b>
<b>Engineer:</b>	<b>Representative:</b>
<b>Tag:</b>	<b>Wholesale Distributor:</b>

#### DESCRIPTION

The Apollo® 95LF series is a full port stop and waste ball valve ideal for plumbing or hydronic systems where draining is required. Features a heavy pattern dezincification resistant **Lead Free\*** bronze body.

#### FEATURES

- **Lead Free\*** Brass & Bronze Materials
- Drain Port with Finger Tight Shut-off
- ½" through 1" Sizes, NPT & Solder
- Easily Identifiable Blue "**Lead Free**" Hang Tag
- Adjustable Stem Packing Nut
- 100% Made in the USA.

#### PERFORMANCE RATING

- Maximum Rated Pressure: 400 psi CWP
- Maximum Working Temperature: 120°F
- Suitable for water and non-hazardous fluids

#### MATERIALS SPECIFICATION

Part Name	Material
Lever and Grip	Steel, Zinc Plated w/ Vinyl
Stem Packing	RPTFE
Stem Bearing	RPTFE
Ball	C27451, <b>Lead Free*</b> Brass, Chrome.Plated
Seat (2)	RPTFE
Retainer	C27451, <b>Lead Free*</b>
Gland Nut	B16 Brass
Stem	C27451, <b>Lead Free*</b>
Lever Nut	Steel, Zinc Plated
Body	C89836, <b>Lead Free*</b> , Bronze

#### APPROVALS

- MSS SP-110; Ball Valves Threaded, Socket-Welding, Solder Joint, Grooved and Flared Ends
- ANSI/NSF 61 Section 8, Annex G, 0.25% Lead max

#### OPTIONS

- ☐ (-04) 2-1/4" Stem Extension
- ☐ (-07) Steel Tee Handle
- ☐ (-11) Therma-Seal™ Insulating Tee Handle
- ☐ (-27) SS Latch-Lock Lever & Nut
- ☐ (-94) 2-1/4" Extension Kit with Balancing Stops

**Consult factory for availability of LF model options**

**\* LEAD FREE:** The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with CA AB1953, VT Act 193, MD HB372, LA HB471 and Federal Public Law 111-380.



#### DIMENSIONS

Part #	Size	A	B	C	D	E	F	G	Wt. (lbs.)
<b>NPT</b>									
95LF10301	1/2"	0.50	1.54	3.08	1.50	3.87	0.53	-	0.63
95LF10401	3/4"	0.75	1.78	3.55	2.01	4.87	0.74	-	1.39
95LF10501	1"	1.00	1.93	3.86	2.20	4.87	0.81	-	1.90
<b>SOLDER</b>									
95LF20301	1/2"	0.50	1.43	2.87	1.75	3.87	0.76	0.50	0.70
95LF20401	3/4"	0.75	2.12	4.12	2.15	4.87	1.04	0.75	1.53
95LF20501	1"	1.00	2.21	4.43	2.43	4.87	1.21	0.91	1.90

