

# **Accord®**

60" x 30" Tile Bath/Shower **71140110** 



#### **Features**

- Alcove installation
- 15" apron
- Solid Vikrell material
- Left drain
- Pivot snap-together modular design
- Tile look
- No caulk required
- Molded-in shelves

### **Included Components**

Product consists of:

71144100 60" x 30" Tile Bath/Shower Wall Set 71141110 60" x 30" Bath



#### Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 HUD, UM Bulletin 73

## Warranty – Bathing Fixtures (and) Kitchen and Utility Sinks Made of Solid Vikrell® Material

See website for detailed warranty information.

#### **Available Colors/Finishes**


Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	KOHLER Biscuit



# **Accord®**

# 60" x 30" Tile Bath/Shower **71140110**



## **Technical Information**

All product dimensions are nominal.

Installation: Three-wall alcove

Drain location: Left

Basin area, bottom: 46-1/4" x 20-1/2" (1175 mm x 521 mm)
Basin area, top: 52-1/4" x 22-1/2" (1327 mm x 572 mm)

Water depth: 11" (279 mm)

Water capacity: 34 gal (128.7 L)

Minimum flat for door: 2-3/4" (70 mm)

Maximum door height: 56-1/2" (1435 mm)

Maximum door width: 56-3/4" (1441 mm)

#### **Notes**

door installations.

Install this product according to the installation instructions.

Product is designed to be used with a single-handle mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width. Studs should be positioned roughly as shown. Double studding is recommended for pivot shower

Bath cannot be installed without the wall surround.

Width of back wall at the top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately ¼" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.