

BZ33-HP09WALL1**BZ33-HP09OUT1****FEATURES**

- Two-way draining
- Green Fin anti-corrosive coating
- Auto restart function
- Low and high ambient cooling
- Chassis and compressor heating belts
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 115V, single phase

TWO-WAY DRAINING

Piping, drainage, and connections are able to be installed on the right and left sides.

AMBIENT COOLING

Keep the area cool with low and high ambient cooling, whether it's cold outside but warm inside or up to 122°F outside.

GREEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

AUTO DEFROST

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

24-HOUR TIMER

Preset the unit to automatically turn on or off.



INDOOR/OUTDOOR MINI-SPLIT SYSTEM

9,000 BTU

UNIT	ID NO.	MODEL
Indoor	.3473331	BZ33-HP09WALL1
Outdoor	.3473335	BZ33-HP09OUT1

COOLING

Capacity (Range)	BTU/H	9,000 (3,600 - 10,300)
Input	W	782
Rated Current	A	6.8
EER	BTU/W	11.5
SEER	BTU/W	19

HEATING

Capacity (Range)	BTU/H	10,000 (3,500 - 10,900)
Input	W	925
Rated Current	A	8.1
COP	W/W	3.11
HSPF4	BTU/W	10
HSPF5	BTU/W	7.8

COMPRESSOR

Type	Rotary	
Capacity	W	3,100
Input	W	790
Rated Current (RLA)	A	6
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 310

REFRIGERANT PIPING

Liquid	In	1/4
Gas	In	3/8
Max. Refrigerant Pipe Length	Ft	82
Max. Different in Level	Ft	33

ROOM TEMPERATURE

Indoor (Cooling/Heating)	°F	62~90 / 32~86
Outdoor (Cooling/Heating)	°F	5~122 / 5~86

SPECIFICATIONS

Application Area	Sq. Ft.	129 - 189
Refrigerant Type	R410A	
Thermostat Type	Wireless Remote	
Warranty	Yes*	

INDOOR FAN MOTOR

Input	W	35.20
Output	W	20
RLA	A	0.71
Speed (High/Med/Low)	r/min	1,050 / 850 / 600
Air Flow (High/Med/Low)	CFM	247 / 182 / 129
Noise Level (High/Med/Low)	dBA	38 / 32 / 25

INDOOR UNIT DIMENSIONS

Product (W x D x H)	In	28-2/5 x 7-2/5 x 11-2/5
Packaging (W x D x H)	In	31-1/10 x 10-3/5 x 14-1/2
Net/Gross Weight	Lbs	17.2 / 22.7

OUTDOOR FAN MOTOR

Input	W	58
Output	W	34
RLA	A	0.39
Speed	r/min	800 / 750 / 650
Air Flow	CFM	1,176.47
Noise Level	dBA	52

OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	30-3/10 x 11-4/5 x 21-4/5
Packaging (W x D x H)	In	35-2/5 x 13-1/2 x 23
Net/Gross Weight	Lbs	66.8 / 71.87

ELECTRICAL DATA

Min. Circuit Ampacity	A	16
Max. Fuse	A	20
Refrigerant Precharge	Ft	25
Additional Charge/Ft	Oz	0.161
Design Pressure	PSIG	550 / 340
Connection Wiring	16AWG*4, Stranded, Unshielded	
Power Supply	Ph/V/Hz	1 / 115 / 60

*5 year warranty on parts, 7 year warranty on compressor.

